

10 33-1 Mercury (10µg/mL in 5% HNO3)

High-Purity Standards

Catalogue number: 10 33-1

Version No: 2.2 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

SECTION 1 IDENTIFICATION

Product Identifier

Product name	10 33-1 Mercury (10µg/mL in 5% HNO3)
Synonyms	10µg/mL Mercury in 5% HNO3
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (contains nitric acid)
Other means of identification	10 33-1

Recommended use of the chemical and restrictions on use

Relevant identified uses Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

SECTION 2 HAZARD(S) IDENTIFICATION

Classification	Serious Eye Damage Category 1, Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A
abel elements	
Hazard pictogram(s)	
SIGNAL WORD	DANGER
lazard statement(s)	
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

Hazard(s) not otherwise specified

Not Applicable

Chemwatch Hazard Alert Code: 3

Issue Date: 05/25/2017

Print Date: 05/25/2017

S.GHS.USA.EN

Chemwatch: 9-245844

Catalogue number: 10 33-1

Version No: 2.2

Page 2 of 10

10 33-1 Mercury (10µg/mL in 5% HNO3)

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
Precautionary statement(s)	Response
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
Propositionary statement(s)	Storage
Precautionary statement(s) P405	Storage Store locked up.
-	-
-	Store locked up.
P405	Store locked up.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7439-97-6	0.001	mercury (elemental)
7697-37-2	5	nitric acid
7732-18-5	balance	water

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casuality can comfortably drink. Transport to hospital or doctor without delay.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- ▶ Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION: Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.

- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

10 33-1 Mercury (10µg/mL in 5% HNO3)

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

Version No: 2.2

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting	
Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous fumes. May emit acrid smoke.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	#

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container DO NOT use aluminium or galvanised containers
--

Version No: 2.2

10 33-1 Mercury (10µg/mL in 5% HNO3)

	▶ Check regularly for spills and leaks
	▶ Lined metal can, lined metal pail/ can.
	▶ Plastic pail.
	▶ Polyliner drum.
	Packing as recommended by manufacturer.
	Check all containers are clearly labelled and free from leaks.
	For low viscosity materials
	Drums and jerricans must be of the non-removable head type.
	Where a can is to be used as an inner package, the can must have a screwed enclosure.
	For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):
	▶ Removable head packaging;
	Cans with friction closures and
	▶ low pressure tubes and cartridges
	may be used.
	Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
	▶ Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
	Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces.
	The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
	The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.
Storage incompatibility	Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.
	Inorganic acids can initiate the polymerisation of certain classes of organic compounds.
	Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.
	Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitriles, sulfides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H2S and SO3), dithionites (SO2), and even
	carbonates.
	Acids often catalyse (increase the rate of) chemical reactions.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Not Available

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	mercury (elemental)	Mercury (vapor)	Hg Vapor: 0.05 mg/m3	Not Available	0.1 mg/m3	See Table Z-2;(as Hg)
US OSHA Permissible Exposure Levels (PELs) - Table Z2	mercury (elemental)	Mercury	Not Available	Not Available	Other:0.1 mg/m3	(Z37.8–1971)
US NIOSH Recommended Exposure Limits (RELs)	mercury (elemental)	Mercury metal: Colloidal mercury, Metallic mercury, Quicksilver	Not Available	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	nitric acid	Nitric acid	5 mg/m3 / 2 ppm	10 mg/m3 / 4 ppm	Not Available	TLV® Basis: URT & eye irr; dental erosion
US NIOSH Recommended Exposure Limits (RELs)	nitric acid	Aqua fortis, Engravers acid, Hydrogen nitrate, Red furning nitric acid (RFNA), White furning nitric acid (WFNA)	5 mg/m3 / 2 ppm	4 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	nitric acid	Nitric acid	2 ppm	Not Available	Not Available	Not Available

EMERGENCY LIMITS TEEL-2 TEEL-3 Material name TEEL-1 Ingredient 0.15 mg/m3 Not Available mercury (elemental) Mercury vapor Not Available Nitric acid Not Available Not Available Not Available nitric acid Ingredient Original IDLH Revised IDLH mercury (elemental) 10 mg/m3 / 28 mg/m3 2 mg/m3 / 10 mg/m3 nitric acid 100 ppm 25 ppm

Exposure controls

water

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.	
Appropriate engineering controls Ine basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.	 effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection.

Not Available

10 33-1 Mercury (10 $\mu g/mL$ in 5% HNO3)

	turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.			
	Type of Contaminant:	Air Speed:		
	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)		
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, platin acid fumes, pickling (released at low velocity into zone of active generation)	g 0.5-1 m/s (100-200 f/min.)		
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)			
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high air motion).	rapid 2.5-10 m/s (500-2000 f/min.)		
	Within each range the appropriate value depends on:			
	Lower end of the range Upper end of the range			
	1: Room air currents minimal or favourable to capture 1: Disturbing room air curr	ents		
	2: Contaminants of low toxicity or of nuisance value only. 2: Contaminants of high to:	icity		
	3: Intermittent, low production. 3: High production, heavy u	se		
	4: Large hood or large air mass in motion 4: Small hood-local control	only		
	distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-4 solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instruction of 10 or more when extraction systems are instruction.	deficits within the extraction		
Personal protection	solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance	00 f/min) for extraction of deficits within the extraction		
Personal protection	solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance	00 f/min) for extraction of deficits within the extraction illed or used. expectacles are not sufficient the material may be under ad. rd face protection. ent, describing the wearing of nd adsorption for the class of suitable equipment should be		
Eye and face protection	 solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instraction when extraction systems are instraction are instructed and the extraction of the extraction of the extraction systems are instructed and the extraction are extracted and the extraction of the extraction of the extraction systems are instructed and the extraction are extracted and the extraction of the extract	00 f/min) for extraction of deficits within the extraction lled or used. spectacles are not sufficient the material may be under ed. rd face protection. ent, describing the wearing of nd adsorption for the class of suitable equipment should be sticable. Lens should be remov		
-	 solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instraction. Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the pressure. Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitt Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these affer. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy docum lenses or restrictions on use, should be created for each workplace or task. This should be trained in their removal and readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as pra at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed 	00 f/min) for extraction of deficits within the extraction lled or used. spectacles are not sufficient te material may be under ed. rd face protection. ent, describing the wearing of nd adsorption for the class of suitable equipment should be sticable. Lens should be remo		
Eye and face protection	 solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instraction. Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the pressure. Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitt Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these affect. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy docume lenses or restrictions on use, should be created for each workplace or task. This should be trained in their removal and readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as praat the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] 	00 f/min) for extraction of deficits within the extraction lled or used. spectacles are not sufficient te material may be under ed. rd face protection. ent, describing the wearing of nd adsorption for the class of suitable equipment should be sticable. Lens should be remo		
Eye and face protection	 solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instraction. Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the pressure. Chemical goggles. whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitt Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these affect. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy docum lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption a chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as prat at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] See Hand protection below Elbow length PVC gloves 	00 f/min) for extraction of deficits within the extraction lled or used. spectacles are not sufficient te material may be under ed. rd face protection. ent, describing the wearing of nd adsorption for the class of suitable equipment should be sticable. Lens should be remo		
Eye and face protection Skin protection Hands/feet protection	 solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instraction and the extraction when extraction systems are instraction and the extraction of the provide the extraction of the extraction of the integration is desirable, as in laboratories; where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the pressure. Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitt if Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these affect and face shield (20 cm, 8 in minimum) may be required for each workplace or task. This should include a review of lens absorption a chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as prate at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed Current Intelligence Bulletin 59], [00 f/min) for extraction of deficits within the extraction lled or used. spectacles are not sufficient te material may be under ed. rd face protection. ent, describing the wearing of nd adsorption for the class of suitable equipment should be sticable. Lens should be remo		

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	colorless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available

Version No: 2.2

10 33-1 Mercury (10µg/mL in 5% HNO3)

Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence.				
Ingestion	Ingestion of acidic corrosives may produce burns around and in the mouth, the speaking may also be evident. The material has NOT been classified by EC Directives or other classification stanimal or human evidence.				
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be of Skin contact is not thought to have harmful health effects (as classified under E through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, ma of the material and ensure that any external damage is suitably protected.	C Directives); the material may	still produce health damage following entry		
Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to lig completely.	ght and burns. Mild burns of the	epithelia generally recover rapidly and		
Chronic	Repeated or prolonged exposure to acids may result in the erosion of teeth, sw and inflammation of lung tissue often occurs. Long-term exposure to respiratory irritants may result in airways disease, involv Substance accumulation, in the human body, may occur and may cause some c	ring difficulty breathing and relat	ed whole-body problems.		
10 33-1 Mercury (10µg/mL in	TOXICITY	IRRITATION			
5% HNO3)	Not Available	Not Available			
	TOXICITY	I	RRITATION		
mercury (elemental)	Oral (rat) LD50: >9.2 mg/kg ^[1]	1	Not Available		
nitric acid	TOXICITY		IRRITATION		
nitro dela	Inhalation (rat) LC50: 625 ppm/1h*t ^[2]		Not Available		
	ΤΟΧΙCΙΤΥ	IRRITATION			
water	Not Available	Not Available			
		Trot Available			
Legend:	 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2 extracted from RTECS - Register of Toxic Effect of chemical Substances 	.* Value obtained from manufac	cturer's SDS. Unless otherwise specified data		
MERCURY (ELEMENTAL)	Animal studies have shown that mercury may be a reproductive effector.				
NITRIC ACID	For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage wh The material may produce severe irritation to the eye causing pronounced inflar				

Page 7 of 10

10 33-1 Mercury (10µg/mL in 5% HNO3)

	The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]				
WATER	No significant acute toxicological data identified in literature se	arch.			
MERCURY (ELEMENTAL) & NITRIC ACID	Asthma-like symptoms may continue for months or even years a	fter exposure to the material ends.			
Acute Toxicity	0	Carcinogenicity	0		
Skin Irritation/Corrosion	✓	Reproductivity	0		
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	0		
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0		
Mutagenicity	\otimes	Aspiration Hazard	\odot		
		Legend: 🗙	– Data available but does not fill the criteria for classification		

Data available to make classification

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

10 33-1 Mercury (10µg/mL in	ENDPOINT		TEST DURATION (HR)		SPECIES		VALUE		SOURCE	
5% HNO3)	Not Applicable		Not Applicable		Not Applicable Not App		blicable Not A		Applicable	
				1						
	ENDPOINT	ENDPOINT TEST DUP		T DURATION (HR) SPECIES			VALUE			SOURCE
	LC50	96		Fish	Fish			0.004mg/L	-	4
	EC50	48		Crustacea		0.0035mg	/L	5		
mercury (elemental)	EC50	72		Algae	Algae or other aquatic plants		0.0025mg	/L	4	
	BCF	720		Fish		0.001mg/L	-	4		
	EC50	240		Fish		0.0003mg	/L	5		
	NOEC	2688		Crustacea		0.00025m	g/L	2		
	ENDPOINT TEST DURATION (HR)			:	SPECIES		VALUE	SC	DURCE	
nitric acid	NOEC	NOEC 16			Crustacea		107mg/L	4		
	ENDPOINT		TEST DURATION (HR)		SPECIES		VALUE		SOU	RCE
water	Not Applicable	Not Applicable Not Applicable			Not Applicable Not Ap		blicable Not Applicable		pplicable	
Legend:			oxicity Data 2. Europe ECHA Re							
	(QSAR) - Aquatic	Toxicity <i>E</i>	Data (Estimated) 4. US EPA, Ec	otox database	e - Aquatic To:	xicity Data 5	5. ECETOC A	quatic Hazard	Assessme	nt Data 6. NITE

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)

Catalogue number: **10 33-1** Version No: **2.2**

Issue Date: 05/25/2017 Print Date: 05/25/2017

10 33-1 Mercury (10µg/mL in 5% HNO3)

Waste treatment methods

 Product / Packaging disposal
 Recycle wherever possible.
 Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
 Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant

Land transport (DOT)

UN number	3264
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (contains nitric acid)
Transport hazard class(es)	Class8SubriskNot Applicable
Packing group	II Contraction of the second
Environmental hazard	Not Applicable
Special precautions for user	Hazard Label8Special provisions386, B2, IB2, T11, TP2, TP27

Air transport (ICAO-IATA / DGR)

UN number	3264			
UN proper shipping name	CORROSIVE LIQUID	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains nitric acid)		
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	8 Not Applicable 8L		
Packing group	II			
Environmental hazard	Not Applicable			
Special precautions for user	Passenger and Cargo Passenger and Cargo		A3A803 855 30 L 851 1 L Y840 0.5 L	

Sea transport (IMDG-Code / GGVSee)

UN number	3264
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. * (contains nitric acid)
Transport hazard class(es)	IMDG Class8IMDG SubriskNot Applicable
Packing group	I
Environmental hazard	Not Applicable
Special precautions for user	EMS NumberF-A, S-BSpecial provisions274

Chemwatch: 9-245844

Catalogue number: **10 33-1** Version No: **2.2** Page 9 of 10

10 33-1 Mercury (10µg/mL in 5% HNO3)

Limited Quantities 1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Product name	Pollution Category	Ship Type
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Nitric acid (70% and over) Nitric acid (less than 70%)	Y; Y	2 2

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

MERCURY (ELEMENTAL)(7439-97-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Washington Permissible exposure limits of air contaminants
Monographs	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - Alaska Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
(CRELs)	US ACGIH Threshold Limit Values (TLV)
US - California Permissible Exposure Limits for Chemical Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - California Proposition 65 - Reproductive Toxicity	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Hawaii Air Contaminant Limits	US Clean Air Act - Hazardous Air Pollutants
US - Idaho - Acceptable Maximum Peak Concentrations	US CWA (Clean Water Act) - Priority Pollutants
US - Idaho - Limits for Air Contaminants	US CWA (Clean Water Act) - Toxic Pollutants
US - Massachusetts - Right To Know Listed Chemicals	US EPA Carcinogens Listing
US - Michigan Exposure Limits for Air Contaminants	US EPCRA Section 313 Chemical List
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-2)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z2
US - Rhode Island Hazardous Substance List	US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	Chemicals Causing Reproductive Toxicity
US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air	US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
L	
NITRIC ACID(7697-37-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
Passenger and Cargo Aircraft	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Alaska Limits for Air Contaminants	Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Massachusetts - Right To Know Listed Chemicals	US CWA (Clean Water Act) - List of Hazardous Substances
US - Michigan Exposure Limits for Air Contaminants	US EPCRA Section 313 Chemical List
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	,
,	US SARA Section 302 Extremely Hazardous Substances
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	,

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Pennsylvania - Hazardous Substance List

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (Ib)	Reportable Quantity in kg
Mercury	1	0.454
Nitric acid	1000	454

State Regulations

US. CALIFORNIA PROPOSITION 65

10 33-1 Mercury (10µg/mL in 5% HNO3)

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PREPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Mercury and mercury compounds Listed

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Y
Canada - NDSL	N (water; mercury (elemental); nitric acid)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	N (water; mercury (elemental); nitric acid)
Korea - KECI	Y
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Init Value LOD: Limit of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.