

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/27/2022

Reviewed on 05/27/2022

Product identifier		
Trade name: <u>Nickel (µg/mL i</u>	2% HNO3)	
Article number: 10-36-1		
Details of the supplier of the s	ıfety data sheet	
Manufacturer/Supplier:		
High-Purity Standards		
7221 Investment Drive, North	Charleston, SC 29418 United States	
<i>Telephone:</i> +1-843-767-7900		
Fax: +1-843-767-7906		
highpuritystandards.com		
Email: info@highpuritystanda	ds.com	
Information department: Prod	uct safety department	
Emergency telephone number		
INFOTRAC		
Emergency telephone numbers	1-800-535-5053	
Other emergency telephone nu	nbers 1-352-323-3500	

2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Met. Corr.1H290 May be corrosive to metals.Skin Corr. 1AH314 Causes severe skin burns and eye damage.Eye Dam.1H318 Causes serious eye damage.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling: nitric acid*

• *Hazard statements* H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.

• **Precautionary statements** Keep only in original container.

(Contd. on page 2)



Printing date 05/27/2022

Reviewed on 05/27/2022

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 1) Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 3 *Health* = 3 FIRE 0 Fire = 0Reactivity = 0REACTIVITY 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients · Chemical characterization: Mixtures · Description: Mixture of the substances listed below with nonhazardous additions. · Dangerous components: 7697-37-2 nitric acid 2.0%

· Chemical i	dentification of the substance/preparation	
7732-18-5	water, distilled, conductivity or of similar purity	97.999%
7440-02-0	nickel	0.001%
		11

(Contd. on page 3)

Page 2/11



Printing date 05/27/2022

Reviewed on 05/27/2022

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- *After skin contact:* Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.	
Wear protective equipment. Keep unprotected persons away.	
• Environmental precautions: No special measures required.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing agent.	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
• PAC-1:	
7697-37-2 nitric acid	0.16 ppm
7440-02-0 nickel	4.5 mg/m ³
· PAC-2:	
<i>TAC-2</i> .	
7697-37-2 nitric acid	24 ppm

Page 3/11



Printing date 05/27/2022

Page 4/11

Safety Data Sheet acc. to OSHA HCS

Reviewed on 05/27/2022

Trade name: Nickel (µg/mL in 2% HNO3)

7440-02-0 nickel	(Contd. of page 3) 50 mg/m ³
• PAC-3:	
7697-37-2 nitric acid	92 ppm
7440-02-0 nickel	99 mg/m ³

7 Handling and storage

- · Handling:
- *Precautions for safe handling* Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

- REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm
- *TLV* Short-term value: 4 ppm Long-term value: 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

(Contd. on page 5)

US



Printing date 05/27/2022

Reviewed on 05/27/2022

(Contd. of page 4)

Trade name: Nickel (µg/mL in 2% HNO3)

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Liquid	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	

Page 5/11



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/27/2022

Reviewed on 05/27/2022

Trade name: Nickel (µg/mL in 2% HNO3)

		(Contd. of page 5
· Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.01014 g/cm ³ (8.42962 lbs/gal)	
· Bulk density:	1,010 kg/m³	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Water:	98.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US



Printing date 05/27/2022

Reviewed on 05/27/2022

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
7440-02-0 nickel	2B
· NTP (National Toxicology Program)	
7440-02-0 nickel	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- *Persistence and degradability No further relevant information available.*
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Not hazardous for water.
- Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

Page 7/11



Printing date 05/27/2022

Reviewed on 05/27/2022

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 7)

13 Disposal considerations

• Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN3264
UN proper shipping name DOT ADR	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.
IMDG, IATA	(NITRIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRI ACID)
Transport hazard class(es)	
DOT	
CORROSIVE 8	
Class Label	8 Corrosive substances 8
ADR	U
Class	8 (C1) Corrosive substances
Label	8
IMDG, IATA	
Class	8 Corrosive substances



Printing date 05/27/2022

Reviewed on 05/27/2022

Trade name: Nickel (µg/mL in 2% HNO3)

	(Contd. of page
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code)	: 80
EMS Number:	F-A, S-B
Segregation groups	Acids
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
2	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: El
(<u></u>)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O., (NITRIC ACID), 8, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

• Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

7440-02-0 nickel

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 10)

Page 9/11

US



Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/27/2022

Reviewed on 05/27/2022

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 9)

A5

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

7440-02-0 nickel

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

7440-02-0 nickel

· NIOSH-Ca (National Institute for Occupational Safety and Health)

7440-02-0 nickel

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: nitric acid
Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.
Precautionary statements Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 11)

US



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 05/27/2022

Reviewed on 05/27/2022

(Contd. of page 10)

Trade name: Nickel (µg/mL in 2% HNO3)

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Department issuing SDS: Environment protection department.

• Contact: High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

· Date of preparation / last revision 05/27/2022 / -

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1 Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eve Dam. 1: Serious eye damage/eye irritation – Category 1

US