

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

1 Identification	
	· Product identifier
	· Trade name: Lutetium 100 µg/mL in 2% HNO3
	• Article number: 100-30-1
	• Details of the supplier of the safety data sheet
	Manufacturer/Supplier:
	Uich Damity Standarda

Manufacturer/Supplier: <u>High-Purity Standards</u> 7221 Investment Drive, North Charleston, SC 29418 United States Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com Email: info@highpuritystandards.com

· Information department: Product safety department

2 Hazard(s) identification

· Classification of the substance or mixture



Corrosive to Metals 1 H290 May be corrosive to metals.

- Skin Corrosion 1A H314 Causes severe skin burns and eye damage.
- *Eye Damage 1* H318 Causes serious eye damage.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



GHS05

· Signal word Danger

Hazard-determining components of labeling: nitric acid
Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.
Precautionary statements Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 2)

US



Printing date 02/27/2023

Safety Data Sheet acc. to OSHA HCS Page 2/11

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

(Contd. of page 1) If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH Health = 3FIRE Fire = 00 **REACTIVITY O** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients · Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.

 • Dangerous components:
 2.0%

 7697-37-2
 nitric acid
 2.0%

 • Chemical identification of the substance/preparation
 7732-18-5
 water, distilled, conductivity or of similar purity

 97.99%
 12032-20-1
 lutetium oxide
 0.01%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

⁻ US



Page 3/11

Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

(Contd. of page 2)

- After eve contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- *After swallowing:* Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Dilute with plenty of water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). *Use neutralizing agent.*
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
7697-37-2 nitric acid	0.16 ppm
12032-20-1 lutetium oxide	30 mg/m ³
· PAC-2:	
7697-37-2 nitric acid	24 ppm
12032-20-1 lutetium oxide	330 mg/m ³
· PAC-3:	
7697-37-2 nitric acid	92 ppm
· · · · · · · · · · · · · · · · · · ·	(Contd. on page 4



Page 4/11

(Contd. of page 3)

 $2,000 \text{ mg/m}^3$

Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

12032-20-1 lutetium oxide

7 Handling and storage

· Handling:

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

- REL Short-term value: 10 mg/m³, 4 ppm
- Long-term value: 5 mg/m³, 2 ppm
- *TLV* Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

US



Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

• Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information		
Appearance: Form: Color: Odor:	Liquid colorless Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	

Page 5/11

(Contd. of page 4)

US



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

	(Contd. o	f page
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	98.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

(Contd. on page 7)

US



Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

• Sensitization: No sensitizing effects known.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- *General notes:* Not hazardous for water.
- Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- \cdot **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

US

Page 7/11

(Contd. of page 6)



Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

• Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information	
UN-Number DOT, ADR, IMDG, IATA	UN3264
UN proper shipping name DOT ADR IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O (NITRIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITR
	ACID)
Transport hazard class(es)	
DOT	
Class Label	8 Corrosive substances 8
ADR	
S S S S S S S S S S S S S S S S S S S	
Class Label	8 (C1) Corrosive substances 8
IMDG, IATA	
Class Label	8 Corrosive substances 8
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler cod EMS Number:	Warning: Corrosive substances
	(Contd. on page

Page 8/11

(Contd. of page 7)

- US



Printing date 02/27/2023

Reviewed on 02/27/2023

Page 9/11

Trade name: Lutetium 100 µg/mL in 2% HNO3

	(Contd. of page a
· Segregation groups · Stowage Category · Stowage Code	Acids A SW2 Clear of living quarters.
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
• DOT • Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (NITRIC ACID), 8, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355	(extremely	hazardous	substances):
---------------	------------	-----------	--------------

7697-37-2 nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 10)



Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

(Contd. of page 9)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

None of the ingredients is listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: nitric acid · Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. · Precautionary statements Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. *IF INHALED: Remove person to fresh air and keep comfortable for breathing.* If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 11) US



Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: Lutetium 100 µg/mL in 2% HNO3

(Contd. of page 10)

Page 11/11

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

Department issuing SDS. Environment protection department.
Contact:
High-Purity Standards
Tel: 843-767-7900
Fax: 843-767-7906
Date of preparation / last revision 02/27/2023
Abbreviations and acronyms:
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Corrosive to Metals 1: Corrosive to metals – Category 1
Skin Corrosion 1A: Skin corrosion/irritation – Category 1A
Eye Damage 1: Serious eye damage/eye irritation – Category 1