

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2022 Reviewed on 11/11/2022

1 Identification

Product identifier

· Trade name: Nickel 1000 μg/mL in 2% HCl

· Article number: 100036-2

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

- · Information department: Product safety department
- · Emergency telephone number:

INFOTRAC

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.



GHS05 Corrosion

Skin Corrosion 1A H314 Causes severe skin burns and eye damage.



GHS07

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS07

CHCUG



Page 2/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

(Contd. of page 1)

- · Signal word Danger
- · Hazard-determining components of labeling:

hydrochloric acid

nickel

- · Hazard statements
- H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *3

Fire = 0

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

US



Page 3/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous components:	
7647-01-0 hydrochloric acid	2.0%
7440-02-0 nickel	0.1%
· Chemical identification of the substance/preparation	
7732-18-5 water, distilled, conductivity or of similar purity	97.9%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Dilute with plenty of water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)





Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

(Contd. of page 3)

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

1 Total Control of the Thirty of Control of the Thirty of	
· PAC-1:	
7647-01-0 hydrochloric acid	1.8 ppm
7440-02-0 nickel	4.5 mg/m ³
· PAC-2:	
7647-01-0 hydrochloric acid	22 ppm
7440-02-0 nickel	50 mg/m³
· PAC-3:	
7647-01-0 hydrochloric acid	100 ppm
7440-02-0 nickel	99 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

7647-01-0 hydrochloric acid

PEL Ceiling limit value: 7 mg/m³, 5 ppm

(Contd. on page 5)





Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

(Contd. of page 4)

REL Ceiling limit value: 7 mg/m³, 5 ppm

TLV Ceiling limit value: 2 ppm

A4

7440-02-0 nickel

PEL Long-term value: 1 mg/m³

REL Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A

TLV Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI

· Ingredients with biological limit values:

7440-02-0 nickel

BEI 5 μg/L

Medium: urine

Time: post-shift at end of workweek Parameter: Nickel (background)

30 μg/L

Medium: urine Time: post-shift at end o

Time: post-shift at end of workweek Parameter: Nickel (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and chemical properties		
General Information Appearance:		
Appearance: Form:	Liquid	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.01091 g/cm³ (8.43604 lbs/gal)	
Bulk density:	$1,011 \text{ kg/m}^3$	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	

(Contd. on page 7)





Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

	(Cont	d. of page 6)	
· Partition coefficient (n-octan	Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
· Solvent content:			
Water:	97.9 %		
VOC content:	0.00 %		
	0.0 g/l / 0.00 lb/gal		
Solids content:	0.1 %		
· Other information	No further relevant information available.		

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7647-01-0 hydrochloric acid

Oral LD50 900 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 8)



Page 8/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

 (Contd. of page 7)

 • Carcinogenic categories

 • IARC (International Agency for Research on Cancer)

 7647-01-0 | hydrochloric acid
 3

 7440-02-0 | nickel
 2B

 • NTP (National Toxicology Program)
 R

 • OSHA-Ca (Occupational Safety & Health Administration)
 R

 None of the ingredients is listed.
 Instance of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA

not regulated

(Contd. on page 9)





Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

		(Contd. of page 8
· UN proper shipping name · DOT, ADR, IMDG, IATA	not regulated	
· Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA · Class	not regulated	
Packing group DOT, ADR, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	
· UN "Model Regulation":	not regulated	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

	Suru
ſ	· Section 355 (extremely hazardous substances):
	7647-01-0 hydrochloric acid
Ī	

Section 313 (Specific toxic chemical listings):

7647-01-0 hydrochloric acid

7440-02-0 nickel

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

7647-01-0 hydrochloric acid

- Proposition 65
- · Chemicals known to cause cancer:

7440-02-0 nickel

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)



Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

(Contd. of page 9)

	Camaina		4	
٠	Carcino	genic	categ	ories

· EPA (Environmental Protection Agency)		
None of the ingredients is listed.		
· TLV (Threshold Limit Value)		
7647-01-0 hydrochloric acid	A4	
7440-02-0 nickel	<i>A5</i>	
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
7440-02-0 nickel		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05 GHS07 G

- · Signal word Danger
- · Hazard-determining components of labeling:

hydrochloric acid

nickel

· Hazard statements

H314 Causes severe skin burns and eve damage.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/11/2022 Reviewed on 11/11/2022

Trade name: Nickel 1000 µg/mL in 2% HCl

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

- · Date of preparation / last revision 11/11/2022
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Skin Corrosion 1A: Skin corrosion/irritation – Category 1A Sensitization - Skin 1: Skin sensitisation - Category 1 Carcinogenicity 2: Carcinogenicity – Category 2