

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 07/15/2021 Reviewed on 07/15/2021

1 Identification

· Product identifier

· Trade name: Molybdenum 10,000 μg/mL in 4% HNO3 + 2% HF

· Article number: 10M34-3

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

· Information department: Product safety department

Emergency telephone number:

INFOTRAC

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS06

- · Signal word Danger
- · Hazard-determining components of labeling: hydrogen fluoride

(Contd. on page 2)



Page 2/12

Safety Data Sheet acc. to OSHA HCS

Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 μg/mL in 4% HNO3 + 2% HF

(Contd. of page 1)

nitric acid

· Hazard statements

H290 May be corrosive to metals.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3

Fire = 0

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

7697-37-2 nitric acid

4.0%

(Contd. on page 3)



Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 µg/mL in 4% HNO3 + 2% HF

		(Contd. of page 2)		
7664-3	9-3 hydrofluoric acid	2.0%		
7439-9	8-7 molybdenum	1.0%		
· Chemical identification of the substance/preparation				
7732-1	8-5 water, distilled, conductivity or of similar purity	93.0%		

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)





Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 µg/mL in 4% HNO3 + 2% HF

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

	Tenon Crucius	
· <i>PAC-1</i> :		
7697-37-2	nitric acid	0.16 ppm
7439-98-7	molybdenum	30 mg/m^3
· PAC-2:		
7697-37-2	nitric acid	24 ppm
7439-98-7	molybdenum	330 mg/m³
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7439-98-7	molybdenum	2,000 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

Components with limit values that require monitoring at the workplace:			
7697	-37-2 nitric acid		
PEL	Long-term value: 5 mg/m³, 2 ppm		
REL	Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm		
TLV	Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm		

(Contd. on page 5)





Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 µg/mL in 4% HNO3 + 2% HF

(Contd. of page 4)

Page 5/12

7664-39-3 hydrofluoric acid

PEL Long-term value: 3 ppm

as F

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5* mg/m³, 6* ppm

*15-min, as F

TLV Long-term value: 0.41 mg/m³, 0.5 ppm

Ceiling limit value: 1.64 mg/m³, 2 ppm

as F; Skin; BEI

7439-98-7 molybdenum

PEL Long-term value: 15* mg/m³

*Total dust, as Mo

TLV Long-term value: 10* 3** mg/m³

as Mo; *inhalable fraction ** respirable fraction

· Ingredients with biological limit values:

7664-39-3 hydrofluoric acid

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Flourides (background)

10 mg/g creatinine Medium: urine Time: end of shift

Parameter: Flourides (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

(Contd. on page 6)





Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 µg/mL in 4% HNO3 + 2% HF

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties · General Information				
· Appearance:				
Form:	Liquid			
Color:	colorless			
· Odor:	Characteristic			
· Odor threshold:	Not determined.			
· pH-value:	Not determined.			
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100°C (212°F)			
· Flash point:	Not applicable.			
· Flammability (solid, gaseous):	Not applicable.			
· Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits:				
Lower:	Not determined.			
Upper:	Not determined.			
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)			

(Contd. on page 7)





Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 µg/mL in 4% HNO3 + 2% HF

		(Contd. of page 6
Density at 20 °C (68 °F):	1.0925 g/cm³ (9.11691 lbs/gal)	
Bulk density:	1,093 kg/m³	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/	water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	93.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · **Possibility of hazardous reactions** No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

(Contd. on page 8)



Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 µg/mL in 4% HNO3 + 2% HF

(Contd. of page 7)

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · **Recommended cleansing agent:** Water, if necessary with cleansing agents.

US





Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 μ g/mL in 4% HNO3 + 2% HF

(Contd. of page 8)

TIM March Law	
UN-Number DOT, ADR, IMDG, IATA	UN2922
UN proper shipping name	
DOT	Corrosive liquids, toxic, n.o.s. (Hydrofluoric acid, Nitric acid)
ADR	2922 CORROSIVE LIQUID, TÓXIC, N.O.S. (HYDROFLUOR
HAD C LATA	ACID, NITRIC ACID)
IMDG, IATA	CORROSIVE LIQUID, TOXIC, N.O.S. (HYDROFLUORIC ACI NITRIC ACID)
Transport hazard class(es)	
DOT	
CORROSIVE TOXIC	
Class	8 Corrosive substances
Label	8, 6.1
ADR	
Class	8 (CT1) Corrosive substances
Label	8+6.1
IMDG	
Class	8 Corrosive substances
Label	8/6.1
IATA	
Class	8 Corrosive substances
Label	8 (6.1)
Packing group	
DOT, ADR, IMDG, IATA	II

(Contd. on page 10)





Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 μ g/mL in 4% HNO3 + 2% HF

	(Contd. of page
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code)	: 86
EMS Number:	F- A , S - B
Segregation groups	Strong acids
Stowage Category	B
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 30 L
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 2922 CORROSIVE LIQUID, TOXIC, N.O.
•	(HYDROFLUORIC ACID, NITRIC ACID), 8 (6.1), II

15 Regulatory information	15 I	Kegul	atory in	formai	ion
---------------------------	------	-------	----------	--------	-----

· Safety, health and	environmental	regulations	legislation	specific for	r the substance	or mixture
Sureiv, neuiin unu	environmeniai	i eguiuiions/	iegisiuuvn	SDECINC ID	i ine subsidice	oi mixime

· Sajety, · Sara

· Section 3.	55 (extremely hazardous substances):	
7697-37-2	2 nitric acid	
· Section 3	13 (Specific toxic chemical listings):	
7697-37-2	2 nitric acid	
· TSCA (To	oxic Substances Control Act):	
7732-18-3	water, distilled, conductivity or of similar purity	ACTIVE
7697-37-2	2 nitric acid	ACTIVE
7439-98-7	7 molybdenum	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

(Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 µg/mL in 4% HNO3 + 2% HF

(Contd. of page 10)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

7439-98-7 molybdenum

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS06

· Signal word Danger

· Hazard-determining components of labeling:

hydrogen fluoride nitric acid

· Hazard statements

H290 May be corrosive to metals.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 12)



Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 07/15/2021 Reviewed on 07/15/2021

Trade name: Molybdenum 10,000 μg/mL in 4% HNO3 + 2% HF

(Contd. of page 11)

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

- Date of preparation / last revision 07/15/2021 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

HIC