

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2021

Reviewed on 03/31/2021

Product identifier	
Trade name: <u>10M46-2 Ruthenium (10,000µg/mL in 5% HCl)</u>	
Article number: 10M46-2	
Details of the supplier of the safety data sheet	
Manufacturer/Supplier:	
High-Purity Standards	
7221 Investment Drive, North Charleston, SC 29418 United States	5
Telephone: +1-843-767-7900	
Fax: +1-843-767-7906	
highpuritystandards.com	
Email: info@highpuritystandards.com	
Information department: Product safety department	
Emergency telephone number:	
INFOTRAC	
Emergency telephone numbers1-800-535-5053	
Other emergency telephone numbers 1-352-323-3500	

2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Skin Corr. 1AH314Causes severe skin burns and eye damage.Eye Dam. 1H318Causes serious eye damage.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: hydrochloric acid ruthenium trichloride
Hazard statements H314 Causes severe skin burns and eye damage.
Precautionary statements Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

⁻ US



Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

(Contd. of page 1) If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) *Health* = 3Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH *3 *Health* = *3 0 Fire = 0FIRE **REACTIVITY O** Reactivity = 0• Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
7647-01-0	hydrochloric acid	5.0%
10049-08-8	ruthenium trichloride	1.0%
	entification of the substance/preparation	
7732-18-5 1	vater, distilled, conductivity or of similar purity	94.0%

4 First-aid measures

· Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- *After skin contact: Immediately wash with water and soap and rinse thoroughly.*
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Page 2/11



Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

(Contd. of page 2) • *After swallowing:* Drink copious amounts of water and provide fresh air. Immediately call a doctor. • *Information for doctor:*

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

Protective Action Criteria for Chemicals

• PAC-1:	
7647-01-0 hydrochloric acid	1.8 ppm
10049-08-8 ruthenium trichloride	2.2 mg/m^3
• PAC-2:	
7647-01-0 hydrochloric acid	22 ppm
10049-08-8 ruthenium trichloride	24 mg/m ³
· PAC-3:	
7647-01-0 hydrochloric acid	100 ppm
10049-08-8 ruthenium trichloride	140 mg/m ³

(Contd. on page 4)

Page 3/11



Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

(Contd. of page 3)

Page 4/11

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

7647-01-0 hydrochloric acid

PEL Ceiling limit value: 7 mg/m³, 5 ppm

- *REL Ceiling limit value:* 7 mg/m³, 5 ppm
- TLV Ceiling limit value: 2.98 mg/m³, 2 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves



Page 5/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and c	hemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	colorless	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

		(Contd. of page
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	94.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:
- 7647-01-0 hydrochloric acid
- Oral LD50 900 mg/kg (rabbit)
- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.
- Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 7)

US -



Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

(Contd. of page 6)

3

Corrosive Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7647-01-0 hydrochloric acid

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

(Contd. on page 8)

Page 7/11



Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

(Contd. of page 7)

UN-Number	
DON-Number DOT, ADR, IMDG, IATA	UN3264
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric acid
ADR	ruthenium trichloride) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.,
IMDG, IATA	(HYDROCHLORIC ACID, ruthenium trichloride) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O., (HYDROCHLORIC ACID, ruthenium trichloride)
Transport hazard class(es)	
DOT	
CORROSIVE 8	
Class	8 Corrosive substances
Label	8
a a a a a a a a a a a a a a a a a a a	
Class	8 (C1) Corrosive substances
Label	8
IMDG, IATA	
Class	8 Corrosive substances
Label	8
Packing group DOT, ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number:	
EMS Number: Segregation groups	F-A,S-B Acids
Stowage Category	B

Page 8/11



Printing date 03/31/2021

Reviewed on 03/31/2021

Page 9/11

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

	(Contd. of page 3
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
ADR	
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (HYDROCHLORIC ACID, RUTHENIUM TRICHLORIDE), 8, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

• Section 355 (extremely hazardous substances):

7647-01-0 hydrochloric acid

• Section 313 (Specific toxic chemical listings):

7647-01-0 hydrochloric acid

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

7647-01-0 hydrochloric acid

Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 10)

US



Page 10/11

(Contd. of page 9)

A4

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

7647-01-0 hydrochloric acid

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: hydrochloric acid *ruthenium trichloride* · Hazard statements H314 Causes severe skin burns and eve damage. · Precautionary statements Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

US -



Printing date 03/31/2021

Reviewed on 03/31/2021

Trade name: 10M46-2 Ruthenium (10,000µg/mL in 5% HCl)

	(Contd. of page 10
D	Department issuing SDS: Environment protection department.
	Contact:
~	ligh-Purity Standards
	lel: 843-767-7900
_	
-	<i>Tax:</i> 843-767-7906
D	Date of preparation / last revision 03/31/2021 / -
A	bbreviations and acronyms:
	DR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internation
	arriage of Dangerous Goods by Road)
IA	MDG: International Maritime Code for Dangerous Goods
D	OT: US Department of Transportation
Ŀ	ATA: International Air Transport Association
A	CGIH: American Conference of Governmental Industrial Hygienists
	INECS: European Inventory of Existing Commercial Chemical Substances
	LINCS: European List of Notified Chemical Substances
	AS: Chemical Abstracts Service (division of the American Chemical Society)
	FPA: National Fire Protection Association (USA)
	MIS: Hazardous Materials Identification System (USA)
	OC: Volatile Organic Compounds (USA, EU)
	C50: Lethal concentration, 50 percent
	D50: Lethal dose, 50 percent
	BT: Persistent, Bioaccumulative and Toxic
	PvB: very Persistent and very Bioaccumulative
	IOSH: National Institute for Occupational Safety
	ISHA: Occupational Safety & Health LV: Threshold Limit Value
	LV: Inresnoid Limit Value EL: Permissible Exposure Limit
	EL: Permissible Exposure Limit EL: Recommended Exposure Limit
	LL. Recommended Exposure Limit kin Corr. 1A: Skin corrosion/irritation – Category 1A
	ye Dam. 1: Serious eye damage/eye irritation – Category 1
Ц.	ye Dum. 1. Serious eye uumugereye irritution – Cutegory 1

Page 11/11