

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

1 Identification

· Product identifier

· Trade name: Beryllium 10,000 µg/mL in 4% HNO3

· Article number: 10M5-1

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

· Information department: Product safety department

· Emergency telephone number:

INFOTRAC

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: nitric acid

(Contd. on page 2)



Page 2/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

(Contd. of page 1)

beryllium acetate

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H350 May cause cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)



Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

	(Contd. of page 2)			
· Dangerous components:				
7697-37-2	nitric acid	4.0%		
543-81-7	beryllium acetate	1.0%		
· Chemical	· Chemical identification of the substance/preparation			
7732-18-5	water, distilled, conductivity or of similar purity	95.0%		

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:	
7697-37-2 nitric acid	0.16 ppm
· PAC-2:	
7697-37-2 nitric acid	24 ppm
· PAC-3:	
7697-37-2 nitric acid	92 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

7697	-37-2 nitric acid
PEL	Long-term value: 5 mg/m³, 2 ppm
REL	Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm
TLV	Short-term value: 4 ppm Long-term value: 2 ppm

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)



Page 5/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

• Odor: Characteristic
• Odor threshold: Not determined.

(Contd. on page 6)





Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

	(Contd. of	fpag
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	95.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

(Contd. on page 7)



Page 7/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

(Contd. of page 6)

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
543-81-7 beryllium acetate	1	
· NTP (National Toxicology Program)		
543-81-7 beryllium acetate	K	
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)



Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

(Contd. of page 7)

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

1 / 70			
14 1	ransport	into	rmation

· UN-Number

· **DOT**, **ADR**, **IMDG**, **IATA** UN3264

· UN proper shipping name

• **DOT** Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)

· ADR 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(NITRIC ACID)

· IMDG, IATA CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC

ACID)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 8 Corrosive substances

· Label

 \cdot ADR



· Class 8 (C1) Corrosive substances

· Label

(Contd. on page 9)



Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

	(Contd. of pag
IMDG, IATA	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code):	
EMS Number:	F-A,S-B
Segregation groups	Acids
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
•	
DOT	O
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
- · · · -	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O
	(NITRIC ACID), 8, III

US



Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

(Contd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

7697-37-2 nitric acid

Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

543-81-7 beryllium acetate

· TSCA (Toxic Substances Control Act):

7732-18-5 water, distilled, conductivity or of similar purity	ACTIVE
7697-37-2 nitric acid	ACTIVE

Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

543-81-7 beryllium acetate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

543-81-7 beryllium acetate

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05 GHS

· Signal word Danger



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

(Contd. of page 10)

· Hazard-determining components of labeling:

nitric acid

beryllium acetate

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H350 May cause cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

· Date of preparation / last revision 06/17/2022 / -

(Contd. on page 12)



Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Beryllium 10,000 µg/mL in 4% HNO3

(Contd. of page 11)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Carc. 1A: Carcinogenicity - Category 1A

US.