

Page 1/11

# Safety Data Sheet acc. to OSHA HCS

### Printing date 06/14/2022

Reviewed on 06/14/2022

Product identif		
Trade name: <u>T</u>	lium (10,000μg/mL in 4% HCl)	
Article number	10M60-2	
Details of the s	plier of the safety data sheet	
Manufacturer/	pplier:	
High-Purity Sta	lards_	
7221 Investmen	Drive, North Charleston, SC 29418 United States	
Telephone: +1-	13-767-7900	
Fax: +1-843-7	-7906	
highpuritystand	ds.com	
Email: info@hi	puritystandards.com	
Information de	rtment: Product safety department	
Emergency tele	none number:	
NFOTRAC		
Emergency tele	one numbers1-800-535-5053	
Other emergen	telephone numbers 1-352-323-3500	

### 2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Skin Corr. 1AH314 Causes severe skin burns and eye damage.Eye Dam. 1H318 Causes serious eye damage.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

• *Hazard-determining components of labeling: hydrochloric acid* 

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 2)

<sup>-</sup> US



*Printing date 06/14/2022* 

Reviewed on 06/14/2022

Page 2/11

### Trade name: Thulium (10,000µg/mL in 4% HCl)

(Contd. of page 1) If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) *Health* = 3 Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH *Health* = \*3FIRE Fire = 00 **REACTIVITY O** Reactivity = 0• Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable.

• **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
7647-01-0	hydrochloric acid	4.0%
· Chemical identification of the substance/preparation		
7732-18-5	water, distilled, conductivity or of similar purity	95.0%
12036-44-1	thulium oxide	1.0%

### 4 First-aid measures

· Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 3)

US



*Printing date 06/14/2022* 

Reviewed on 06/14/2022

Trade name: Thulium (10,000µg/mL in 4% HCl)

· Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

Mount respiratory protective device.	
Wear protective equipment. Keep unprotected persons away.	
Environmental precautions: Do not allow to enter sewers/ surface or ground water.	
Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing agent.	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Destanting Asting Criteria for Chaming In	
Protective Action Criteria for Chemicals	
	1.8 ppm
PAC-1:	
PAC-1:     7647-01-0   hydrochloric acid     12036-44-1   thulium oxide	
PAC-1: 7647-01-0 hydrochloric acid	
PAC-1:   7647-01-0 hydrochloric acid   12036-44-1 thulium oxide   PAC-2: Image: Constraint of the second secon	30 mg/m <sup>3</sup>
PAC-1:   7647-01-0 hydrochloric acid   12036-44-1 thulium oxide   PAC-2: 7647-01-0   7647-01-0 hydrochloric acid	30 mg/m <sup>3</sup>
PAC-1:   7647-01-0 hydrochloric acid   12036-44-1 thulium oxide   PAC-2: 7647-01-0   7647-01-0 hydrochloric acid   12036-44-1 thulium oxide	30 mg/m <sup>3</sup>

(Contd. on page 4)

Page 3/11

(Contd. of page 2)



Printing date 06/14/2022

Reviewed on 06/14/2022

Trade name: Thulium (10,000µg/mL in 4% HCl)

(Contd. of page 3)

### 7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

#### 7647-01-0 hydrochloric acid

PEL Ceiling limit value: 7 mg/m<sup>3</sup>, 5 ppm

- *REL Ceiling limit value: 7 mg/m<sup>3</sup>, 5 ppm*
- *TLV Ceiling limit value: 2 ppm A4*

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

(Contd. on page 5)

Page 4/11



Page 5/11

## Safety Data Sheet acc. to OSHA HCS

#### *Printing date 06/14/2022*

Reviewed on 06/14/2022

### Trade name: Thulium (10,000µg/mL in 4% HCl)

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

General Information	hemical properties	
Appearance:		
Form:	Liquid	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	



Page 6/11

## Safety Data Sheet acc. to OSHA HCS

Printing date 06/14/2022

Reviewed on 06/14/2022

### Trade name: Thulium (10,000µg/mL in 4% HCl)

		(Contd. of page
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol	/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	95.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

## **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7647-01-0 hydrochloric acid

Oral LD50 900 mg/kg (rabbit)

Primary irritant effect:

- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

(Contd. on page 7)

US



#### Printing date 06/14/2022

Reviewed on 06/14/2022

#### Trade name: Thulium (10,000µg/mL in 4% HCl)

#### • Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7647-01-0 hydrochloric acid

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### **12 Ecological information**

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

(Contd. on page 8)

(Contd. of page 6)

3

Page 7/11



Printing date 06/14/2022

Reviewed on 06/14/2022

Trade name: Thulium (10,000µg/mL in 4% HCl)

(Contd. of page 7)

FINT NT I	
UN-Number DOT	UN3264
ADR, IMDG, IATA	UN1789
	011707
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric acid)
ADR	1789 HYDROCHLORIC ACID mixture
IMDG, IATA	HYDROCHLORIC ACID mixture
Transport hazard class(es)	
DOT	
$\hat{\wedge}$	
J. J.	
CORROSIVE	
8	
Class	8 Corrosive substances
Label	8
ADR	
Ea	
8	
Class	8 (C1) Corrosive substances
Label	8
	-
IMDG, IATA	
8	
Class	8 Corrosive substances
Label	8 Corrosive substances 8
	0
Packing group	
DOT, ĀDR, ĪMDG, IATA	11
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code):	
EMS Number:	F-A,S-B
Segregation groups	Strong acids
Stowage Category	C



*Printing date 06/14/2022* 

Reviewed on 06/14/2022

Trade name: Thulium (10,000µg/mL in 4% HCl)

	(Contd. of page
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 30 L
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1789 HYDROCHLORIC ACID MIXTURE, 8, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

• Section 355 (extremely hazardous substances):

7647-01-0 hydrochloric acid

· Section 313 (Specific toxic chemical listings):

7647-01-0 hydrochloric acid

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

7647-01-0 hydrochloric acid

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 10)

US

Page 9/11



Page 10/11

(Contd. of page 9)

A4

## Safety Data Sheet acc. to OSHA HCS

Printing date 06/14/2022

Reviewed on 06/14/2022

Trade name: Thulium (10,000µg/mL in 4% HCl)

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value)

7647-01-0 hydrochloric acid

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-determining components of labeling: hydrochloric acid · Hazard statements H314 Causes severe skin burns and eye damage. · Precautionary statements Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. *IF INHALED: Remove person to fresh air and keep comfortable for breathing.* If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Department issuing SDS: Environment protection department.

(Contd. on page 11)

US



## Printing date 06/14/2022

Reviewed on 06/14/2022

Trade name: Thulium (10,000µg/mL in 4% HCl)

	(Contd. of page 10
Contact:	
High-Purity Standards	
Tel: 843-767-7900	
Fax: 843-767-7906	
Date of preparation / last revision 06/14/2022 / -	
Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par rout	te (European Agreement Concerning the Internationa
Carriage of Dangerous Goods by Road)	· · · · · · · · · · · · · · · · · · ·
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Skin Corr. 1A: Skin corrosion/irritation – Category 1A	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	

Page 11/11