



## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

### 1 Identification

· Product identifier

· Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

· Article number: 10M65-3

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

*Telephone:* +1-843-767-7900 *Fax:* +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

· Information department: Product safety department

· Emergency telephone number:

**INFOTRAC** 

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Toxicity - Dermal 3 H311 Toxic in contact with skin.



GHS05 Corrosion

Corrosive to Metals 1 H290 May be corrosive to metals.

Skin Corrosion 1A H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. Eye Damage 1



GHS07

Acute Toxicity - Oral 4 H302 Harmful if swallowed.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)



Page 2/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 1)

#### · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

Ammonium Vanadate

hydrofluoric acid

· Hazard statements

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

*If swallowed: Call a poison center/doctor if you feel unwell.* 

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

*IF INHALED:* Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



Health = 3Fire = 0



Page 3/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
7697-37-2 nitric acid	10.0%
7803-55-6 Ammonium Vanadate	1.0%
7664-39-3 hydrofluoric acid	0.49%
· Chemical identification of the substance/preparation	
7732-18-5 water, distilled, conductivity or of similar purity	88.51%

## 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)



Page 4/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 3)

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
7697-37-2		0.16 ppm
7803-55-6	Ammonium Vanadate	$0.01 \text{ mg/m}^3$
· PAC-2:		
7697-37-2	nitric acid	24 ppm
7803-55-6	Ammonium Vanadate	0.11 mg/m³
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7803-55-6	Ammonium Vanadate	80 mg/m³

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)



Page 5/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 4)

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 7697-37-2 nitric acid

- PEL Long-term value: 5 mg/m³, 2 ppm
- REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: (4) NIC-0.025\* ppm

Long-term value: (2) ppm \*inh. fraction + vapor

### 7664-39-3 hydrofluoric acid

PEL Long-term value: 1\* mg/m³, 3 ppm

as F, \*sulfuric acid

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5\* mg/m³, 6\* ppm

\*15-min, as F

TLV Long-term value: 0.5 ppm

Ceiling limit value: 2 ppm

as F; Skin; BEI

#### · Ingredients with biological limit values:

#### 7664-39-3 hydrofluoric acid

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Flourides (background)

10 mg/g creatinine Medium: urine

Time: end of shift Parameter: Flourides (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 6)



Page 6/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 5)

*Immediately remove all soiled and contaminated clothing.* 

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

*Color:* According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 83 °C (181.4 °F)

(Contd. on page 7)





# Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

	(Cont	d. of pa
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.0587 g/cm³ (8.83485 lbs/gal)	
Bulk density:	$1,041 \text{ kg/m}^3$	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	88.5 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	1.0 %	
Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 8)



Page 8/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 7)

· Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7803-55-6 Ammonium Vanadate

Oral LD50 160 mg/kg (rat)

- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

*Toxic* 

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

(Contd. on page 9)



Page 9/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 8)

Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

147			7.0
14L	ransport	unto	rmation

· UN-Number	
-------------	--

· **DOT**, **ADR**, **IMDG**, **IATA** UN2922

· UN proper shipping name

• **DOT** Corrosive liquids, toxic, n.o.s. (Nitric acid, Hydrofluoric acid)
• **ADR** 2922 CORROSIVE LIQUID, TOXIC, N.O.S. (NITRIC AC

2922 CORROSIVE LIQUID, TOXIC, N.O.S. (NITRIC ACID, HYDROFLUORIC ACID)

· IMDG, IATA CORROSIVE LIQUID, TOXIC, N.O.S. (NITRIC ACID,

HYDROFLUORIC ACID)

- · Transport hazard class(es)
- $\cdot DOT$





· Class 8 Corrosive substances

• **Label** 8, 6.1

 $\cdot ADR$ 





Class 8 (CT1) Corrosive substances

(Contd. on page 10)





# Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

	(Contd. of page
Label	8+6.1
· IMDG	
Class	8 Corrosive substances
Label	8/6.1
IATA  Solve	
Class	8 Corrosive substances
Label	8 (6.1)
Packing group DOT, ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups Stowage Category Stowage Code	Warning: Corrosive substances 86 F-A,S-B (SGG1a) Strong acids B SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
ADR Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)





## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 10)

· UN "Model Regulation":

UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S. (NITRIC ACID, HYDROFLUORIC ACID), 8 (6.1), II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

- · Section 313 (Specific toxic chemical listings):
- 7697-37-2 nitric acid

7803-55-6 Ammonium Vanadate

· TSCA (Toxic Substances Control Act):

7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
7697-37-2	nitric acid	ACTIVE
7803-55-6	Ammonium Vanadate	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)



Page 12/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 11)

#### · Hazard pictograms





GHS05 GHS06

- · Signal word Danger
- Hazard-determining components of labeling:

nitric acid

Ammonium Vanadate

hydrofluoric acid

· Hazard statements

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

*If swallowed: Call a poison center/doctor if you feel unwell.* 

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906



Page 13/13

## Safety Data Sheet acc. to OSHA HCS

Printing date 01/27/2023 Reviewed on 01/27/2023

Trade name: Vanadium 10000 µg/mL in 10% HNO3 + Tr HF

(Contd. of page 12)

#### · Date of preparation / last revision 01/27/2023

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Corrosive to Metals 1: Corrosive to metals – Category 1

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Acute Toxicity - Dermal 3: Acute toxicity - Category 3

Skin Corrosion 1A: Skin corrosion/irritation – Category 1A

Eye Damage 1: Serious eye damage/eye irritation – Category 1

HS