

Printing date 08/04/2022

Reviewed on 08/04/2022

Page 1/14

1 Identification · Product identifier · Trade name: Stock Standard · Article number: CLP-CAL-1-A • Details of the supplier of the safety data sheet · Manufacturer/Supplier: High-Purity Standards 7221 Investment Drive, North Charleston, SC 29418 United States *Telephone:* +1-843-767-7900 *Fax:* +1-843-767-7906 highpuritystandards.com Email: info@highpuritystandards.com · Information department: Product safety department • Emergency telephone number: **INFOTRAC** Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Met. Corr.1H290 May be corrosive to metals.Skin Corr. 1AH314 Causes severe skin burns and eye damage.Eye Dam.1H318 Causes serious eye damage.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling: nitric acid*

• *Hazard statements* H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.

• **Precautionary statements** Keep only in original container.

(Contd. on page 2)



Printing date 08/04/2022

Trade name: Stock Standard

Page 2/14

Reviewed on 08/04/2022

(Contd. of page 1) Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. *IF INHALED: Remove person to fresh air and keep comfortable for breathing.* If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 3 Health = 3FIRE 0 Fire = 0**REACTIVITY O** Reactivity = 0• Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients · Chemical characterization: Mixtures · Description: Mixture of the substances listed below with nonhazardous additions. · Dangerous components: 7697-37-2 nitric acid 4.0% · Chemical identification of the substance/preparation 7732-18-5 water distilled conductivity or of similar purity 03 20/

//32-10-3	water, distilled, conductivity or of stimular parity	95.270
7439-95-4	magnesium	0.5%
7440-09-7	potassium	0.5%
7440-23-5	sodium	0.5%
7440-70-2	calcium	0.5%
	(Contd	l. on page 3)



Page 3/14

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: Stock Standard

		(Contd. of page 2)
7429-90-5	aluminium	0.2%
7440-39-3	barium	0.2%
7439-89-6	iron	0.1%
7439-96-5	manganese	0.05%
7440-02-0	nickel	0.05%
7440-48-4	cobalt	0.05%
7440-62-2	vanadium	0.05%
7440-66-6	zinc	0.05%
7440-50-8	copper	0.025%
7440-47-3	chromium	0.02%
7440-41-7	beryllium	0.005%

4 First-aid measures

· Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

US



Printing date 08/04/2022

Trade name: Stock Standard

16 4 1		(Contd. of page
	nd material for containment and cleaning up: th liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
	ilizing agent.	
	ontaminated material as waste according to item 13.	
Ensure ade	equate ventilation.	
	to other sections	
	n 7 for information on safe handling.	
	n 8 for information on personal protection equipment. n 13 for disposal information.	
	Action Criteria for Chemicals	
PAC-1:		
7697-37-2	nitric acid	0.16 ppm
7439-95-4	magnesium	18 mg/m ³
7440-09-7	potassium	2.3 mg/m ³
7440-23-5	sodium	13 mg/m ³
7440-39-3	barium	1.5 mg/m ³
7439-89-6	iron	3.2 mg/m ³
7439-96-5	manganese	3 mg/m ³
7440-02-0	nickel	$4.5 \ mg/m^3$
7440-48-4	cobalt	0.18 mg/m ³
7440-62-2	vanadium	3 mg/m ³
7440-66-6	zinc	6 mg/m³
7440-50-8	copper	3 mg/m ³
7440-47-3	chromium	1.5 mg/m ³
7440-41-7	beryllium	0.0023 mg/n
PAC-2:		
7697-37-2	nitric acid	24 ppm
7439-95-4	magnesium	200 mg/m ³
7440-09-7	potassium	25 mg/m ³
7440-23-5	sodium	140 mg/m ³
7440-39-3	barium	180 mg/m ³
7439-89-6	iron	35 mg/m ³
7439-96-5	manganese	5 mg/m ³
7440-02-0	nickel	50 mg/m³
7440-48-4	cobalt	2 mg/m ³
	vanadium	5.8 mg/m ³
7440-66-6		21 mg/m³
7440-50-8	copper	33 mg/m ³
7110 17 2	chromium	17 mg/m ³

Page 4/14

US

Reviewed on 08/04/2022



Printing date 08/04/2022

Reviewed on 08/04/2022

Page 5/14

Trade name: Stock Standard

7440-41-7	bomilium	(Contd. of page 4 0.025 mg/m ³
		0.025 mg/m ²
<i>PAC-3</i> :		
7697-37-2	nitric acid	92 ppm
7439-95-4	magnesium	1,200 mg/m ³
7440-09-7	potassium	150 mg/m ³
7440-23-5	sodium	870 mg/m ³
7440-39-3	barium	1,100 mg/m
7439-89-6	iron	150 mg/m ³
7439-96-5	manganese	1,800 mg/m ⁻
7440-02-0	nickel	99 mg/m ³
7440-48-4	cobalt	20 mg/m ³
7440-62-2	vanadium	35 mg/m ³
7440-66-6	zinc	120 mg/m ³
7440-50-8	copper	200 mg/m ³
7440-47-3	chromium	99 mg/m ³
7440-41-7	beryllium	$0.1 \ mg/m^3$

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- \cdot Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

(Contd. on page 6)

US



Page 6/14

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: Stock Standard

REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm TLV Short-term value: 4 ppm

Long-term value: 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 7)



Printing date 08/04/2022

Trade name: Stock Standard

Reviewed on 08/04/2022

(Contd. of page 6)

Information on basic physical and c	hemical properties	
General Information		
Appearance: Form:	Liquid	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.06101 g/cm³ (8.85413 lbs/gal)	
Bulk density:	1,046 kg/m ³	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:	60 0 67	
Water:	93.2 %	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal	
Solids content:	2.8 %	

Page 7/14



Page 8/14

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

(Contd. of page 7)

Trade name: Stock Standard

• Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.

· Carcinogenic categories

- Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

IARC (Inte	rnational Agency for Research on Cancer)	
7440-02-0	nickel	21
7440-48-4	cobalt	21
7440-47-3		3
7440-41-7	beryllium	1
NTP (Natio	onal Toxicology Program)	
7440-02-0	nickel	1
7440-48-4	cobalt	1
7440-41-7	beryllium	K
		(Contd. on page



Page 9/14

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

(Contd. of page 8)

Trade name: Stock Standard

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (NITRIC ACID)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)



Printing date 08/04/2022

Trade name: Stock Standard

Reviewed on 08/04/2022

		(Contd. of pag
Transport hazard class(es)		
DOT		
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		
JE SAL		
CORROSIVE		
8		
Class	8 Corrosive substances	
Label	8	
ADR		
$\sim$		
See		
Class	8 (C1) Corrosive substances	
Label	8	
IMDG, IATA		
$\sim$		
J. J		
Class	8 Corrosive substances	
Label	8	
Packing group		
DOT, ADR, IMDG, IATA	III	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Corrosive substances	
Hazard identification number (Kemler co		
EMS Number:	F-A,S-B	
Segregation groups	Acids	
Stowage Category	A	
Stowage Code	SW2 Clear of living quarters.	
Transport in bulk according to Annex II		
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 5 L	
2y	On cargo aircraft only: 60 L	

Page 10/14



Page 11/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: Stock Standard

	(Contd. of page 10
· ADR	
$\cdot$ Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (NITRIC ACID), 8, III

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

7697-37-2	nitric acid	
	13 (Specific toxic chemical listings):	
7697-37-2	nitric acid	
7429-90-5	aluminium	
7440-39-3	barium	
7439-96-5	manganese	
7440-02-0	nickel	
7440-48-4	cobalt	
7440-62-2	vanadium	
7440-66-6	zinc	
7440-50-8	copper	
7440-47-3	chromium	
7440-41-7	beryllium	
TSCA (To	xic Substances Control Act):	
All compo	nents have the value ACTIVE.	
Hazardou	s Air Pollutants	
7439-96-5	manganese	
7440-48-4	cobalt	



Page 12/14

# Safety Data Sheet acc. to OSHA HCS

Reviewed on 08/04/2022

Trade name: Stock Standard

Printing date 08/04/2022

· Proposition	65	(Contd. of page 11)
-	known to cause cancer:	
7440-02-0	nickel	
7440-48-4	cobalt	
7440-41-7	beryllium	
· Chemicals	known to cause reproductive toxicity for females:	
	ingredients is listed.	
· Chemicals	known to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
· Chemicals	known to cause developmental toxicity:	
	ingredients is listed.	
· Carcinoga	iic categories	
-	ronmental Protection Agency)	
7440-39-3		D, CBD(inh), NL(oral)
	manganese	D
7440-66-6	0	D, I, II
7440-50-8	copper	D
7440-47-3		D
7440-41-7	beryllium	B1, K/L(inh), CBD(oral)
• TLV (Thre	shold Limit Value)	
7429-90-5		A4
7440-39-3	barium	A4
7440-02-0	nickel	A5
7440-48-4	cobalt	A3
7440-47-3	chromium	A4
7440-41-7	beryllium	Al
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
7440-02-0	nickel	
7440-41-7	beryllium	

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

(Contd. on page 13)



Printing date 08/04/2022

#### Trade name: Stock Standard

Reviewed on 08/04/2022

(Contd. of page 12)

Page 13/14

· Hazard-determining components of labeling: nitric acid · Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. · Precautionary statements Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Environment protection department.

· Contact: *High-Purity Standards* Tel: 843-767-7900 Fax: 843-767-7906 · Date of preparation / last revision 08/04/2022 / -· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

(Contd. on page 14)



Printing date 08/04/2022

Trade name: Stock Standard

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Met. Corr.1: Corrosive to metals – Category 1 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Page 14/14

Reviewed on 08/04/2022

(Contd. of page 13)

US