

Page 1/18

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

1 Identification

· Product identifier

· Trade name: ICP-MS Calibration Standard-Modified

· Article number: ICP-MSCS-M

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

· Information department: Product safety department

· Emergency telephone number:

INFOTRAC

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: nitric acid

(Contd. on page 2)



Page 2/18

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 1)

hydrogen fluoride

· Hazard statements

H290 May be corrosive to metals.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



3 Health = 3

Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)





Printing date 04/12/2022 Reviewed on 04/12/2022

_		(Contd.	. of page
_	components:		
7697-37-2			2.0%
	hydrogen fluoride		0.49
	dentification of the substance/preparation		
	water, distilled, conductivity or of similar purity	9	7.4789
	calcium carbonate	(0.0019
	S sodium carbonate		0.0019
	barium carbonate		0.0019
	beryllium acetate	(0.0019
	lithium carbonate	(0.0019
	europium(III) oxide	(0.0019
	lanthanum oxide	(0.0019
	thorium dioxide		0.0019
1314-37-0	ytterbium (III) oxide	(0.0019
	Manganese(II) acetate tetrahydrate	(0.0019
7429-90-5	aluminium	(0.0019
7439-89-6	iron	(0.0019
7439-92-1		(0.0019
7439-95-4	magnesium	(0.0019
7439-98-7	molybdenum	(0.0019
7440-02-0	nickel	(0.0019
7440-22-4	l silver	(0.0019
7440-28-0	thallium	(0.0019
7440-36-0	antimony	(0.0019
7440-38-2	? arsenic	(0.0019
7440-43-9	cadmium	(0.0019
7440-47-3	chromium	(0.0019
7440-48-4	l cobalt	(0.0019
7440-50-8	copper copper	(0.0019
7440-66-6	j zinc	(0.0019
7440-69-9	bismuth	(0.0019
7782-49-2	? selenium	(0.0019
7803-55-6	Ammonium Vanadate	(0.0019
10042-76-9	strontium nitrate	(0.0019
10043-35-3	B boric acid	(0.0019
10102-06-4	Uranyl nitrate	(0.0019



Page 4/18

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 3)

12055-62-8 holmium oxide

0.001%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 5)





Printing date 04/12/2022 Reviewed on 04/12/2022

Protective Action Criteria for Chemicals	(Contd. of page
PAC-1:	
7697-37-2 nitric acid	0.16 ppm
7664-39-3 hydrogen fluoride	1.0 ppm
471-34-1 calcium carbonate	45 mg/m^3
497-19-8 sodium carbonate	7.6 mg/m^3
513-77-9 barium carbonate	2.2 mg/m^3
554-13-2 lithium carbonate	3.1 mg/m^3
1308-96-9 europium(III) oxide	15 mg/m^3
1312-81-8 lanthanum oxide	4 mg/m ³
1314-20-1 thorium dioxide	30 mg/m^3
1314-37-0 ytterbium (III) oxide	30 mg/m^3
6156-78-1 Manganese(II) acetate tetrahydrate	13 mg/m^3
7439-89-6 iron	3.2 mg/m^3
7439-92-1 lead	0.15 mg/m
7439-95-4 magnesium	18 mg/m^3
7439-98-7 molybdenum	30 mg/m^3
7440-02-0 nickel	4.5 mg/m^3
7440-22-4 silver	0.3 mg/m^3
7440-28-0 thallium	0.06 mg/m
7440-36-0 antimony	1.5 mg/m ³
7440-38-2 arsenic	1.5 mg/m^3
7440-43-9 cadmium	0.10 mg/m
7440-47-3 chromium	1.5 mg/m ³
7440-48-4 cobalt	0.18 mg/m
7440-50-8 copper	3 mg/m ³
7440-66-6 zinc	6 mg/m³
7440-69-9 bismuth	15 mg/m^3
7782-49-2 selenium	0.6 mg/m^3
7803-55-6 Ammonium Vanadate	0.01 mg/m
10042-76-9 strontium nitrate	5.7 mg/m ³
10043-35-3 boric acid	6 mg/m ³
PAC-2:	
7697-37-2 nitric acid	24 ppm
7664-39-3 hydrogen fluoride	24 ppm
471-34-1 calcium carbonate	210 mg/m
497-19-8 sodium carbonate	83 mg/m^3





Printing date 04/12/2022 Reviewed on 04/12/2022

513-77-9	barium carbonate	(Contd. of page 270 mg/m
554-13-2	lithium carbonate	34 mg/m^3
1308-96-9	europium(III) oxide	170 mg/m
	lanthanum oxide	44 mg/m^3
1314-20-1	thorium dioxide	330 mg/m
1314-37-0	ytterbium (III) oxide	330 mg/m
	Manganese(II) acetate tetrahydrate	22 mg/m^3
7439-89-6	•	35 mg/m^3
7439-92-1	lead	120 mg/m
7439-95-4	magnesium	200 mg/m
	molybdenum	330 mg/m
7440-02-0	· ·	50 mg/m^3
7440-22-4	silver	170 mg/m
7440-28-0	thallium	3.3 mg/m^3
7440-36-0	antimony	13 mg/m³
7440-38-2	-	17 mg/m³
7440-43-9	cadmium	0.76 mg/n
7440-47-3	chromium	17 mg/m³
7440-48-4	cobalt	2 mg/m^3
7440-50-8	copper	33 mg/m ³
7440-66-6		21 mg/m^3
7440-69-9	bismuth	170 mg/m
7782-49-2	selenium	6.6 mg/m^3
7803-55-6	Ammonium Vanadate	0.11 mg/n
10042-76-9	strontium nitrate	62 mg/m^3
10043-35-3	boric acid	23 mg/m^3
<i>PAC-3:</i>		
7697-37-2	nitric acid	92 ppm
7664-39-3	hydrogen fluoride	44 ppm
	calcium carbonate	1,300 mg/m
497-19-8	sodium carbonate	500 mg/m^3
513-77-9	barium carbonate	1,600 mg/m
554-13-2	lithium carbonate	210 mg/m³
1308-96-9	europium(III) oxide	990 mg/m³
	lanthanum oxide	$\frac{270 \text{ mg/m}^3}{\text{mg}}$
1314-20-1	thorium dioxide	2,000 mg/m
1314-37-0	ytterbium (III) oxide	2,000 mg/m





Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

	(Contd. of page
6156-78-1 Manganese(II) acetate tetrahydrate	740 mg/m^3
7439-89-6 iron	150 mg/m^3
7439-92-1 lead	700 mg/m^3
7439-95-4 magnesium	1,200 mg/m
7439-98-7 molybdenum	2,000 mg/m ⁻
7440-02-0 nickel	99 mg/m³
7440-22-4 silver	990 mg/m³
7440-28-0 thallium	20 mg/m^3
7440-36-0 antimony	80 mg/m^3
7440-38-2 arsenic	100 mg/m^3
7440-43-9 cadmium	4.7 mg/m³
7440-47-3 chromium	99 mg/m³
7440-48-4 cobalt	20 mg/m³
7440-50-8 copper	200 mg/m^3
7440-66-6 zinc	120 mg/m^3
7440-69-9 bismuth	990 mg/m³
7782-49-2 selenium	40 mg/m^3
7803-55-6 Ammonium Vanadate	80 mg/m^3
10042-76-9 strontium nitrate	370 mg/m^3
10043-35-3 boric acid	830 mg/m^3

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 8)



Page 8/18

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 7)

· Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 4 ppm Long-term value: 2 ppm

7664-39-3 hydrogen fluoride

PEL Long-term value: 1* mg/m³, 3 ppm

as F, *sulfuric acid

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5* mg/m³, 6* ppm

*15-min, as F

TLV Long-term value: 0.5 ppm

Ceiling limit value: 2 ppm

as F; Skin, BEI

· Ingredients with biological limit values:

7664-39-3 hydrogen fluoride

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Fluorides (background, nonspecific)

10 mg/g creatinine Medium: urine Time: end of shift

Parameter: Fluorides (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 9)



Page 9/18

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 8)

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

· Odor: Characteristic · Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:100 °C (212 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

• **Decomposition temperature:** Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

(Contd. on page 10)





Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

	(Contd. of	pag
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	e r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	97.5 %	
VOC content:	0.00 %	
	0.0g/l/0.00lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7664-39-3 hydrogen fluoride

Oral LD50 1,276 mg/kg (rat)

(Contd. on page 11)





Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 10)

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

•	ernational Agency for Research on Cancer)	
543-81-7	beryllium acetate	4
7439-92-1	lead	2
7440-02-0	nickel	2
7440-38-2	arsenic	
7440-43-9	cadmium	
7440-47-3	chromium	
7440-48-4	cobalt	2
7782-49-2	selenium	
NTP (Nati	onal Toxicology Program)	
543-81-7	beryllium acetate	
1314-20-1	thorium dioxide	
7439-92-1	lead	
7440-02-0	nickel	
7440-38-2	arsenic	
7440-43-9	cadmium	
7440-48-4	cobalt	
OSHA-Ca	(Occupational Safety & Health Administration)	
7440-38-2	arsenic	
7440-43-9	cadmium	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 12)



Page 12/18

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 11)

- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

 anspor		,,,,,,

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name	
$\cdot DOT$	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, Hydrogen
	fluoride)
· ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
	(NITRIC ACID, HYDROGEN FLUORIDE)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC
	ACID, HYDROGEN FLUORIDE)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 8 Corrosive substances

(Contd. on page 13)



Page 13/18



Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

	(Contd. of pag
Label	8
ADR	
Class	8 (C1) Corrosive substances
Label	8
IMDG, IATA	
<u> </u>	
0	
Class	8 Corrosive substances
Label	8
	<u>-</u>
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code):	. 80
EMS Number:	F- A , S - B
Segregation groups	Acids
Stowage Category Stowage Code	A SW2 Clear of living quarters.
	572 Cicar of army quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
	The applicable.
Transport/Additional information:	
DOT Ovantity limitations	On nassangar aircraft/rail: 5 I
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
400	on one go an orage only. To b
ADR Excepted quantities (EQ)	Code: E1
Encepten quantines (12)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 14)





Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 13)

· UN "Model Regulation":

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID, HYDROGEN FLUORIDE), 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

Section 355	(extremely hazardous substances):	
7697-37-2	nitric acid	
7664-39-3	nydrogen fluoride	
Section 313	(Specific toxic chemical listings):	
7697-37-2	nitric acid	
7664-39-3	hydrogen fluoride	
513-77-9	barium carbonate	
543-81-7	beryllium acetate	
554-13-2	lithium carbonate	
1314-20-1	thorium dioxide	
7429-90-5	aluminium	
7439-92-1	lead	
7440-02-0	nickel	
7440-22-4	silver	
7440-28-0	thallium	
7440-36-0	antimony	
7440-38-2	arsenic	
7440-43-9	cadmium	
7440-47-3	chromium	
7440-48-4	cobalt	
7440-50-8	copper	
7440-66-6	zinc	
7782-49-2	selenium	
7803-55-6	Ammonium Vanadate	
10042-76-9	strontium nitrate	
TSCA (Toxi	c Substances Control Act):	
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
7697-37-2	nitric acid	ACTIVE
7664-39-3	hydrogen fluoride	ACTIVE

(Contd. on page 15)





Printing date 04/12/2022 Reviewed on 04/12/2022

		(Contd. of pag
	calcium carbonate	ACTI
	sodium carbonate	ACTI
	barium carbonate	ACTI
	lithium carbonate	ACTI
	europium(III) oxide	ACTI
	lanthanum oxide	ACTI
1314-20-1	thorium dioxide	ACTI
1314-37-0	ytterbium (III) oxide	ACTI
7429-90-5	aluminium	ACTI
7439-89-6	iron	ACTI
7439-92-1	lead	ACTI
7439-95-4	magnesium	ACTI
7439-98-7	molybdenum	ACTI
7440-02-0	nickel	ACTI
7440-22-4	silver	ACTI
7440-28-0	thallium	ACTI
7440-36-0	antimony	ACTI
7440-38-2	arsenic	ACTI
7440-43-9	cadmium	ACTI
7440-47-3	chromium	ACTI
7440-48-4	cobalt	ACTI
7440-50-8	copper	ACTI
7440-66-6	zinc	ACTI
7440-69-9	bismuth	ACTI
7782-49-2	selenium	ACTI
7803-55-6	Ammonium Vanadate	ACTI
10042-76-9	strontium nitrate	ACTI
Hazardous A	lir Pollutants	
7664-39-3 h	ydrogen fluoride	
7439-92-1 l	ead	
7440-48-4 c	obalt	
Proposition		
_	nown to cause cancer:	
	eryllium acetate	
	horium dioxide	
7439-92-1 la		
7440-02-0 n	ickel	





Printing date 04/12/2022 Reviewed on 04/12/2022

7.440.20.2		(Contd. of pag
7440-38-2		
7440-43-9		
7440-48-4		
	known to cause reproductive toxicity for females:	
7439-92-1	lead	
· Chemicals	known to cause reproductive toxicity for males:	
7439-92-1	lead	
7440-43-9	cadmium	
· Chemicals	known to cause developmental toxicity:	
554-13-2	lithium carbonate	
7439-92-1	lead	
7440-43-9	cadmium	
· Carcinoge	nic categories	
_	ronmental Protection Agency)	
	barium carbonate	D, CBD(inh), NL(o
7439-92-1		B2
7440-22-4	silver	D
7440-38-2	? arsenic	A
7440-43-9	Cadmium	BI
7440-47-3	chromium	D
7440-50-8	copper	D
7440-66-6	s zinc	D, I, II
7782-49-2	? selenium	D
10043-35-3	B boric acid	I (oral)
· TLV (Thre	shold Limit Value)	
513-77-9	barium carbonate	
7429-90-5	aluminium	
7439-92-1	lead	
	7 molybdenum	
7440-02-0	nickel	
7440-38-2		
	Cadmium	
	3 chromium	
7440-48-4		
7440-48-4 10043-35-3	B boric acid	



Page 17/18

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 16)

	(Conta. or page 10)
7440-02-0	nickel
7440-38-2	arsenic
7440-43-9	cadmium
10102-06-4	Uranyl nitrate

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- Hazard-determining components of labeling:

nitric acid

hydrogen fluoride

· Hazard statements

H290 May be corrosive to metals.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 18)



Page 18/18

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2022 Reviewed on 04/12/2022

Trade name: ICP-MS Calibration Standard-Modified

(Contd. of page 17)

· Department issuing SDS: Environment protection department.

· Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

· Date of preparation / last revision 04/12/2022 / -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1 Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation - Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1