

Page 1/16

US

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022

Reviewed on 05/31/2022

1 ming une 05/51/2022	100000000000000000000000000000000000000
1 Identification	
· Product identifier	
· Trade name: <u>Stock Standard</u>	
· Article number: INFCS-1-A	
<ul> <li>Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: <u>High-Purity Standards</u></li> <li>7221 Investment Drive, North Charleston, SC 29418 United States</li> <li>Telephone: +1-843-767-7900</li> <li>Fax: +1-843-767-7906</li> <li>highpuritystandards.com</li> <li>Email: info@highpuritystandards.com</li> </ul>	
· Information department: Product safety department	
• <b>Emergency telephone number:</b> INFOTRAC	
Emergency telephone numbers1-800-535-5053	
Other emergency telephone numbers 1-352-323-3500	
GHS08 Health hazard	
Carc. 1A H350 May cause cancer.	
<i>Repr. 1A</i> H360 May damage fertility or the unborn child.	
GHS05 Corrosion	
Met. Corr.1 H290 May be corrosive to metals.	
Skin Corr. 1A H314 Causes severe skin burns and eye damage.	
<i>Eye Dam. 1 H318 Causes serious eye damage.</i>	
• <b>Label elements</b> • <b>GHS label elements</b> The product is classified and labeled according to the G • <b>Hazard pictograms</b>	lobally Harmonized System (GHS).
GHS05 GHS08	
· Signal word Danger	(Contd. on page 2)



Printing date 05/31/2022

#### Trade name: Stock Standard

Page 2/16

Reviewed on 05/31/2022

(Contd. of page 1) · Hazard-determining components of labeling: nitric acid arsenic lead potassium · Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H350 May cause cancer. H360 May damage fertility or the unborn child. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. *IF INHALED: Remove person to fresh air and keep comfortable for breathing.* If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 0*Reactivity* = 0· HMIS-ratings (scale 0 - 4) HEALTH \*3 *Health* = \*3 FIRE 0 Fire = 0**REACTIVITY O** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. (Contd. on page 3) US



Printing date 05/31/2022

Trade name: Stock Standard

· vPvB: Not applicable.

### 3 Composition/information on ingredients

Dangerous	s components:		
7697-37-2	nitric acid		4.0%
7440-09-7	potassium		2.0%
7439-92-1	lead		0.1%
7440-28-0	thallium		0.1%
7440-38-2	arsenic		0.1%
Chemical i	identification of the substance/preparation		<u> </u>
7732-18-5	water, distilled, conductivity or of similar purity	93	8.375%
7782-49-2	selenium	6	0.05%
7440-02-0	nickel	6	0.03%
7440-39-3	barium	6	0.03%
7440-43-9	cadmium	6	0.03%
7440-47-3	chromium	6	0.03%
7440-48-4	cobalt	6	0.03%
7440-50-8	copper	6	0.03%
7440-62-2	vanadium	6	0.03%
7440-66-6	zinc	6	0.03%
7439-96-5	manganese	6	0.02%
7440-41-7	beryllium	6	0.01%
7439-97-6	mercury	0.	.005%

### 4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- *After inhalation:* In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- *After eye contact:* Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

- US -

Page 3/16

*Reviewed on 05/31/2022* 

(Contd. of page 2)



Printing date 05/31/2022

Reviewed on 05/31/2022

Page 4/16

(Contd. of page 3)

Trade name: Stock Standard

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.* 

#### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
   Wear protective equipment. Keep unprotected persons away.
   Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Г

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

• Protective Action Criteria for Chemicals

· PAC-1:		0.14
7697-37-2		0.16 ppm
7440-09-7	potassium	$2.3 mg/m^3$
7439-92-1	lead	0.15 mg/m <sup>3</sup>
7440-28-0	thallium	$0.06 \ mg/m^3$
7440-38-2	arsenic	1.5 mg/m <sup>3</sup>
7782-49-2	selenium	$0.6 \ mg/m^3$
7440-02-0	nickel	$4.5 mg/m^3$
7440-39-3	barium	1.5 mg/m <sup>3</sup>
7440-43-9	cadmium	0.10 mg/m <sup>3</sup>
7440-47-3	chromium	1.5 mg/m <sup>3</sup>
7440-48-4	cobalt	0.18 mg/m <sup>3</sup>
7440-50-8	copper	3 mg/m <sup>3</sup>
		(Contd. on page



Printing date 05/31/2022

*Reviewed on 05/31/2022* 

Trade name: Stock Standard

7440-62-2	vanadium	(Contd. of page 3 mg/m <sup>3</sup>
7440-66-6		6 mg/m <sup>3</sup>
	manganese	3 mg/m <sup>3</sup>
7440-41-7		0.0023 mg/m
7439-97-6	•	0.15 mg/m <sup>3</sup>
<i>PAC-2:</i>		
	nitric acid	24 ppm
7440-09-7		24 ppm 25 mg/m <sup>3</sup>
7439-92-1	*	120 mg/m <sup>3</sup>
7440-28-0		3.3 mg/m <sup>3</sup>
7440-28-0		17 mg/m <sup>3</sup>
7782-49-2		6.6 mg/m <sup>3</sup>
7440-02-0		50 mg/m <sup>3</sup>
7440-02-0		180 mg/m <sup>3</sup>
7440-39-3		0.76 mg/m <sup>3</sup>
7440-43-9		0.70 mg/m <sup>2</sup>
7440-47-3		$\frac{17 \text{ mg/m}^2}{2 \text{ mg/m}^3}$
7440-48-4		33 mg/m <sup>3</sup>
7440-30-8		5.8 mg/m <sup>2</sup>
7440-62-2		
	zinc manganese	$\frac{21 \text{ mg/m}^3}{5 \text{ mg/m}^3}$
		5 mg/m <sup>3</sup> 0.025 mg/m
7440-41-7	-	0.025 mg/m 1.7 mg/m <sup>3</sup>
7439-97-6	mercury	1.7 mg/m <sup>3</sup>
PAC-3:		
	nitric acid	92 ppm
7440-09-7	-	150 mg/m <sup>3</sup>
7439-92-1		700 mg/m <sup>3</sup>
7440-28-0		20 mg/m <sup>3</sup>
7440-38-2		100 mg/m <sup>3</sup>
7782-49-2		40 mg/m <sup>3</sup>
7440-02-0		99 mg/m <sup>3</sup>
7440-39-3		1,100 mg/m
7440-43-9		$4.7 mg/m^3$
7440-47-3		99 mg/m <sup>3</sup>
7440-48-4		20 mg/m <sup>3</sup>
7440-50-8		200 mg/m <sup>3</sup>
7440-62-2	vanadium	35 mg/m <sup>3</sup>

Page 5/16



Page 6/16

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022

Reviewed on 05/31/2022

Trade name: Stock Standard

		(Contd. of page 5)
7440-66-6	zinc	120 mg/m <sup>3</sup>
7439-96-5	manganese	$1,800 \text{ mg/m}^3$
7440-41-7	beryllium	$0.1 mg/m^3$
7439-97-6	mercury	8.9 mg/m <sup>3</sup>

### 7 Handling and storage

#### · Handling:

- · Precautions for safe handling
- *Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.*
- Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

7697	-37-2 nitric acid
PEL	Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
REL	Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm
TLV	Short-term value: 4 ppm Long-term value: 2 ppm
7440	-38-2 arsenic
	Long-term value: 0.5* 0.01** mg/m <sup>3</sup> as As; *organic**inorg. compds.; 29 CFR 1910.1018
	Ceiling limit value: 0.002 mg/m <sup>3</sup> as As; 15min; See Pocket Guide App. A
	Long-term value: 0.01 mg/m <sup>3</sup> as As; BEI, A1
	(Contd. on page 7)



Printing date 05/31/2022

Reviewed on 05/31/2022

Trade name: Stock Standard

(Contd. of page 6) · Ingredients with biological limit values: 7440-38-2 arsenic BEI 35 µg As/L Medium: urine Time: end of workweek Parameter: Inorganic arsenic plus methylated metabolites (background) • Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands: Protective gloves *The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.* Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles

Page 7/16

(Contd. on page 8)



Printing date 05/31/2022

Trade name: Stock Standard

Reviewed on 05/31/2022

(Contd. of page 7)

Information on basic physical and a	chemical properties	
General Information		
Appearance: Form:	Liquid	
Form: Color:	Liquid According to product specification	
Odor:	<i>Characteristic</i>	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.06255 g/cm³ (8.86698 lbs/gal)	
Bulk density:	1,050 kg/m <sup>3</sup>	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	93.4%	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal	
Solids content:	2.6 %	

Page 8/16



Page 9/16

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022

Reviewed on 05/31/2022

(Contd. of page 8)

Trade name: Stock Standard

• Other information

No further relevant information available.

### **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:
- 7440-38-2 arsenic

Oral LD50 763 mg/kg (rat)

- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

#### · Carcinogenic categories

· IARC (Inte	ernational Agency for Research on Cancer)	
7439-92-1	lead	2B
7440-38-2	arsenic	1
7782-49-2	selenium	3
7440-02-0	nickel	2B
7440-43-9	cadmium	1
7440-47-3	chromium	3
7440-48-4	cobalt	2B
	(Contd. on pa	ge 10)



Page 10/16

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022

Reviewed on 05/31/2022

Trade name: Stock Standard

7440-41-7		d. of page 9)
7439-97-6		3
· NTP (Natio	onal Toxicology Program)	
7439-92-1	lead	R
7440-38-2	arsenic	K
7440-02-0	nickel	R
7440-43-9	cadmium	K
7440-48-4	cobalt	R
7440-41-7	beryllium	K
· OSHA-Ca	(Occupational Safety & Health Administration)	
7440-38-2	arsenic	
7440-43-9	cadmium	

# **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

• General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- *Recommendation:* Disposal must be made according to official regulations.

(Contd. on page 11)



Printing date 05/31/2022

Reviewed on 05/31/2022

Trade name: Stock Standard

(Contd. of page 10)

UN-Number	
DOT, ADR, IMDG, IATA	UN3264
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O. (NITRIC ACID)
IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRI ACID)
Transport hazard class(es)	
DOT	
$\wedge$	
CORROSIVE	
8	
Class	8 Corrosive substances
Label	8
ADR	
$\wedge$	
8	
Class	8 (C1) Corrosive substances
Label	8
IMDG, IATA	
$\wedge$	
8	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, ĂĎR, ÎMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code).	
EMS Number:	F-A,S-B
Segregation groups Stowage Category	Acids A

Page 11/16



Page 12/16

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022

Reviewed on 05/31/2022

Trade name: Stock Standard

	(Contd. of page 11
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (NITRIC ACID), 8, III

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

7697-37-2	nitric acid
• Section 31	3 (Specific toxic chemical listings):
7697-37-2	nitric acid
7439-92-1	lead
7440-28-0	thallium
7440-38-2	arsenic
7782-49-2	selenium
7440-02-0	nickel
7440-39-3	barium
7440-43-9	cadmium
7440-47-3	chromium
7440-48-4	cobalt
7440-50-8	copper
7440-62-2	vanadium

US



Page 13/16

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022

Reviewed on 05/31/2022

Trade name: Stock Standard

		(Contd. of page 12)
7440-66-6		
	manganese	
7440-41-7		
7439-97-6	mercury	
	ic Substances Control Act):	
All compon	ents have the value ACTIVE.	
· Hazardous	Air Pollutants	
7439-92-1	lead	
7440-48-4		
7439-96-5	manganese	
· Proposition		
	known to cause cancer:	
7439-92-1	lead	
7440-38-2	arsenic	
7440-02-0		
7440-43-9	cadmium	
7440-48-4		
7440-41-7	beryllium	
	known to cause reproductive toxicity for females:	
7439-92-1	lead	
	known to cause reproductive toxicity for males:	
7439-92-1	lead	
7440-43-9	cadmium	
· Chemicals	known to cause developmental toxicity:	
7439-92-1	lead	
7440-43-9	cadmium	
7439-97-6	mercury	
· Carcinoger	iic categories	
-	ronmental Protection Agency)	
7439-92-1	lead	<i>B2</i>
7440-38-2	arsenic	A
7782-49-2	selenium	D
7440-39-3	barium	D, CBD(inh), NL(oral)
7440-43-9	cadmium	B1
7440-47-3	chromium	D
7440-50-8	copper	D
7440-66-6	zinc	D, I, II
		(Contd. on page 14)



Page 14/16

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022

Reviewed on 05/31/2022

Trade name: Stock Standard

		(Contd. of page 13)		
7439-96-5	manganese	D		
7440-41-7	beryllium	B1, K/L(inh), CBD(oral)		
7439-97-6	mercury	D		
· TLV (Threshold Limit Value)				
7439-92-1	lead	A3		
7440-38-2	arsenic	Al		
7440-02-0	nickel	A5		
7440-39-3	barium	A4		
7440-43-9	cadmium	A2		
7440-47-3	chromium	A4		
7440-48-4	cobalt	A3		
7440-41-7	beryllium	Al		
7439-97-6	mercury	A4		
NIOSH-Ca (National Institute for Occupational Safety and Health)				
7440-38-2	arsenic			
7440-02-0	nickel			
7440-43-9	cadmium			
7440-41-7	beryllium			

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

Hazard-determining components of labeling: nitric acid arsenic lead potassium
Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H350 May cause cancer. H360 May damage fertility or the unborn child.
Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Do not breathe dusts or mists.

(Contd. on page 15)

US



#### Printing date 05/31/2022

Trade name: Stock Standard

Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Absorb spillage to prevent material damage.
Store locked up.
Store in corrosive resistant container with a resistant inner liner.
Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906 · Date of preparation / last revision 05/31/2022 / -• Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

Page 15/16

Reviewed on 05/31/2022

(Contd. of page 14)

(Contd. on page 16) US



Printing date 05/31/2022

Trade name: Stock Standard

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Met. Corr. 1: Corrosive to metals – Category 1 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Carc. 1A: Carcinogenicity – Category 1A Repr. 1A: Reproductive toxicity – Category 1A Page 16/16

Reviewed on 05/31/2022

(Contd. of page 15)

US