

# **Continuing Check Verification Standard 3**

## **High-Purity Standards**

Catalogue number: CCV-3 Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

## SECTION 1 IDENTIFICATION

## **Product Identifier**

Product name	Continuing Check Verification Standard 3
Synonyms	CCV-3
Proper shipping name	Hydrochloric acid
Other means of identification	CCV-3

## Recommended use of the chemical and restrictions on use

Relevant identified uses Use according to manufacturer's directions.

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

## Emergency phone number

• • •	
Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

#### SECTION 2 HAZARD(S) IDENTIFICATION

Classification	Gas under Pressure (Liquefied gas), Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1
el elements	
Hazard pictogram(s)	

#### Hazard statement(s)

H280	Contains gas under pressure; may explode if heated.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

## Hazard(s) not otherwise specified

Not Applicable

Chemwatch Hazard Alert Code: 3

Issue Date: 06/03/2017 Print Date: 06/03/2017

S.GHS.USA.EN

Catalogue number: CCV-3 Version No: 1.1

## **Continuing Check Verification Standard 3**

#### Precautionary statement(s) Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
Precautionary statement(s)	) Response	
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
Precautionary statement(s)	) Storage	
Precautionary statement(s)		
Precautionary statement(s) P405	) Storage Store locked up.	
	Store locked up.	
P405	Store locked up.	

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
7647-01-0	2	hydrochloric acid
7732-18-5	balance	water
7440-57-5	0.01	gold
7440-05-3	0.01	palladium
7440-06-4	0.01	platinum

#### **SECTION 4 FIRST-AID MEASURES**

#### Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: <ul> <li>Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>Transport to hospital or doctor without delay.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin or hair contact occurs:</li> <li>Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>Quickly remove all contaminated clothing, including footwear.</li> <li>Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>Transport to hospital, or doctor.</li> </ul>
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> <li>Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.</li> <li>Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</li> <li>As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</li> <li>This must definitely be left to a doctor or person authorised by him/her.</li> <li>(ICSC13719)</li> </ul>
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

#### Most important symptoms and effects, both acute and delayed

See Section 11

## Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- ▶ Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- ▶ Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- ▶ Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.
- INGESTION:
- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.

Chemwatch: 9-405954 Catalogue number: CCV-3

Version No: 1.1

#### **Continuing Check Verification Standard 3**

• DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.

Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.

- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

#### SKIN:

Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.

Deep second-degree burns may benefit from topical silver sulfadiazine.

#### EYE:

Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.

- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

## SECTION 5 FIRE-FIGHTING MEASURES

#### Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

## Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

#### Special protective equipment and precautions for fire-fighters

Fire Fighting	
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered to be a significant fire risk.</li> <li>Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>May emit corrosive, poisonous fumes. May emit acrid smoke.</li> </ul>

#### SECTION 6 ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</li> <li>Check regularly for spills and leaks.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours/ aerosols or dusts and avoid contact with skin and eyes.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

#### Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.</li> <li>Avoid smoking, naked lights or ignition sources.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

ue number: CCV-3	Continuing Check Verification Standard 3 Print Date: 06/03/2
No: <b>1.1</b>	
Suitable container	<ul> <li>DO NOT use aluminium or galvanised containers</li> <li>Check regularly for spills and leaks</li> <li>For low viscosity materials</li> <li>Drums and jerricans must be of the non-removable head type.</li> <li>Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):</li> <li>Removable head packaging;</li> <li>Cans with friction closures and</li> <li>low pressure tubes and cartridges may be used.</li> </ul>
	Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	<ul> <li>Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.</li> <li>Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces.</li> <li>The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.</li> <li>The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.</li> <li>Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.</li> <li>Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.</li> <li>Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitriles, sulfides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H2S and SO3), dithionites (SO2), and even carbonates.</li> <li>Acids often catalyse (increase the rate of) chemical reactions.</li> <li>Hydrogen chloride:</li> <li>reacts strongly with strong oxidisers (releasing chlorine gas), acetic anhydride, caesium cyanotridecahydrodecaborate(2-), ethylidene difluoride, hexalithiu disilicide, metal acetylide, sodium, silicon dioxide, tetraselenium tetranitride, and many organic materials</li> <li>is incompatible with alkaline materials, acetic anhydride, acetylides, isocyanates, metals, metal oxides, carbonates, cyanides, chlorosulfonic acid, ethylenediamine, ethyleneimine, epichlorohydrin, formaldehyde, isocyanates, metals, metal oxides, and hydroxides, metal acetylides, output explicites, output explicites, potassium permanganate, perchloric acid, pho</li></ul>
	<ul> <li>attacks most metals forming flammable hydrogen gas, and some plastics, rubbers and coatings</li> <li>reacts with zinc, brass, galvanised iron, aluminium, copper and copper alloys</li> </ul>

## **Control parameters**

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	7 mg/m3 / 5 ppm	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	hydrochloric acid	Anhydrous hydrogen chloride; Aqueous hydrogen chloride (i.e., Hydrochloric acid, Muriatic acid) [Note: Often used in an aqueous solution.]	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available
US ACGIH Threshold Limit Values (TLV)	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	2 ppm	Not Available
US NIOSH Recommended Exposure Limits (RELs)	platinum	Platinum black, Platinum metal, Platinum sponge	1 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	т	EEL-1	TEEL-2	TEEL-3
hydrochloric acid	Hydrogen chloride; (Hydrochloric acid)	Hydrogen chloride; (Hydrochloric acid) New York (Hydrochloric acid)			Not Available
hydrochloric acid	Deuterochloric acid; (Deuterium chloride)	Deuterochloric acid; (Deuterium chloride) 1.			100 ppm
gold	Gold	0.4	46 mg/m3	5.1 mg/m3	30 mg/m3
palladium	Palladium	6	mg/m3	66 mg/m3	400 mg/m3
platinum	Platinum	3	mg/m3	33 mg/m3	200 mg/m3
Ingredient	Original IDLH		Revised IDLH		
hydrochloric acid	100 ppm		50 ppm		
water	Not Available		Not Available		
gold	Not Available		Not Available		
palladium	Not Available		Not Available		
platinum	N.E. / N.E.		4 mg/m3		

## Exposure controls

Appropriate engineering controls Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

## **Continuing Check Verification Standard 3**

Personal protection Eye and face protection Skin protection Hands/feet protection Body protection Other protection	<ul> <li>Safety glasses with unperforated side shields may be used where continuous eye protection is or where complete eye protection is needed such as when handling bulk-quantities, where there is pressure.</li> <li>Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; Q</li> <li>Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary (</li> <li>Alternatively a gas mask may replace splash goggles and face shields.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritilenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> <li>See Hand protection below</li> <li>Insulated gloves:</li> <li>NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upor be placed in the liquid; they provide only short-term protection from accidental contact with the liquid.</li> <li>See Other protection below</li> <li>Overalls.</li> <li>PVC Apron.</li> <li>PVC protective suit may be required if exposure severe.</li> <li>Eyewash unit.</li> <li>Ensure there is ready access to a safety shower.</li> </ul>	a danger of splashing, or if the main goggles must be properly fitted. protection of eyes; these afford face ants. A written policy document, de a review of lens absorption and ad trained in their removal and suitable contact lens as soon as practicable rafter workers have washed hands	terial may be under e protection. escribing the wearing of Isorption for the class of le equipment should be le. Lens should be remov s thoroughly. [CDC NIOS			
Eye and face protection Skin protection Hands/feet protection	<ul> <li>where complete eye protection is needed such as when handling bulk-quantities, where there is pressure.</li> <li>Chemical goggles whenever there is a danger of the material coming in contact with the eyes; of Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary posterior of the material coming in contact with the eyes; of Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irrit lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> <li>See Hand protection below</li> <li>Insulated gloves:</li> <li>NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upor be placed in the liquid; they provide only short-term protection from accidental contact with the liquid. See Other protection below</li> </ul>	a danger of splashing, or if the main goggles must be properly fitted. protection of eyes; these afford face ants. A written policy document, de a review of lens absorption and ad trained in their removal and suitable contact lens as soon as practicable rafter workers have washed hands	terial may be under e protection. escribing the wearing of Isorption for the class of le equipment should be le. Lens should be remov s thoroughly. [CDC NIOS			
Eye and face protection Skin protection Hands/feet protection	<ul> <li>where complete eye protection is needed such as when handling bulk-quantities, where there is pressure.</li> <li>Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; g</li> <li>Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary p</li> <li>Alternatively a gas mask may replace splash goggles and face shields.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irrit.</li> <li>Ienses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> <li>See Hand protection below</li> <li>Insulated gloves:</li> <li>NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upor be placed in the liquid; they provide only short-term protection from accidental contact with the liquid.</li> </ul>	a danger of splashing, or if the main goggles must be properly fitted. protection of eyes; these afford face ants. A written policy document, de a review of lens absorption and ad trained in their removal and suitable contact lens as soon as practicable rafter workers have washed hands	terial may be under e protection. escribing the wearing of Isorption for the class of le equipment should be le. Lens should be remov s thoroughly. [CDC NIOS			
Eye and face protection	<ul> <li>where complete eye protection is needed such as when handling bulk-quantities, where there is pressure.</li> <li>Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; g</li> <li>Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary j</li> <li>Alternatively a gas mask may replace splash goggles and face shields.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irriti lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/INZS 1336 or national equivalent]</li> <li>See Hand protection below</li> <li>Insulated gloves:</li> <li>NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upor</li> </ul>	a danger of splashing, or if the main goggles must be properly fitted. protection of eyes; these afford face ants. A written policy document, de a review of lens absorption and ad trained in their removal and suitable contact lens as soon as practicable rafter workers have washed hands	terial may be under e protection. escribing the wearing of Isorption for the class of le equipment should be le. Lens should be remov s thoroughly. [CDC NIOS			
Eye and face protection	<ul> <li>where complete eye protection is needed such as when handling bulk-quantities, where there is pressure.</li> <li>Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; g</li> <li>Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary is Alternatively a gas mask may replace splash goggles and face shields.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritic lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>	a danger of splashing, or if the main goggles must be properly fitted. protection of eyes; these afford face ants. A written policy document, de a review of lens absorption and ad trained in their removal and suitab contact lens as soon as practicabl	terial may be under e protection. escribing the wearing of Isorption for the class of e equipment should be le. Lens should be remov			
	<ul> <li>where complete eye protection is needed such as when handling bulk-quantities, where there is pressure.</li> <li>Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; g</li> <li>Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary  </li> <li>Alternatively a gas mask may replace splash goggles and face shields.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irrit lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only</li> </ul>	a danger of splashing, or if the main goggles must be properly fitted. protection of eyes; these afford face ants. A written policy document, de a review of lens absorption and ad trained in their removal and suitab contact lens as soon as practicabl	terial may be under e protection. escribing the wearing of Isorption for the class of e equipment should be le. Lens should be remov			
Personal protection						
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extuant of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point distance from the contaminating source. The air velocity at the extraction fan, for example, should be a solvents generated in a tank 2 meters distant from the extraction point. Other mechanical consideration apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when	raction pipe. Velocity generally dec should be adjusted, accordingly, a a minimum of 1-2 m/s (200-400 f/m ons, producing performance deficit	after reference to hin) for extraction of ts within the extraction			
	4: Large hood or large air mass in motion	4: Small hood-local control only				
	2: Contaminants of low toxicity or of nuisance value only. 3: Intermittent, low production.	<ul><li>2: Contaminants of high toxicity</li><li>3: High production, heavy use</li></ul>	/			
	1: Room air currents minimal or favourable to capture 1: Disturbing room air currents					
	Lower end of the range	Upper end of the range				
	Within each range the appropriate value depends on:					
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial ve air motion).	locity into zone of very high rapid	2.5-10 m/s (500-2000 f/min.)			
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas dis zone of rapid air motion)	scharge (active generation into	1-2.5 m/s (200-500 f/min.)			
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers acid fumes, pickling (released at low velocity into zone of active generation)	s, welding, spray drift, plating	0.5-1 m/s (100-200 f/min.)			
	solvent, vapours, degreasing etc., evaporating from tank (in still air).		0.25-0.5 m/s (50-100 f/min.)			
	Type of Contaminant: Air Speed:					
	Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the turn, determine the "capture velocities" of fresh circulating air required to effectively remove the conta					
	Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensu An approved self contained breathing apparatus (SCBA) may be required in some situations.					
	An approved self contained breathing apparatus (SCBA) may be required in some situations.	d properly. The design of a ventilation	on system must match			

## **Respiratory protection**

Type B-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

76b-p()

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
	· · · · · · · · ·		
Physical state	Liquified Gas	Relative density (Water = 1)	Not Available

Page 6 of 11

## Continuing Check Verification Standard 3

Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. Hydrogen chloride (HCI) vapour or fumes present a hazard from a single acute exposure. Exposures of 1300 to 2000 ppm have been lethal to humans in a few minutes. Inhalation of HCI may cause choking, coughing, burning sensation and may cause ulceration of the nose, throat and larynx. Fluid on the lungs followed by generalised lung damage may follow. Breathing of HCI vapour may aggravate asthma and inflammatory or fibrotic pulmonary disease. High concentrations cause necrosis of the tracheal and bronchial epithelium, pulmonary oedema, atelectasis and emphysema and damage to the pulmonary blood vessels and liver.					
Ingestion	Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.					
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.					
Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely.					
Chronic	Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Chronic minor exposure to hydrogen chloride (HCI) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and gums; and ulceration of the muccus membranes of the nose. Workers exposed to hydrochloric acid suffered from stomach inflammation and a number of cases of chronic bronchitis (airway inflammation) have also been reported. Repeated or prolonged exposure to dilute solutions of hydrogen chloride may cause skin inflammation.					
Continuing Check Verification Standard 3	TOXICITY     IRRITATION       Not Available     Not Available					

## **Continuing Check Verification Standard 3**

	ΤΟΧΙCITY		IDDITATION		
	TOXICITY		IRRITATION		
hydrochloric acid	Inhalation (rat) LC50: 781 ppm/1hr <sup>[2]</sup>	Eye (rabbit): 5mg/30s - mild			
	Oral (rat) LD50: 900 mg/kg <sup>[2]</sup>				
water	TOXICITY	IRRITA	FION		
water	Not Available	Not Ava	ilable		
	TOXICITY	IRRITATION			
gold	Not Available	Not Available			
	TOXICITY	IRRITA	TION		
palladium	Not Available	Not Ava	vailable		
	TOXICITY	IRRITA	TION		
platinum	Not Available	Not Ava	ilable		
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances				

HYDROCHLORIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ends. For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. The material may be irritating to the eye, with prolonged contact causing inflammation. The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans.						
GOLD	Substance has been investigated as a tumorigen by implantat	ubstance has been investigated as a tumorigen by implantation in rodents:					
PLATINUM	The following information refers to contact allergens as a grou	up and may not be specific to this pro	oduct.				
HYDROCHLORIC ACID & WATER & PALLADIUM & PLATINUM	No significant acute toxicological data identified in literature search.						
Acute Toxicity	$\otimes$	Carcinogenicity	0				
Skin Irritation/Corrosion	×	✓ Reproductivity					
Serious Eye Damage/Irritation	✓ STOT - Single Exposure						
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0				
Mutagenicity	$\otimes$	Aspiration Hazard	$\odot$				
		Ŭ 🗸	<ul> <li>Data available but does not fill the criteria for classification</li> <li>Data available to make classification</li> <li>Data Not Available to make classification</li> </ul>				

## SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Continuing Check	ENDPOINT		TEST DURATION (HR)	SPECIES VALUE		E SOURCE		CE	
Verification Standard 3	Not Applicable		Not Applicable		Not Applicable	Not Applicable		Not Applicable	
							1		
	ENDPOINT	TEST DURATION (HR)		SPECI	SPECIES		VALUE		SOURCE
	LC50	96	96		Fish		70.057mg/L		3
hydrochloric acid	EC50	96		Algae	Algae or other aquatic plants		344.947mg/L		3
EC50 NOEC		9.33	9.33		Fish		0.014000mg/L		4
		0.08	0.08		Fish		10mg/L 4		4
			1		1				
water	ENDPOINT		TEST DURATION (HR)		SPECIES	VALUE		SOUR	CE
Waler	Not Applicable		Not Applicable		Not Applicable	Not Appli	cable	Not Ap	plicable
			1		1				
gold	ENDPOINT		TEST DURATION (HR)		SPECIES	VALUE		SOUR	CE
golu	Not Applicable		Not Applicable		Not Applicable Not App		cable	Not Ar	plicable

#### **Continuing Check Verification Standard 3**

palladium	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
panadium	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
platinum	Not Applicable				
	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Legend:		Toxicity Data 2. Europe ECHA Registe	0	1	5
	(QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

For Platinum Group Metals (PGM):

Environmental Fate: The PGMs are a group of rare elements including platinum, palladium, rhodium, ruthenium, iridium, and osmium. Platinum group metals emitted as particles, from catalytic converters, behave inertly and have limited mobility in soil so there would appear to be negligible risk to health, groundwater and the environment. However, it is possible for transformations to soluble, biologically active forms to occur. Besides terrestrial habitats, these metals are also introduced into aquatic biotopes via road runoff, where they accumulate in sediments of lakes and rivers.

Atmospheric Fate: These substances are not expected to partition to the atmosphere.

Terrestrial Fate: Once released to moist soils, their fate depends on solubility and breakup in the presence of water. Environmental processes, (such as oxidation and the presence of acids or bases), may transform insoluble metals to more soluble ionic forms. Microbiological processes may also transform insoluble metals to more soluble forms. Such ionic species may bind to certain soil components or sorb to solid particles in aquatic or aqueous media.

When released to dry soil most metals will exhibit limited mobility and remain in the upper layer; some will leach locally into groundwater/surface water ecosystems when soaked by rain or melt ice. Aquatic Fate: PGMs can accumulate in lake and river sediment where it is introduced during runoff events. Solubility of PGMs can increase in the presence of natural complexing agents, such as humic acids. Platinum is found as platinate in fresh water or bound to organic matter as platinum chloride. In seawater PtCl42- is also seen. Platinum can be assimilated by algae and plankton in the aquatic environment, and is released once the organic material degrades. It is not strongly bound to particles. Once released to surface waters, their fate depends on solubility and chemical breakup in water. A significant proportion of dissolved/ sorbed metals will end up in sediments through the settling of suspended particles. The remaining metal ions can then be taken up by aquatic organisms. Environmental processes may also be important in changing solubilities.

Ecotoxicity: These substances are expected to accumulate in the tissues of living organisms exposed to the substances. PGMs are harmful to aquatic organisms. Even though many metals show few toxic effects at normal pH, transformation of these substances may result in new or magnified effects. These substances are toxic to tubifex worms.

Prevent, by any means available, spillage from entering drains or water courses. **DO NOT** discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
hydrochloric acid	LOW	LOW
water	LOW	LOW

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
hydrochloric acid	LOW (LogKOW = 0.5392)
water	LOW (LogKOW = -1.38)

#### Mobility in soil

Ingredient	Mobility
hydrochloric acid	LOW (KOC = 14.3)
water	LOW (KOC = 14.3)

## SECTION 13 DISPOSAL CONSIDERATIONS

Product / Packaging disposal	<ul> <li>Recycle wherever possible.</li> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurrying in water; Neutralisation followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material)</li> <li>Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul>
---------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## SECTION 14 TRANSPORT INFORMATION

## Labels Required



Marine Pollutant

## **Continuing Check Verification Standard 3**

## Land transport (DOT)

• • • •	
UN number	1789
UN proper shipping name	Hydrochloric acid
Transport hazard class(es)	Class8SubriskNot Applicable
Packing group	II Contraction of the second sec
Environmental hazard	Not Applicable
Special precautions for user	Hazard Label8Special provisions386, A3, A6, B3, B15, B133, IB2, N41, T8, TP2

#### Air transport (ICAO-IATA / DGR)

UN number	1789	
UN proper shipping name	Hydrochloric acid	
Transport hazard class(es)	ICAO/IATA Class8ICAO / IATA SubriskNot ApplicableERG Code8L	
Packing group	П	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions         Cargo Only Packing Instructions         Cargo Only Maximum Qty / Pack         Passenger and Cargo Packing Instructions         Passenger and Cargo Maximum Qty / Pack         Passenger and Cargo Limited Quantity Packing Instructions         Passenger and Cargo Limited Maximum Qty / Pack	A3A803 855 30 L 851 1 L Y840 0.5 L

## Sea transport (IMDG-Code / GGVSee)

UN number	1789
UN proper shipping name	HYDROCHLORIC ACID
Transport hazard class(es)	IMDG Class8IMDG SubriskNot Applicable
Packing group	Ш
Environmental hazard	Not Applicable
Special precautions for user	EMS NumberF-A, S-BSpecial provisionsNot ApplicableLimited Quantities1 L

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

#### **SECTION 15 REGULATORY INFORMATION**

Safety, health and environmental regulations / legislation specific for the substance or mixture

HYDROCHLORIC ACID(7647-01-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Catalogue number: CCV-3

Version No: 1.1

Continued...

## **Continuing Check Verification Standard 3**

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
(CRELs)	US ACGIH Threshold Limit Values (TLV)
US - California Permissible Exposure Limits for Chemical Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Hawaii Air Contaminant Limits	US Clean Air Act - Hazardous Air Pollutants
US - Idaho - Limits for Air Contaminants	US CWA (Clean Water Act) - List of Hazardous Substances
US - Massachusetts - Right To Know Listed Chemicals	US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals
US - Michigan Exposure Limits for Air Contaminants	US EPCRA Section 313 Chemical List
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	US SARA Section 302 Extremely Hazardous Substances
US - Rhode Island Hazardous Substance List	US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	
WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
GOLD(7440-57-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory	
PALLADIUM(7440-05-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Oregon Permissible Exposure Limits (Z-1)
Monographs	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US - Washington Permissible exposure limits of air contaminants
(CRELs)	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Hawaii Air Contaminant Limits	
US - Michigan Exposure Limits for Air Contaminants	
PLATINUM(7440-06-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contamina
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Idaho - Limits for Air Contaminants	Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US - Washington Permissible exposure limits of air contaminants
US - Michigan Exposure Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV)
US - Pennsylvania - Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### Federal Regulations

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes	
Delayed (chronic) health hazard	No	
Fire hazard	No	
Pressure hazard	Yes	
Reactivity hazard	No	
US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)		

Name	Reportable Quantity in Pounds (Ib)	Reportable Quantity in kg
Hydrochloric acid	5000	2270

#### State Regulations

#### US. CALIFORNIA PROPOSITION 65

None Reported Status National Inventory Australia - AICS Υ Canada - DSL Y Canada - NDSL N (platinum; hydrochloric acid; water; gold; palladium) China - IECSC Y Europe - EINEC / ELINCS / Y NLP Japan - ENCS N (platinum; water; gold; palladium) Korea - KECI Υ Y New Zealand - NZIoC

Page 11 of 11

#### Issue Date: 06/03/2017 Print Date: 06/03/2017

#### **Continuing Check Verification Standard 3**

Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

#### **SECTION 16 OTHER INFORMATION**

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

#### This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

