

## QCS-7-M

## **High-Purity Standards**

Catalogue number: QCS-7M

Version No: 4.6

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: **06/03/2017**Print Date: **06/03/2017**S GHS USA EN

#### **SECTION 1 IDENTIFICATION**

#### **Product Identifier**

Product name	QCS-7-M	
Synonyms	000μg/mL Potassium 100μg/mL Aluminum, Barium, Boron, Silica, Sodium 50μg/mL Silver	
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (contains nitric acid)	
Other means of identification	QCS-7M	

#### Recommended use of the chemical and restrictions on use

Relevant identified uses Use according to manufacturer's directions.

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

#### **Emergency phone number**

• • •	
Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

#### **SECTION 2 HAZARD(S) IDENTIFICATION**

#### Classification of the substance or mixture

Classification

Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1

## Label elements

Hazard pictogram(s)



SIGNAL WORD

DANGER

#### Hazard statement(s)

• •	
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

#### Hazard(s) not otherwise specified

Not Applicable

#### Precautionary statement(s) Prevention

Page 2 of 13

QCS-7-M

Issue Date: **06/03/2017**Print Date: **06/03/2017** 

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

#### Precautionary statement(s) Response

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

#### Precautionary statement(s) Storage

P405

Store locked up.

#### Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

#### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

Version No: 4.6

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
7429-90-5	0.01	aluminium
10022-31-8	0.01 (as Ba)	barium nitrate
10043-35-3	0.01 (as B)	boric acid
7757-79-1	0.1 (as K)	potassium nitrate
16919-19-0	0.01 (as Si)	ammonium fluorosilicate
7440-22-4	0.005	silver
497-19-8	0.01 (as Na)	sodium carbonate
7697-37-2	2	nitric acid
7732-18-5	0.01	water

#### **SECTION 4 FIRST-AID MEASURES**

#### Description of first aid measures

Е١	/e	Co	nta	ct

If this product comes in contact with the eyes

- Immediately hold eyelids apart and flush the eye continuously with running water.
- ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ► Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- ► Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

## Skin Contact

- If skin or hair contact occurs:
  - ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.
- act ► Quickly remove all contaminated clothing, including footwear.
  - Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
  - ► Transport to hospital, or doctor.
  - If fumes or combustion products are inhaled remove from contaminated area.
    - Lay patient down. Keep warm and rested.
    - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
    - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- ► Transport to hospital, or doctor, without delay.

  Inhalation

  Inhalation of vapours or aerosols (mists, fume
  - Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.
  - Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).
  - As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.
  - ▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.

This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
   If swallowed do NOT induce vomiting.
- Ingestion If vomiting occurs, lea
  - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
  - ► Observe the patient carefully.
  - ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
  - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
  - ► Transport to hospital or doctor without delay.

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling

Print Date: 06/03/2017

Issue Date: 06/03/2017

Version No: 4.6

- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise
- Figure 3. Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues. INGESTION:

▶ Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.

- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- ▶ Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- ▶ Some authors suggest the use of lavage within 1 hour of ingestion.

#### SKIN:

- ▶ Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping
- ▶ Deep second-degree burns may benefit from topical silver sulfadiazine.

#### EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist)

[Ellenhorn and Barceloux: Medical Toxicology]

#### **SECTION 5 FIRE-FIGHTING MEASURES**

#### **Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

#### Special protective equipment and precautions for fire-fighters

#### Fire Fighting

- ► Non combustible.
- ▶ Not considered to be a significant fire risk.
- Fire/Explosion Hazard
- ▶ Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- ▶ May emit corrosive, poisonous fumes. May emit acrid smoke

When aluminium oxide dust is dispersed in air, firefighters should wear protection against inhalation of dust particles, which can also contain hazardous substances from the fire absorbed on the alumina particles.

#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

- ▶ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks.
- ► Clean up all spills immediately.
- Minor Spills
- Avoid breathing vapours and contact with skin and eyes.
  - Control personal contact with the substance, by using protective equipment.
  - ▶ Contain and absorb spill with sand, earth, inert material or vermiculite
  - ▶ Wipe up.
  - ▶ Place in a suitable, labelled container for waste disposal.

**Major Spills** 

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 HANDLING AND STORAGE**

Safe handling

#### Precautions for safe handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- ▶ When handling, **DO NOT** eat, drink or smoke
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

QCS-7-M

Issue Date: **06/03/2017**Print Date: **06/03/2017** 

#### Other information

- Store in original containers.
- Keep containers securely sealed.
- ▶ Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- ▶ Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

#### Conditions for safe storage, including any incompatibilities

#### ► DO NOT use aluminium or galvanised containers

- ▶ Check regularly for spills and leaks
- ► Lined metal can, lined metal pail/ can.
- ► Plastic pail.
- ▶ Polyliner drum.
- ▶ Packing as recommended by manufacturer.
- ► Check all containers are clearly labelled and free from leaks.

For low viscosity materials

#### Suitable container

- ▶ Drums and jerricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- ► Removable head packaging;
- Cans with friction closures and
- ▶ low pressure tubes and cartridges

may be used.

-

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

For aluminas (aluminium oxide):

Incompatible with hot chlorinated rubber.

In the presence of chlorine trifluoride may react violently and ignite.

-May initiate explosive polymerisation of olefin oxides including ethylene oxide.

-Produces exothermic reaction above 200 C with halocarbons and an exothermic reaction at ambient temperatures with halocarbons in the presence of other metals.

-Produces exothermic reaction with oxygen difluoride.

-May form explosive mixture with oxygen difluoride.

-Forms explosive mixtures with sodium nitrate

-Reacts vigorously with vinyl acetate.

Aluminium oxide is an amphoteric substance, meaning it can react with both acids and bases, such as hydrofluoric acid and sodium hydroxide, acting as an acid with a base and a base with an acid, neutralising the other and producing a salt.

- ▶ Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
- ▶ Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts neutralisation can generate dangerously large amounts of heat in small spaces.
- The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
- ▶ The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.
- ▶ Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.
- ▶ Inorganic acids can initiate the polymerisation of certain classes of organic compounds.
- ▶ Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.
- Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitrides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H2S and SO3), dithionites (SO2), and even carbonates.
- Acids often catalyse (increase the rate of) chemical reactions.
- ▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

#### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

Storage incompatibility

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	aluminium	Aluminum, metal	15 mg/m3	Not Available	Not Available	Total dust; (as Al)
US OSHA Permissible Exposure Levels (PELs) - Table Z1	aluminium	Aluminum, metal- Respirable fraction	5 mg/m3	Not Available	Not Available	(as Al)
US NIOSH Recommended Exposure Limits (RELs)	aluminium	Aluminium, Aluminum metal, Aluminum powder, Elemental aluminum	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	barium nitrate	Barium dinitrate, Barium(II) nitrate (1:2), Barium salt of nitric acid	0.5 mg/m3	Not Available	Not Available	[*Note: The REL also applies to other soluble barium compounds (as Ba) except Barium sulfate.]
US NIOSH Recommended Exposure Limits (RELs)	silver	Silver metal: Argentum	0.01 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	nitric acid	Nitric acid	5 mg/m3 / 2 ppm	10 mg/m3 / 4 ppm	Not Available	TLV® Basis: URT & eye irr; dental erosion

QCS-7-M

Issue Date: **06/03/2017** Print Date: **06/03/2017** 

US NIOSH Recommended Exposure Limits (RELs)	nitric acid	Aqua fortis, Engravers acid, Hydrogen nitrate, Red fuming nitric acid (RFNA), White fuming nitric acid (WFNA)	5 mg/m3 / 2 ppm	4 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	nitric acid	Nitric acid	2 ppm	Not Available	Not Available	Not Available

#### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
barium nitrate	Barium nitrate	2.9 mg/m3	350 mg/m3	2,100 mg/m3
boric acid	Boric acid	6 mg/m3	23 mg/m3	830 mg/m3
potassium nitrate	Potassium nitrate	9 mg/m3	100 mg/m3	600 mg/m3
ammonium fluorosilicate	Ammonium hexafluorosilicate; (Ammonium silicofluoride)	12 mg/m3	130 mg/m3	780 mg/m3
silver	Silver	0.3 mg/m3	170 mg/m3	990 mg/m3
sodium carbonate	Sodium carbonate	7.6 mg/m3	83 mg/m3	500 mg/m3
nitric acid	Nitric acid	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
aluminium	Not Available	Not Available
barium nitrate	1,100 mg/m3	50 mg/m3
boric acid	Not Available	Not Available
potassium nitrate	Not Available	Not Available
ammonium fluorosilicate	Not Available	Not Available
silver	N.E. / N.E.	10 mg/m3
sodium carbonate	Not Available	Not Available
nitric acid	100 ppm	25 ppm
water	Not Available	Not Available

#### **Exposure controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

# Appropriate engineering controls

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Personal protection











QCS-7-M

Issue Date: 06/03/2017 Print Date: 06/03/2017

Eye and face protection	<ul> <li>Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.</li> <li>Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.</li> <li>Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.</li> <li>Alternatively a gas mask may replace splash goggles and face shields.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Elbow length PVC gloves</li> <li>When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.</li> </ul>
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>PVC Apron.</li> <li>PVC protective suit may be required if exposure severe.</li> <li>Eyewash unit.</li> <li>Ensure there is ready access to a safety shower.</li> </ul>
Thermal hazards	Not Available

#### Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

Appearance	colorless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

#### **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	► Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## **SECTION 11 TOXICOLOGICAL INFORMATION**

#### Information on toxicological effects

Inhaled

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.

QCS-7-M

Issue Date: **06/03/2017** Print Date: **06/03/2017** 

	The material has <b>NOT</b> been classified by EC Directives or other of animal or human evidence.	classification sys	stems as "harmful by inhalatio	n". This is because of the lack of corroborating
Ingestion	Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident.  The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.  Ingestion or skin absorption of boric acid causes nausea, abdominal pain, diarrhoea and profuse vomiting which may be blood stained, headache, weakness, reddened lesions on the skin. In severe cases, it may cause shock, with fall in blood pressure, increase in heart rate, blue skin colour, brain and nervous irritation, reduced urine volume or even absence of urine.  Borate poisoning causes nausea, vomiting, diarrhoea and pain in the upper abdomen. Often persistent vomiting occurs, and there may be blood in the faeces.			
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  Though considered non-harmful, slight irritation may result from contact because of the abrasive nature of the aluminium oxide particles. Thus it may cause itching and skin reaction and inflammation.  Boric acid is not absorbed via intact skin but absorbed on broken or inflamed skin.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Eye	If applied to the eyes, this material causes severe eye damage.  Direct eye contact with acid corrosives may produce pain, tears, s completely.	sensitivity to ligh	t and burns. Mild burns of the	epithelia generally recover rapidly and
Chronic	Repeated or prolonged exposure to acids may result in the erosic and inflammation of lung tissue often occurs.  Long-term exposure to respiratory irritants may result in airways of Substance accumulation, in the human body, may occur and may of Animal testing shows long term exposure to aluminium oxides may the greater the tendencies of causing harm.  Chronic boric acid poisoning is characterized by mild gastrointes irregular and discoloured rash. Dryness of skin, reddening of tong Borate can accumulate in the testes and deplete germ cells and of stomach ulcer and anaemia can all occur.	lisease, involvin cause some cor ny cause lung di tinal irritation, lo ue, loss of hair,	g difficulty breathing and relate noem following repeated or lon sease and cancer, depending ass of appetite, disturbed diges inflammation of conjunctiva, a	ed whole-body problems. g-term occupational exposure. on the size of the particle. The smaller the size, stion, nausea, possibly vomiting and a hard nd kidney injury have also been reported.
QCS-7-M	TOXICITY		IRRITATION	
	Not Available		Not Available	
aluminium	TOXICITY  Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>			IRRITATION  Not Available
barium nitrate	TOXICITY  Oral (rat) LD50: 355 mg/kgd <sup>[2]</sup>	Eye (	TATION rabbit):100 mg/24h - moderate (rabbit): 500 mg/24h - mild	•
boric acid	TOXICITY  Oral (rat) LD50: 2500 mg/kg <sup>[2]</sup>		RRITATION Skin (human): 15 mg/3d -l- mil	d
potassium nitrate	TOXICITY  dermal (rat) LD50: >5000 mg/kg <sup>[1]</sup> Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>			IRRITATION  Not Available
ammonium fluorosilicate	TOXICITY  Oral (mouse) LD50: 70 mg/kg <sup>[2]</sup>			IRRITATION  Not Available
silver	TOXICITY IRRITATION  Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup> Not Available			
sodium carbonate	TOXICITY  dermal (rat) LD50: >2000 mg/kg*E <sup>[2]</sup> Oral (rat) LD50: 2800 mg/kg*d <sup>[2]</sup>		IRRITATION  Eye (rabbit): 100 mg/24h m  Eye (rabbit): 100 mg/30s m  Eye (rabbit): 50 mg SEVER  Skin (rabbit): 500 mg/24h m	ild RE
nitric acid	TOXICITY			IRRITATION

Issue Date: 06/03/2017 Print Date: 06/03/2017

QCS-7-M Version No: 4.6

	Inhalation (rat) LC50: 625 ppm/1h*t <sup>[2]</sup>	Not Available		
water	TOXICITY IRRITATION			
	Not Available Not Available			
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances			
BARIUM NITRATE	The material may produce moderate eye irritation leading to inflammation.			
SODIUM CARBONATE	For sodium carbonate: Sodium carbonate has little potential for skin irritation, but is irritating to the eyes.			
	For acid mists, aerosols, vapours  Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls	o about 6.5.		
NITRIC ACID	The material may produce severe irritation to the eye causing pronounced inflammation.  The material may produce respiratory tract irritation, and result in damage to the lung including. The material may cause severe skin irritation after prolonged or repeated exposure and may provesicles, scaling and thickening of the skin.  Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]	reduced lung function.		
NITRIC ACID	The material may produce severe irritation to the eye causing pronounced inflammation.  The material may produce respiratory tract irritation, and result in damage to the lung including.  The material may cause severe skin irritation after prolonged or repeated exposure and may provesicles, scaling and thickening of the skin.	reduced lung function.		
	The material may produce severe irritation to the eye causing pronounced inflammation.  The material may produce respiratory tract irritation, and result in damage to the lung including.  The material may cause severe skin irritation after prolonged or repeated exposure and may provesicles, scaling and thickening of the skin.  Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]	reduced lung function.  duce on contact skin redness, swelling, the production of		
ALUMINIUM & WATER BARIUM NITRATE & BORIC ACID & SODIUM	The material may produce severe irritation to the eye causing pronounced inflammation.  The material may produce respiratory tract irritation, and result in damage to the lung including. The material may cause severe skin irritation after prolonged or repeated exposure and may provesicles, scaling and thickening of the skin.  Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]  No significant acute toxicological data identified in literature search.  The material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce of the material may cause skin irritation after prolonged or repeated exposure and may produce or prolonged or prolonge	reduced lung function.  Induce on contact skin redness, swelling, the production of second contact skin redness, swelling, the production of vesicles,		
ALUMINIUM & WATER BARIUM NITRATE & BORIC ACID & SODIUM CARBONATE SODIUM CARBONATE &	The material may produce severe irritation to the eye causing pronounced inflammation.  The material may produce respiratory tract irritation, and result in damage to the lung including. The material may cause severe skin irritation after prolonged or repeated exposure and may provesicles, scaling and thickening of the skin.  Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]  No significant acute toxicological data identified in literature search.  The material may cause skin irritation after prolonged or repeated exposure and may produce of scaling and thickening of the skin.	reduced lung function.  aduce on contact skin redness, swelling, the production of  on contact skin redness, swelling, the production of vesicles,  ss.		
ALUMINIUM & WATER BARIUM NITRATE & BORIC ACID & SODIUM CARBONATE SODIUM CARBONATE & NITRIC ACID	The material may produce severe irritation to the eye causing pronounced inflammation. The material may produce respiratory tract irritation, and result in damage to the lung including The material may cause severe skin irritation after prolonged or repeated exposure and may provesicles, scaling and thickening of the skin.  Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]  No significant acute toxicological data identified in literature search.  The material may cause skin irritation after prolonged or repeated exposure and may produce of scaling and thickening of the skin.  Asthma-like symptoms may continue for months or even years after exposure to the material end	reduced lung function. aduce on contact skin redness, swelling, the production of on contact skin redness, swelling, the production of vesicles, is.		
ALUMINIUM & WATER BARIUM NITRATE & BORIC ACID & SODIUM CARBONATE SODIUM CARBONATE & NITRIC ACID Acute Toxicity	The material may produce severe irritation to the eye causing pronounced inflammation.  The material may produce respiratory tract irritation, and result in damage to the lung including The material may cause severe skin irritation after prolonged or repeated exposure and may provesicles, scaling and thickening of the skin.  Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]  No significant acute toxicological data identified in literature search.  The material may cause skin irritation after prolonged or repeated exposure and may produce of scaling and thickening of the skin.  Asthma-like symptoms may continue for months or even years after exposure to the material end	reduced lung function. aduce on contact skin redness, swelling, the production of on contact skin redness, swelling, the production of vesicles, s.		
ALUMINIUM & WATER BARIUM NITRATE & BORIC ACID & SODIUM CARBONATE SODIUM CARBONATE & NITRIC ACID  Acute Toxicity Skin Irritation/Corrosion Serious Eye	The material may produce severe irritation to the eye causing pronounced inflammation.  The material may produce respiratory tract irritation, and result in damage to the lung including. The material may cause severe skin irritation after prolonged or repeated exposure and may provesicles, scaling and thickening of the skin.  Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]  No significant acute toxicological data identified in literature search.  The material may cause skin irritation after prolonged or repeated exposure and may produce of scaling and thickening of the skin.  Asthma-like symptoms may continue for months or even years after exposure to the material end  Carcinogenicity  Reproductivity	reduced lung function. aduce on contact skin redness, swelling, the production of on contact skin redness, swelling, the production of vesicles, s.		

Data available but does not fill the cri
 Data available to make classification

O – Data Not Available to make classification

## **SECTION 12 ECOLOGICAL INFORMATION**

# Toxicity

QCS-7-M	ENDPOINT	TEST DURATION (HR)		SPECIES	VALUE		SOURCE
QC3-7-IVI	Not Applicable	Not Applicable		Not Applicable	Not App	olicable	Not Applicable
	ENDPOINT	TEST DURATION (HR)	SPE	CIES		VALUE	SOURCE
	LC50	96	Fish			0.078-0.108mg/L	2
	EC50	48	Crus	stacea		0.7364mg/L	2
aluminium	EC50	96	Alga	e or other aquatic plants		0.0054mg/L	2
	BCF	360	Alga	e or other aquatic plants		9mg/L	4
	EC50	120	Fish			0.000051mg/L	5
	NOEC	72	Alga	e or other aquatic plants		>=0.004mg/L	2
	ENDPOINT	TEST DURATION (HR)	s	PECIES		VALUE	SOURCE
	LC50	96	F	ish		>3.5mg/L	2
barium nitrate	EC50	72	A	lgae or other aquatic plants	3	>1.92mg/L	2
	EC50	72	A	lgae or other aquatic plants	3	>34.31mg/L	2
	NOEC	72	A	lgae or other aquatic plants	3	>=1.92mg/L	2
	ENDPOINT	TEST DURATION (HR)	:	SPECIES		VALUE	SOURCE
boric acid	LC50	96		Fish		74mg/L	2
	EC50	48		Crustacea		133mg/L	4
bonc acid	EC50	72		Algae or other aquatic plan	ts	54mg/L	2
	EC50	72		Algae or other aquatic plan	ts	66mg/L	2

QCS-7-M

Issue Date: 06/03/2017 Print Date: 06/03/2017

#### Leaend:

Extracted from 1, IUCLID Toxicity Data 2, Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3, EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

#### Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

For Fluorides; Small amounts of fluoride have beneficial effects however; excessive intake over long periods may cause dental and/or skeletal fluorosis. Fluorides are absorbed by humans following inhalation of workplace and ambient air that has been contaminated, ingestion of drinking water and foods and dermal contact. Populations living in areas with high fluoride levels in groundwater may be exposed to higher levels of fluorides in their drinking water or in beverages prepared with the water. Among these populations, outdoor labourers, people living in hot climates, and people with excessive thirst will generally have the greatest daily intake of fluorides because they consume greater amounts of water.

Atmospheric Fate: Both hydrogen fluoride and particulate fluorides will be transported in the atmosphere and deposited on land or water by wet and dry deposition. Non-volatile inorganic fluoride particulates are removed from the atmosphere via condensation or nucleation processes. Fluorides adsorbed on particulate matter in the atmosphere are generally stable and are not readily hydrolyzed, although they may be degraded by radiation if they persist in the atmosphere. Fluorine and the silicon fluorides, silicofluorides) are hydrolyzed in the atmosphere to form hydrogen fluoride. Hydrogen fluoride may combine with water vapour to produce an aerosol or fog of aqueous hydrofluoric acid. Inorganic fluoride compounds, with the exception of sulfur hexafluoride, are not expected to remain in the troposphere for long periods or to migrate to the stratosphere. Estimates of the residence time of sulfur hexafluoride in the atmosphere range from 500 to several thousand years. Fluoride in aerosols can be transported over large distances by wind or as a result of atmospheric turbulence. Fluorosilicic acid and hydrofluoric acid in high aquatic concentrations such as may be found in industrial waste ponds may volatilize, releasing silicon tetrafluoride and hydrogen fluoride into the atmosphere. Soluble inorganic fluorides may also form aerosols at the air/water interface or vaporize into the atmosphere whereas undissolved species generally undergo sedimentation.

Terrestrial Fate: Soils - Atmospheric fluorides may be transported to soils and surface waters through both wet and dry deposition processes where they may form complexes and bind strongly to soil and sediment. Solubilisation of inorganic fluorides from minerals may also be enhanced by the presence of bentonite clays and humic acid. Factors that influence the mobility of inorganic fluorides in soil are pH and the formation of aluminium and calcium complexes. In more acidic soils, concentrations of inorganic fluoride were considerably higher in the deeper horizons. The low affinity of fluorides for organic material results in leaching from the more acidic surface horizon and increased retention by clay minerals and silts in the more alkaline, deeper horizons. The maximum adsorption of fluoride to soil was reported to occur at pH 5.5. In acidic soils with pH below 6, most of the fluoride is in complexes with either aluminium or iron. Fluoride in alkaline soils at pH 6.5 and above is almost completely fixed in soils as calcium fluoride, if sufficient calcium carbonate is available. Fluoride is extremely immobile in soil.

Aquatic Fate: Fresh Water: - In water, the transport and transformation of inorganic fluorides are influenced by pH, water hardness and the presence of ion-exchange materials such as clays. In natural water, fluoride forms strong complexes with aluminium in water, and fluorine chemistry in water is largely regulated by aluminium concentration and pH. Below pH 5, fluoride is almost entirely complexed with aluminium and consequently, the concentration of free F- is low. Once dissolved, inorganic fluorides remain in solution under conditions of low pH and hardness and in the presence of ion-exchange material. Sea Water - Fluoride forms stable complexes with calcium and magnesium, which are present in sea water. Calcium carbonate precipitation dominates the removal of dissolved fluoride from sea water. The residence time for fluoride in ocean sediment is calculated to be 2-3 million years.

Ecotoxicity: Fluorides have been shown to accumulate in animals that consume fluoride-containing foliage. However, accumulation is primarily in skeletal tissue and therefore, it is unlikely that fluoride will biomagnify up the food chain.

for Boron and Borates:

Environmental Fate - Boron is generally found in nature bound to oxygen and is never found as the free element. As an element, boron itself cannot be degraded in the environment, however; it may undergo various reactions that change the form of boron (e.g., precipitation, polymerization, and acid-base reactions) depending on conditions such as its concentration in water and pH. As boron is a natural component of the environment, individuals will have some exposure from foods and drinking water.

Atmospheric Fate: Atmospheric boron may be in the form of particulate matter or aerosols as borides, boron oxides, borates, organoboron compounds, trihalide boron compounds, or borazines. Boron and borates will probably be removed from the atmosphere by precipitation and dry deposition. The half-life of airborne particles is usually on the order of days, depending on the size of the particle and atmospheric conditions.

Aquatic Fate: Borates are relatively soluble in water. Boron readily hydrolyses in water and, in concentrated solutions, may polymerize. The mineral content of water is not likely to control the fate of boron in water. Boron was found to not be significantly removed during the conventional treatment of waste water. Boron may, however; be co-precipitated with aluminium, silicon, or iron to form hydroxyborate compounds on the surfaces of minerals. Waterborne boron may be adsorbed by soils and sediments. Adsorption-desorption reactions are expected to be the only significant mechanism that will influence the fate of boron in water.

Terrestrial Fate: Soil - Boron is added to farmland as a soil improving agent, but there is not sufficient data to evaluate its effect on soil organisms. The extent of boron adsorption depends on the pH of the water and the chemical composition of the soil. The greatest adsorption is generally observed at pH 7.5-9.0. The single most important property of soil that will influence the mobility of boron is the abundance of amorphous aluminium oxide. The extent of boron adsorption has also been attributed to the levels of iron oxide, and to a lesser extent, the organic matter present in the soil, although other studies found that the amount of organic matter present was not important. The adsorption of boron may not be reversible in some soils. Most boron compounds are transformed to borates in soil due to the presence of moisture. Borates themselves are not further degraded in soil, however; borates can exist in a variety of forms in soil. Borates are removed from soils by water leaching and by assimilation by plants. Surface soil, unpolluted waterways and seawater all typically contain significant amounts of boron as borate. Plants - Boron is an essential micronutrient for healthy growth of plants, however, it can be harmful to boron sensitive plants in higher quantities. In some areas such as the American Southwest, boron occurs naturally in surface waters in concentrations that have been shown to be toxic to commercially important plants.

Ecotoxicity: It is unlikely that boron is bioconcentrated significantly by organisms from water. Boron is not expected to bioaccumulate and bioconcentration factors for fish, plants and invertebrates are low. Boron is not regarded to be dangerous to aquatic organisms. In aquatic environments low concentrations of borates generally promote the growth of algae, whereas higher concentrations inhibited algal growth. Boron has little effect on freshwater algae and water fleas. The toxicity of boron in fish is often higher in soft water than in hard water. Zebra fish and rainbow trout are the most sensitive species to the effects of boron.

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or w

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
boric acid	LOW	LOW
potassium nitrate	LOW	LOW
sodium carbonate	LOW	LOW
water	LOW	LOW

#### Bioaccumulative potential

Ingredient	Bioaccumulation
boric acid	LOW (BCF = 0)
potassium nitrate	LOW (LogKOW = 0.209)
sodium carbonate	LOW (LogKOW = -0.4605)
water	LOW (LogKOW = -1.38)

#### Mobility in soil

Ingredient	Mobility
boric acid	LOW (KOC = 35.04)
potassium nitrate	LOW (KOC = 14.3)
sodium carbonate	HIGH (KOC = 1)
water	LOW (KOC = 14.3)

Issue Date: 06/03/2017 Print Date: 06/03/2017

Version No: 4.6

## **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Product / Packaging

- ► Recycle wherever possible.
- ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- ► Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible
- Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

#### **SECTION 14 TRANSPORT INFORMATION**

disposal

#### **Labels Required**



**Marine Pollutant** 

NO

#### Land transport (DOT)

UN number	3264
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (contains nitric acid)
Transport hazard class(es)	Class 8 Subrisk Not Applicable
Packing group	Ш
Environmental hazard	Not Applicable
Special precautions for user	Hazard Label 8 Special provisions 386, B2, IB2, T11, TP2, TP27

## Air transport (ICAO-IATA / DGR)

#### Sea transport (IMDG-Code / GGVSee)

UN number	3264
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains nitric acid)
Transport hazard class(es)	IMDG Class     8       IMDG Subrisk     Not Applicable
Packing group	П
Environmental hazard	Not Applicable

QCS-7-M

Issue Date: 06/03/2017 Print Date: 06/03/2017

Special precautions for user

EMS Number	F-A, S-B
Special provisions	274
Limited Quantities	1 L

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Product name	Pollution Category	Ship Type
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Nitric acid (70% and over) Nitric acid (less than 70%)	Y; Y	2 2

#### **SECTION 15 REGULATORY INFORMATION**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

ALUMINIUM(7429-90-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Massachusetts - Right To Know Listed Chemicals	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Michigan Exposure Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Oregon Permissible Exposure Limits (Z-1)	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Pennsylvania - Hazardous Substance List	US EPCRA Section 313 Chemical List
US - Rhode Island Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

BARIUM NITRATE(10022-31-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV)
US - Michigan Exposure Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Minnesota Permissible Exposure Limits (PELs)	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Oregon Permissible Exposure Limits (Z-1)	US EPA Carcinogens Listing
US - Pennsylvania - Hazardous Substance List	US EPCRA Section 313 Chemical List
US - Rhode Island Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

## BORIC ACID(10043-35-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US ACGIH Threshold Limit Values (TLV)	US EPA Carcinogens Listing
US ACGIH Threshold Limit Values (TLV) - Carcinogens	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### DOTA SSILIM NITD ATE/7757 70 4) IS EQUIND ON THE EQUI OWING DECLI ATODY LISTS

FORASSION NITRATE(1737-75-1) IS FOUND ON THE FOLLOWING REGULATOR TEISTS	
US - Massachusetts - Right To Know Listed Chemicals	US EPCRA Section 313 Chemical List
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Rhode Island Hazardous Substance List	

# AMMONIUM FLUOROSILICATE(16919-19-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
Contaminants
US - Washington Permissible exposure limits of air contaminants
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration,
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
US CWA (Clean Water Act) - List of Hazardous Substances
US OSHA Permissible Exposure Levels (PELs) - Table Z1
US OSHA Permissible Exposure Levels (PELs) - Table Z2
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### SILVER(7440-22-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Page 12 of 13

QCS-7-M

Issue Date: **06/03/2017**Print Date: **06/03/2017** 

US - Alaska Limits for Air Contaminants US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air US - California Permissible Exposure Limits for Chemical Contaminants US - Washington Permissible exposure limits of air contaminants US - Hawaii Air Contaminant Limits US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants US - Idaho - Limits for Air Contaminants US - Massachusetts - Right To Know Listed Chemicals US ACGIH Threshold Limit Values (TLV) US - Michigan Exposure Limits for Air Contaminants US CWA (Clean Water Act) - Priority Pollutants US CWA (Clean Water Act) - Toxic Pollutants US - Minnesota Permissible Exposure Limits (PELs) US EPA Carcinogens Listing US - Oregon Permissible Exposure Limits (Z-1) US EPCRA Section 313 Chemical List US - Pennsylvania - Hazardous Substance List US NIOSH Recommended Exposure Limits (RELs) US - Rhode Island Hazardous Substance List US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants US OSHA Permissible Exposure Levels (PELs) - Table Z1

# US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants SODIUM CARBONATE(497-19-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### NITRIC ACID(7697-37-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

- US Alaska Limits for Air Contaminants
- US California OEHHA/ARB Acute Reference Exposure Levels and Target Organs (RELs)
- US California Permissible Exposure Limits for Chemical Contaminants
- US Hawaii Air Contaminant Limits
- US Idaho Limits for Air Contaminants
- US Massachusetts Right To Know Listed Chemicals
- US Michigan Exposure Limits for Air Contaminants
- US Minnesota Permissible Exposure Limits (PELs)
- US Oregon Permissible Exposure Limits (Z-1)
- US Pennsylvania Hazardous Substance List
- US Rhode Island Hazardous Substance List
- US Tennessee Occupational Exposure Limits Limits For Air Contaminants

- US Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US - Washington Permissible exposure limits of air contaminants

- US Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
- US Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
- US ACGIH Threshold Limit Values (TLV)
- US CWA (Clean Water Act) List of Hazardous Substances
- US EPCRA Section 313 Chemical List
- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Permissible Exposure Levels (PELs) Table Z1
- US SARA Section 302 Extremely Hazardous Substances
  US Toxic Substances Control Act (TSCA) Chemical Substance Inventory

#### WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Pennsylvania - Hazardous Substance List

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### **Federal Regulations**

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

#### US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Ammonium silicofluoride	1000	454
Silver	1000	454
Nitric acid	1000	454

#### State Regulations

#### US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	N (barium nitrate; water; ammonium fluorosilicate; aluminium; boric acid; potassium nitrate; silver; sodium carbonate; nitric acid)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water; ammonium fluorosilicate; aluminium; boric acid; silver; sodium carbonate; nitric acid)
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

Issue Date: 06/03/2017 Catalogue number: QCS-7M Print Date: 06/03/2017 QCS-7-M Version No: 4.6

#### **SECTION 16 OTHER INFORMATION**

#### Other information

#### Ingredients with multiple cas numbers

Name	CAS No
aluminium	7429-90-5, 91728-14-2
barium nitrate	10022-31-8, 34053-87-7
boric acid	10043-35-3, 11113-50-1, 41685-84-1
ammonium fluorosilicate	16919-19-0, 1309-32-6
sodium carbonate	497-19-8, 7542-12-3, 1314087-39-2, 1332-57-6

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$ 

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.