Section 1. Product and Company Identification

Product Identification:	WAVECAL-2	
SDS Number:	WAVECAL-2	
Recommended Use:	For Laboratory Use.	
Company Identification:	High-Purity Standards	
	P.O. Box 41727	
	Charleston, SC 29423	
	Telephone: (843) 767-7900	
	FAX: (843) 767-7906	
In case of emergency call INFOTRAC: 800-535-5053		

Section 2. Hazard Identification

Classification:

Skin Corrosion/Irritation, Category 1 Serious Eye Damage/ Eye Irritation, Category 1 Labeling:

Symbol:

Signal Word: Danger.
Hazard Statement: Causes severe skin burns and eye damage.
Precautionary Statement: Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling.

Section 3. Composition		
Component	CAS/EINECS Registry #	Percent Concentration
Aluminum	7429-90-5/231-072-3	0.005
Arsenic	7440-38-2/231-148-6	0.005
Barium Carbonate (BaCO ₃)	513-77-9/208-167-3	- 0.005 (as Ba)
Barium Nitrate $(Ba(NO_3)_2)$	10022-31-8/233-020-5	0.005 (as Ba)
Cadmium	7440-43-9/231-152-8	0.005
Chromium	7440-47-3/231-157-5	0.005
Cobalt	7440-48-4/231-158-0	0.005
Copper	7440-50-8/231-159-6	0.005
Lead	7439-92-1/231-100-4	0.005
Manganese Acetate Tetrahydrate (Mn(CH ₃ CO ₂) ₂)*4H ₂ O	6156-78-1/211-334-3	0.005 (as Mn)
Ammonium Molybdate ((NH ₄) ₂ MoO ₄ ·4H ₂ O)	13106-76-8/236-031-3	0.005 (as Mo)
Nickel	7440-02-0/231-111-4	0.005
Potassium Nitrate (KNO ₃)	7757-79-1/231-818-8	0.05 (as K)

Safety Data Sheet No. WAVECAL-2	Date: April 18, 2014	
WAVECAL-2	Revision: 001	Page 2 of 5

Selenium	7782-49-2/231-957-4	0.005
Strontium Nitrate (Sr(NO ₃) ₂)	10042-76-9/233-131-9	0.005 (as Sr)
Zinc	7440-66-6/231-175-3	0.005
Nitric Acid	7697-37-2/231-714-2	5
Water, deionized	7732-18-5/231-791-2	Balance

*Note: Barium is derived from either Barium carbonate or Barium Nitrate. For this reason both sources are listed on the SDS. Refer to the product's Certificate of Analysis to determine which source was used in the production of the lot number received.

Section 4. First Aid Measures

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Call a physician if irritation develops.

- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Call a physician. May cause nausea, vomiting, and diarrhea.
- **IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membrane and upper respiratory tract.

Target Organs: Eyes, skin

Section 5. Fire Fighting Measures

Fire & Explosion hazards: While nitric acid is not combustible, it is a strong oxidizing agent that can react with combustible materials; however, it is present in limited quantities in this solution. NO_x compounds can be released in case of fire.

Extinguishing Media: Use any extinguishing media that is suitable for the surrounding area. Use a water spray to dilute nitric acid and to absorb liberated nitrogen oxides.

Specific Methods: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Section 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Do not allow to enter drainage systems or water ways. Dike area and dilute spill with water and neutralize with soda ash, limestone, etc. Place the neutralized material into containers suitable for eventual disposal, reclamation, or destruction. Always dispose of in accordance with local regulations.

Section 7. Handling and Storage

Store in a cool, dry, ventilated storage area with acid resistant floors and good drainage. Keep out of direct sunlight and away from heat, water, and incompatible materials. When diluting, the acid should always be added slowly to water and in small amounts. Refer to Section 8 for personal handling instructions.

Section 8. Exposure Controls and Personal Protection

Safety Data Sheet No. WAVECAL-2	Date: April 18, 2014	
WAVECAL-2	Revision: 001	Page 3 of 5

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep any buildup of airborne contaminants below their respective threshold limit value. Ensure the availability of eyewash stations and safety showers.

Respiratory Protection: Provide approved respiratory apparatus for non-routine or emergency use. Use an approved vapor respirator when the vapor or mist concentrations are high. If necessary, refer to the NIOSH document Guide to the Selection and Use of Particulate Respirators Certified under 42 CFR 84 for selection and use of respirators certified by NIOSH.

Personal Protection: Wear proper gloves, safety glasses with side shields, lab coat/apron. **Exposure Limits:**

Component	ACGIH TLV	OSHA PEL
Aluminum	10 mg/m^3	15 mg/m^3
Arsenic	0.01 mg/m^3	$10 \ \mu g/m^3$
Barium	0.5 mg/m^3	0.5 mg/m^3
Cadmium	0.002 mg/m^3	0.005 mg/m^3
	(respirable particulate)	
Chromium	0.5 mg/m^3	1 mg/m^3
Cobalt	0.02 mg/m^3	0.1 mg/m^3
Copper	0.2 mg/m^3 (fumes)	0.1 mg/m^3 (fumes)
Lead	0.05 mg/m^3	0.05 mg/m^3
Manganese Acetate	0.2 mg/m^3	$C 5 mg/m^3$
Tetrahydrate		
Ammonium Molybdate	5 mg/m^3	5 mg/m^3
Nickel	1.5 mg/m^3	1 mg/m^3
Potassium Nitrate	Not Available	Not Available
Selenium	0.2 mg/m^3	0.2 mg/m^3
Strontium Nitrate	Not Available	Not Available
Zinc	5 mg/m^3	1 mg/m^3
Nitric Acid	2 mg/kg	5 mg/m^3

Section 9. Physical and Chemical Properties

Physical State: Liquid Color: Clear, blueish-grey liquid Odor: Odorless to a faint pungent odor Odor threshold: None pH: <2 Melting point: N/A Freezing Point: N/A Boiling Point: Approximately 100°C Flash point: N/A Evaporation rate: N/A Flammability: N/A Explosion limits: N/A Vapor Pressure (mm): N/A Vapor Density (air+1): N/A Relative density: $(H_2O = 1)$: Approximately 1.0 Solubility in H₂O: Complete Auto ignition temperature: N/A Decomposition temperature: N/A

Safety Data Sheet No. WAVECAL-2	Date: April 18, 2014	
WAVECAL-2	Revision: 001	Page 4 of 5

Molecular Weight: N/A

Section 10. Stability and Reactivity

Stability Indicator: YES

Conditions to Avoid: Metals, chlorine, organic materials, strong alkali, cyanides.

Incompatibles: Strong reducing agents.

Hazardous Decomposition Products: NO_x compounds including nitric oxide (NO), nitrogen dioxide (NO₂), nitrous oxide (N₂O) and nitric acid mist or vapor.

Hazardous Polymerization: Will not occur.

Section 11. Toxicological Information

May affect skin, mucous membranes and eyes. Swallowing may lead to a negative effect on mouth and throat and to the risk of perforation or the corrosion of esophagus and stomach. **RTECS#**

HNO₃: OU5775000 As : CG0525000 A1 : BD0330000 BaCO₃: CQ8600000 Cd : EU9800000 Co : GF8750000 Cr: GB4200000 Cu: GL5325000 Pb : OF7525000 KNO3: TT3700000 Ni: QR5950000 Mn : AI5775000 (NH₄)₂MoO₄: QA4680000 Zn: ZG8600000 Se : VS7700000 Sr(NO₃)₂: WK9800000 Ba(NO₃)₂- CQ9625000

Toxicity Data:

LD_{LO} Oral, Human: (Nitric Acid) 430 mg/kg LD₅₀ Oral, Rat: (Aluminum) >5000 mg/kg LD₅₀, Oral, Rat: (Arsenic) 763 mg/kg Oral, Human: (Barium Carbonate) 17 mg/kg LD₅₀ Oral, Rat: (Ba(NO₃)₂) 355 mg/kg. LD_{LO} Oral, Human: (Cadmium) 2330 mg/kg LD_{LO} Oral, Rabbit: (Cobalt) 750 mg/kg LD₅₀ Unreported Route, Rat: (Chromium) 27.5 mg/kg TD_{LO} Oral, Human: (Copper) 120 µg/kg LD₅₀ Oral, Rat: (Potassium Nitrate) 3750 mg/kg LD₅₀ Oral, Rat: (Manganese Acetate) 3730mg/kg TD_{LO} Oral, Rat: (Molybdenum) 333 mg/kg (multigenerations) LD₅₀, Intravenous, Mouse: (Nickel) 50 mg/kg TD₅₀ Oral, Woman: (Lead) 450 mg/kg/6 years LD₅₀, Oral, Rat: (Selenium) 6700 mg/kg LD_{LO} Oral, Duck: (Zinc) 388 mg/kg

Section 12. Ecological Information

Ecotoxicological information: Do not allow material to reach ground water, water bodies, or sewage system.

Section 13. Disposal Considerations

General: Follow Federal, state and local regulations for waste.

Safety Data Sheet No. WAVECAL-2	Date: April 18, 2014	
WAVECAL-2	Revision: 001	Page 5 of 5

Section 14. Transport Information

D.O.T. Classification: Hazardous by IATA and 49CFR regulations (based on concentration of acid). D.O.T. Shipping Name: Corrosive liquid, Acidic, Inorganic, n.o.s. (Nitric Acid Solution) D.O.T. Hazard Class: 8 U.N./N.A. Number: 3264 Packing Group: II D.O.T. Label: Corrosive (8)

Section 15. Regulations (Not meant to be all inclusive-selected regulation listed)

TSCA Status: Components of this solution are listed on the TSCA Inventory. RCRA Status: No.

SARA: Subject to the reporting requirements of Section 313 of SARA Title III and of 40 CFR 372 Risk Phrases: R36/38 Irritating to eyes and skin.

Safety Phrases: S36/37/39 Wear suitable protective clothing, gloves and eye/face protection WHMIS Information (Canada): E: Corrosive

Section 16. Other Information

HPS products are intended for laboratory use only. All products should be handled and used by trained professional personnel only. The responsibility for the safe handling and use of these products rests solely with the buyer and/or user. The SDS was prepared carefully and represents the best data currently available to us; however, HPS does not certify the data on the SDS. Certified values for this material are given only on the Certificate of Analysis.

Theodore C. Rains, Ph.D.