

## Safety Data Sheet

### Section 1. Product and Company Identification

Product Identification: 100 µg/mL Beryllium in 2% HNO<sub>3</sub>  
SDS Number: 100 5-1  
Recommended Use: For Laboratory Use.  
Company Identification: High-Purity Standards  
P.O. Box 41727  
Charleston, SC 29423  
Telephone: (843) 767-7900  
FAX: (843) 767-7906

In case of emergency call INFOTRAC: 800-535-5053

### Section 2. Hazard Identification

**Classification:**

Skin Corrosion/Irritation, Category 1

Serious Eye Damage/ Eye Irritation, Category 1

**Labeling:**



**Symbol:**

**Signal Word:** Danger.

**Hazard Statement:** Causes severe skin burns and eye damage.

**Precautionary Statement:** Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling.

### Section 3. Composition

Component	CAS/EINECS Registry #	Percent Concentration
Beryllium Acetate (Be <sub>4</sub> O(C <sub>2</sub> H <sub>3</sub> O <sub>2</sub> ) <sub>6</sub> )	19049-40-2/242-785-4	0.01 (as Be)
Nitric Acid	7697-37-2/ 231-714-2	2
Water, deionized	7732-18-5/ 231-791-2	Balance

### Section 4. First Aid Measures

**IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Call a physician if irritation develops.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician.

**IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing.

**IF exposed or concerned:** Get medical attention.

**Target Organs:** Eyes, skin.

<b>Safety Data Sheet No. 100 5-1</b>	<b>Date: March 31, 2014</b>	
<b>100 µg/mL Beryllium in 2% HNO<sub>3</sub></b>	<b>Revision: 001</b>	<b>Page 2 of 4</b>

#### Section 5. Fire Fighting Measures

Fire & Explosion hazards: While nitric acid is not combustible, it is a strong oxidizing agent that can react with combustible materials; however, it is present in limited quantities in this solution. NO<sub>x</sub> compounds can be released in case of fire.

Extinguishing Media: Use any extinguishing media that is suitable for the surrounding area. Use a water spray to dilute nitric acid and to absorb liberated nitrogen oxides.

Specific Methods: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

#### Section 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Do not allow to enter drainage systems or water ways. Dike area and dilute spill with water and neutralize with soda ash, limestone, etc. Place the neutralized material into containers suitable for eventual disposal, reclamation, or destruction. Always dispose of in accordance with local regulations.

#### Section 7. Handling and Storage

Store in a cool, dry, ventilated storage area with acid resistant floors and good drainage. Keep out of direct sunlight and away from heat, water, and incompatible materials. When diluting, the acid should always be added slowly to water and in small amounts. Refer to Section 8 for personal handling instructions.

#### Section 8. Exposure Controls and Personal Protection

Engineering Controls: Provide general and local (e.g., fume hood) ventilation systems to maintain airborne concentrations below the TLV. Ensure the availability of eyewash stations and safety showers.

Personal Protection: Wear proper gloves, safety glasses with side shields, lab coat/apron.

##### Exposure Limits:

Component	ACGIH TLV	OSHA PEL
Beryllium Acetate	0.002 mg/m <sup>3</sup>	0.002 mg/m <sup>3</sup>
Nitric Acid	2 mg/kg	5 mg/m <sup>3</sup>

#### Section 9. Physical and Chemical Properties

Physical State: Liquid

Color: Clear, colorless liquid

Odor: Odorless to a faint pungent odor

Odor threshold: None

pH: <2

Melting point: N/A

Freezing Point: N/A

Boiling Point: Approximately 100°C

Flash point: N/A

Evaporation rate: N/A

Flammability: N/A

Explosion limits: N/A

Vapor Pressure (mm): N/A

<b>Safety Data Sheet No. 100 5-1</b>	<b>Date: March 31, 2014</b>	
<b>100 µg/mL Beryllium in 2% HNO<sub>3</sub></b>	<b>Revision: 001</b>	<b>Page 3 of 4</b>

Vapor Density (air+1): N/A  
Relative density: (H<sub>2</sub>O = 1): Approximately 1.0  
Solubility in H<sub>2</sub>O: Complete  
Auto ignition temperature: N/A  
Decomposition temperature: N/A  
Molecular Weight: 9.01 (Be)

#### Section 10. Stability and Reactivity

Stability Indicator: Decomposes slowly to release oxygen.  
Conditions to Avoid: Metals, chlorine, organic materials, strong alkali, cyanides.  
Incompatibles: Strong reducing agents.  
Hazardous Decomposition Products: NO<sub>x</sub> compounds including nitric oxide (NO), nitrogen dioxide (NO<sub>2</sub>), nitrous oxide (N<sub>2</sub>O) and nitric acid mist or vapor.  
Hazardous Polymerization: Will not occur.

#### Section 11. Toxicological Information

May affect skin, mucous membranes and eyes. Swallowing may lead to a negative effect on mouth and throat and to the risk of perforation or the corrosion of esophagus and stomach.  
Beryllium considered a carcinogen.  
**RTECS#**  
HNO<sub>3</sub>; QU5775000  
Be<sub>4</sub>O(C<sub>2</sub>H<sub>3</sub>O<sub>2</sub>)<sub>6</sub>; DS1750000  
LD<sub>LO</sub> Oral, Human: (Nitric Acid) 430 mg/kg.  
TD<sub>LO</sub> Intratracheal, Rat: (Beryllium Acetate) 13 mg/kg.

#### Section 12. Ecological Information

Ecotoxicological information: Do not allow material to reach ground water, water bodies, or sewage system. Beryllium and its compounds are considered to have high acute and chronic toxicity to aquatic life. Beryllium is more toxic in soft water than in hard water.

#### Section 13. Disposal Considerations

General: Follow Federal, state and local regulations for waste.

#### Section 14. Transport Information

D.O.T. Classification: Hazardous by IATA and 49CFR regulations (based on concentration of acid).  
D.O.T. Shipping Name: Corrosive liquid, Acidic, Inorganic, n.o.s. (Nitric Acid Solution)  
D.O.T. Hazard Class: 8  
U.N./N.A. Number: 3264  
Packing Group: II  
D.O.T. Label: Corrosive (8)

#### Section 15. Regulations (Not meant to be all inclusive-selected regulation listed)

TSCA Status: Components of this solution are listed on the TSCA Inventory.  
RCRA Status: No.

<b>Safety Data Sheet No. 100 5-1</b>	<b>Date: March 31, 2014</b>	
<b>100 µg/mL Beryllium in 2% HNO<sub>3</sub></b>	<b>Revision: 001</b>	<b>Page 4 of 4</b>

SARA: Subject to the reporting requirements of Section 313 of SARA Title III and of 40 CFR 372

Risk Phrases: R20/21/22 Harmful by inhalation, skin contact, or if swallowed.

Safety Phrases: S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

Note: Restricted to Professional Users.

WHMIS Information (Canada): E: Corrosive

#### Section 16. Other Information

HPS products are intended for laboratory use only. All products should be handled and used by trained professional personnel only. The responsibility for the safe handling and use of these products rests solely with the buyer and/or user. The SDS was prepared carefully and represents the best data currently available to us; however, HPS does not certify the data on the SDS.

Certified values for this material are given only on the Certificate of Analysis.

Theodore C. Rains, Ph.D.