



Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

1 Identification

- · Product identifier
- · Trade name: Thallium (from Thallium Nitrate) 10,000 μg/mL in 4% HNO3
- · Article number: 10M58-1 (Nitrate source)
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

Telephone: +1-843-767-7900 *Fax:* +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

- · Information department: Product safety department
- · Emergency telephone number:

INFOTRAC

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)



Page 2/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

(Contd. of page 1)

· Hazard pictograms







GHS05

05 GHS06

· Signal word Danger

· Hazard-determining components of labeling:

nitric acid

thallium nitrate

· Hazard statements

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3 Fire = 0Reactivity = 0

(Contd. on page 3)



Page 3/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--|---|-------|
| 7697-37-2 | nitric acid | 4.0% |
| 10102-45-1 | thallium nitrate | 1.0% |
| · Chemical identification of the substance/preparation | | |
| 7732-18-5 | water, distilled, conductivity or of similar purity | 95.0% |

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

 $Remove\ breathing\ apparatus\ only\ after\ contaminated\ clothing\ have\ been\ completely\ removed.$

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

HC



Page 4/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

(Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

| · <i>PAC-1</i> : | | |
|------------------|--------------------|----------------|
| 7697-37-2 | nitric acid 0 |).16 ppm |
| 10102-45-1 | thallium nitrate 0 | $0.078~mg/m^3$ |
| · PAC-2: | | |
| 7697-37-2 | nitric acid | 24 ppm |
| 10102-45-1 | thallium nitrate | 4.3 mg/m³ |
| · PAC-3: | | |
| 7697-37-2 | nitric acid | 92 ppm |
| 10102-45-1 | thallium nitrate | 26 mg/m³ |

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)



Page 5/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

(Contd. of page 4)

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

| · Components with | limit values that r | eauire monitoring | at the workplace: |
|-------------------|---------------------|-------------------|-------------------|
| | | | |

7697-37-2 nitric acid

| PEL | Long-term value: 5 mg/m³, 2 ppm |
|-----|---|
| REL | Short-term value: 10 mg/m³, 4 ppm |
| | Long-term value: 5 mg/m³, 2 ppm Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm |
| TLV | Short-term value: 10 mg/m³, 4 ppm |
| | Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm |

10102-45-1 thallium nitrate

PEL Long-term value: 0.1 mg/m³

as Tl; Skin

REL Long-term value: 0.1 mg/m³

as Tl; Skin

TLV Long-term value: 0.02* mg/m³

as Tl; *inhalable fraction; Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)



Page 6/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

(Contd. of page 5)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Color:
Color:
Characteristic
Odor threshold:
Not determined.

Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 100 °C (212 °F)

Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

(Contd. on page 7)





Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

| | | (Contd. of pag |
|---------------------------------------|--|----------------|
| Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| Vapor pressure at 20 °C (68 °F): | 23 hPa (17.3 mm Hg) | |
| Density at 20 °C (68 °F): | 1.06568 g/cm³ (8.8931 lbs/gal) | |
| Bulk density: | $1,066 \text{ kg/m}^3$ | |
| Relative density | Not determined. | |
| Vapor density | Not determined. | |
| Evaporation rate | Not determined. | |
| Solubility in / Miscibility with | | |
| Water: | Fully miscible. | |
| Partition coefficient (n-octanol/wate | e r): Not determined. | |
| Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| Solvent content: | | |
| Water: | 95.0 % | |
| VOC content: | 0.00 % | |
| | 0.0 g/l / 0.00 lb/gal | |
| Solids content: | 1.0 % | |
| Other information | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

10102-45-1 thallium nitrate

Oral LD50 15 mg/kg (mouse)

(Contd. on page 8)



Page 8/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 μg/mL in 4% HNO3

(Contd. of page 7)

- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

US ·



Page 9/13

Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/16/2021 Printing date 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

(Contd. of page 8)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

| UN2922 |
|---|
| 0142722 |
| |
| Corrosive liquids, toxic, n.o.s. (Nitric acid, Thallium nitrate) |
| 2922 CORROSIVE LIQUID, TOXIC, N.O.S. (NITRIC ACID) THALLIUM NITRATE) |
| |

· IMDG, IATA CORROSIVE LIQUID, TOXIC, N.O.S. (NITRIC ACID,

THALLIUM NITRATE)

· Transport hazard class(es)

 \cdot **DOT**





8 Corrosive substances · Class · Label 8, 6.1

 \cdot ADR





· Class 8 (CT1) Corrosive substances 8+6.1 · Label

 \cdot IMDG





· Class 8 Corrosive substances

(Contd. on page 10)



Page 10/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

| | (Contd. of page |
|--|--|
| Label | 8/6.1 |
| IATA | |
| | |
| Class | 8 Corrosive substances |
| Label | 8 (6.1) |
| Packing group DOT, ADR, IMDG, IATA | III |
| Environmental hazards: | Not applicable. |
| Special precautions for user | Warning: Corrosive substances |
| Hazard identification number (Kemler code). | |
| EMS Number: | F- A , S - B |
| Segregation groups | Strong acids |
| Stowage Category | B |
| Stowage Code | SW2 Clear of living quarters. |
| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| DOT | |
| Quantity limitations | On passenger aircraft/rail: 5 L |
| 2 | On cargo aircraft only: 60 L |
| ADR | |
| Excepted quantities (EQ) | Code: E1 |
| · · · - · | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| - · · · · · · · · · · · · · · · · · · · | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation": | UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S. (NITRIC ACID |
| The state of the s | THALLIUM NITRATE), 8 (6.1), III |

-US



Page 11/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

(Contd. of page 10)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

10102-45-1 thallium nitrate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

10102-45-1 thallium nitrate

II

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS06

GHS08

· Signal word Danger

(Contd. on page 12)



Page 12/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 µg/mL in 4% HNO3

(Contd. of page 11)

· Hazard-determining components of labeling:

nitric acid

thallium nitrate

· Hazard statements

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

- · Date of preparation / last revision 02/16/2021 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 13)



Page 13/13

Safety Data Sheet acc. to OSHA HCS

Printing date 02/16/2021 Reviewed on 02/16/2021

Trade name: Thallium (from Thallium Nitrate) 10,000 μg/mL in 4% HNO3

(Contd. of page 12)

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation - Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2