

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2021

Reviewed on 07/12/2021

Product identifier	
Trade name: <u>Lead 50 μg/mL in 2% HNO3</u>	
Article number: 50-28-1	
Details of the supplier of the safety data sheet	
Manufacturer/Supplier:	
High-Purity Standards	
7221 Investment Drive, North Charleston, SC 29418 United States	1
Telephone: +1-843-767-7900	
Fax: +1-843-767-7906	
highpuritystandards.com	
Email: info@highpuritystandards.com	
Information department: Product safety department	
Emergency telephone number:	
INFOTRAC	
Emergency telephone numbers1-800-535-5053	
Other emergency telephone numbers 1-352-323-3500	

2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Met. Corr.1H290May be corrosive to metals.Skin Corr. 1AH314Causes severe skin burns and eye damage.Eye Dam. 1H318Causes serious eye damage.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling: nitric acid*

• *Hazard statements* H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.

• **Precautionary statements** Keep only in original container.

(Contd. on page 2)

[•] US



Printing date 07/12/2021

Reviewed on 07/12/2021

Trade name: Lead 50 µg/mL in 2% HNO3

(Contd. of page 1) Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. *IF INHALED: Remove person to fresh air and keep comfortable for breathing.* If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 3 *Health* = 3 FIRE 0 Fire = 0Reactivity = 0REACTIVITY 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. 3 Composition/information on ingredients · Chemical characterization: Mixtures · Description: Mixture of the substances listed below with nonhazardous additions. · Dangerous components: 7697-37-2 nitric acid 2.0% · Chemical identification of the substance/preparation

Chemical identification of the substance/preparation7732-18-5water, distilled, conductivity or of similar purity97.995%7439-92-1lead0.005%

(Contd. on page 3)

Page 2/11



Printing date 07/12/2021

Reviewed on 07/12/2021

Trade name: Lead 50 µg/mL in 2% HNO3

(Contd. of page 2)

Page 3/11

4 First-aid measures

· Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- *After inhalation:* In case of unconsciousness place patient stably in side position for transportation.
- *After skin contact: Immediately wash with water and soap and rinse thoroughly.*
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures	
Mount respiratory protective device.	
Wear protective equipment. Keep unprotected persons away.	
Environmental precautions: Dilute with plenty of water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing agent.	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
7697-37-2 nitric acid	0.16 ppm
7439-92-1 lead	0.15 mg/m ³
· PAC-2:	
7697-37-2 nitric acid	24 ppm
	(Contd. on page 4



Page 4/11

Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2021

Reviewed on 07/12/2021

Trade name: Lead 50 µg/mL in 2% HNO3

7439-92-1 lead	(Contd. of page 3) 120 mg/m^3
• PAC-3:	
7697-37-2 nitric acid	92 ppm
7439-92-1 lead	700 mg/m ³

7 Handling and storage

- · Handling:
- *Precautions for safe handling* Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

(Contd. on page 5)

US



Printing date 07/12/2021

Reviewed on 07/12/2021

Page 5/11

(Contd. of page 4)

Trade name: Lead 50 µg/mL in 2% HNO3

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and General Information Appearance:	chemical properties	
Form:	Liquid	
Color:	colorless	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2021

Reviewed on 07/12/2021

Trade name: Lead 50 µg/mL in 2% HNO3

		(Contd. of page 2
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.01058 g/cm³ (8.43329 lbs/gal)	
Bulk density:	1,010 kg/m ³	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	98.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)



Printing date 07/12/2021

Reviewed on 07/12/2021

Trade name: Lead 50 µg/mL in 2% HNO3

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.
- Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
7439-92-1 lead	28
· NTP (National Toxicology Program)	
7439-92-1 lead	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- *Persistence and degradability No further relevant information available.*
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:
- Not hazardous for water.
- Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 8)

Page 7/11



Printing date 07/12/2021

Reviewed on 07/12/2021

Trade name: Lead 50 µg/mL in 2% HNO3

(Contd. of page 7)

Page 8/11

13 Disposal considerations

· Waste treatment methods

• *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· Uncleaned packagings:

• *Recommendation: Disposal must be made according to official regulations.*

· Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
DOT, ADR, IMDG, IATA	UN3264
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.
IMDC LATA	(NITRIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRI
IMDG, IATA	ACID)
Transport hazard class(es)	
DOT	
CORROSVE 8	
Class	8 Corrosive substances
Label	8
ADR	
Class	8 (C1) Corrosive substances
Label	8
IMDG, IATA	
8	
Class	8 Corrosive substances



Printing date 07/12/2021

Reviewed on 07/12/2021

Trade name: Lead 50 µg/mL in 2% HNO3

	(Contd. of page
Label	8
Packing group DOT, ADR, IMDG, IATA	111
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code) EMS Number: Segregation groups	F-A,S-B Acids
Stowage Category Stowage Code	A SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O., (NITRIC ACID), 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

· Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

• Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

7439-92-1 lead

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 10)

Page 9/11

US



Page 10/11

B2

AЗ

Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2021

Reviewed on 07/12/2021

Trade name: Lead 50 µg/mL in 2% HNO3

	(Contd. of page 9)	
· Hazardous Air Pollutants		
7439-92-1 lead		
· Proposition 65		
· Chemicals known to cause cancer:		
7439-92-1 lead		
· Chemicals known to cause reproductive toxicity for females:		
7439-92-1 lead		
· Chemicals known to cause reproductive toxicity for males:		
7439-92-1 lead		
· Chemicals known to cause developmental toxicity:		
7439-92-1 lead		

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7439-92-1 lead

· TLV (Threshold Limit Value established by ACGIH)

7439-92-1 lead

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: nitric acid
Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.
Precautionary statements Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 11)

US



Printing date 07/12/2021

Reviewed on 07/12/2021

Page 11/11

(Contd. of page 10)

Trade name: Lead 50 µg/mL in 2% HNO3

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

• Contact: High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

· Date of preparation / last revision 07/12/2021 / -

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit Met. Corr.1: Corrosive to metals – Category 1

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

US