

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

### 1 Identification

- **Product identifier**
- **Trade name:** CLP Analyte Standard-Revised
- **Article number:** ANALCS-R
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
High-Purity Standards  
7221 Investment Drive, North Charleston, SC 29418 United States  
Telephone: +1-843-767-7900  
Fax: +1-843-767-7906  
[highpuritystandards.com](http://highpuritystandards.com)  
Email: [info@highpuritystandards.com](mailto:info@highpuritystandards.com)
- **Information department:** Product safety department
- **Emergency telephone number:**  
INFOTRAC  
Emergency telephone numbers 1-800-535-5053  
Other emergency telephone numbers 1-352-323-3500

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Corrosive to Metals 1      H290 May be corrosive to metals.  
Skin Corrosion 1A      H314 Causes severe skin burns and eye damage.  
Eye Damage 1      H318 Causes serious eye damage.



GHS07

Acute Toxicity - Oral 4      H302 Harmful if swallowed.  
Acute Toxicity - Dermal 4      H312 Harmful in contact with skin.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07

- **Signal word** Danger

(Contd. on page 2)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 1)

**Hazard-determining components of labeling:**

nitric acid

hydrofluoric acid

**Hazard statements**

H290 May be corrosive to metals.

H302+H312 Harmful if swallowed or in contact with skin.

H314 Causes severe skin burns and eye damage.

**Precautionary statements**

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:****NFPA ratings (scale 0 - 4)**

Health = 3

Fire = 0

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = 3

Fire = 0

Reactivity = 0

**Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

US

(Contd. on page 3)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: CLP Analyte Standard-Revised

(Contd. of page 2)

**3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

7697-37-2	nitric acid	2.0%
7664-39-3	hydrofluoric acid	0.49%

· **Chemical identification of the substance/preparation**

7732-18-5	water, distilled, conductivity or of similar purity	97.434%
7440-02-0	nickel	0.01%
7440-43-9	cadmium	0.01%
7440-66-6	zinc	0.01%
7440-36-0	antimony	0.006%
513-77-9	barium carbonate	0.005%
543-81-7	beryllium acetate	0.005%
6156-78-1	Manganese(II) acetate tetrahydrate	0.005%
7440-47-3	chromium	0.005%
7440-48-4	cobalt	0.005%
7440-50-8	copper	0.005%
7803-55-6	Ammonium Vanadate	0.005%
7440-22-4	silver	0.002%
7440-28-0	thallium	0.001%
7440-38-2	arsenic	0.001%
7439-92-1	lead	0.0005%
7782-49-2	selenium	0.0005%

**4 First-aid measures**

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Immediately call a doctor.  
Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

7697-37-2	nitric acid	0.16 ppm
7440-02-0	nickel	4.5 mg/m <sup>3</sup>
7440-43-9	cadmium	0.10 mg/m <sup>3</sup>
7440-66-6	zinc	6 mg/m <sup>3</sup>
7440-36-0	antimony	1.5 mg/m <sup>3</sup>
513-77-9	barium carbonate	2.2 mg/m <sup>3</sup>
6156-78-1	Manganese(II) acetate tetrahydrate	13 mg/m <sup>3</sup>
7440-47-3	chromium	1.5 mg/m <sup>3</sup>
7440-48-4	cobalt	0.18 mg/m <sup>3</sup>

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 4)

7440-50-8	copper	3 mg/m <sup>3</sup>
7803-55-6	Ammonium Vanadate	0.01 mg/m <sup>3</sup>
7440-22-4	silver	0.3 mg/m <sup>3</sup>
7440-28-0	thallium	0.06 mg/m <sup>3</sup>
7440-38-2	arsenic	1.5 mg/m <sup>3</sup>
7439-92-1	lead	0.15 mg/m <sup>3</sup>
7782-49-2	selenium	0.6 mg/m <sup>3</sup>

**PAC-2:**

7697-37-2	nitric acid	24 ppm
7440-02-0	nickel	50 mg/m <sup>3</sup>
7440-43-9	cadmium	0.76 mg/m <sup>3</sup>
7440-66-6	zinc	21 mg/m <sup>3</sup>
7440-36-0	antimony	13 mg/m <sup>3</sup>
513-77-9	barium carbonate	270 mg/m <sup>3</sup>
6156-78-1	Manganese(II) acetate tetrahydrate	22 mg/m <sup>3</sup>
7440-47-3	chromium	17 mg/m <sup>3</sup>
7440-48-4	cobalt	2 mg/m <sup>3</sup>
7440-50-8	copper	33 mg/m <sup>3</sup>
7803-55-6	Ammonium Vanadate	0.11 mg/m <sup>3</sup>
7440-22-4	silver	170 mg/m <sup>3</sup>
7440-28-0	thallium	3.3 mg/m <sup>3</sup>
7440-38-2	arsenic	17 mg/m <sup>3</sup>
7439-92-1	lead	120 mg/m <sup>3</sup>
7782-49-2	selenium	6.6 mg/m <sup>3</sup>

**PAC-3:**

7697-37-2	nitric acid	92 ppm
7440-02-0	nickel	99 mg/m <sup>3</sup>
7440-43-9	cadmium	4.7 mg/m <sup>3</sup>
7440-66-6	zinc	120 mg/m <sup>3</sup>
7440-36-0	antimony	80 mg/m <sup>3</sup>
513-77-9	barium carbonate	1,600 mg/m <sup>3</sup>
6156-78-1	Manganese(II) acetate tetrahydrate	740 mg/m <sup>3</sup>
7440-47-3	chromium	99 mg/m <sup>3</sup>
7440-48-4	cobalt	20 mg/m <sup>3</sup>
7440-50-8	copper	200 mg/m <sup>3</sup>
7803-55-6	Ammonium Vanadate	80 mg/m <sup>3</sup>
7440-22-4	silver	990 mg/m <sup>3</sup>

(Contd. on page 6)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 5)

7440-28-0	thallium	20 mg/m <sup>3</sup>
7440-38-2	arsenic	100 mg/m <sup>3</sup>
7439-92-1	lead	700 mg/m <sup>3</sup>
7782-49-2	selenium	40 mg/m <sup>3</sup>

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

<b>7697-37-2 nitric acid</b>	
PEL	Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
REL	Short-term value: 10 mg/m <sup>3</sup> , 4 ppm Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
TLV	Short-term value: 10 mg/m <sup>3</sup> , 4 ppm Long-term value: 5.2 mg/m <sup>3</sup> , 2 ppm
<b>7664-39-3 hydrofluoric acid</b>	
PEL	Long-term value: 3 ppm as F
REL	Long-term value: 2.5 mg/m <sup>3</sup> , 3 ppm Ceiling limit value: 5* mg/m <sup>3</sup> , 6* ppm *15-min, as F
TLV	Long-term value: 0.41 mg/m <sup>3</sup> , 0.5 ppm Ceiling limit value: 1.64 mg/m <sup>3</sup> , 2 ppm as F; Skin; BEI

(Contd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 6)

**· Ingredients with biological limit values:**

**7664-39-3 hydrofluoric acid**

BEI 3 mg/g creatinine  
Medium: urine  
Time: prior to shift  
Parameter: Flourides (background)

10 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Flourides (background)

**· Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**· Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

Trade name: CLP Analyte Standard-Revised

(Contd. of page 7)

· Eye protection:



Tightly sealed goggles

**9 Physical and chemical properties**

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	colorless
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

· Density at 20 °C (68 °F): 1.00994 g/cm<sup>3</sup> (8.42795 lbs/gal)

Bulk density:	1,009 kg/m <sup>3</sup>
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

· Solubility in / Miscibility with Water:

Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

(Contd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 8)

<b>Kinematic:</b>	<i>Not determined.</i>
<b>Solvent content:</b>	
<b>Water:</b>	97.4 %
<b>VOC content:</b>	0.00 % 0.0 g/l / 0.00 lb/gal
<b>Solids content:</b>	0.1 %
<b>Other information</b>	<i>No further relevant information available.</i>

**10 Stability and reactivity**

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** *Strong caustic effect on skin and mucous membranes.*
- **on the eye:**  
*Strong caustic effect.*  
*Strong irritant with the danger of severe eye injury.*
- **Sensitization:** *No sensitizing effects known.*
- **Additional toxicological information:**  
*The product shows the following dangers according to internally approved calculation methods for preparations:*  
*Harmful*  
*Corrosive*  
*Irritant*  
*Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.*

· **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
7440-02-0	<i>nickel</i>	<i>2B</i>
7440-43-9	<i>cadmium</i>	<i>1</i>
543-81-7	<i>beryllium acetate</i>	<i>1</i>
7440-47-3	<i>chromium</i>	<i>3</i>

(Contd. on page 10)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 9)

7440-48-4	cobalt	2B
7440-38-2	arsenic	I
7439-92-1	lead	2B
7782-49-2	selenium	3

**· NTP (National Toxicology Program)**

7440-02-0	nickel	R
7440-43-9	cadmium	K
543-81-7	beryllium acetate	K
7440-48-4	cobalt	R
7440-38-2	arsenic	K
7439-92-1	lead	R

**· OSHA-Ca (Occupational Safety & Health Administration)**

7440-43-9	cadmium	
7440-38-2	arsenic	

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 1 (Self-assessment): slightly hazardous for water*  
*Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.*  
*Must not reach bodies of water or drainage ditch undiluted or unneutralized.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 11)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 10)

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

**14 Transport information**

· **UN-Number**  
· **DOT, ADR, IMDG, IATA** UN3264

· **UN proper shipping name**  
· **DOT** Corrosive liquid, acidic, inorganic, n.o.s. (Hydrofluoric acid, Nitric acid)  
· **ADR** 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROFLUORIC ACID, NITRIC ACID)  
· **IMDG, IATA** CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROFLUORIC ACID, NITRIC ACID)

· **Transport hazard class(es)**  
· **DOT**



· **Class** 8 Corrosive substances  
· **Label** 8

· **ADR**



· **Class** 8 (C1) Corrosive substances  
· **Label** 8

· **IMDG, IATA**



· **Class** 8 Corrosive substances  
· **Label** 8

· **Packing group**  
· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Corrosive substances  
· **Hazard identification number (Kemler code):** 80

(Contd. on page 12)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 11)

· <b>EMS Number:</b>	F-A,S-B
· <b>Segregation groups</b>	Acids
· <b>Stowage Category</b>	A
· <b>Stowage Code</b>	SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROFLUORIC ACID, NITRIC ACID), 8, III

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **Sara**

· <b>Section 355 (extremely hazardous substances):</b>	
7697-37-2	nitric acid
· <b>Section 313 (Specific toxic chemical listings):</b>	
7697-37-2	nitric acid
7440-02-0	nickel
7440-43-9	cadmium
7440-66-6	zinc
7440-36-0	antimony
513-77-9	barium carbonate
543-81-7	beryllium acetate
7440-47-3	chromium
7440-48-4	cobalt

(Contd. on page 13)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 12)

7440-50-8	copper
7803-55-6	Ammonium Vanadate
7440-22-4	silver
7440-28-0	thallium
7440-38-2	arsenic
7439-92-1	lead
7782-49-2	selenium

**· TSCA (Toxic Substances Control Act):**

7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
7697-37-2	nitric acid	ACTIVE
7440-02-0	nickel	ACTIVE
7440-43-9	cadmium	ACTIVE
7440-66-6	zinc	ACTIVE
7440-36-0	antimony	ACTIVE
513-77-9	barium carbonate	ACTIVE
7440-47-3	chromium	ACTIVE
7440-48-4	cobalt	ACTIVE
7440-50-8	copper	ACTIVE
7803-55-6	Ammonium Vanadate	ACTIVE
7440-22-4	silver	ACTIVE
7440-28-0	thallium	ACTIVE
7440-38-2	arsenic	ACTIVE
7439-92-1	lead	ACTIVE
7782-49-2	selenium	ACTIVE

**· Hazardous Air Pollutants**

7440-48-4	cobalt
7439-92-1	lead

**· Proposition 65**

**· Chemicals known to cause cancer:**

7440-02-0	nickel
7440-43-9	cadmium
543-81-7	beryllium acetate
7440-48-4	cobalt
7440-38-2	arsenic
7439-92-1	lead

**· Chemicals known to cause reproductive toxicity for females:**

7439-92-1	lead
-----------	------

(Contd. on page 14)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 13)

**· Chemicals known to cause reproductive toxicity for males:**

7440-43-9	cadmium
7439-92-1	lead

**· Chemicals known to cause developmental toxicity:**

7440-43-9	cadmium
7439-92-1	lead

**· Carcinogenic categories**

**· EPA (Environmental Protection Agency)**

7440-43-9	cadmium	B1
7440-66-6	zinc	D, I, II
513-77-9	barium carbonate	D, CBD(inh), NL(oral)
7440-47-3	chromium	D
7440-50-8	copper	D
7440-22-4	silver	D
7440-38-2	arsenic	A
7439-92-1	lead	B2
7782-49-2	selenium	D

**· TLV (Threshold Limit Value)**

7440-02-0	nickel	A5
7440-43-9	cadmium	A2
513-77-9	barium carbonate	A4
7440-47-3	chromium	A4
7440-48-4	cobalt	A3
7440-38-2	arsenic	A1
7439-92-1	lead	A3

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

7440-02-0	nickel
7440-43-9	cadmium
543-81-7	beryllium acetate
7440-38-2	arsenic

**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**



GHS05 GHS07

(Contd. on page 15)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 14)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*nitric acid*

*hydrofluoric acid*

· **Hazard statements**

*H290 May be corrosive to metals.*

*H302+H312 Harmful if swallowed or in contact with skin.*

*H314 Causes severe skin burns and eye damage.*

· **Precautionary statements**

*Keep only in original container.*

*Do not breathe dusts or mists.*

*Wash thoroughly after handling.*

*Do not eat, drink or smoke when using this product.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If swallowed: Call a poison center/doctor if you feel unwell.*

*If swallowed: Rinse mouth. Do NOT induce vomiting.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Immediately call a poison center/doctor.*

*Specific treatment (see on this label).*

*Take off contaminated clothing and wash it before reuse.*

*Wash contaminated clothing before reuse.*

*Absorb spillage to prevent material damage.*

*Store locked up.*

*Store in corrosive resistant container with a resistant inner liner.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** *Environment protection department.*

· **Contact:**

*High-Purity Standards*

*Tel: 843-767-7900*

*Fax: 843-767-7906*

· **Date of preparation / last revision** *02/27/2023*

· **Abbreviations and acronyms:**

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

(Contd. on page 16)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 02/27/2023

Reviewed on 02/27/2023

**Trade name: CLP Analyte Standard-Revised**

(Contd. of page 15)

*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*NFPA: National Fire Protection Association (USA)*  
*HMIS: Hazardous Materials Identification System (USA)*  
*VOC: Volatile Organic Compounds (USA, EU)*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*NIOSH: National Institute for Occupational Safety*  
*OSHA: Occupational Safety & Health*  
*TLV: Threshold Limit Value*  
*PEL: Permissible Exposure Limit*  
*REL: Recommended Exposure Limit*  
*BEI: Biological Exposure Limit*  
*Corrosive to Metals 1: Corrosive to metals – Category 1*  
*Acute Toxicity - Oral 4: Acute toxicity – Category 4*  
*Skin Corrosion 1A: Skin corrosion/irritation – Category 1A*  
*Eye Damage 1: Serious eye damage/eye irritation – Category 1*

US