

Printing date 08/04/2022

Reviewed on 08/04/2022

Page 1/14

Product identifier	
Trade name: <u>CLP Analyte Standard</u>	
Article number: ANALCS	
Details of the supplier of the safety data sheet	
Manufacturer/Supplier:	
High-Purity Standards	
7221 Investment Drive, North Charleston, SC 29418 United States	
Telephone: +1-843-767-7900	
<i>Fax:</i> +1-843-767-7906	
highpuritystandards.com	
Email: info@highpuritystandards.com	
Information department: Product safety department	
Emergency telephone number:	
INFOTRAC	
Emergency telephone numbers1-800-535-5053	
Other emergency telephone numbers 1-352-323-3500	

· Classification of the substance or mixture

GHS05 Corrosion

Met. Corr.1H290 May be corrosive to metals.Skin Corr. 1AH314 Causes severe skin burns and eye damage.Eye Dam.1H318 Causes serious eye damage.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling: nitric acid*

• *Hazard statements* H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.

• **Precautionary statements** *Keep only in original container.*

(Contd. on page 2)



Printing date 08/04/2022

Trade name: CLP Analyte Standard

Reviewed on 08/04/2022

(Contd. of page 1) Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. *IF INHALED: Remove person to fresh air and keep comfortable for breathing.* If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. *Immediately call a poison center/doctor.* Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 3 Health = 3FIRE 0 Fire = 0**REACTIVITY O** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients · Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
7697-37-2	nitric acid	2.0%
· Chemical i	dentification of the substance/preparation	
7732-18-5	water, distilled, conductivity or of similar purity	97.915%
7439-92-1	lead	0.01%
7440-02-0	nickel	0.01%
7440-22-4	silver	0.01%
7440-43-9	cadmium	0.01%
	(Con	td. on page 3

Page 2/14



Page 3/14

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: CLP Analyte Standard

		(Contd. of page 2)
7440-66-6		0.01%
513-77-9	barium carbonate	0.005%
543-81-7	beryllium acetate	0.005%
6156-78-1	Manganese(II) acetate tetrahydrate	0.005%
7440-47-3	chromium	0.005%
7440-48-4	cobalt	0.005%
7440-50-8	**	0.005%
7803-55-6	Ammonium Vanadate	0.005%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

- Dispose contaminated material as waste according to item 13.
- *Ensure adequate ventilation.*

(Contd. on page 4)

US



Printing date 08/04/2022

Trade name: CLP Analyte Standard

Defense to other sections	(Contd. of page
Reference to other sections See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
PAC-1:	
7697-37-2 nitric acid	0.16 ppm
7439-92-1 lead	0.15 mg/m
7440-02-0 nickel	$4.5 mg/m^3$
7440-22-4 silver	$0.3 mg/m^3$
7440-43-9 cadmium	0.10 mg/m
7440-66-6 zinc	$6 mg/m^3$
513-77-9 barium carbonate	2.2 mg/m ³
6156-78-1 Manganese(II) acetate tetrahydrate	13 mg/m ³
7440-47-3 chromium	1.5 mg/m ³
7440-48-4 cobalt	0.18 mg/m
7440-50-8 copper	3 mg/m ³
7803-55-6 Ammonium Vanadate	0.01 mg/m
PAC-2:	•
7697-37-2 nitric acid	24 ppm
7439-92-1 lead	120 mg/m ³
7440-02-0 nickel	50 mg/m ³
7440-22-4 silver	170 mg/m ³
7440-43-9 cadmium	0.76 mg/m
7440-66-6 zinc	21 mg/m ³
513-77-9 barium carbonate	270 mg/m ³
6156-78-1 Manganese(II) acetate tetrahydrate	22 mg/m ³
7440-47-3 chromium	17 mg/m ³
7440-48-4 cobalt	$2 mg/m^3$
7440-50-8 copper	33 mg/m ³
7803-55-6 Ammonium Vanadate	0.11 mg/m
PAC-3:	
7697-37-2 nitric acid	92 ppm
7439-92-1 lead	700 mg/m^3
7440-02-0 nickel	99 mg/m ³
7440-22-4 silver	990 mg/m ³
7440-43-9 cadmium	4.7 mg/m^3
7440-66-6 zinc	120 mg/m ³

Page 4/14

US

Reviewed on 08/04/2022



Page 5/14

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: CLP Analyte Standard

513-77-9	barium carbonate	(Contd. of page 4) <i>1,600 mg/m³</i>
6156-78-1	Manganese(II) acetate tetrahydrate	740 mg/m ³
7440-47-3	chromium	99 mg/m ³
7440-48-4		20 mg/m ³
7440-50-8	11	200 mg/m ³
7803-55-6	Ammonium Vanadate	80 mg/m ³

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

• Components with limit values that require monitoring at the workplace:

- PEL Long-term value: 5 mg/m³, 2 ppm
- REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm
- TLV Short-term value: 4 ppm

Long-term value: 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.



Printing date 08/04/2022

Reviewed on 08/04/2022

(Contd. of page 5)

Trade name: CLP Analyte Standard

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Information on basic physical and chemical properties · General Information · Appearance:			
Form:	Liquid		
Color:	According to product specification		
Odor:	Characteristic		
Odor threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100 °C (212 °F)		
Flash point:	Not applicable.		
Flammability (solid, gaseous):	Not applicable.		
Decomposition temperature:	Not determined.		

Page 6/14



Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: CLP Analyte Standard

		(Contd. of page 6
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.01606 g/cm³ (8.47902 lbs/gal)	
· Bulk density:	1,014 kg/m ³	
· Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Water:	97.9 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.1 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

US



Printing date 08/04/2022

Trade name: CLP Analyte Standard

Reviewed on 08/04/2022

(Contd. of page 7)

11 Toxicological information

· Information	on	toxicologico	al effects
mjormanon	<i>un</i>	ionicologici	n ejjecis

- Acute toxicity:
- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Inte	ernational Agency for Research on Cancer)	
7439-92-1	lead	2B
7440-02-0	nickel	2B
7440-43-9	cadmium	1
543-81-7	beryllium acetate	1
7440-47-3	chromium	3
7440-48-4	cobalt	2B
· NTP (Nati	onal Toxicology Program)	
7439-92-1	lead	R
7440-02-0	nickel	R
7440-43-9	cadmium	K
543-81-7	beryllium acetate	K
7440-48-4	cobalt	R
· OSHA-Ca	(Occupational Safety & Health Administration)	
7440-43-9	cadmium	

12 Ecological information

· Toxicity

• Aquatic toxicity: No further relevant information available.

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

Page 8/14

US



Printing date 08/04/2022

Trade name: CLP Analyte Standard

• Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

UN-Number DOT, ADR, IMDG, IATA	UN3264
UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S
	(NITRIC ACID)
IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
Transport hazard class(es)	
DOT	
ORROSIVE 8	
Class	8 Corrosive substances
Label	8

Page 9/14

Reviewed on 08/04/2022

(Contd. of page 8)



Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: CLP Analyte Standard

	(Contd. of page
ADR	
and the second s	
8	
Class Label	8 (C1) Corrosive substances 8
IMDG, IATA	
Class Label	8 Corrosive substances 8
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code):	
EMS Number:	F-A,S-B
Segregation groups	Acids
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page

Page 10/14



Page 11/14

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

(Contd. of page 10)

Trade name: CLP Analyte Standard

· UN "Model Regulation":

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

Section 35	5 (extremely hazardous substances):	
	nitric acid	
Section 31	3 (Specific toxic chemical listings):	
	nitric acid	
7439-92-1	lead	
7440-02-0	nickel	
7440-22-4	silver	
7440-43-9	cadmium	
7440-66-6	zinc	
513-77-9	barium carbonate	
543-81-7	beryllium acetate	
7440-47-3	chromium	
7440-48-4	cobalt	
7440-50-8	copper	
7803-55-6	Ammonium Vanadate	
TSCA (To:	cic Substances Control Act):	
	water, distilled, conductivity or of similar purity	ACTIV
7697-37-2	nitric acid	ACTIV
7439-92-1	lead	ACTIV
7440-02-0	nickel	ACTIV
7440-22-4	silver	ACTIV
7440-43-9	cadmium	ACTIV
7440-66-6	zinc	ACTIV
513-77-9	barium carbonate	ACTIV
7440-47-3	chromium	ACTIV
7440-48-4	cobalt	ACTIV
7440-50-8	copper	ACTIV
7002 55 6	Ammonium Vanadate	ACTIV



Page 12/14

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: CLP Analyte Standard

Hazardous	Air Pollutants	
7439-92-1	lead	
7440-48-4	cobalt	
Proposition	n 65	
Chemicals	known to cause cancer:	
7439-92-1	lead	
7440-02-0	nickel	
7440-43-9	cadmium	
	beryllium acetate	
7440-48-4	cobalt	
Chemicals	known to cause reproductive toxicity for females:	
7439-92-1	lead	
Chemicals	known to cause reproductive toxicity for males:	
7439-92-1	lead	
7440-43-9	cadmium	
Chemicals	known to cause developmental toxicity:	
7439-92-1		
7440-43-9	cadmium	
Carcinoge	nic categories	
-	ronmental Protection Agency)	
7439-92-1		<i>B2</i>
7440-22-4		D
7440-43-9	cadmium	B1
7440-66-6	zinc	D, I, II
513-77-9	barium carbonate	D, CBD(inh), NL(ora
7440-47-3	chromium	D
7440-50-8	copper	D
TLV (Thre	shold Limit Value)	I
7439-92-1	· · · · · · · · · · · · · · · · · · ·	A
7440-02-0	nickel	A
7440-43-9	cadmium	A
513-77-9	barium carbonate	A
7440-47-3	chromium	A
7440-48-4	cobalt	A
NIOSH-Ca	(National Institute for Occupational Safety and H	Iealth)
7440-02-0	nickel	
	cadmium	

- US



Page 13/14

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

Trade name: CLP Analyte Standard

(Contd. of page 12) 543-81-7 beryllium acetate • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS05 · Signal word Danger · Hazard-determining components of labeling: nitric acid · Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. · Precautionary statements Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

Contact: High-Purity Standards Tel: 843-767-7900
Fax: 843-767-7906
Date of preparation / last revision 08/04/2022 / -

(Contd. on page 14)

US



Printing date 08/04/2022

Reviewed on 08/04/2022

(Contd. of page 13)

Trade name: CLP Analyte Standard

• Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Met. Corr.1: Corrosive to metals - Category 1 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Eye Dam. 1: Serious eye damage/eye irritation - Category 1