

Page 1/17

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

1 Identification

· Product identifier

· Trade name: Continuing Check Verification Std 1

· Article number: CCV-1-A

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

· Information department: Product safety department

· Emergency telephone number:

INFOTRAC

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: nitric acid

(Contd. on page 2)



Page 2/17

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 1)

hydrogen fluoride

· Hazard statements

H290 May be corrosive to metals.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



3 Health = 3

Fire = 0

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)





Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

		(Contd.	of page
Dangerous of	=		
7697-37-2 n			4.0%
7664-39-3 I	hydrogen fluoride		0.49
	lentification of the substance/preparation		
7732-18-5	water, distilled, conductivity or of similar purity	9.	5.0359
7722-76-1	Ammonium dihydrogenphosphate	(0.05%
	potassium nitrate	(0.05%
	calcium carbonate	(0.02%
554-13-2	lithium carbonate	(0.02%
7429-90-5	aluminium	(0.02%
7439-89-6	iron	(0.02%
7439-92-1	lead	(0.02%
7439-95-4	magnesium	(0.02%
7439-98-7	molybdenum	(0.02%
7440-02-0	nickel	(0.02%
7440-28-0	thallium	(0.02%
7440-38-2	arsenic	(0.02%
7440-50-8	copper	(0.02%
7440-69-9	bismuth	(0.02%
7782-49-2	selenium	(0.02%
10042-76-9	strontium nitrate	(0.02%
10043-35-3	boric acid	(0.02%
513-77-9	barium carbonate	(0.01%
543-81-7	beryllium acetate	(0.01%
6156-78-1	Manganese(II) acetate tetrahydrate	(0.01%
7440-43-9	cadmium	(0.01%
7440-48-4	cobalt	(0.01%
7440-66-6	zinc	(0.01%
7803-55-6	Ammonium Vanadate	(0.01%
7440-47-3	chromium	0	0.0059

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)





Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 3)

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
0.16 ppm		
1.0 ppm		
17 mg/m³		
9 mg/m³		
45 mg/m ³		
3.1 mg/m		
3.2 mg/m		
0.15 mg/n		

US -





Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

7439-95-4	magnesium	(Contd. of page 18 mg/m³
	molybdenum	30 mg/m^3
7440-02-0	· ·	4.5 mg/m^3
7440-28-0		0.06 mg/m
7440-38-2		1.5 mg/m^3
7440-50-8		3 mg/m^3
7440-69-9	**	15 mg/m³
7782-49-2		0.6 mg/m^3
	strontium nitrate	5.7 mg/m^3
10043-35-3	boric acid	6 mg/m^3
513-77-9	barium carbonate	2.2 mg/m^3
6156-78-1	Manganese(II) acetate tetrahydrate	13 mg/m³
7440-43-9	· · · · · · · · · · · · · · · · · · ·	0.10 mg/m
7440-48-4	cobalt	0.18 mg/m
7440-66-6	zinc	6 mg/m ³
7803-55-6	Ammonium Vanadate	0.01 mg/m
7440-47-3	chromium	1.5 mg/m^3
PAC-2:		
	nitric acid	24 ppm
7664-39-3	hydrogen fluoride	24 ppm
	Ammonium dihydrogenphosphate	190 mg/m ³
	potassium nitrate	100 mg/m^2
471-34-1	calcium carbonate	210 mg/m ²
554-13-2	lithium carbonate	34 mg/m^3
7439-89-6	iron	35 mg/m^3
7439-92-1	lead	120 mg/m ²
7439-95-4	magnesium	200 mg/m ²
7439-98-7	molybdenum	330 mg/m ²
7440-02-0	nickel	50 mg/m ³
7440-28-0	thallium	3.3 mg/m^3
7440-38-2	arsenic	17 mg/m³
7440-50-8	copper	33 mg/m^3
7440-69-9	bismuth	170 mg/m ²
7782-49-2	selenium	6.6 mg/m^3
10042-76-9	strontium nitrate	62 mg/m^3
10042 25 2	boric acid	23 mg/m^3
10043-33-3		23 1112/111





Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

6156-78-1 Manganese(II) acetate tetrahydrate	(Contd. of p
7440-43-9 cadmium	0.76 mg
7440-48-4 cobalt	2 mg/m
7440-66-6 zinc	21 mg/n
7803-55-6 Ammonium Vanadate	0.11 mg
7440-47-3 chromium	17 mg/r
PAC-3:	-
7697-37-2 nitric acid	92 ppm
7664-39-3 hydrogen fluoride	44 ppm
7722-76-1 Ammonium dihydrogenphosphate	1,100 mg
7757-79-1 potassium nitrate	600 mg/m
471-34-1 calcium carbonate	1,300 mg
554-13-2 lithium carbonate	210 mg/n
7439-89-6 iron	150 mg/n
7439-92-1 lead	700 mg/n
7439-95-4 magnesium	1,200 mg
7439-98-7 molybdenum	2,000 mg
7440-02-0 nickel	99 mg/m
7440-28-0 thallium	20 mg/m
7440-38-2 arsenic	100 mg/n
7440-50-8 copper	200 mg/n
7440-69-9 bismuth	990 mg/n
7782-49-2 selenium	40 mg/m
10042-76-9 strontium nitrate	370 mg/n
10043-35-3 boric acid	830 mg/n
513-77-9 barium carbonate	1,600 mg
6156-78-1 Manganese(II) acetate tetrahydrate	740 mg/n
7440-43-9 cadmium	4.7 mg/m
7440-48-4 cobalt	20 mg/m
7440-66-6 zinc	120 mg/n
7803-55-6 Ammonium Vanadate	80 mg/m
7440-47-3 chromium	99 mg/m ⁻

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 7)



Page 7/17

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 6)

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 4 ppm Long-term value: 2 ppm

7664-39-3 hydrogen fluoride

PEL Long-term value: 1* mg/m³, 3 ppm

as F, *sulfuric acid

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5* mg/m³, 6* ppm

*15-min, as F

TLV Long-term value: 0.5 ppm

Ceiling limit value: 2 ppm

as F; Skin, BEI

· Ingredients with biological limit values:

7664-39-3 hydrogen fluoride

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Fluorides (background, nonspecific)

10 mg/g creatinine Medium: urine Time: end of shift

Parameter: Fluorides (background, nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 8)



Page 8/17

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 7)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

· Odor: Characteristic · Odor threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 9)





Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

		(Contd. of pa
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	
Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	95.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 10)



Page 10/17

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 9)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7664-39-3 hydrogen fluoride

Oral LD50 1,276 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic categories

· IARC (Inte	ernational Agency for Research on Cancer)	
7439-92-1	lead	2B
7440-02-0	nickel	2B
7440-38-2	arsenic	1
7782-49-2	selenium	3
543-81-7	beryllium acetate	1
7440-43-9	cadmium	1
7440-48-4	cobalt	2B
7440-47-3	chromium	3
· NTP (Nati	onal Toxicology Program)	
7439-92-1	lead	R
7440-02-0	nickel	R
7440-38-2	arsenic	K
543-81-7	beryllium acetate	K
7440-43-9	cadmium	K
7440-48-4	cobalt	R
		(Contd. on page 11)

- US





Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 10)

· OSHA-Ca	(Occupational Safety & Health Administration)
7440-38-2	arsenic
7440-43-9	cadmium

12 Ecological information

- **Toxicity**
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	UN3264	
· UN proper shipping name		
$\cdot DOT$	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)	
· ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGÂNIC, N.O. (NITRIC ACID)	
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITR ACID)	

(Contd. on page 12)



Page 12/17

acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 11)

· Transport hazard class(es)

 $\cdot DOT$



· Class 8 Corrosive substances

· Label

 \cdot ADR



· Class 8 (C1) Corrosive substances

· Label

· IMDG, IATA



· Class 8 Corrosive substances

· Label

· Packing group

· DOT, ADR, IMDG, IATA III

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Corrosive substances

Hazard identification number (Kemler code): 80
EMS Number: F-A,S-B
Segregation groups Acids
Stowage Category A

• Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

 \cdot **DOT**

• Quantity limitations On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

(Contd. on page 13)



(Contd. of page 12)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

· ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

(NITRIC ACID), 8, III

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

15 Regulatory information

· UN "Model Regulation":

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- ·Sara

· Section 355	(extremely hazardous substances):
7697-37-2	nitric acid
7664-39-3	hydrogen fluoride
· Section 313	(Specific toxic chemical listings):
	nitric acid
7664-39-3	hydrogen fluoride
7757-79-1	potassium nitrate
554-13-2	lithium carbonate
7429-90-5	aluminium
7439-92-1	lead
7440-02-0	nickel
7440-28-0	thallium
7440-38-2	arsenic
7440-50-8	copper
7782-49-2	selenium
10042-76-9	strontium nitrate
513-77-9	barium carbonate
543-81-7	beryllium acetate
7440-43-9	cadmium
7440-48-4	cobalt
7440-66-6	zinc

(Contd. on page 14)





Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

	(Contd. of page
7803-55-6 Ammonium Vanadate	
7440-47-3 chromium	
TSCA (Toxic Substances Control Act):	
7732-18-5 water, distilled, conductivity or of similar purity	ACTIV.
7697-37-2 nitric acid	ACTIV.
7664-39-3 hydrogen fluoride	ACTIV.
7722-76-1 Ammonium dihydrogenphosphate	ACTIV.
7757-79-1 potassium nitrate	ACTIV.
471-34-1 calcium carbonate	ACTIV.
554-13-2 lithium carbonate	ACTIV.
7429-90-5 aluminium	ACTIV.
7439-89-6 iron	ACTIV.
7439-92-1 lead	ACTIV.
7439-95-4 magnesium	ACTIV.
7439-98-7 molybdenum	ACTIV.
7440-02-0 nickel	ACTIV.
7440-28-0 thallium	ACTIV.
7440-38-2 arsenic	ACTIV.
7440-50-8 copper	ACTIV.
7440-69-9 bismuth	ACTIV.
7782-49-2 selenium	ACTIV.
10042-76-9 strontium nitrate	ACTIV.
10043-35-3 boric acid	ACTIV.
513-77-9 barium carbonate	ACTIV.
7440-43-9 cadmium	ACTIV.
7440-48-4 cobalt	ACTIV.
7440-66-6 zinc	ACTIV.
7803-55-6 Ammonium Vanadate	ACTIV.
7440-47-3 chromium	ACTIV.
Hazardous Air Pollutants	·
7664-39-3 hydrogen fluoride	
7439-92-1 lead	
7440-48-4 cobalt	
Proposition 65	
Chemicals known to cause cancer:	
7439-92-1 lead	
7440-02-0 nickel	



Page 15/17

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

7440-38-2	arsenic	(Contd. of pag
	beryllium acetate	
7440-43-9		
7440-48-4	cobalt	
· Chemicals	known to cause reproductive toxicity for females:	
7439-92-1		
· Chemicals	known to cause reproductive toxicity for males:	
7439-92-1	lead	
7440-43-9	cadmium	
· Chemicals	known to cause developmental toxicity:	
554-13-2	lithium carbonate	
7439-92-1	lead	
7440-43-9	cadmium	
· Carcinoger	iic categories	
	ronmental Protection Agency)	
7439-92-1	=	<i>B2</i>
7440-38-2	arsenic	A
7440-50-8	copper	D
	selenium	D
10043-35-3	boric acid	I (oral)
513-77-9	barium carbonate	D, CBD(inh), NL(or
7440-43-9	cadmium	<i>B1</i>
7440-66-6	zinc	D, I, II
7440-47-3	chromium	D
· TLV (Thre	shold Limit Value)	
7429-90-5	aluminium	
7439-92-1	lead	
7439-98-7	molybdenum	
7440-02-0	nickel	
7440-38-2	arsenic	
10043-35-3	boric acid	
513-77-9	barium carbonate	
7440-43-9	cadmium	
7440-48-4	cobalt	
7440-47-3	chromium	
· NIOSH-Ca	(National Institute for Occupational Safety and Health,)
NIOSH-Ca 7440-02-0	· · · · · · · · · · · · · · · · · · ·)



Page 16/17

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 15)

(Conta. of page 13
arsenic
beryllium acetate
cadmium

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- Hazard-determining components of labeling:

nitric acid

hydrogen fluoride

· Hazard statements

H290 May be corrosive to metals.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

(Contd. on page 17)



Page 17/17

Safety Data Sheet acc. to OSHA HCS

Printing date 06/17/2022 Reviewed on 06/17/2022

Trade name: Continuing Check Verification Std 1

(Contd. of page 16)

· Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

· Date of preparation / last revision 06/17/2022 / -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

-US