

Page 1/15

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2020 Reviewed on 05/22/2020

1 Identification

· Product identifier

· Trade name: CRDL Detection Limit Standard

· Article number: CRDL

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

· Information department: Product safety department

Emergency telephone number:

INFOTRAC

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: nitric acid

(Contd. on page 2)



Page 2/15

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 1)

hydrogen fluoride

· Hazard statements

H290 May be corrosive to metals.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



3 Health = 3

Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)



Page 3/15

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

	(Contd. of page
Dangerous components:	
7697-37-2 nitric acid	2.0%
7664-39-3 hydrofluoric acid	0.49%
Chemical identification of the substance/preparation	
7732-18-5 water, distilled, conductivity or of similar purity	97.446%
7440-36-0 antimony	0.012%
7440-48-4 cobalt	0.01%
7803-55-6 Ammonium Vanadate	0.01%
7440-02-0 nickel	0.008%
7440-50-8 copper	0.005%
7440-66-6 zinc	0.004%
6156-78-1 Manganese(II) acetate tetrahydrate	0.003%
7440-22-4 silver	0.002%
7440-28-0 thallium	0.002%
7440-38-2 arsenic	0.002%
7440-47-3 chromium	0.002%
543-81-7 beryllium acetate	0.001%
7440-43-9 cadmium	0.001%
7782-49-2 selenium	0.001%
7439-92-1 lead	0.0006%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

. . .





Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Dilute with plenty of water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:	
7697-37-2 nitric acid	0.16 ppm
7440-36-0 antimony	1.5 mg/m^3
7440-48-4 cobalt	0.18 mg/m
7803-55-6 Ammonium Vanadate	0.01 mg/m
7440-02-0 nickel	4.5 mg/m ³
7440-50-8 copper	3 mg/m ³
7440-66-6 zinc	6 mg/m³
6156-78-1 Manganese(II) acetate tetrahydrate	13 mg/m³
7440-22-4 silver	0.3 mg/m ³
7440-28-0 thallium	0.06 mg/m
7440-38-2 arsenic	1.5 mg/m ³
7440-47-3 chromium	1.5 mg/m ³
7440-43-9 cadmium	0.10 mg/m
7782-49-2 selenium	0.6 mg/m^3
7439-92-1 lead	0.15 mg/m





Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

D (C)	(Contd. of page
PAC-2:	24
7697-37-2 nitric acid	24 ppm
7440-36-0 antimony	13 mg/m^3
7440-48-4 cobalt	$2 mg/m^3$
7803-55-6 Ammonium Vanadate	0.11 mg/n
7440-02-0 nickel	50 mg/m^3
7440-50-8 copper	33 mg/m ³
7440-66-6 zinc	21 mg/m³
6156-78-1 Manganese(II) acetate tetrahydrate	22 mg/m³
7440-22-4 silver	170 mg/m
7440-28-0 thallium	3.3 mg/m^{3}
7440-38-2 arsenic	17 mg/m³
7440-47-3 chromium	17 mg/m³
7440-43-9 cadmium	0.76 mg/n
7782-49-2 selenium	6.6 mg/m ³
7439-92-1 lead	120 mg/m
PAC-3:	
7697-37-2 nitric acid	92 ppm
7440-36-0 antimony	80 mg/m ²
7440-48-4 cobalt	20 mg/m ²
7803-55-6 Ammonium Vanadate	80 mg/m ²
7440-02-0 nickel	99 mg/m ²
7440-50-8 copper	200 mg/n
7440-66-6 zinc	120 mg/n
6156-78-1 Manganese(II) acetate tetrahydrate	740 mg/n
7440-22-4 silver	990 mg/n
7440-28-0 thallium	20 mg/m ²
7440-38-2 arsenic	100 mg/n
7440-47-3 chromium	99 mg/m ³
7440-43-9 cadmium	4.7 mg/m
7782-49-2 selenium	40 mg/m^3
7439-92-1 lead	700 mg/n

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 6)



Page 6/15

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 5)

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

7664-39-3 hydrofluoric acid

PEL Long-term value: 3 ppm

REL Long-term value: 2.5 mg/m³, 3 ppm Ceiling limit value: 5* mg/m³, 6* ppm *15-min, as F

TLV Long-term value: 0.41 mg/m³, 0.5 ppm Ceiling limit value: 1.64 mg/m³, 2 ppm

as F; Skin; BEI

Ingredients with biological limit values:

7664-39-3 hydrofluoric acid

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Flourides (background)

10 mg/g creatinine Medium: urine Time: end of shift

Parameter: Flourides (background)

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 7)



Page 7/15

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 6)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: colorless
Odor: Characteristic
Odor threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 8)





Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

	(Contd.	of page
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100°C (212°F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.00943 g/cm³ (8.42369 lbs/gal)	
· Bulk density: · Relative density · Vapor density · Evaporation rate	1,008 kg/m³ Not determined. Not determined. Not determined.	
· Solubility in / Miscibility with Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
· Solvent content: Water: VOC content:	97.4 % 0.00 % 0.0 g/l / 0.00 lb/gal	
Solids content: Other information	0.1 % No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.

(Contd. on page 9)





Page 9/15

acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 8)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on (Cancer)	
7440-48-4 cobalt		2 <i>E</i>
7440-02-0 nickel		2E
7440-38-2 arsenic		1
7440-47-3 chromium		3
543-81-7 beryllium acetate		1
7440-43-9 cadmium		1
7782-49-2 selenium		3
7439-92-1 lead		2 <i>E</i>
· NTP (National Toxicology Program)		
7440-48-4 cobalt		K
7440-02-0 nickel		F
7440-38-2 arsenic		K
543-81-7 beryllium acetate		K
7440-43-9 cadmium		K
7439-92-1 lead		F
OSHA-Ca (Occupational Safety & Health Adn	ninistration)	
7440-38-2 arsenic		



Page 10/15

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 9)

7440-43-9 cadmium

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name	
$\cdot DOT$	Corrosive liquid, acidic, inorganic, n.o.s. (Hydrofluoric acid, Nitric acid)
· ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
	(HYDROFLUORIC ACID, NITRIC ACID)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
	(HYDROFLUORIC ACID, NITRIC ACID)

(Contd. on page 11)





Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 10)

- · Transport hazard class(es)
- $\cdot DOT$



- · Class 8 Corrosive substances
- · Label
- $\cdot ADR$



- · Class 8 (C1) Corrosive substances
- · Label
- · IMDG, IATA



- · Class 8 Corrosive substances
- · Label
- · Packing group
- · DOT, ADR, IMDG, IATA III
- Environmental hazards: Not applicable.
- · Special precautions for user Warning: Corrosive substances
- Hazard identification number (Kemler code): 80
 EMS Number: F-A,S-B
 Segregation groups Acids
- · Stowage Category A
- Stowage Code SW2 Clear of living quarters.
- · Transport in bulk according to Annex II of
- MARPOL73/78 and the IBC Code Not applicable.
- · Transport/Additional information:
- $\cdot DOT$
- Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

(Contd. on page 12)





Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 11)

· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (HYDROFLUORIC ACID, NITRIC ACID), 8, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Section 35.	5 (extremely hazardous substances):	
7697-37-2	nitric acid	
Section 31.	3 (Specific toxic chemical listings):	
7697-37-2	nitric acid	
7440-36-0	antimony	
7440-48-4	cobalt	
7803-55-6	Ammonium Vanadate	
7440-02-0		
7440-50-8	copper	
7440-66-6	zinc	
7440-22-4	silver	
7440-28-0	thallium	
7440-38-2	arsenic	
7440-47-3	chromium	
543-81-7	beryllium acetate	
7440-43-9	cadmium	
7782-49-2	selenium	
7439-92-1	lead	
TSCA (Tox	xic Substances Control Act):	
7732-18-5	water, distilled, conductivity or of similar purity	ACTIV
7697-37-2	nitric acid	ACTIV
7440-36-0	antimony	ACTIV

(Contd. on page 13)





Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

		(Contd. of page
7440-48-4		ACTI
	Ammonium Vanadate	ACTI
7440-02-0		ACTI
7440-50-8		ACTI
7440-66-6		ACTI
7440-22-4		ACTI
7440-28-0	thallium	ACTI
7440-38-2	arsenic	ACTI
7440-47-3	chromium	ACTI
7440-43-9	cadmium	ACTI
7782-49-2	selenium	ACTI
7439-92-1	lead	ACTI
Hazardous	Air Pollutants	'
7440-48-4	cobalt	
7439-92-1	lead	
Proposition	1 65	
-	known to cause cancer:	
7440-48-4	cobalt	
7440-02-0	nickel	
7440-38-2	arsenic	
543-81-7	beryllium acetate	
7440-43-9	cadmium	
7439-92-1	lead	
Chemicals	known to cause reproductive toxicity for females:	
7439-92-1		
Chomicals	known to cause reproductive toxicity for males:	
7440-43-9		
7439-92-1		
	known to cause developmental toxicity:	
7440-43-9		
7439-92-1	ieaa	
Carcinoger	nic categories	
EPA (Envi	ronmental Protection Agency)	
7440-50-8	copper	D
7440-66-6	zinc	D, I,
7440-22-4	silver	D
	arsenic	



Page 14/15

acc. to OSHA HCS

Reviewed on 05/22/2020 Printing date 05/22/2020

Trade name: CRDL Detection Limit Standard

		Contd. of page
7440-47-3	chromium	D
7440-43-9	cadmium	<i>B1</i>
7782-49-2	selenium	D
7439-92-1	lead	B2
· TLV (Thre	shold Limit Value established by ACGIH)	
7440-48-4	cobalt	A
7440-02-0	nickel	£
7440-38-2	arsenic	£
7440-47-3	chromium	P.
7440-43-9	cadmium	£
7439-92-1	lead	I
· NIOSH-Co	a (National Institute for Occupational Safety and Health)	
7440-02-0	nickel	
7440-38-2	arsenic	
543-81-7	beryllium acetate	
7440-43-9	cadmium	

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

hydrogen fluoride

· Hazard statements

H290 May be corrosive to metals.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 15)



Page 15/15

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2020 Reviewed on 05/22/2020

Trade name: CRDL Detection Limit Standard

(Contd. of page 14)

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

- · Date of preparation / last revision 05/22/2020 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

 ${\it IATA: International Air Transport Association}$

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1