

Page 1/17

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

Product id	lentifier
Trade nar	ne: <u>Certified Waste Water Trace Metals G</u>
Article nu	mber: CWW-TM-G
Manufact High-Puri 7221 Inver Telephone Fax: +1-8 highpurity	the supplier of the safety data sheet urer/Supplier: ty Standards stment Drive, North Charleston, SC 29418 United States : +1-843-767-7900 43-767-7906 standards.com b@highpuritystandards.com
	on department: Product safety department
INFOTRA Emergenc	v telephone numbers1-800-535-5053
Other eme	rgency telephone numbers 1-352-323-3500
	s) identification
Hazard(
Hazard(Classifica	s) identification tion of the substance or mixture
Hazard(Classifica	s) identification
Hazard(Classifica	s) identification tion of the substance or mixture GHS05 Corrosion
Hazard(Classifica	s) identification tion of the substance or mixture GHS05 Corrosion
Hazard Classifica	s) identification tion of the substance or mixture GHS05 Corrosion 1 H290 May be corrosive to metals.
Hazard Classifica	s) identification tion of the substance or mixture GHS05 Corrosion 1 H290 May be corrosive to metals. 1A H314 Causes severe skin burns and eye damage.
Hazard(Classifica (Met. Corr Skin Corr. Eye Dam.	s) identification tion of the substance or mixture GHS05 Corrosion 1 H290 May be corrosive to metals. 1A H314 Causes severe skin burns and eye damage. 1 H318 Causes serious eye damage.
Hazard Classifica Met. Corr Skin Corr. Eye Dam. Eye Dam. Acute Tox Label elei	 s) identification s) identification tion of the substance or mixture GHS05 Corrosion 1 H290 May be corrosive to metals. 1A H314 Causes severe skin burns and eye damage. 1 H318 Causes serious eye damage. GHS07 4 H312 Harmful in contact with skin. tents telements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Signal word Danger

• Hazard-determining components of labeling: nitric acid

(Contd. on page 2)

⁻ US



Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

1 1 0	(Contd. of page
hydrogen fluo	
Hazard staten	
	corrosive to metals.
	in contact with skin.
	evere skin burns and eye damage.
Precautionary	
	riginal container.
	e dusts or mists.
	nly after handling.
	e gloves/protective clothing/eye protection/face protection.
	Rinse mouth. Do NOT induce vomiting.
	air): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rin	se cautiously with water for several minutes. Remove contact lenses, if present and easy to a
Continue rins	ıg.
Immediately c	Ill a poison center/doctor.
Specific treatr	ent (see on this label).
Take off conta	ninated clothing and wash it before reuse.
	nated clothing before reuse.
	e to prevent material damage.
Store locked u	
Store in corro	ive resistant container with a resistant inner liner.
Dispose of con	tents/container in accordance with local/regional/national/international regulations.
Classification	system:
NFPA ratings	(scale 0 - 4)
	Health = 3
	Fire $= 0$
$\langle 3 \rangle \langle 0 \rangle$	Reactivity = 0
\checkmark	<i>Teactivity</i> = 0
HMIS-ratings	(scale 0 - 4)
HEALTH 3	Health = 3
FIRE 0	
	Fire = 0
REACTIVITY 0	Reactivity = 0
Other hazard	
	and vPvB assessment
PBT: Not app	
vPvB: Not app	
0	n/information on ingredients

• Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Page 2/17



Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

	(Contd. of page 2
· Dangerous components:	
7697-37-2 nitric acid	10.0%
7664-39-3 hydrogen fluoride	0.49%
· Chemical identification of the substance/preparation	
7732-18-5 water, distilled, conductivity or of similar purity	89.4258%
7429-90-5 aluminium	0.01%
7439-89-6 iron	0.01%
7439-96-5 manganese	0.01%
7439-98-7 molybdenum	0.01%
7440-24-6 strontium	0.01%
7440-48-4 cobalt	0.01%
7440-62-2 vanadium	0.01%
7440-02-0 nickel	0.0025%
7440-38-2 arsenic	0.0025%
7440-41-7 beryllium	0.0025%
7440-43-9 cadmium	0.0025%
7782-49-2 selenium	0.0025%
7439-92-1 lead	0.00025%
7440-39-3 barium	0.00025%
7440-42-8 boron	0.00025%
7440-47-3 chromium	0.00025%
7440-50-8 copper	0.00025%
7440-66-6 zinc	0.00025%

4 First-aid measures

• Description of first aid measures

• General information:

- Immediately remove any clothing soiled by the product.
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- *After inhalation:* In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.

(Contd. on page 4)

US

Page 3/17



Printing date 05/26/2022

Reviewed on 05/26/2022

(Contd. of page 3)

US

Trade name: Certified Waste Water Trace Metals G

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

0 / ICC/IIC/II	in release measures	
	recautions, protective equipment and emergency procedures	
	iratory protective device.	
	ctive equipment. Keep unprotected persons away.	
	ental precautions:	
	plenty of water.	
	w to enter sewers/ surface or ground water.	
	nd material for containment and cleaning up:	
	h liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
	lizing agent.	
	ntaminated material as waste according to item 13.	
	quate ventilation.	
	to other sections	
	27 for information on safe handling. 28 for information on personal protection equipment.	
	2 13 for disposal information.	
	Action Criteria for Chemicals	
· PAC-1:	Action Crueriu for Chemicuis	
		0.14
7697-37-2		0.16 ppm
	hydrogen fluoride	1.0 ppm
7439-89-6	iron	$3.2 mg/m^3$
7439-96-5	manganese	3 mg/m ³
7439-98-7	molybdenum	30 mg/m ³
7440-24-6	strontium	30 mg/m ³
7440-48-4	cobalt	0.18 mg/m ³
7440-62-2	vanadium	3 mg/m ³
7440-02-0	nickel	$4.5 mg/m^{3}$
7440-38-2	arsenic	1.5 mg/m ³
7440-41-7	beryllium	0.0023 mg/m ³
		(Contd. on page 5)

Page 4/17



Page 5/17

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

7440 42 0		(Contd. of page
7440-43-9		0.10 mg/m ³
7782-49-2		0.6 mg/m^3
7439-92-1		$0.15 mg/m^3$
7440-39-3		1.5 mg/m ³
7440-42-8		1.9 mg/m ³
7440-47-3		1.5 mg/m ³
7440-50-8		$3 mg/m^3$
7440-66-6	zinc	6 mg/m ³
7439-97-6	mercury	$0.15 mg/m^3$
7440-22-4	silver	$0.3 mg/m^3$
7440-28-0	thallium	$0.06 mg/m^3$
7440-36-0	antimony	1.5 mg/m ³
PAC-2:		-
7697-37-2	nitric acid	24 ppm
7664-39-3	hydrogen fluoride	24 ppm
7439-89-6	iron	35 mg/m ³
7439-96-5	manganese	$5 mg/m^3$
7439-98-7	molybdenum	330 mg/m ³
7440-24-6	strontium	330 mg/m ³
7440-48-4	cobalt	$2 mg/m^3$
7440-62-2	vanadium	5.8 mg/m ³
7440-02-0	nickel	50 mg/m ³
7440-38-2	arsenic	17 mg/m ³
7440-41-7	bervllium	0.025 mg/m
7440-43-9	•	0.76 mg/m ³
7782-49-2	selenium	6.6 mg/m ³
7439-92-1		120 mg/m ³
7440-39-3		180 mg/m ³
7440-42-8		21 mg/m ³
7440-47-3		17 mg/m ³
7440-50-8		33 mg/m ³
7440-66-6		21 mg/m ³
7439-97-6		1.7 mg/m ³
7440-22-4	-	170 mg/m ³
7440-28-0		3.3 mg/m ³
7440-36-0		13 mg/m ³
/ 770- 00-0	инипопу	(Contd. on page



Page 6/17

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

		(Contd. of page 5)
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7664-39-3	hydrogen fluoride	44 ppm
7439-89-6	iron	150 mg/m ³
7439-96-5	manganese	1,800 mg/m ³
7439-98-7	molybdenum	2,000 mg/m ³
7440-24-6	strontium	2,000 mg/m ³
7440-48-4	cobalt	20 mg/m ³
7440-62-2	vanadium	35 mg/m ³
7440-02-0	nickel	99 mg/m ³
7440-38-2	arsenic	100 mg/m ³
7440-41-7	beryllium	$0.1 \ mg/m^3$
7440-43-9	cadmium	$4.7 mg/m^3$
7782-49-2	selenium	40 mg/m ³
7439-92-1	lead	700 mg/m ³
7440-39-3	barium	1,100 mg/m ³
7440-42-8	boron	130 mg/m ³
7440-47-3	chromium	99 mg/m ³
7440-50-8	copper	200 mg/m ³
7440-66-6	zinc	120 mg/m ³
7439-97-6	mercury	8.9 mg/m ³
7440-22-4	silver	990 mg/m ³
7440-28-0	thallium	20 mg/m^3
7440-36-0	antimony	80 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 7)

US



Printing date 05/26/2022

Trade name: Certified Waste Water Trace Metals G

• *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
	-37-2 nitric acid
PEL	Long-term value: 5 mg/m ³ , 2 ppm
RFI	Short-term value: 10 mg/m ³ 4 nnm

- REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm TLV Short-term value: 4 ppm
 - Long-term value: 2 ppm

7664-39-3 hydrogen fluoride

- PEL Long-term value: 1* mg/m³, 3 ppm as F, *sulfuric acid
- REL Long-term value: 2.5 mg/m³, 3 ppm Ceiling limit value: 5* mg/m³, 6* ppm *15-min, as F
- TLV Long-term value: 0.5 ppm Ceiling limit value: 2 ppm as F; Skin, BEI

· Ingredients with biological limit values:

7664-39-3 hydrogen fluoride

BEI 3 mg/g creatinine Medium: urine Time: prior to shift Parameter: Fluorides (background, nonspecific)

10 mg/g creatinine Medium: urine Time: end of shift Parameter: Fluorides (background, nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Page 7/17

Reviewed on 05/26/2022

(Contd. of page 6)



Printing date 05/26/2022

Reviewed on 05/26/2022

(Contd. of page 7)

Trade name: Certified Waste Water Trace Metals G

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and General Information Appearance:	chemical properties	
Form:	Liquid	
Color:	colorless	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 83 °C (181.4 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	

Page 8/17



Page 9/17

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

	(Contd. of page
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Water:	89.4 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	0.1 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 10)

US



Page 10/17

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

(Contd. of page 9)

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

7664-39-3 hydrogen fluoride

Oral LD50 1,276 mg/kg (rat)

· Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

• on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

7440-48-4 cobalt	
7440-02-0 nickel	
7440-38-2 arsenic	
7440-41-7 beryllium	
7440-43-9 cadmium	
7782-49-2 selenium	
7439-92-1 lead	
7440-47-3 chromium	
7439-97-6 mercury	
NTP (National Toxicology Program)	
7440-48-4 cobalt	
7440-02-0 nickel	
7440-38-2 arsenic	
7440-41-7 beryllium	
7440-43-9 cadmium	
7439-92-1 lead	
OSHA-Ca (Occupational Safety & Health Administration,)
7440-38-2 arsenic	



Page 11/17

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

(Contd. of page 10)

Trade name: Certified Waste Water Trace Metals G

7440-43-9 cadmium

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S
	(NITRIC ACID)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC
	ACID)



Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

		(Contd. of page
Transport hazard class(es)		
DOT		
CORROSIVE 8		
· Class	8 Corrosive substances	
Label	8	
ADR		
Class Label	8 (C1) Corrosive substances 8	
Class	8 Corrosive substances	
Label	8	
Packing group DOT, ADR, IMDG, IATA	II	
Environmental hazards:	Not applicable.	
Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Corrosive substances 80 F-A,S-B	
Segregation groups	Acids	
Stowage Category	B SW2 Class of living superstand	
Stowage Code Transport in bulk according to Annex II of	SW2 Clear of living quarters.	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
DOT Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L	
	~ · ·	(Contd. on page

Page 12/17



Page 13/17

US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

	(Contd. of page 12)
· ADR · Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
• UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

7697-37-2	nitric acid
7664-39-3	hydrogen fluoride
Section 313	3 (Specific toxic chemical listings):
7697-37-2	nitric acid
7664-39-3	hydrogen fluoride
7429-90-5	aluminium
7439-96-5	manganese
7440-48-4	cobalt
7440-62-2	vanadium
7440-02-0	nickel
7440-38-2	arsenic
7440-41-7	beryllium
7440-43-9	cadmium
7782-49-2	selenium
7439-92-1	lead
7440-39-3	barium
7440-47-3	chromium
7440-50-8	copper
7440-66-6	zinc
7439-97-6	mercury



Page 14/17

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

		(Contd. of page 1)
7440-22-4		
7440-28-0	thallium	
7440-36-0	antimony	
TSCA (Tox	cic Substances Control Act):	
All compon	nents have the value ACTIVE.	
Hazardous	Air Pollutants	
7664-39-3	hydrogen fluoride	
7439-96-5	manganese	
7440-48-4	cobalt	
7439-92-1	lead	
Proposition	n 65	
Chemicals	known to cause cancer:	
7440-48-4	cobalt	
7440-02-0		
7440-38-2	arsenic	
7440-41-7	beryllium	
7440-43-9	cadmium	
7439-92-1	lead	
Chemicals	known to cause reproductive toxicity for females:	
7439-92-1	lead	
Chemicals	known to cause reproductive toxicity for males:	
7440-43-9		
7439-92-1	lead	
Chemicals	known to cause developmental toxicity:	
7440-43-9		
7439-92-1	lead	
7439-97-6	mercury	
-	nic categories ronmental Protection Agency)	
	manganese	D
7439-90-3		
7440-38-2		B1, K/L(inh), CBD(oral,
7440-41-7	-	B1, K/L(inn), CBD(oral) B1
7782-49-2		D
7439-92-1		<u> </u>
7440-39-3		D, CBD(inh), NL(oral)
7440-39-3		I (oral)
7770-42-0	001011	(Contd. on page 1)



Page 15/17

Safety Data Sheet acc. to OSHA HCS

Printing date 05/26/2022

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

		(Contd. of pag	ge 1
7440-47-3	chromium	D	
7440-50-8	copper	D	
7440-66-6	zinc	D, I, II	
7439-97-6	mercury	D	
7440-22-4	silver	D	
TLV (Thre	shold Limit Value)		_
7429-90-5	aluminium		A
7439-98-7	molybdenum		A.
7440-48-4	cobalt		A.
7440-02-0	nickel		A.
7440-38-2	arsenic		Α.
7440-41-7	beryllium		Α.
7440-43-9	cadmium		A.
7439-92-1	lead		A.
7440-39-3	barium		A
7440-47-3	chromium		A^2
7439-97-6	mercury		A
NIOSH-Ca	(National Institute for Occupational Safety and Health)	·	
7440-02-0	nickel		
7440-38-2	arsenic		
7440-41-7	beryllium		
7440-43-9	cadmium		

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: nitric acid hydrogen fluoride
Hazard statements H290 May be corrosive to metals. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage.
Precautionary statements Keep only in original container. Do not breathe dusts or mists.

(Contd. on page 16)

US



Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eve protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: *High-Purity Standards* Tel: 843-767-7900 Fax: 843-767-7906

· Date of preparation / last revision 05/26/2022 / -

• Abbreviations and acronvms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA:** Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Met. Corr.1: Corrosive to metals – Category 1 Acute Tox. 4: Acute toxicity - Category 4

(Contd. on page 17)

Page 16/17

(Contd. of page 15)



Printing date 05/26/2022

Page 17/17

Reviewed on 05/26/2022

Trade name: Certified Waste Water Trace Metals G

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1 (Contd. of page 16)

US