

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

1 Identification

- **Product identifier**
- **Trade name:** Urine Multi-Element Stock
- **Article number:** HEALTH-3-A
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 High-Purity Standards
 P.O. Box 41727
 Charleston, SC 29423
 Telephone: (843) 767-7900
 FAX: (843) 767-7906
- **Information department:** Product safety department
- **Emergency telephone number:**
 INFOTRAC
 Emergency telephone numbers 1-800-535-5053
 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
 nitric acid
 arsenic
- **Hazard statements**
 H290 May be corrosive to metals.
 H314 Causes severe skin burns and eye damage.
 H350 May cause cancer.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 1)

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep only in original container.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Absorb spillage to prevent material damage.
Store locked up.
Store in corrosive resistant container with a resistant inner liner.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

7697-37-2	nitric acid	5.0%
10042-76-9	strontium nitrate	1.2%
7440-38-2	arsenic	0.4%

· **Chemical identification of the substance/preparation**

21351-79-1	caesium hydroxide	0.04%
513-77-9	barium carbonate	0.04%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 2)

6156-78-1	Manganese(II) acetate tetrahydrate	0.02%
7439-92-1	lead	0.02%
543-81-7	beryllium acetate	0.02%
7440-43-9	cadmium (non-pyrophoric)	0.016%
7440-48-4	cobalt	0.015%
7440-28-0	thallium	0.008%
10102-06-4	Uranyl nitrate	0.001%
7732-18-5	water, distilled, conductivity or of similar purity	93.22%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 3)

· Protective Action Criteria for Chemicals
· PAC-1:

7697-37-2	nitric acid	0.16 ppm
10042-76-9	strontium nitrate	5.7 mg/m ³
7440-38-2	arsenic	1.5 mg/m ³
21351-79-1	caesium hydroxide	6 mg/m ³
513-77-9	barium carbonate	2.2 mg/m ³
6156-78-1	Manganese(II) acetate tetrahydrate	13 mg/m ³
7439-92-1	lead	0.15 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	0.10 mg/m ³
7440-48-4	cobalt	0.18 mg/m ³
7440-28-0	thallium	0.06 mg/m ³
10102-06-4	Uranyl nitrate	0.99 mg/m ³

· PAC-2:

7697-37-2	nitric acid	24 ppm
10042-76-9	strontium nitrate	62 mg/m ³
7440-38-2	arsenic	17 mg/m ³
21351-79-1	caesium hydroxide	19 mg/m ³
513-77-9	barium carbonate	270 mg/m ³
6156-78-1	Manganese(II) acetate tetrahydrate	22 mg/m ³
7439-92-1	lead	120 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	0.76 mg/m ³
7440-48-4	cobalt	2 mg/m ³
7440-28-0	thallium	3.3 mg/m ³
10102-06-4	Uranyl nitrate	5.5 mg/m ³

· PAC-3:

7697-37-2	nitric acid	92 ppm
10042-76-9	strontium nitrate	370 mg/m ³
7440-38-2	arsenic	100 mg/m ³
21351-79-1	caesium hydroxide	110 mg/m ³
513-77-9	barium carbonate	1,600 mg/m ³
6156-78-1	Manganese(II) acetate tetrahydrate	740 mg/m ³
7439-92-1	lead	700 mg/m ³
7440-43-9	cadmium (non-pyrophoric)	4.7 mg/m ³
7440-48-4	cobalt	20 mg/m ³
7440-28-0	thallium	20 mg/m ³
10102-06-4	Uranyl nitrate	33 mg/m ³

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
*Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.*
- **Information about protection against explosions and fires:** *Keep respiratory protective device available.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep receptacle tightly sealed.*
- **Specific end use(s)** *No further relevant information available.*

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
*The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.*

7697-37-2 nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

7440-38-2 arsenic

PEL	Long-term value: 0.5* 0.01** mg/m ³ as As; *organic**inorg. compds.; 29 CFR 1910.1018
REL	Ceiling limit value: 0.002 mg/m ³ as As; 15min; See Pocket Guide App. A
TLV	Long-term value: 0.01 mg/m ³ as As; BEI

· **Ingredients with biological limit values:**

7440-38-2 arsenic

BEI	35 µg As/L Medium: urine Time: end of workweek Parameter: Inorganic arsenic plus methylated metabolites (background)
-----	---

- **Additional information:** *The lists that were valid during the creation were used as basis.*

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 5)

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Light Pink

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 6)

Boiling point/Boiling range:	83 °C (181.4 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	93.2 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	1.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 7)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

10042-76-9 strontium nitrate

Oral	LD50	2,750 mg/kg (rat)
------	------	-------------------

7440-38-2 arsenic

Oral	LD50	763 mg/kg (rat)
------	------	-----------------

· **Primary irritant effect:**

· **on the skin:** Strong caustic effect on skin and mucous membranes.

· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

7440-38-2	arsenic	I
7439-92-1	lead	2B
543-81-7	beryllium acetate	I
7440-43-9	cadmium (non-pyrophoric)	I
7440-48-4	cobalt	2B

· **NTP (National Toxicology Program)**

7440-38-2	arsenic	K
7439-92-1	lead	R
543-81-7	beryllium acetate	K
7440-43-9	cadmium (non-pyrophoric)	K
7440-48-4	cobalt	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

7440-38-2	arsenic
7440-43-9	cadmium (non-pyrophoric)

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock



(Contd. of page 8)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | UN3264 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID) |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 8 Corrosive substances
8 |
| <ul style="list-style-type: none"> · ADR, IMDG, IATA | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class | 8 Corrosive substances |

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 9)

· Label	8
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups · Stowage Category · Stowage Code	Warning: Corrosive substances 80 F-A,S-B Acids A SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations	 On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

7697-37-2	nitric acid
-----------	-------------

· Section 313 (Specific toxic chemical listings):

7697-37-2	nitric acid
10042-76-9	strontium nitrate
7440-38-2	arsenic
513-77-9	barium carbonate
7439-92-1	lead
543-81-7	beryllium acetate
7440-43-9	cadmium (non-pyrophoric)

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 10)

7440-48-4	cobalt
7440-28-0	thallium

· TSCA (Toxic Substances Control Act):

7697-37-2	nitric acid
10042-76-9	strontium nitrate
7440-38-2	arsenic
21351-79-1	caesium hydroxide
513-77-9	barium carbonate
7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)
7440-48-4	cobalt
7440-28-0	thallium
10102-06-4	Uranyl nitrate
7732-18-5	water, distilled, conductivity or of similar purity

· Proposition 65
· Chemicals known to cause cancer:

7440-38-2	arsenic
7439-92-1	lead
543-81-7	beryllium acetate
7440-43-9	cadmium (non-pyrophoric)
7440-48-4	cobalt

· Chemicals known to cause reproductive toxicity for females:

7439-92-1	lead
-----------	------

· Chemicals known to cause reproductive toxicity for males:

7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)

· Chemicals known to cause developmental toxicity:

7439-92-1	lead
7440-43-9	cadmium (non-pyrophoric)

· Carcinogenic categories
· EPA (Environmental Protection Agency) (Substances not listed)

7697-37-2	nitric acid
10042-76-9	strontium nitrate
21351-79-1	caesium hydroxide
6156-78-1	Manganese(II) acetate tetrahydrate
543-81-7	beryllium acetate
7440-48-4	cobalt
7440-28-0	thallium
10102-06-4	Uranyl nitrate
7732-18-5	water, distilled, conductivity or of similar purity

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 11)

· TLV (Threshold Limit Value established by ACGIH)		
7440-38-2	arsenic	A1
513-77-9	barium carbonate	A4
7439-92-1	lead	A3
7440-43-9	cadmium (non-pyrophoric)	A2
7440-48-4	cobalt	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
7440-38-2	arsenic	
7440-43-9	cadmium (non-pyrophoric)	

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**


GHS05 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**
nitric acid
arsenic

· **Hazard statements**
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H350 May cause cancer.

· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep only in original container.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Absorb spillage to prevent material damage.
Store locked up.
Store in corrosive resistant container with a resistant inner liner.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: Urine Multi-Element Stock

(Contd. of page 12)

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
High-Purity Standards
Tel: 843-767-7900
Fax: 843-767-7906
- **Date of preparation / last revision** 03/19/2019 / -
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Met. Corr. 1: Corrosive to metals – Category 1
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Carc. 1A: Carcinogenicity – Category 1A