

Section 1. Product and Company Identification

Product Identification: CLP-CAL-3
 MSDS Number: CLP-CAL-3
 Recommended Use: For Laboratory Use.
 Company Identification: High-Purity Standards
 P.O. Box 41727
 Charleston, SC 29423
 Telephone: (843) 767-7900
 FAX: (843) 767-7906

In case of emergency call INFOTRAC: 800-535-5053

Section 2. Hazard Identification

Classification:

Skin Corrosion/Irritation, Category 1
 Serious Eye Damage/ Eye Irritation, Category 1
 Carcinogenicity, Category 1A

Labeling:**Symbol:**

Signal Word: Danger.

Hazard Statement: Causes severe skin burns and eye damage. May cause cancer.

Precautionary Statement: Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Section 3. Composition

Component	CAS/EINECS Registry #	Percent Concentration
Arsenic	7440-38-2/231-148-6	0.1
Cadmium	7440-43-9/231-152-8	0.05
Lead	7439-92-1/231-100-4	0.1
Selenium	7782-49-2/231-957-4	0.1
Thallium	7440-28-0/231-138-1	0.1
Nitric Acid	7697-37-2/231-714-2	2
Water, deionized	7732-18-5/231-791-2	Balance

Section 4. First Aid Measures

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Call a physician if irritation develops.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Safety Data Sheet No. CLP-CAL-3	Date: April 9, 2014	
CLP-CAL-3	Revision: 001	Page 2 of 4

IF exposed or concerned: Get medical attention/advice.

Target Organs: Eyes, skin, respiratory system. Increases risk of lung, liver, kidney, and bladder cancer with prolonged exposure.

Section 5. Fire Fighting Measures

Fire & Explosion hazards: While nitric acid is not combustible, it is a strong oxidizing agent that can react with combustible materials; however, it is present in limited quantities in this solution. NO_x compounds can be released in case of fire.

Extinguishing Media: Use any extinguishing media that is suitable for the surrounding area. Use a water spray to dilute nitric acid and to absorb liberated nitrogen oxides.

Specific Methods: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Section 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Do not allow to enter drainage systems or water ways. Dike area and dilute spill with water and neutralize with soda ash, limestone, etc. Place the neutralized material into containers suitable for eventual disposal, reclamation, or destruction. Always dispose of in accordance with local regulations.

Section 7. Handling and Storage

Store in a cool, dry, ventilated storage area with acid resistant floors and good drainage. Keep out of direct sunlight and away from heat, water, and incompatible materials. When diluting, the acid should always be added slowly to water and in small amounts. Refer to Section 8 for personal handling instructions.

Section 8. Exposure Controls and Personal Protection

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep any buildup of airborne contaminants below their respective threshold limit value. Ensure the availability of eyewash stations and safety showers.

Personal Protection: Wear proper gloves, safety glasses with side shields, lab coat/apron.

Exposure Limits:

Component	ACGIH TLV	OSHA PEL
Arsenic	0.01 mg/m ³	10 µg/ m ³
Cadmium	0.002 mg/m ³	0.005 mg/m ³
	(respirable particulate)	
Lead	0.05 mg/m ³	0.05 mg/m ³
Selenium	0.2 mg/m ³	0.2 mg/ m ³
Thallium	0.1 mg/m ³	0.1 mg/m ³
Nitric Acid	2 mg/kg	5 mg/m ³

Section 9. Physical and Chemical Properties

Physical State: Liquid

Color: Clear, colorless

Odor: Odorless to a faint pungent odor

Odor threshold: None

pH: <2

Safety Data Sheet No. CLP-CAL-3	Date: April 9, 2014	
CLP-CAL-3	Revision: 001	Page 3 of 4

Melting point: N/A
 Freezing Point: N/A
 Boiling Point: Approximately 100°C
 Flash point: N/A
 Evaporation rate: N/A
 Flammability: N/A
 Explosion limits: N/A
 Vapor Pressure (mm): N/A
 Vapor Density (air+1): N/A
 Relative density: (H₂O = 1): Approximately 1.0
 Solubility in H₂O: Complete
 Auto ignition temperature: N/A
 Decomposition temperature: N/A
 Molecular Weight: N/A

Section 10. Stability and Reactivity

Stability Indicator: Decomposes slowly to release oxygen.
 Conditions to Avoid: Metals, chlorine, organic materials, strong alkali, cyanides.
 Incompatibles: Strong reducing agents.
 Hazardous Decomposition Products: NO_x compounds including nitric oxide (NO), nitrogen dioxide (NO₂), nitrous oxide (N₂O) and nitric acid mist or vapor.
 Hazardous Polymerization: Will not occur.

Section 11. Toxicological Information

May affect skin, mucous membranes and eyes. Swallowing may lead to a negative effect on mouth and throat and to the risk of perforation or the corrosion of esophagus and stomach.

RTECS#

HNO ₃ : QU5775000	As: CG0525000	Cd: EU9800000
Pb: OF7525000	Se: VS7700000	Tl: XG3425000
Sb: CC4025000		

LD_{LO} Oral, Human: (Nitric Acid) 430 mg/kg
 LD₅₀, Oral, Rat: (Arsenic) 763 mg/kg
 LD_{LO} Oral, Human: (Cadmium) 2330 mg/kg
 TD_{LO} Oral, Woman: (Lead) 450 mg/kg/6 year
 LD₅₀, Oral, Rat: (Selenium) 6700 mg/kg
 TD_{LO} Oral, Man: (Thallium) 5,714 µg/kg
 LD₅₀ Oral, Rat: (Antimony) 7g/kg

Section 12. Ecological Information

Ecotoxicological information: Do not allow material to reach ground water, water bodies, or sewage system.

Section 13. Disposal Considerations

General: Follow Federal, state and local regulations for waste.

Safety Data Sheet No. CLP-CAL-3	Date: April 9, 2014	
CLP-CAL-3	Revision: 001	Page 4 of 4

Section 14. Transport Information

D.O.T. Classification: Hazardous by IATA and 49CFR regulations (based on concentration of acid).

D.O.T. Shipping Name: Corrosive liquid, Acidic, Inorganic, n.o.s. (Nitric Acid Solution)

D.O.T. Hazard Class: 8

U.N./N.A. Number: 3264

Packing Group: II

D.O.T. Label: Corrosive (8)

Section 15. Regulations (Not meant to be all inclusive-selected regulation listed)

OSHA Status: These items meet the OSHA Hazard Communication Standard (29 CFR 1910.1200) definition of a hazardous material.

TSCA Status: Components of this solution are listed on the TSCA Inventory.

RCRA Status: No

SARA: Subject to the reporting requirements of Section 313 or SARA Title III and of 40 CFR 372

Risk Phrases: R20/21/22. R24/25. R33. R34. R45. R48. Harmful by inhalation, skin contact, or ingestion. Toxic in contact with the skin and if swallowed. Danger of cumulative effects. Cause burns. May cause cancer. Danger of serious damage to health by prolonged exposure.

Safety Phrases: S36/37/3. S53. Wear suitable protective clothing, gloves and eye/face protection. Avoid exposure- obtain special instruction before use.

WHMIS Information (Canada): E: Corrosive

D: Poisonous/Carcinogen – category 2.

D2A: Very Toxic Material Causing Other Toxic Effects

Section 16. Other Information

HPS products are intended for laboratory use only. All products should be handled and used by trained professional personnel only. The responsibility for the safe handling and use of these products rests solely with the buyer and/or user. The SDS was prepared carefully and represents the best data currently available to us; however, HPS does not certify the data on the SDS. Certified values for this material are given only on the Certificate of Analysis.

Theodore C. Rains, Ph.D.