

Section 1. Product and Company Identification

Product Identification: CRDL
 MSDS Number: CRDL
 Recommended Use: For Laboratory Use.
 Company Identification: High-Purity Standards
 P.O. Box 41727
 Charleston, SC 29423
 Telephone: (843) 767-7900
 FAX: (843) 767-7906

In case of emergency call INFOTRAC: 800-535-5053

Section 2. Hazard Identification

Classification:

Skin Corrosion/Irritation, Category 1

Serious Eye Damage/ Eye Irritation, Category 1

Labeling:**Symbol:**

Signal Word: Danger.

Hazard Statement: Causes severe skin burns and eye damage.

Precautionary Statement: Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling.

Section 3. Composition

Component	CAS/EINECS Registry #	Percent Concentration
Antimony	7440-36-0/231-146-5	0.012
Arsenic	7440-38-2/231-148-6	0.002
Beryllium Acetate (Be ₄ O(C ₂ H ₃ O ₂) ₆)	19049-40-2/242-785-4	0.001 (as Be)
Cadmium	7440-43-9/231-152-8	0.001
Chromium	7440-47-3/231-157-5	0.002
Cobalt	7440-48-4/231-158-0	0.01
Copper	7440-50-8/231-159-6	0.005
Lead	7439-92-1/231-100-4	<0.001
Manganese Acetate Tetrahydrate (Mn(CH ₃ CO ₂) ₂)*4H ₂ O	6156-78-1/211-334-3	0.1 (as Mn)
Nickel	7440-02-0/231-111-4	0.008
Selenium	7782-49-2/231-957-4	0.001
Silver	7440-22-4/231-131-3	0.002

Safety Data Sheet No. CRDL	Date: April 9, 2014	
CRDL	Revision: 001	Page 2 of 5

Thallium	7440-28-0/231-138-1	0.002
Ammonium Metavanadate (NH ₄ VO ₃)	7803-55-6/232-261-3	0.01 (as V)
Zinc	7440-66-6/231-175-3	0.004
Nitric Acid	7697-37-2/ 231-714-2	2
Hydrofluoric Acid	7664-39-3/231-634-8	0.05
Water, deionized	7732-18-5/ 231-791-2	Balance

Section 4. First Aid Measures

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Gently wash with plenty of soap and water. Rub calcium gluconate gel immediately to skin. Obtain medical assistance. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER doctor/physician.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Target Organs: Eyes, skin, respiratory system, teeth, and skeletal system.

Section 5. Fire Fighting Measures

Fire & Explosion hazards: While nitric acid is not combustible, it is a strong oxidizing agent that can react with combustible materials; however, it is present in limited quantities in this solution. NO_x compounds can be released in case of fire. Hydrofluoric acid may ignite or explode on contact with combustible materials.

Extinguishing Media: Use any extinguishing media that is suitable for the surrounding area. Use a water spray to dilute nitric acid and to absorb liberated nitrogen oxides.

Specific Methods: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Section 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Do not allow to enter drainage systems or water ways. Dike area and dilute spill with water and neutralize with soda ash, limestone, etc. Place the neutralized material into containers suitable for eventual disposal, reclamation, or destruction. Always dispose of in accordance with local regulations.

Section 7. Handling and Storage

Store in a cool, dry, ventilated storage area with acid resistant floors and good drainage. Keep out of direct sunlight and away from heat, water, and incompatible materials. When diluting, the acid should always be added slowly to water and in small amounts. Refer to Section 8 for personal handling instructions.

Section 8. Exposure Controls and Personal Protection

Safety Data Sheet No. CRDL	Date: April 9, 2014	
CRDL	Revision: 001	Page 3 of 5

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep any buildup of airborne contaminants below their respective threshold limit value. Ensure the availability of eyewash stations and safety showers.

Personal Protection: Wear appropriate gloves impermeable to HF, safety glasses with face shield, and lab coat/apron to avoid any direct skin contact.

Exposure Limits:

Component	ACGIH TLV	OSHA PEL
Antimony	0.5 mg/m ³	0.5 mg/m ³
Arsenic	0.01 mg/m ³	10 µg/ m ³
Beryllium Acetate	0.002 mg/m ³	0.002 mg/m ³
Cadmium	0.002 mg/m ³ (respirable particulate)	0.005 mg/m ³
Chromium	0.5 mg/m ³	1 mg/m ³
Cobalt	0.02 mg/m ³	0.1 mg/m ³
Copper	0.2 mg/m ³ (fumes)	0.1 mg/m ³ (fumes)
Lead	0.05 mg/m ³	0.05 mg/m ³
Manganese Acetate Tetrahydrate	0.2 mg/m ³	C 5 mg/m ³
Nickel	1.5 mg/m ³	1 mg/m ³
Selenium	0.2 mg/m ³	0.2 mg/ m ³
Silver	0.1 mg/m ³	Not Available
Thallium	0.1 mg/m ³	0.1 mg/m ³
Ammonium Metavanadate	0.05 mg/m ³	Not Available
Zinc	5 mg/m ³	1 mg/m ³
Nitric Acid	2 mg/kg	5 mg/m ³
Hydrofluoric Acid	C: 3 mg/ml	2.5 mg/m ³ STEL: 6 mg/ml

Section 9. Physical and Chemical Properties

Physical State: Liquid

Color: Colorless to light gray

Odor: Odorless to a faint pungent odor

Odor threshold: None

pH: <2

Melting point: N/A

Freezing Point: N/A

Boiling Point: Approximately 100°C

Flash point: N/A

Evaporation rate: N/A

Flammability: N/A

Explosion limits: N/A

Vapor Pressure (mm): N/A

Vapor Density (air+1): N/A

Relative density: (H₂O = 1): Approximately 1.0

Solubility in H₂O: Complete

Auto ignition temperature: N/A

Decomposition temperature: N/A

Safety Data Sheet No. CRDL	Date: April 9, 2014	
CRDL	Revision: 001	Page 4 of 5

Molecular Weight: N/A

Section 10. Stability and Reactivity

Stability Indicator: YES

Conditions to Avoid: Avoid heat and contact with combustible and other incompatible materials.

Incompatibles: Strong reducing agents, metallic powders, strong bases, chlorine, calcium compounds, hydroxides, organic materials, strong alkali, cyanides.

Hazardous Decomposition Products: HF and NO_x compounds including nitric oxide (NO), nitrogen dioxide (NO₂), nitrous oxide (N₂O) and nitric acid mist or vapor.

Hazardous Polymerization: Will not occur.

Section 11. Toxicological Information

May cause severe irritation/burns to respiratory system and areas of contact. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. The symptoms may be delayed.

RTECS#

HNO₃:QU5775000

HF: MW7875000

Sb: CC4025000

As: CG0525000

Be₄O(C₂H₃O₂)₆: DS2900000

Cd: EU9800000

Cr: GB4200000

Co: GF8750000

Cu: GL5325000

Pb: OF7525000

Mn: AI5775000

Ni: QR5950000

Se: VS7700000

Ag: VW3500000

Tl: XG3425000

NH₄VO₃: YW0875000

Zn: ZG8600000

Toxicity Data:

LD_{LO} Oral, Human: (Nitric Acid) 430 mg/kg

LC_{LO} Inhalation, Human: (Hydrofluoric Acid) 50 mg/kg/30 min

LD₅₀ Oral, Rat: (Antimony) 7g/kg

LD₅₀, Oral, Rat: (Arsenic) 763 mg/kg

TD_{LO} Intratracheal, Rat: (Beryllium Acetate) 13 mg/kg

LD_{LO}, LD_{LO} Oral, Human: (Cadmium) 2330 mg/kg

LD₅₀ Unreported Route, Rat: (Chromium) 27.5 mg/kg

LD_{LO} Oral, Rabbit: (Cobalt) 750 mg/kg

TD_{LO} Oral, Human: (Copper) 120 µg/kg

TD₅₀ Oral, Woman: (Lead) 450 mg/kg/6 year

LD₅₀ Oral, Rat: (Manganese) 3730mg/kg

LD₅₀, Intravenous, Mouse: (Nickel) 50 mg/kg

LD₅₀, Oral, Rat: (Selenium) 6700 mg/kg

TD_{LO} Implant; Mouse: (Silver) 11 g/kg

TD_{LO} Oral, Man: (Thallium) 5,714 µg/kg

LD₅₀ Oral, Rat: (Ammonium Metavanadate) 58,100 µg/kg

LD_{LO} Oral, Duck: (Zinc) 388 mg/kg

Section 12. Ecological Information

Ecotoxicological information: Do not allow material to reach ground water, water bodies, or sewage system. Beryllium and its compounds are considered to have high acute and chronic toxicity to aquatic life. Beryllium is more toxic in soft water than in hard water.

Safety Data Sheet No. CRDL	Date: April 9, 2014	
CRDL	Revision: 001	Page 5 of 5

Section 13. Disposal Considerations

General: Follow Federal, state and local regulations for waste.

Section 14. Transport Information

D.O.T. Classification: Hazardous by IATA and 49CFR regulations (based on concentration of acid).

D.O.T. Shipping Name: Corrosive liquid, Acidic, Inorganic, n.o.s. (Nitric Acid Solution)

D.O.T. Hazard Class: 8

U.N./N.A. Number: 3264

Packing Group: II

D.O.T. Label: Corrosive (8)

Section 15. Regulations (Not meant to be all inclusive-selected regulation listed)

TSCA Status: Components of this solution are listed on the TSCA Inventory.

RCRA Status: Yes (Hydrofluoric Acid-U134); (Ammonium Metavanadate-P119).

SARA: Subject to the reporting requirements of Section 313 or SARA Title III and of 40 CFR 372

Risk Phrases: R20/21/22. R45 Harmful by inhalation or skin contact or if swallowed; May cause cancer.

Safety Phrases: S24, S25, S36/37/39, S53 Avoid contact with the skin. Avoid contact with eyes. Wear suitable protective clothing, gloves and eye/face protection; Avoid exposure- obtain special instruction before use.

WHMIS Information (Canada): E: Corrosive

Section 16. Other Information

HPS products are intended for laboratory use only. All products should be handled and used by trained professional personnel only. The responsibility for the safe handling and use of these products rests solely with the buyer and/or user. The SDS was prepared carefully and represents the best data currently available to us; however, HPS does not certify the data on the SDS. Certified values for this material are given only on the Certificate of Analysis.

Theodore C. Rains, Ph.D.