Section 1. Product and Company Identification

Product Identification: ICP-200.8.3 Solution A
SDS Number: ICP-200.8.3 Solution A
Recommended Use: For Laboratory Use.
Company Identification: High-Purity Standards
P.O. Box 41727
Charleston, SC 29423
Telephone: (843) 767-7900
FAX: (843) 767-7906
In case of emergency call INFOTRAC: 800-535-5053

Section 2. Hazard Identification

Classification:
Skin Corrosion/Irritation, Category 1
Serious Eye Damage/ Eye Irritation, Category 1
Labeling:

Symbol:
Signal Word: Danger.
Hazard Statement: Causes severe skin burns and eye damage.
Precautionary Statement: Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling.

Section 3. Composition

Component	CAS/EINECS Registry #	Percent Concentration
Aluminum	7429-90-5/231-072-3	0.002
Arsenic	7440-38-2/231-148-6	0.002
Barium Carbonate ($BaCO_3$)	513-77-9/208-167-3	0.002 (as Ba)
Barium Nitrate ($Ba(NO_3)_2$)	10022-31-8/233-020-5	
Beryllium Acetate ($Be_4O(C_2H_3O_2)_6$)	19049-40-2/242-785-4	0.002 (as Be)
Cadmium	7440-43-9/231-152-8	0.002
Chromium	7440-47-3/231-157-5	0.002
Cobalt	7440-48-4/231-158-0	0.002
Copper	7440-50-8/231-159-6	0.002
Lead	7439-92-1/231-100-4	0.002
Manganese Acetate Tetrahydrate $(Mn(CH_3CO_2)_2)*4H_2O$	6156-78-1/211-334-3	0.1 (as Mn)
Nickel	7440-02-0/231-111-4	0.002
Selenium	7782-49-2/231-957-4	0.01
Silver	7440-22-4/231-131-3	0.002

Thallium	7440-28-0/231-138-1	0.002
Thorium Oxide (ThO_2)	1314-20-1/215-225-1	0.002 (as Th)
Uranium Oxide (U_3O_8)	1344-59-8/215-702-4	0.002 (as U)
Nitric Acid	7697-37-2/ 231-714-2	2.0
Water, deionized	7732-18-5/ 231-791-2	Balance

**Note: Barium is derived from either Barium carbonate or Barium Nitrate. For this reason both sources are listed on the SDS. Refer to the product's Certificate of Analysis to determine which source was used in the production of the lot number received.*

Section 4. First Aid Measures

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Call a physician if irritation develops.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a physician. May cause nausea, vomiting, and diarrhea.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Target Organs: Eyes, skin.

Section 5. Fire Fighting Measures

Fire & Explosion hazards: While nitric acid is not combustible, it is a strong oxidizing agent that can react with combustible materials; however, it is present in limited quantities in this solution. NO_x compounds can be released in case of fire.

Extinguishing Media: Use any extinguishing media that is suitable for the surrounding area. Use a water spray to dilute nitric acid and to absorb liberated nitrogen oxides.

Specific Methods: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Section 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Do not allow to enter drainage systems or water ways. Dike area and dilute spill with water and neutralize with soda ash, limestone, etc. Place the neutralized material into containers suitable for eventual disposal, reclamation, or destruction. Always dispose of in accordance with local regulations.

Section 7. Handling and Storage

Store in a cool, dry, ventilated storage area with acid resistant floors and good drainage. Keep out of direct sunlight and away from heat, water, and incompatible materials. When diluting, the acid should always be added slowly to water and in small amounts. Refer to Section 8 for personal handling instructions.

Section 8. Exposure Controls and Personal Protection

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep any buildup of airborne contaminants below their respective threshold limit value. Ensure the availability of eyewash stations and safety showers.

Personal Protection: Wear proper gloves, safety glasses with side shields, lab coat/apron.

Exposure Limits:

Component	ACGIH TLV	OSHA PEL
Aluminum	10 mg/m^3	15 mg/m^3
Arsenic	0.01 mg/m^3	10 µg/ m^3
Barium	0.5 mg/m^3	0.5 mg/m^3
Beryllium Acetate	0.002 mg/m^3	0.002 mg/m^3
Cadmium	0.002 mg/m^3 (respirable particulate)	0.005 mg/m^3
Chromium	0.5 mg/m^3	1 mg/m^3
Cobalt	0.02 mg/m^3	0.1 mg/m^3
Copper	0.2 mg/m^3 (fumes)	0.1 mg/m^3 (fumes)
Lead	0.05 mg/m^3	0.05 mg/m^3
Manganese Acetate Tetrahydrate	0.2 mg/m^3	C 5 mg/m^3
Nickel	1.5 mg/m^3	1 mg/m^3
Selenium	0.2 mg/m^3	0.2 mg/ m^3
Silver	0.1 mg/m^3	Not Available
Thallium	0.1 mg/m^3	0.1 mg/m^3
Thorium Oxide	Not Available	Not Available
Uranium Oxide	0.2 mg/m^3	0.05 mg/m^3
Ammonium Metavanadate	0.05 mg/m^3	Not Available
Nitric Acid	2 mg/kg	5 mg/m^3

Section 9. Physical and Chemical Properties

Physical State: Liquid
Color: Clear, liquid
Odor: Odorless to a faint pungent odor
Odor threshold: None
pH: <2
Melting point: N/A
Freezing Point: N/A
Boiling Point: Approximately 100°C
Flash point: N/A
Evaporation rate: N/A
Flammability: N/A
Explosion limits: N/A
Vapor Pressure (mm): N/A
Vapor Density (air+1): N/A
Relative density: (H_2O = 1): Approximately 1.0
Solubility in H_2O: Complete
Auto ignition temperature: N/A
Decomposition temperature: N/A
Molecular Weight: N/A

Section 10. Stability and Reactivity

Stability Indicator: YES
Conditions to Avoid: Metals, chlorine, organic materials, strong alkali, cyanides.
Incompatibles: Strong reducing agents.
Hazardous Decomposition Products: NO_x compounds including nitric oxide (NO), nitrogen dioxide (NO_2), nitrous oxide (N_2O) and nitric acid mist or vapor.
Hazardous Polymerization: Will not occur.

Section 11. Toxicological Information

May affect skin, mucous membranes and eyes. Swallowing may lead to a negative effect on mouth and throat and to the risk of perforation or the corrosion of esophagus and stomach.
This solution contains depleted radioactive thorium oxide and natural uranium oxide at total concentration of 0.004%. Both are weakly radioactive and emits alpha particles which are harmful to the body. For the energy range of alpha particles usually encountered, a fraction of a millimeter of any ordinary material is sufficient for absorbance. Thin rubber, acrylic, stout paper, or cardboard will suffice.

RTECS#

HNO_3- QU5775000	Al-BD0330000
As- CG0525000	$BaCO_3$- CQ8600000
$Be_4O(C_2H_3O_2)_6$ – DS29750000	Cd- EU9800000
Cr- GB4200000	Co- GF8750000
Cu- GL5325000	Pb- OF7525000
Mn-AI5775000	Ni- QR5950000
Se- VS7700000	Ag- VW3500000
ThO_2 - XO6950000	Tl- XG3425000
U_3O_8 - YR3490000	NH_4VO_3-YW0875000
Zn- ZG8600000	$Ba(NO_3)_2$- CQ9625000

LD_{LO} Oral, Human: (Nitric Acid) 430 mg/kg
LD_{50} Oral, Rat: (Aluminum) >5000 mg/kg
LD_{50}, Oral, Rat: (Arsenic) 763 mg/kg
LD_{LO} Oral, Human: (Barium Carbonate) 17 mg/kg
LD_{50} Oral, Rat: ($Ba(NO_3)_2$) 355 mg/kg.
TD_{LO} Intratracheal, Rat: (Beryllium Acetate) 13 mg/kg
LD_{LO} Oral, Human: (Cadmium) 2330 mg/kg
LD_{50} Unreported Route, Rat: (Chromium) 27.5 mg/kg
LD_{LO} Oral, Rabbit: (Cobalt) 750 mg/kg
TD_{LO} Oral, Human: (Copper) 120 µg/kg
TD_{50} Oral, Woman: (Lead) 450 mg/kg/6 year
LD_{50} Oral, Rat: (Manganese) 3730mg/kg
LD_{50}, Intravenous; Mouse: (Nickel) 50 mg/kg
TD_{LO} Implant, Mouse: (Silver) 11 g/kg
TD_{LO} Oral, Man: (Thallium) 5,714 µg/kg
TD_{LO} Intraarterial, Human: (Thorium Oxide) 490 mg/kg
TD_{50} Unreported Route, Rat: (Uranium Oxide) 750 mg/kg
LD_{50} Oral, Rat: (Ammonium Metavanadate) 58,100 µg/kg
LD_{LO} Oral, Duck: (Zinc) 388 mg/kg

Section 12. Ecological Information

Ecotoxicological information: Do not allow material to reach ground water, water bodies, or sewage system. Beryllium and its compounds are considered to have high acute and chronic toxicity to aquatic life. Beryllium is more toxic in soft water than in hard water.

Section 13. Disposal Considerations

General: Follow Federal, state and local regulations for waste.

Section 14. Transport Information

D.O.T. Classification: Hazardous by IATA and 49CFR regulations (based on concentration of acid).
D.O.T. Shipping Name: Corrosive liquid, Acidic, Inorganic, n.o.s. (Nitric Acid Solution)
D.O.T. Hazard Class: 8
U.N./N.A. Number: 3264
Packing Group: II
D.O.T. Label: Corrosive (8)

Section 15. Regulations (Not meant to be all inclusive-selected regulation listed)

OSHA Status: These items meet the OSHA Hazard Communication Standard (29 CFR 1910.1200) definition of a hazardous material.
TSCA Status: Components of this solution are listed on the TSCA Inventory.
RCRA Status: 7803-55-6 (Ammonium Metavanadate)
SARA: Subject to the reporting requirements of Section 313 or SARA Title III and of 40 CFR 372
Risk Phrases: R20/21/22, R45, R48 Harmful by inhalation or skin contact or if swallowed; May cause cancer; Danger of serious damage to health by prolonged exposure; Danger of cumulative effects.
Safety Phrases: S36/37/39, S53 Wear suitable protective clothing, gloves and eye/face protection; Avoid exposure- obtain special instruction before use.
WHMIS Information (Canada): E: Corrosive

ICP-200.8-3 Solution A contains a limited quantity radioactive material that is exempt from radioactive labeling requirements under 49CFR section 173.421. The massic activity for 1 literof ICP-200.8-3 Solution A is less than 0.6 kBq

Section 16. Other Information

HPS products are intended for laboratory use only. All products should be handled and used by trained professional personnel only. The responsibility for the safe handling and use of these products rests solely with the buyer and/or user. The SDS was prepared carefully and represents the best data currently available to us; however, HPS does not certify the data on the SDS. Certified values for this material are given only on the Certificate of Analysis

Theodore C. Rains, Ph.D.