

Safety Data Sheet

Section 1. Product and Company Identification

Product Identification: PE Stock Tuning Solution 1
 SDS Number: ICP-MS-TS-16
 Recommended Use: For Laboratory Use.
 Company Identification: High-Purity Standards
 P.O. Box 41727
 Charleston, SC 29423
 Telephone: (843) 767-7900
 FAX: (843) 767-7906

In case of emergency call INFOTRAC: 800-535-5053

Section 2. Hazard Identification

Classification:

Skin Corrosion/Irritation, Category 1

Serious Eye Damage/ Eye Irritation, Category 1

Labeling:



Symbol:

Signal Word: Danger.

Hazard Statement: H314 - Causes severe skin burns and eye damage

Precautionary Statement:

P280: Wear protective gloves/protective clothing/eye protection/face protection

P264: Wash hands thoroughly after handling

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P310: Immediately call a POISON CENTER or doctor/physician

Section 3. Composition

Element:	Cas#/EINECS	Concentration %
Water, deionized	7732-18-5/ 231-791-2	balance
Barium (BaCO ₃)	513-77-9/208-167-3	0.001
Beryllium (Be ₄ O(C ₂ H ₃ O ₂) ₆)	19049-40-2/242-785-4	0.001
Cerium (CeO ₂)	1306-38-3/215-150-4	0.001
Cobalt	7440-48-4/231-158-0	0.001
Indium	7440-74-6/231-180-0	0.001
Lead	7439-92-1/231-100-4	0.001
Magnesium	7439-95-4/231-104-6	0.001
Rhodium (N ₃ O ₉ Rh • xH ₂ O)	10139-58-9	0.001
Uranium (U ₃ O ₈)	1344-59-8/215-702-4	0.001

Safety Data Sheet No. PE Stock Tuning Solution 1	Date: May 11, 2016	
ICP-MS-TS-16	Revision: New	Page 2 of 5

Lithium (Li ₂ CO ₃)	554-13-2/209-062-5	0.001
Thallium	7440-28-0/231-138-1	0.001
Yttrium (Y ₂ O ₃)	1314-36-9/215-233-5	0.001
Nitric Acid	7697-37-2/ 231-714-2	2
Hydrochloric Acid	7647-01-0/231-595-7	5

Section 4. First Aid Measures

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Call a physician if irritation develops. Harmful if absorbed through the skin.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a physician. May cause nausea, vomiting, and diarrhea.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membrane and upper respiratory tract.

Target Organs: Eyes, skin.

Section 5. Fire Fighting Measures

Fire & Explosion hazards: While nitric acid is not combustible, it is a strong oxidizing agent that can react with combustible materials; however, it is present in limited quantities in this solution. NO_x compounds can be released in case of fire. Hydrochloric acid is a negligible fire hazard when exposed to heat and/or flames. Hydrochloric acid may react with the evolution of heat on contact with water; the acid may release toxic, corrosive, flammable, or explosive gases.

Extinguishing Media: Use any extinguishing media that is suitable for the surrounding area. Use a water spray to dilute nitric acid and to absorb liberated nitrogen oxides.

Specific Methods: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Section 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Do not allow to enter drainage systems or water ways. Dike area and dilute spill with water and neutralize with soda ash, limestone, etc. Avoid breathing vapors, mist, or gas. Place the neutralized material into containers suitable for eventual disposal, reclamation, or destruction. Always dispose of in accordance with local regulations.

Section 7. Handling and Storage

Store in a cool, dry, ventilated storage area with acid resistant floors and good drainage. Keep out of direct sunlight and away from heat, water, and incompatible materials. When diluting, the acid should always be added slowly to water and in small amounts. Refer to Section 8 for personal handling instructions.

Safety Data Sheet No. PE Stock Tuning Solution 1	Date: May 11, 2016	
ICP-MS-TS-16	Revision: New	Page 3 of 5

Section 8. Exposure Controls and Personal Protection

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep any buildup of airborne contaminants below their respective threshold limit value. Ensure the availability of eyewash stations and safety showers.

Personal Protection: Wear proper gloves, safety glasses with side shields, lab coat/apron.

Exposure Limits:

Component	ACGIH TLV	OSHA PEL
Barium (BaCO ₃)	0.5 mg/m ³	0.5 mg/m ³
Beryllium (Be ₄ O(C ₂ H ₃ O ₂) ₆)	0.00005 mg/m ³	0.002 mg/m ³
Cerium (CeO ₂)	Not Available	Not Available
Cobalt	0.02 mg/m ³	0.1 mg/m ³
Indium	0.05 mg/m ³	0.05 mg/m ³
Lead	0.1 mg/m ³	0.05 mg/m ³
Magnesium	Not Available	Not Available
Rhodium (N ₃ O ₉ Rh • xH ₂ O)	Not Available	Not Available
Uranium (U ₃ O ₈)	0.2 mg/m ³	C 5 mg/m ³
Lithium (Li ₂ CO ₃)	Not Available	Not Available
Thallium	0.1 mg/m ³	0.1 mg/m ³
Yttrium (Y ₂ O ₃)	1 mg/m ³	1 mg/m ³
Nitric Acid	2 mg/kg	5 mg/m ³
Hydrochloric Acid	C: 3 mg/ml	2.5 mg/m ³ ; STEL: 6 mg/ml

Section 9. Physical and Chemical Properties

Physical State: Liquid

Color: Light Pink

Odor: Odorless to a faint pungent odor

Odor threshold: None

pH: <2

Melting point: N/A

Freezing Point: N/A

Boiling Point: Approximately 100°C

Flash point: N/A

Evaporation rate: N/A

Flammability: N/A

Explosion limits: N/A

Vapor Pressure (mm): N/A

Vapor Density (air+1): N/A

Relative density: (H₂O = 1): N/A

Solubility in H₂O: Complete

Auto ignition temperature: N/A

Decomposition temperature: N/A

Safety Data Sheet No. PE Stock Tuning Solution 1	Date: May 11, 2016	
ICP-MS-TS-16	Revision: New	Page 4 of 5

Molecular Weight: N/A

Section 10. Stability and Reactivity

Stability Indicator: YES

Conditions to Avoid: Metals, chlorine, hydroxides, carbonates, organic materials, strong alkali, cyanides.

Incompatibles: Strong reducing agents. Strong oxidizing agents

Hazardous Decomposition Products: NO_x compounds including nitric oxide (NO), nitrogen dioxide (NO₂), nitrous oxide (N₂O) and nitric acid mist or vapor. When heated to decomposition, emits toxic hydrogen chloride fumes and will react with water or steam to produce heat and toxic and corrosive fumes. Thermal oxidative decomposition produces toxic chlorine fumes and explosive hydrogen gas.

Hazardous Polymerization: Will not occur.

Section 11. Toxicological Information

May affect skin, mucous membranes and eyes. Swallowing may lead to a negative effect on mouth and throat and to the risk of perforation or the corrosion of esophagus and stomach.

Component	RTECS	Toxicity
Barium (BaCO ₃)	CQ8600000	LDLO Oral, Human: (Barium Carbonate) 17 mg/kg.
Beryllium (Be ₄ O(C ₂ H ₃ O ₂) ₆)	DS2900000	N/A
Cerium (CeO ₂)	FK6310000	LD50 Oral, Rat: (Cerium Dioxide) >5 g/kg.
Cobalt	VV7800000	LD50, Oral, Rat, 125 mg/kg.
Indium	NL1050000	LDLO Subcutaneous, Mouse: (Indium) 10mg/kg.
Lead	OF7525000	TD50 Oral, Woman: (Lead) 450 mg/kg/6 years
Magnesium	OM2100000	N/A
Rhodium (N ₃ O ₉ Rh • xH ₂ O)	N/A	N/A
Uranium (U ₃ O ₈)	YR3490000	TD50 Unreported Route, Rat: (Uranium Oxide) 750 mg/kg.
Lithium (Li ₂ CO ₃)	OJ5800000	LD50 Oral, Rat: (Lithium Carbonate) 525 mg/kg.
Thallium	XG3425000	TDLO Oral, Man: (Thallium) 5,714 mg/kg.
Yttrium (Y ₂ O ₃)	ZG3850000	LDLO Oral, Mouse: (Yttrium Oxide) >6 g/kg.
Nitric Acid	QU5775000	LDLO Oral, Human: (Nitric Acid) 430 mg/kg.
Hydrochloric Acid	MW7875000	Oral, rabbit: (Hydrochloric Acid) LD50 = 900 mg/kg

Section 12. Ecological Information

Ecotoxicological information: Do not allow material to reach ground water, water bodies, or sewage system.

Section 13. Disposal Considerations

General: Follow Federal, state and local regulations for waste.

Section 14. Transport Information

Safety Data Sheet No. PE Stock Tuning Solution 1	Date: May 11, 2016	
ICP-MS-TS-16	Revision: New	Page 5 of 5

D.O.T. Classification: Hazardous by IATA and 49CFR regulations (based on concentration of acid).

D.O.T. Shipping Name: Corrosive liquid, Acidic, Inorganic, n.o.s. (Nitric Acid Solution)

D.O.T. Hazard Class: 8

U.N./N.A. Number: 3264

Packing Group: II

D.O.T. Label: Corrosive (8)

Section 15. Regulations (Not meant to be all inclusive-selected regulation listed)

TSCA Status: Components of this solution are listed on the TSCA Inventory.

RCRA Status: No.

SARA: Subject to the reporting requirements of Section 313 of SARA Title III and of 40 CFR 372

Risk Phrases: R36/38 Irritating to eyes and skin.

Safety Phrases: S36/37/39 Wear suitable protective clothing, gloves and eye/face protection

WHMIS Information (Canada): E: Corrosive

Section 16. Other Information

HPS products are intended for laboratory use only. All products should be handled and used by trained professional personnel only. The responsibility for the safe handling and use of these products rests solely with the buyer and/or user. The SDS was prepared carefully and represents the best data currently available to us; however, HPS does not certify the data on the SDS. Certified values for this material are given only on the Certificate of Analysis.

Theodore C. Rains, Ph.D.