

Page 1/13

Safety Data Sheet acc. to OSHA HCS

Printing date 06/15/2020 Reviewed on 06/15/2020

1 Identification

· Product identifier

· Trade name: Custom Organic Standard

· Article number: ICP-MS-B-R

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

High-Purity Standards

7221 Investment Drive, North Charleston, SC 29418 United States

Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com

Email: info@highpuritystandards.com

· Information department: Product safety department

· Emergency telephone number:

INFOTRAC

Emergency telephone numbers 1-800-535-5053 Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling: nitric acid
- · Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

(Contd. on page 2)





Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 1)

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
7697-37-2 nitric acid	2.0%
· Chemical identification of the substance/preparation	
7732-18-5 water, distilled, conductivity or of similar purity	97.982%
7429-91-6 dysprosium	0.001%
7439-91-0 lanthanum	0.001%
7440-00-8 neodymium	0.001%
7440-19-9 samarium	0.001%
<u> </u>	(Contd. on page 3)



Page 3/13

Safety Data Sheet acc. to OSHA HCS

Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

		(Contd. of page 2)
7440-27-9	terbium	0.001%
7440-29-1	thorium	0.001%
7440-45-1	cerium	0.001%
7440-52-0	erbium	0.001%
7440-53-1	europium	0.001%
7440-54-2	gadolinium	0.001%
7440-60-0	holmium	0.001%
7440-61-1	uranium	0.001%
7440-64-4	ytterbium	0.001%
7440-65-5	yttrium	0.001%
12032-20-1	lutetium oxide	0.001%
12036-44-1	thulium oxide	0.001%
12037-29-5	Praseodymium(III,IV) oxide	0.001%
12060-08-1	scandium oxide	0.001%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

(Contd. on page 4)





Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 3)

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Dilute with plenty of water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
7697-37-2 nitric	acid	0.16 ppm
7429-91-6 dyspro	osium	30 mg/m^3
7439-91-0 lantha	num	30 mg/m^3
7440-00-8 neody	mium	30 mg/m^3
7440-19-9 samar	ium	30 mg/m^3
7440-27-9 terbiu	n	1.2 mg/m^3
7440-29-1 thoriu	m	30 mg/m^3
7440-45-1 ceriun	1	30 mg/m ³
7440-53-1 europ	ium	30 mg/m³
7440-54-2 gadoli	nium	30 mg/m ³
7440-60-0 holmi	ım	12 mg/m³
7440-61-1 uranii	um .	0.6 mg/m^3
7440-65-5 yttriur		3 mg/m ³
12032-20-1 lutetiv	m oxide	30 mg/m³
12036-44-1 thuliu		30 mg/m³
	odymium(III,IV) oxide	15 mg/m³
12060-08-1 scand	ium oxide	30 mg/m³
· PAC-2:		
7697-37-2 nitric	acid	24 ppm
7429-91-6 dyspro	osium	330 mg/m^3
7439-91-0 lantha	num	330 mg/m^3
7440-00-8 neody	mium	330 mg/m^3
7440-19-9 samar	ium	330 mg/m³
7440-27-9 terbiu	n	13 mg/m^3
7440-29-1 thoriu	m	330 mg/m^3
7440-45-1 ceriun	1	330 mg/m³
7440-53-1 europ	ium	330 mg/m^3





Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

7440-54-2	gadolinium	(Contd. of page 330 mg/s
7440-60-0		130 mg/s
7440-61-1	uranium	5 mg/m^3
7440-65-5	yttrium	33 mg/m
12032-20-1	lutetium oxide	330 mg/s
12036-44-1	thulium oxide	330 mg/s
12037-29-5	Praseodymium(III,IV) oxide	170 mg/s
12060-08-1	scandium oxide	330 mg/s
<i>PAC-3</i> :		-
7697-37-2	nitric acid	92 ppm
7429-91-6	dysprosium	2,000 mg/s
7439-91-0	lanthanum	2,000 mg/s
7440-00-8	neodymium	2,000 mg/i
7440-19-9	samarium	2,000 mg/s
7440-27-9	terbium	79 mg/m³
7440-29-1	thorium	2,000 mg/s
7440-45-1	cerium	2,000 mg/s
7440-53-1	europium	2,000 mg/s
7440-54-2	gadolinium	2,000 mg/s
7440-60-0	holmium	790 mg/m ⁻
7440-61-1	uranium	30 mg/m^3
7440-65-5	yttrium	200 mg/m
12032-20-1	lutetium oxide	2,000 mg/s
12036-44-1	thulium oxide	2,000 mg/s
12037-29-5	Praseodymium(III,IV) oxide	990 mg/m
12060-08-1	scandium oxide	2,000 mg/i

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 6)



Page 6/13

Safety Data Sheet acc. to OSHA HCS

Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 5)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm
REL Short-term value: 10 mg/m³, 4 ppm
Long-term value: 5 mg/m³, 2 ppm
TLV Short-term value: 10 mg/m³, 4 ppm
Long-term value: 5.2 mg/m³, 2 ppm

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)





Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

α \mathbf{D}_{1}	•	1		hemical		
U Ph	1101001	and	α	a amazea	nva	novilac
7 1 11		TO THE O		[[]		
	<i>y</i> 20000				P . U	P

· Information	on basic	physical	and	chemical	properties

General Information

· Appearance:

Form:
Color:
Color:
Codor:
Characteristic
Not determined.

PH-value:
Not determined.

pii ruine.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

- Flash point:

Not applicable.

· Flammability (solid, gaseous): Not applicable.

· **Decomposition temperature:** Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

• Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

Density: Not determined.
 Relative density Not determined.
 Vapor density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

(Contd. on page 8)



Page 8/13

Safety Data Sheet acc. to OSHA HCS

Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

	(Contd. of p	age 7)
· Solvent content: Water: VOC content:	98.0 % 0.00 % 0.0 g/l / 0.00 lb/gal	
Solids content: Other information	0.0% No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

 ${\it The product shows the following dangers according to internally approved calculation methods for preparations:}$

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

None of the ingredients is listed.

Curemogenic curegories	
· IARC (International Agency for Research on Cancer)	
7440-29-1 thorium	1
· NTP (National Toxicology Program)	

(Contd. on page 9)



Page 9/13

Safety Data Sheet acc. to OSHA HCS

Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 8)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1/1/	7		c ,	
14 1	ransp	ort int	ormat	1.0N
	· ····································	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	0.1.1.1.1.1.	

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name · DOT · ADR	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
· IMDG, IATA	(NITRIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)

(Contd. on page 10)



Page 10/13

Safety Data Sheet acc. to OSHA HCS

Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 9)

· Transport hazard class(es)

 $\cdot DOT$



· Class 8 Corrosive substances

· Label

 $\cdot ADR$



· Class 8 (C1) Corrosive substances

· Label

· IMDG, IATA



· Class 8 Corrosive substances

· Label

· Packing group

· DOT, ADR, IMDG, IATA III

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Corrosive substances

Hazard identification number (Kemler code): 80
 EMS Number: F-A,S-B
 Segregation groups Acids
 Stowage Category A

• Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot DOT$

• Quantity limitations On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

(Contd. on page 11)





Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 10)

· ADR	
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O. (NITRIC ACID), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 12)



Page 12/13

Safety Data Sheet acc. to OSHA HCS

Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 11)

TLV (Threshold Limit Value established by ACGIH)

7440-61-1 uranium

A1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

7440-61-1 uranium

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

(Contd. on page 13)



Page 13/13

Safety Data Sheet acc. to OSHA HCS

Printing date 06/15/2020 Reviewed on 06/15/2020

Trade name: Custom Organic Standard

(Contd. of page 12)

· Contact:

High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906

 \cdot Date of preparation / last revision 06/15/2020 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

US ·