

Safety Data Sheet acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

1 Identification

- **Product identifier**
- **Trade name:** PE Stock Tuning Solution 2
- **Article number:** ICP-MS-TS-13
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
High-Purity Standards
7221 Investment Drive, North Charleston, SC 29418 United States
Telephone: +1-843-767-7900
Fax: +1-843-767-7906
highpuritystandards.com
Email: info@highpuritystandards.com
- **Information department:** Product safety department
- **Emergency telephone number:**
INFOTRAC
Emergency telephone numbers 1-800-535-5053
Other emergency telephone numbers 1-352-323-3500

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Met. Corr. 1 H290 May be corrosive to metals.
Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**
nitric acid
- **Hazard statements**
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**
Keep only in original container.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 1)

Do not breathe dusts or mists.
 Wash thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: Rinse mouth. Do NOT induce vomiting.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Wash contaminated clothing before reuse.
 Absorb spillage to prevent material damage.
 Store locked up.
 Store in corrosive resistant container with a resistant inner liner.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

7697-37-2	nitric acid	2.0%
-----------	-------------	------

· **Chemical identification of the substance/preparation**

7732-18-5	water, distilled, conductivity or of similar purity	97.501%
7647-01-0	hydrochloric acid	0.49%
513-77-9	barium carbonate	0.001%
543-81-7	beryllium acetate	0.001%
1306-38-3	cerium dioxide	0.001%

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 2)

7439-92-1	lead	0.001%
7439-95-4	magnesium	0.001%
7440-48-4	cobalt	0.001%
7440-74-6	indium	0.001%
10049-07-7	rhodium trichloride	0.001%
10102-06-4	Uranyl nitrate	0.001%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 3)

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

7697-37-2	nitric acid	0.16 ppm
7647-01-0	hydrochloric acid	1.8 ppm
513-77-9	barium carbonate	2.2 mg/m ³
1306-38-3	cerium dioxide	3 mg/m ³
7439-92-1	lead	0.15 mg/m ³
7439-95-4	magnesium	18 mg/m ³
7440-48-4	cobalt	0.18 mg/m ³
7440-74-6	indium	0.3 mg/m ³
10102-06-4	Uranyl nitrate	0.99 mg/m ³

· PAC-2:

7697-37-2	nitric acid	24 ppm
7647-01-0	hydrochloric acid	22 ppm
513-77-9	barium carbonate	270 mg/m ³
1306-38-3	cerium dioxide	33 mg/m ³
7439-92-1	lead	120 mg/m ³
7439-95-4	magnesium	200 mg/m ³
7440-48-4	cobalt	2 mg/m ³
7440-74-6	indium	3.3 mg/m ³
10102-06-4	Uranyl nitrate	5.5 mg/m ³

· PAC-3:

7697-37-2	nitric acid	92 ppm
7647-01-0	hydrochloric acid	100 ppm
513-77-9	barium carbonate	1,600 mg/m ³
1306-38-3	cerium dioxide	200 mg/m ³
7439-92-1	lead	700 mg/m ³
7439-95-4	magnesium	1,200 mg/m ³
7440-48-4	cobalt	20 mg/m ³
7440-74-6	indium	20 mg/m ³
10102-06-4	Uranyl nitrate	33 mg/m ³

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 4)

- Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7697-37-2 nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 5)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

· **Density at 20 °C (68 °F):** 1.01143 g/cm³ (8.44038 lbs/gal)

· Bulk density:	1,011 kg/m ³
· Relative density	Not determined.
· Vapor density	Not determined.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 6)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	97.5 %
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
· Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
7647-01-0 hydrochloric acid		
Oral	LD50	900 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 7)

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

7647-01-0	hydrochloric acid	3
543-81-7	beryllium acetate	1
7439-92-1	lead	2B
7440-48-4	cobalt	2B

· **NTP (National Toxicology Program)**

543-81-7	beryllium acetate	K
7439-92-1	lead	R
7440-48-4	cobalt	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Not hazardous for water.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020




Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 8)

· Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name · DOT · ADR · IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
· Transport hazard class(es) · DOT	
	
· Class · Label	8 Corrosive substances 8
· ADR	
	
· Class · Label	8 (C1) Corrosive substances 8
· IMDG, IATA	
	
· Class · Label	8 Corrosive substances 8
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Corrosive substances 80 F-A,S-B

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 9)

· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):		
7697-37-2	nitric acid	
7647-01-0	hydrochloric acid	
· Section 313 (Specific toxic chemical listings):		
7697-37-2	nitric acid	
7647-01-0	hydrochloric acid	
513-77-9	barium carbonate	
543-81-7	beryllium acetate	
7439-92-1	lead	
7440-48-4	cobalt	
· TSCA (Toxic Substances Control Act):		
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
7697-37-2	nitric acid	ACTIVE

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 10)

7647-01-0	hydrochloric acid	ACTIVE
513-77-9	barium carbonate	ACTIVE
1306-38-3	cerium dioxide	ACTIVE
7439-92-1	lead	ACTIVE
7439-95-4	magnesium	ACTIVE
7440-48-4	cobalt	ACTIVE
7440-74-6	indium	ACTIVE
10049-07-7	rhodium trichloride	ACTIVE
10102-06-4	Uranyl nitrate	ACTIVE

· Hazardous Air Pollutants

7647-01-0	hydrochloric acid
7439-92-1	lead
7440-48-4	cobalt

· Proposition 65

· Chemicals known to cause cancer:

543-81-7	beryllium acetate
7439-92-1	lead
7440-48-4	cobalt

· Chemicals known to cause reproductive toxicity for females:

7439-92-1	lead
-----------	------

· Chemicals known to cause reproductive toxicity for males:

7439-92-1	lead
-----------	------

· Chemicals known to cause developmental toxicity:

7439-92-1	lead
-----------	------

· Carcinogenic categories

· EPA (Environmental Protection Agency)

513-77-9	barium carbonate	D, CBD(inh), NL(oral)
1306-38-3	cerium dioxide	II
7439-92-1	lead	B2

· TLV (Threshold Limit Value established by ACGIH)

7647-01-0	hydrochloric acid	A4
513-77-9	barium carbonate	A4
7439-92-1	lead	A3
7440-48-4	cobalt	A3
10049-07-7	rhodium trichloride	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

543-81-7	beryllium acetate
----------	-------------------

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 11)

10102-06-4 Uranyl nitrate

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
nitric acid
- **Hazard statements**
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**
Keep only in original container.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Absorb spillage to prevent material damage.
Store locked up.
Store in corrosive resistant container with a resistant inner liner.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** *Environment protection department.*
- **Contact:**
High-Purity Standards
Tel: 843-767-7900
Fax: 843-767-7906
- **Date of preparation / last revision** *05/22/2020 / -*

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/22/2020

Reviewed on 05/22/2020

Trade name: PE Stock Tuning Solution 2

(Contd. of page 12)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Met. Corr. 1: Corrosive to metals – Category 1
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Eye Dam. 1: Serious eye damage/eye irritation – Category 1