

## Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

### 1 Identification

- **Product identifier**
- **Trade name:** Stock Standard
- **Article number:** ICV-1-A
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
High-Purity Standards  
7221 Investment Drive, North Charleston, SC 29418 United States  
Telephone: +1-843-767-7900  
Fax: +1-843-767-7906  
[highpuritystandards.com](http://highpuritystandards.com)  
Email: [info@highpuritystandards.com](mailto:info@highpuritystandards.com)
- **Information department:** Product safety department
- **Emergency telephone number:**  
INFOTRAC  
Emergency telephone numbers 1-800-535-5053  
Other emergency telephone numbers 1-352-323-3500

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Met. Corr. 1 H290 May be corrosive to metals.  
Skin Corr. 1A H314 Causes severe skin burns and eye damage.  
Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
nitric acid

(Contd. on page 2)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 1)

*hydrogen fluoride***Hazard statements***H290 May be corrosive to metals.**H312 Harmful in contact with skin.**H314 Causes severe skin burns and eye damage.***Precautionary statements***Keep only in original container.**Do not breathe dusts or mists.**Wash thoroughly after handling.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Rinse mouth. Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Immediately call a poison center/doctor.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**Wash contaminated clothing before reuse.**Absorb spillage to prevent material damage.**Store locked up.**Store in corrosive resistant container with a resistant inner liner.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Classification system:****NFPA ratings (scale 0 - 4)***Health = 3**Fire = 0**Reactivity = 0***HMIS-ratings (scale 0 - 4)***Health = 3**Fire = 0**Reactivity = 0***Other hazards****Results of PBT and vPvB assessment***PBT: Not applicable.**vPvB: Not applicable.*

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures***Description: Mixture of the substances listed below with nonhazardous additions.*

(Contd. on page 3)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 2)

<b>· Dangerous components:</b>		
7697-37-2	nitric acid	4.0%
7664-39-3	hydrogen fluoride	0.49%
<b>· Chemical identification of the substance/preparation</b>		
7732-18-5	water, distilled, conductivity or of similar purity	95.27%
7440-09-7	potassium	0.02%
7722-76-1	Ammonium dihydrogenphosphate	0.02%
7782-49-2	selenium	0.02%
7429-90-5	aluminium	0.01%
7439-89-6	iron	0.01%
7439-92-1	lead	0.01%
7439-93-2	lithium	0.01%
7439-95-4	magnesium	0.01%
7439-98-7	molybdenum	0.01%
7440-02-0	nickel	0.01%
7440-24-6	strontium	0.01%
7440-28-0	thallium	0.01%
7440-38-2	arsenic	0.01%
7440-42-8	boron	0.01%
7440-50-8	copper	0.01%
7440-69-9	bismuth	0.01%
7440-70-2	calcium	0.01%
7439-96-5	manganese	0.005%
7440-39-3	barium	0.005%
7440-41-7	beryllium	0.005%
7440-43-9	cadmium	0.005%
7440-47-3	chromium	0.005%
7440-48-4	cobalt	0.005%
7440-62-2	vanadium	0.005%
7440-66-6	zinc	0.005%

**4 First-aid measures**

- **Description of first aid measures**
- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 3)

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-I:**

7697-37-2	nitric acid	0.16 ppm
7664-39-3	hydrogen fluoride	1.0 ppm
7440-09-7	potassium	2.3 mg/m <sup>3</sup>
7722-76-1	Ammonium dihydrogenphosphate	17 mg/m <sup>3</sup>
7782-49-2	selenium	0.6 mg/m <sup>3</sup>
7439-89-6	iron	3.2 mg/m <sup>3</sup>
7439-92-1	lead	0.15 mg/m <sup>3</sup>
7439-93-2	lithium	3.3 mg/m <sup>3</sup>

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 4)

7439-95-4	magnesium	18 mg/m <sup>3</sup>
7439-98-7	molybdenum	30 mg/m <sup>3</sup>
7440-02-0	nickel	4.5 mg/m <sup>3</sup>
7440-24-6	strontium	30 mg/m <sup>3</sup>
7440-28-0	thallium	0.06 mg/m <sup>3</sup>
7440-38-2	arsenic	1.5 mg/m <sup>3</sup>
7440-42-8	boron	1.9 mg/m <sup>3</sup>
7440-50-8	copper	3 mg/m <sup>3</sup>
7440-69-9	bismuth	15 mg/m <sup>3</sup>
7439-96-5	manganese	3 mg/m <sup>3</sup>
7440-39-3	barium	1.5 mg/m <sup>3</sup>
7440-41-7	beryllium	0.0023 mg/m <sup>3</sup>
7440-43-9	cadmium	0.10 mg/m <sup>3</sup>
7440-47-3	chromium	1.5 mg/m <sup>3</sup>
7440-48-4	cobalt	0.18 mg/m <sup>3</sup>
7440-62-2	vanadium	3 mg/m <sup>3</sup>
7440-66-6	zinc	6 mg/m <sup>3</sup>

**PAC-2:**

7697-37-2	nitric acid	24 ppm
7664-39-3	hydrogen fluoride	24 ppm
7440-09-7	potassium	25 mg/m <sup>3</sup>
7722-76-1	Ammonium dihydrogenphosphate	190 mg/m <sup>3</sup>
7782-49-2	selenium	6.6 mg/m <sup>3</sup>
7439-89-6	iron	35 mg/m <sup>3</sup>
7439-92-1	lead	120 mg/m <sup>3</sup>
7439-93-2	lithium	36 mg/m <sup>3</sup>
7439-95-4	magnesium	200 mg/m <sup>3</sup>
7439-98-7	molybdenum	330 mg/m <sup>3</sup>
7440-02-0	nickel	50 mg/m <sup>3</sup>
7440-24-6	strontium	330 mg/m <sup>3</sup>
7440-28-0	thallium	3.3 mg/m <sup>3</sup>
7440-38-2	arsenic	17 mg/m <sup>3</sup>
7440-42-8	boron	21 mg/m <sup>3</sup>
7440-50-8	copper	33 mg/m <sup>3</sup>
7440-69-9	bismuth	170 mg/m <sup>3</sup>
7439-96-5	manganese	5 mg/m <sup>3</sup>
7440-39-3	barium	180 mg/m <sup>3</sup>

(Contd. on page 6)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 5)

7440-41-7	beryllium	0.025 mg/m <sup>3</sup>
7440-43-9	cadmium	0.76 mg/m <sup>3</sup>
7440-47-3	chromium	17 mg/m <sup>3</sup>
7440-48-4	cobalt	2 mg/m <sup>3</sup>
7440-62-2	vanadium	5.8 mg/m <sup>3</sup>
7440-66-6	zinc	21 mg/m <sup>3</sup>

**· PAC-3:**

7697-37-2	nitric acid	92 ppm
7664-39-3	hydrogen fluoride	44 ppm
7440-09-7	potassium	150 mg/m <sup>3</sup>
7722-76-1	Ammonium dihydrogenphosphate	1,100 mg/m <sup>3</sup>
7782-49-2	selenium	40 mg/m <sup>3</sup>
7439-89-6	iron	150 mg/m <sup>3</sup>
7439-92-1	lead	700 mg/m <sup>3</sup>
7439-93-2	lithium	220 mg/m <sup>3</sup>
7439-95-4	magnesium	1,200 mg/m <sup>3</sup>
7439-98-7	molybdenum	2,000 mg/m <sup>3</sup>
7440-02-0	nickel	99 mg/m <sup>3</sup>
7440-24-6	strontium	2,000 mg/m <sup>3</sup>
7440-28-0	thallium	20 mg/m <sup>3</sup>
7440-38-2	arsenic	100 mg/m <sup>3</sup>
7440-42-8	boron	130 mg/m <sup>3</sup>
7440-50-8	copper	200 mg/m <sup>3</sup>
7440-69-9	bismuth	990 mg/m <sup>3</sup>
7439-96-5	manganese	1,800 mg/m <sup>3</sup>
7440-39-3	barium	1,100 mg/m <sup>3</sup>
7440-41-7	beryllium	0.1 mg/m <sup>3</sup>
7440-43-9	cadmium	4.7 mg/m <sup>3</sup>
7440-47-3	chromium	99 mg/m <sup>3</sup>
7440-48-4	cobalt	20 mg/m <sup>3</sup>
7440-62-2	vanadium	35 mg/m <sup>3</sup>
7440-66-6	zinc	120 mg/m <sup>3</sup>

**7 Handling and storage**

**· Handling:**

**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 6)

- Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**7697-37-2 nitric acid**

PEL	Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
REL	Short-term value: 10 mg/m <sup>3</sup> , 4 ppm Long-term value: 5 mg/m <sup>3</sup> , 2 ppm
TLV	Short-term value: 4 ppm Long-term value: 2 ppm

**7664-39-3 hydrogen fluoride**

PEL	Long-term value: 1* mg/m <sup>3</sup> , 3 ppm as F, *sulfuric acid
REL	Long-term value: 2.5 mg/m <sup>3</sup> , 3 ppm Ceiling limit value: 5* mg/m <sup>3</sup> , 6* ppm *15-min, as F
TLV	Long-term value: 0.5 ppm Ceiling limit value: 2 ppm as F; Skin, BEI

· **Ingredients with biological limit values:**

**7664-39-3 hydrogen fluoride**

BEI	3 mg/g creatinine Medium: urine Time: prior to shift Parameter: Fluorides (background, nonspecific)
	10 mg/g creatinine Medium: urine Time: end of shift Parameter: Fluorides (background, nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 7)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
*Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes.  
 Avoid contact with the eyes and skin.*
- **Breathing equipment:**  
*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*
- **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

- **Material of gloves**  
*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- **Penetration time of glove material**  
*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*
- **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.
- **pH-value:** Not determined.

(Contd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 8)

· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	100 °C (212 °F)
· <b>Flash point:</b>	Not applicable.
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapor pressure at 20 °C (68 °F):</b>	23 hPa (17.3 mm Hg)
· <b>Density:</b>	Not determined.
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Water:</b>	95.3 %
<b>VOC content:</b>	0.00 % 0.0 g/l / 0.00 lb/gal
<b>Solids content:</b>	0.2 %
· <b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 10)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 9)

· **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**7664-39-3 hydrogen fluoride**

Oral	LD50	1,276 mg/kg (rat)
------	------	-------------------

· **Primary irritant effect:**

· **on the skin:** Strong caustic effect on skin and mucous membranes.

· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

7782-49-2	selenium	3
7439-92-1	lead	2B
7440-02-0	nickel	2B
7440-38-2	arsenic	1
7440-41-7	beryllium	1
7440-43-9	cadmium	1
7440-47-3	chromium	3
7440-48-4	cobalt	2B

· **NTP (National Toxicology Program)**

7439-92-1	lead	R
7440-02-0	nickel	R
7440-38-2	arsenic	K
7440-41-7	beryllium	K
7440-43-9	cadmium	K
7440-48-4	cobalt	R

(Contd. on page 11)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 10)

· **OSHA-Ca (Occupational Safety & Health Administration)**

7440-38-2 arsenic

7440-43-9 cadmium

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN3264
- **UN proper shipping name**
- **DOT** Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
- **ADR** 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
- **IMDG, IATA** CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)

(Contd. on page 12)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 11)

· **Transport hazard class(es)**

· **DOT**



· **Class** 8 Corrosive substances  
· **Label** 8

· **ADR**



· **Class** 8 (C1) Corrosive substances  
· **Label** 8

· **IMDG, IATA**



· **Class** 8 Corrosive substances  
· **Label** 8

· **Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Corrosive substances

· **Hazard identification number (Kemler code):** 80

· **EMS Number:** F-A,S-B

· **Segregation groups** Acids

· **Stowage Category** A

· **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L

(Contd. on page 13)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 12)

<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p>Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	<p>UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III</p>

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **Sara**

· **Section 355 (extremely hazardous substances):**

7697-37-2	nitric acid
7664-39-3	hydrogen fluoride

· **Section 313 (Specific toxic chemical listings):**

7697-37-2	nitric acid
7664-39-3	hydrogen fluoride
7782-49-2	selenium
7429-90-5	aluminium
7439-92-1	lead
7440-02-0	nickel
7440-28-0	thallium
7440-38-2	arsenic
7440-50-8	copper
7439-96-5	manganese
7440-39-3	barium
7440-41-7	beryllium
7440-43-9	cadmium
7440-47-3	chromium
7440-48-4	cobalt
7440-62-2	vanadium
7440-66-6	zinc

(Contd. on page 14)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 13)

**· TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

**· Hazardous Air Pollutants**

7664-39-3 hydrogen fluoride

7439-92-1 lead

7439-96-5 manganese

7440-48-4 cobalt

**· Proposition 65**

**· Chemicals known to cause cancer:**

7439-92-1 lead

7440-02-0 nickel

7440-38-2 arsenic

7440-41-7 beryllium

7440-43-9 cadmium

7440-48-4 cobalt

**· Chemicals known to cause reproductive toxicity for females:**

7439-92-1 lead

**· Chemicals known to cause reproductive toxicity for males:**

7439-92-1 lead

7440-43-9 cadmium

**· Chemicals known to cause developmental toxicity:**

7439-92-1 lead

7440-43-9 cadmium

**· Carcinogenic categories**

**· EPA (Environmental Protection Agency)**

7782-49-2 selenium

D

7439-92-1 lead

B2

7440-38-2 arsenic

A

7440-42-8 boron

I (oral)

7440-50-8 copper

D

7439-96-5 manganese

D

7440-39-3 barium

D, CBD(inh), NL(oral)

7440-41-7 beryllium

B1, K/L(inh), CBD(oral)

7440-43-9 cadmium

B1

7440-47-3 chromium

D

7440-66-6 zinc

D, I, II

(Contd. on page 15)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 14)

· <b>TLV (Threshold Limit Value)</b>		
7429-90-5	aluminium	A4
7439-92-1	lead	A3
7439-98-7	molybdenum	A3
7440-02-0	nickel	A5
7440-38-2	arsenic	A1
7440-39-3	barium	A4
7440-41-7	beryllium	A1
7440-43-9	cadmium	A2
7440-47-3	chromium	A4
7440-48-4	cobalt	A3

· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
7440-02-0	nickel	
7440-38-2	arsenic	
7440-41-7	beryllium	
7440-43-9	cadmium	

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

nitric acid

hydrogen fluoride

· **Hazard statements**

H290 May be corrosive to metals.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· **Precautionary statements**

Keep only in original container.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

(Contd. on page 16)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2022

Reviewed on 08/04/2022

**Trade name: Stock Standard**

(Contd. of page 15)

Immediately call a poison center/doctor.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
Wash contaminated clothing before reuse.  
Absorb spillage to prevent material damage.  
Store locked up.  
Store in corrosive resistant container with a resistant inner liner.  
Dispose of contents/container in accordance with local/regional/national/international regulations.  
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

High-Purity Standards

Tel: 843-767-7900

Fax: 843-767-7906

· **Date of preparation / last revision** 08/04/2022 / -

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Met. Corr. 1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1