

## Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

### 1 Identification

- **Product identifier**
- **Trade name:** KKXYL
- **Article number:** KKXYL
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
High-Purity Standards  
7221 Investment Drive, North Charleston, SC 29418 United States  
Telephone: +1-843-767-7900  
Fax: +1-843-767-7906  
[highpuritystandards.com](http://highpuritystandards.com)  
Email: [info@highpuritystandards.com](mailto:info@highpuritystandards.com)
- **Information department:** Product safety department
- **Emergency telephone number:**  
INFOTRAC  
Emergency telephone numbers 1-800-535-5053  
Other emergency telephone numbers 1-352-323-3500

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**  
xylene

(Contd. on page 2)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

**Trade name: KKXYL**

(Contd. of page 1)

**· Hazard statements***H226 Flammable liquid and vapor.**H332 Harmful if inhaled.**H315 Causes skin irritation.***· Precautionary statements***Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**Call a poison center/doctor if you feel unwell.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.**Store in a well-ventilated place. Keep cool.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)***Health = 1**Fire = 3**Reactivity = 0***· HMIS-ratings (scale 0 - 4)***Health = 1**Fire = 3**Reactivity = 0***· Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**3 Composition/information on ingredients****· Chemical characterization: Mixtures****· Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

Trade name: KKXYL

(Contd. of page 2)

### · **Dangerous components:**

1330-20-7	xylene	99.9%
-----------	--------	-------

### · **Chemical identification of the substance/preparation**

7440-09-7	potassium	0.1%
-----------	-----------	------

## 4 First-aid measures

### · **Description of first aid measures**

#### · **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

#### · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

#### · **After eye contact:** Rinse opened eye for several minutes under running water.

#### · **After swallowing:** If symptoms persist consult doctor.

#### · **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

### · **Extinguishing media**

#### · **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### · **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

#### · **Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

### · **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

#### · **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

#### · **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

**Trade name: KKXYL**

(Contd. of page 3)

- **Reference to other sections**  
*See Section 7 for information on safe handling.*  
*See Section 8 for information on personal protection equipment.*  
*See Section 13 for disposal information.*
- **Protective Action Criteria for Chemicals**

**PAC-1:**

1330-20-7	xylene	130 ppm
7440-09-7	potassium	2.3 mg/m <sup>3</sup>

**PAC-2:**

1330-20-7	xylene	920* ppm
7440-09-7	potassium	25 mg/m <sup>3</sup>

**PAC-3:**

1330-20-7	xylene	2500* ppm
7440-09-7	potassium	150 mg/m <sup>3</sup>

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
*Ensure good ventilation/exhaustion at the workplace.*  
*Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**  
*Keep ignition sources away - Do not smoke.*  
*Protect against electrostatic charges.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep receptacle tightly sealed.*
- **Specific end use(s)** *No further relevant information available.*

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*
- **Control parameters**

**Components with limit values that require monitoring at the workplace:**

1330-20-7	xylene
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

**Trade name: KKXYL**

(Contd. of page 4)

REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

· **Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

## Safety Data Sheet

*acc. to OSHA HCS*

Printing date 06/08/2022

Reviewed on 06/08/2022

Trade name: KKXYL

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137-143 °C (278.6-289.4 °F)

· Flash point: 30 °C (86 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 500 °C (932 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	1.1 Vol %
Upper:	7 Vol %

· Vapor pressure at 20 °C (68 °F): 6.7-8.2 hPa (5-6.2 mm Hg)

· Density at 20 °C (68 °F): 0.86999 g/cm<sup>3</sup> (7.26007 lbs/gal)

· Bulk density: 870 kg/m<sup>3</sup>

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

(Contd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

Trade name: KKXYL

(Contd. of page 6)

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

    **Dynamic:** Not determined.

    **Kinematic:** Not determined.

· **Solvent content:**

    **Organic solvents:** 99.9 %

    **VOC content:** 99.90 %

869.1 g/l / 7.25 lb/gal

**Solids content:** 0.1 %

· **Other information** No further relevant information available.

### 10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

· **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

**Trade name: KKXYL**

(Contd. of page 7)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7 xylene

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UNI1307

· **UN proper shipping name**

· **DOT**

Xylenes solution

(Contd. on page 9)



## Safety Data Sheet

*acc. to OSHA HCS*

Printing date 06/08/2022

Reviewed on 06/08/2022

Trade name: KKXYL

(Contd. of page 8)

· **ADR** 1307 XYLENES solution  
· **IMDG, IATA** XYLENES solution

· **Transport hazard class(es)**

· **DOT**


· **Class** 3 Flammable liquids  
· **Label** 3

· **ADR**


· **Class** 3 (F1) Flammable liquids  
· **Label** 3

· **IMDG, IATA**


· **Class** 3 Flammable liquids  
· **Label** 3

· **Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 30

· **EMS Number:** F-E,S-D

· **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 60 L  
On cargo aircraft only: 220 L

(Contd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

**Trade name: KKXYL**

(Contd. of page 9)

· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1307 XYLENES SOLUTION, 3, III

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **Sara**

#### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

#### · Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

#### · TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

#### · Hazardous Air Pollutants

1330-20-7 xylene

#### · Proposition 65

##### · Chemicals known to cause cancer:

None of the ingredients is listed.

##### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

##### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

##### · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### · Carcinogenic categories

##### · EPA (Environmental Protection Agency)

1330-20-7 xylene

I

(Contd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Reviewed on 06/08/2022

**Trade name: KKXYL**

(Contd. of page 10)

**· TLV (Threshold Limit Value)**

1330-20-7 xylene

A4

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**


GHS02 GHS07

**· Signal word** Warning

**· Hazard-determining components of labeling:**

xylene

**· Hazard statements**

H226 Flammable liquid and vapor.

H332 Harmful if inhaled.

H315 Causes skin irritation.

**· Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 12)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 06/08/2022

Reviewed on 06/08/2022

**Trade name: KKXYL**

(Contd. of page 11)

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:**

High-Purity Standards

Tel: 843-767-7900

Fax: 843-767-7906

· **Date of preparation / last revision** 06/08/2022 / -

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2