

## **RB-MMA-1**

## **High-Purity Standards**

Catalogue number: RB-MMA-1

Version No: 2.2

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: **05/05/2017** Print Date: **05/05/2017** S.GHS.USA.EN

#### **SECTION 1 IDENTIFICATION**

#### **Product Identifier**

Product name	RB-MMA-1
Synonyms	Not Available
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Other means of identification	RB-MMA-1

#### Recommended use of the chemical and restrictions on use

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

#### **Emergency phone number**

· , .	
Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

#### **SECTION 2 HAZARD(S) IDENTIFICATION**

## 

Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 3, Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A

## Label elements

Hazard pictogram(s)





SIGNAL WORD DANGER

#### Hazard statement(s)

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

RB-MMA-1

Version No: 2.2

Not Applicable

Precautionary statement(s) Prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

Precautionary statement(s) Response

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Precautionary statement(s) Storage

P405

Store locked up.

Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

#### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
7664-39-3	0.5	hydrofluoric acid
7697-37-2	2	nitric acid
7732-18-5	Balance	water

#### **SECTION 4 FIRST-AID MEASURES**

#### Description of first aid measures

# Eye Contact

If this product comes in contact with the eyes:

- ▶ Immediately hold eyelids apart and flush the eye continuously with running water.
- ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ► Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel

## **Skin Contact**

- If there is evidence of severe skin irritation or skin burns:
- Avoid further contact. Immediately remove contaminated clothing, including footwear Flush skin under running water for 15 minutes
- Avoiding contamination of the hands, massage calcium gluconate gel into affected areas, pay particular attention to creases in skin.
- ► Contact the Poisons Information Centre.
  - Continue gel application for at least 15 minutes after burning sensation ceases.
  - If pain recurs, repeat application of calcium gluconate gel or apply every 20 minutes.
  - ▶ If no gel is available, continue washing for at least 15 minutes, using soap if available. If patient is conscious, give six calcium gluconate or calcium carbonate tablets in water by mouth.
  - ▶ Transport to hospital, or doctor, urgently
  - ▶ If fumes or combustion products are inhaled remove from contaminated area.
  - Lay patient down. Keep warm and rested.
  - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
  - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if
  - Transport to hospital, or doctor, without delay.
  - Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.
  - Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).
  - As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. ▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.
  - This must definitely be left to a doctor or person authorised by him/her

# Inhalation

(ICSC13719) For massive exposures:

- ▶ If dusts, vapours, aerosols, fumes or combustion products are inhaled, remove from contaminated area.
- ► Lay patient down.
- Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if
- ▶ If victim is conscious, give six calcium gluconate or calcium carbonate tablets in water by mouth.
- ► Transport to hospital, or doctor, urgently.

## Ingestion

- ▶ For advice, contact a Poisons Information Centre or a doctor at once.
- ▶ Urgent hospital treatment is likely to be needed.
- If swallowed do **NOT** induce vomiting
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
  - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
  - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
  - Transport to hospital or doctor without delay.

Issue Date: 05/05/2017

Print Date: 05/05/2017

Version No: 2.2

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

Following acute or short term repeated exposure to hydrofluoric acid:

- Subcutaneous injections of Calcium Gluconate may be necessary around the burnt area. Continued application of Calcium Gluconate Gel or subcutaneous Calcium Gluconate should then continue for 3-4 days at a frequency of 4-6 times per day. If a "burning" sensation recurs, apply more frequently.
- Systemic effects of extensive hydrofluoric acid burns include renal damage, hypocalcaemia and consequent cardiac arrhythmias. Monitor haematological, respiratory, renal, cardiac and electrolyte status at least daily. Tests should include FBE, blood gases, chest X-ray, creatinine and electrolytes, urine output, Ca ions, Mg ions and phosphate ions. Continuous ECG monitoring may be required.
- Where serum calcium is low, or clinical, or ECG signs of hypocalcaemia develop, infusions of calcium gluconate, or if less serious, oral Sandocal, should be given. Hydrocortisone 500 mg in a four to six hourly infusion may help.
- Antibiotics should not be given as a routine, but only when indicated.
- ▶ Eye contact pain may be excruciating and 2-3 drops of 0.05% pentocaine hydrochloride may be instilled, followed by further irrigation

#### BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

DeterminantIndexSampling TimeComments1. Methaemoglobin in blood1.5% of haemoglobinDuring or end of shiftB, NS, SQ

- B: Background levels occur in specimens collected from subjects NOT exposed.
- NS: Non-specific determinant; Also seen after exposure to other materials
- SQ: Semi-quantitative determinant Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

For acute or short term repeated exposures to fluorides:

- Fluoride absorption from gastro-intestinal tract may be retarded by calcium salts, milk or antacids.
- Fluoride particulates or fume may be absorbed through the respiratory tract with 20-30% deposited at alveolar level.
- ▶ Peak serum levels are reached 30 mins. post-exposure; 50% appears in the urine within 24 hours.
- For acute poisoning (endotracheal intubation if inadequate tidal volume), monitor breathing and evaluate/monitor blood pressure and pulse frequently since shock may supervene with little warning. Monitor ECG immediately; watch for arrhythmias and evidence of Q-T prolongation or T-wave changes. Maintain monitor. Treat shock vigorously with isotonic saline (in 5% glucose) to restore blood volume and enhance renal excretion.
- ▶ Where evidence of hypocalcaemic or normocalcaemic tetany exists, calcium gluconate (10 ml of a 10% solution) is injected to avoid tachycardia.

#### BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

 Determinant
 Index
 Sampling Time
 Comments

 Fluorides in urine
 3 mg/gm creatinine
 Prior to shift
 B, NS

 10mg/gm creatinine
 End of shift
 B, NS

B: Background levels occur in specimens collected from subjects  $\boldsymbol{\mathsf{NOT}}$  exposed

NS: Non-specific determinant; also observed after exposure to other exposures.

## **SECTION 5 FIRE-FIGHTING MEASURES**

#### **Extinguishing media**

- ► There is no restriction on the type of extinguisher which may be used
- ▶ Use extinguishing media suitable for surrounding area.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

None known

## Special protective equipment and precautions for fire-fighters

Fire Fighting

- ▶ Non combustible.
- ▶ Not considered to be a significant fire risk.

Fire/Explosion Hazard

- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- ► May emit corrosive, poisonous fumes. May emit acrid smoke.

May emit corrosive fumes

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills

► Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.

Chemwatch: 9-394570 Catalogue number: RB-MMA-1

RB-MMA-1

Page 4 of 12 Issue Date: 05/05/2017 Print Date: 05/05/2017

Version No: 2.2

 Check regularly for spills and leaks. Clean up all spills immediately Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite Wipe up. ▶ Place in a suitable, labelled container for waste disposal. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Major Spills Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 HANDLING AND STORAGE**

#### Precautions for safe handling

Avoid all personal contact, including inhalation Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke Safe handling Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. Store in original containers. Keep containers securely sealed Store in a cool, drv. well-ventilated area. Other information Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

## Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>DO NOT use aluminium or galvanised containers</li> <li>Lined metal can, lined metal pail/ can.</li> <li>Plastic pail.</li> <li>Polyliner drum.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> <li>For low viscosity materials</li> <li>Drums and jerricans must be of the non-removable head type.</li> <li>Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):</li> <li>Removable head packaging;</li> <li>Cans with friction closures and</li> <li>low pressure tubes and cartridges</li> <li>may be used.</li> <li>Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning macontact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible we plastic.</li> </ul>
--------------------	--

naterial in with the

- ▶ Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
- Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts neutralisation can generate dangerously large amounts of heat in small spaces
- The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
- ► The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.
- Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.
- Inorganic acids can initiate the polymerisation of certain classes of organic compounds.

#### Storage incompatibility

- Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.
- Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitriles, sulfides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H2S and SO3), dithionites (SO2), and even carbonates
- ▶ Acids often catalyse (increase the rate of) chemical reactions.

## Salts of inorganic fluoride:

- react with water forming acidic solutions.
- are violent reactive with boron, bromine pentafluoride, bromine trifluoride, calcium disilicide, calcium hydride, oxygen difluoride, platinum, potassium.
- in aqueous solutions are incompatible with sulfuric acid, alkalis, ammonia, aliphatic amines, alkanolamines, alkylene oxides, amides, epichlorohydrin,

Catalogue number: RB-MMA-1

Version No: 2.2

Chemwatch: 9-394570

RB-MMA-1

Issue Date: **05/05/2017**Print Date: **05/05/2017** 

- ▶ isocyanates, nitromethane, organic anhydrides, vinyl acetate
- corrode metals in presence of moisture
- ▶ may be incompatible with glass and porcelain
- $\blacksquare \ \ \, \text{Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.} \\$

#### Hydrogen fluoride:

- reacts violently with strong oxidisers, acetic anhydride, alkalis, 2-aminoethanol, arsenic trioxide (with generation of heat), bismuthic acid, calcium oxide, chlorosulfonic acid, cyanogen fluoride, ethylenediamine, ethyleneimine, fluorine gas reacts vigorously with a 50% hydrofluoric acid solution and may burst into flame), nitrogen trifluoride, N-phenylazopiperidine, oleum, oxygen difluoride, phosphorus pentoxide, potassium permanganate, potassium tetrafluorosilicate(2-), beta-propiolactone, propylene oxide, sodium, sodium tetrafluorosilicate, sulfuric acid, vinyl acetate
- reacts (possibly violently) with aliphatic amines, alcohols, alkanolamines, alkylene oxides, aromatic amines, amides, ammonia, ammonium hydroxide, epichlorohydrin, isocyanates, metal acetylides, metal silicides, methanesulfonic acid, nitrogen compounds, organic anhydrides, oxides, silicon compounds, vinylidene fluoride
- attacks glass and siliceous materials, concrete, ceramics, metals (flammable hydrogen gas may be produced), metal alloys, some plastics, rubber coatings, leather, and most other materials with the exception of lead, platinum, polyethylene, wax.

#### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **Control parameters**

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrofluoric acid	Hydrogen fluoride	Not Available	Not Available	Not Available	See Table Z-2;(as F)
US OSHA Permissible Exposure Levels (PELs) - Table Z2	hydrofluoric acid	Hydrogen fluoride	3 ppm	Not Available	Not Available	(Z37.28–1969)
US ACGIH Threshold Limit Values (TLV)	hydrofluoric acid	Hydrogen fluoride, as F	0.5 ppm	Not Available	2 ppm	TLV® Basis: URT, LRT, skin, & eye irr; fluorosis; BEI
US NIOSH Recommended Exposure Limits (RELs)	hydrofluoric acid	Anhydrous hydrogen fluoride; Aqueous hydrogen fluoride (i.e., Hydrofluoric acid); HF-A	2.5 mg/m3 / 3 ppm	Not Available	5 mg/m3 / 6 ppm	[15-minute]
US OSHA Permissible Exposure Levels (PELs) - Table Z1	nitric acid	Nitric acid	5 mg/m3 / 2 ppm	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	nitric acid	Nitric acid	2 ppm	4 ppm	Not Available	TLV® Basis: URT & eye irr; dental erosion
US NIOSH Recommended Exposure Limits (RELs)	nitric acid	Aqua fortis, Engravers acid, Hydrogen nitrate, Red furning nitric acid (RFNA), White furning nitric acid (WFNA)	5 mg/m3 / 2 ppm	10 mg/m3 / 4 ppm	Not Available	Not Available

## EMERGENCY LIMITS

hydrofluoric acid Hydrogen fluoride; (Hydrofluoric acid) Not Available Not Available Not Available	Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
	hydrofluoric acid	Hydrogen fluoride; (Hydrofluoric acid)	Not Available	Not Available	Not Available
nitric acid Nitric acid Not Available Not Available Not Available	nitric acid	Nitric acid	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
hydrofluoric acid	30 ppm	30 [Unch] ppm
nitric acid	100 ppm	25 ppm
water	Not Available	Not Available

#### **Exposure controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Appropriate engineering

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generate

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

# controls

Version No: 2.2

grinding, shreaker bleating, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid   2-51 on his (500-2000   2-51 on his		grisding physics blooking trapbling high appeal whool governed dusts (sological at high initial)	valonity into zono of your bigh round	3 F 10 m/s /F00 3000		
Lower end of the range  1. Room air currents minimal or favourable to capture  1. Disturbing room air currents  2. Contaminants of low toxicity or of nuisance value only.  3. Intermittent, low production.  4. Large hood or large air mass in motion  3. High production, heavy use  4. Small hood-local control only  Simple theory shows that air velocity fails rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity after the extraction of the opening of a simple extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The extraction point should be adjusted, accordingly, after reference to distance from the contamination of 1-2 m's case and spirated to an air an a			velocity into zone or very high rapid	,		
1: Room air currents minimal or favourable to capture 2: Contaminants of low toxicity or of nuisance value only. 3: Intermittent, low production. 4: Large hood or large air mass is motion 4: Large hood or large air mass is motion 5: Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the contaminating source. The air velocity of the extraction falls in the extraction point is should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity of the extraction fall, for example, should be a minimum of 1-2 m/s (200-400 time) for extraction of solvenis generated in a fank. Zemetes distant from the extraction fall for extraction fall for mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.  Personal protection  **Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.  **Pull face protection**  **Eye and face protection**  **Alternatively again small, may replace ospisal progeties and face shields, where there is a danger of splashing, or if the material may be under pressure.  **Pull face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afforts face protection.  **Eye and face protection**  **Eye and face protection**  **Alternatively again saak may replace ospisal		Within each range the appropriate value depends on:				
2: Contaminants of low toxicity or of nuisance value only. 3: Intermittent, low production. 4: Large hood or large air mass in motion 4: Large hood or large air mass in motion 4: Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 fmin) for extraction of solvents generated in a tank 2 meters distant from the extraction (on 10-12 m/s (200-400 fmin) for extraction of solvents generated in a tank 2 meters distant from the extraction (on 10-12 m/s (200-400 fmin) for extraction of apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.  Personal protection  **Personal protection**  **Part of the material complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.  **Personal protection**  **Pull face shield (20 m, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  **Pull face shield (20 m, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  **Pull face shield (20 m, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  **Pull face shield (20 m, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  **Pull face shield (20 m, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  **Pull face shield (20 m, 8 in mi		Lower end of the range	Upper end of the range			
3: Intermittent, low production. 4: Large hood or large air mass in motion  4: Small hood-local control only  Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point of 1-2 ms (200-40) timin) for extraction of solvents generated in a tank? 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.  Personal protection  Personal protection  **Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.  **Pull face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  **Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  **Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  **Enterprise of eye restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of hermicals in use and an account of injury experience. Medical and filteral protection below to be readily available. In the event of chemical exposure, begin eye irrigation immediately and r		1: Room air currents minimal or favourable to capture	1: Disturbing room air currents			
4: Large hood or large air mass in motion  4: Small hood-local control only  Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction pipe. Velocity generally decreases with the square of distance from the contaminating source. The air velocity at the extraction fan, for examination point should be an institution of 12 m/s (200-400 film) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.  Personal protection  1 Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.  2 Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.  3 Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  4 Alternatively a gas mask may replace splash goggles and face shields.  4 Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created in first-aid personnel should be trained in their removal and subsible equipment should be readyly available. In the event of hemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed and their removal and alterial expone		2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity			
Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the extraction point. Other mechanical considerations, producing performance deficits within the extraction appearatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.  Personal protection  Personal protection  I Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.  Personal protection  Eye and face protection  A laternatively a gas mask may replace splash goggles and face shields.  Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  A laternatively a gas mask may replace splash goggles and face shields.  Contract renses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available, in the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. [AS/NZS 1336 or na		3: Intermittent, low production.	3: High production, heavy use			
of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 kmin) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.  Personal protection  **Near Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectades are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.  **Near Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectades are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.  **Near Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectades are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material complete is a stanger of splashing, or if the material complete is specially splashed pressure.  **Near Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectades are not sufficient where complete eye protection.  **Near Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectades are not sufficient where continuous e		4: Large hood or large air mass in motion	4: Small hood-local control only			
Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.   Chemical goggles, whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.   Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.   Alternatively a gas mask may replace splash goggles and face shields.   Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]    Skin protection		of distance from the extraction point (in simple cases). Therefore the air speed at the extraction poi distance from the contaminating source. The air velocity at the extraction fan, for example, should b solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considera	nt should be adjusted, accordingly, a e a minimum of 1-2 m/s (200-400 f/n ations, producing performance defici	after reference to inin) for extraction of the within the extraction		
where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.  • Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.  • Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.  • Alternatively a gas mask may replace splash goggles and face shields.  • Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]  Skin protection  Bady protection  • Elbow length PVC gloves  • When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.  See Other protection below  • Overalls.  • PVC Apron.  • PVC Apron.  • PVC Protective suit may be required if exposure severe.  • Eyewash unit.  • Ensure there is ready access to a safety shower.	Personal protection					
Hands/feet protection    Elbow length PVC gloves   When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.    Body protection   See Other protection below	Eye and face protection	<ul> <li>where complete eye protection is needed such as when handling bulk-quantities, where there pressure.</li> <li>Chemical goggles.whenever there is a danger of the material coming in contact with the eyes</li> <li>Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primar</li> <li>Alternatively a gas mask may replace splash goggles and face shields.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate ir lenses or restrictions on use, should be created for each workplace or task. This should includ chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remorat the first signs of eye redness or irritation - lens should be removed in a clean environment or</li> </ul>	is a danger of splashing, or if the ma ; goggles must be properly fitted. y protection of eyes; these afford fac ritants. A written policy document, do e a review of lens absorption and ac be trained in their removal and suitable we contact lens as soon as practicab	terial may be under se protection. sescribing the wearing of disorption for the class of sole equipment should be le. Lens should be removed		
Hands/feet protection  When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.  See Other protection below  Other protection  Other protection  PVC Apron.  PVC protective suit may be required if exposure severe.  Eyewash unit.  Ensure there is ready access to a safety shower.	Skin protection	See Hand protection below				
Coveralls.     PVC Apron.     PVC protective suit may be required if exposure severe.     Eyewash unit.     Ensure there is ready access to a safety shower.	Hands/feet protection	0 0	tering boots.			
<ul> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> </ul>	Body protection	See Other protection below				
Thermal hazards Not Available	Other protection	<ul> <li>PVC Apron.</li> <li>PVC protective suit may be required if exposure severe.</li> <li>Eyewash unit.</li> </ul>				
	Thermal hazards	Not Available				

## Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

Appearance	Colourless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available

Version No: 2.2

RB-MMA-1

 Vapour density (Air = 1)
 Not Available

 VOC g/L
 Not Available

## **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	► Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

Information	۸n	toxicological effects	
intormation	on	toxicological effects	i

defined an experience of the formal and the first f
nalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.  The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. There may be dizziness, headache, usea and weakness.  The defects of fluoride inhalation include irritation of nose and throat, coughing and chest discomfort. A single acute over-exposure may even cause nose end.  The inhalation of hydrogen fluoride (hydrofluoric acid) vapours causes severe irritation of the eye, nose and throat, delayed fever, bluing of the extremities and atter in the lungs, and may cause death. The above irritation occurs even with fairly low concentrations of hydrogen fluoride. Hydrogen fluoride has a strong tating odour, that can be detected at concentrations of about 0.04 parts per million. Higher levels cause corrosion of the throat, nose and lungs, leading to vere inflammation and water buildup in the lungs (which may occur with 1 hour of exposure). A vapour concentration of 10 parts per million is regarded as olerable, but a vapour concentration of 30 parts per million is considered as immediately dangerous to life and health.  The sestimated that the lowest lethal concentration for a 5-minute human exposure to hydrogen fluoride is in the range of 50 to 250 parts per million. Exposure by her skin contact or inhalation may lead to low levels of calcium and magnesium in the blood, which may result in heart rhythm disturbances. Animal testing geests that repeated exposure produces liver and kidney damage.
ccidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious mage to the health of the individual.  gestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and eaking may also be evident.  uoride causes severe loss of calcium in the blood, with symptoms appearing several hours later including painful and rigid muscle contractions of the limbs. ardiovascular collapse can occur and may cause death with increased heart rate and other heart rhythm irregularities.
cin contact with the material may be harmful; systemic effects may result following absorption.  In contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. In contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. In contact of the skin with liquid hydrofluoric acid (hydrogen fluoride) may cause severe burns, erythema, and swelling, vesiculation, and serious crusting. With bore serious burns, ulceration, blue-gray discoloration, and necrosis may occur. Solutions of hydrofluoric acid, as dilute as 2%, may cause severe skin burns. Jorides are easily absorbed through the skin and cause death of soft tissue and erode bone. Healing is delayed and death of tissue may continue to spread neath skin.  In the paint of the skin should not be exposed to this material attry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use the material and ensure that any external damage is suitably protected.
applied to the eyes, this material causes severe eye damage. rect eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and impletely.  nimal testing showed that a 20% solution of hydrofluoric acid (hydrogen fluoride) in water caused immediate damage in the form of total clouding of the lens in the conjunctiva. Swelling of the stroma of the cornea occurred within 1 hour, followed by tissue death (necrosis) of structures of the front of the e.
ing-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.  Ibstance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, dinflammation of lung tissue often occurs.  Itended exposure to inorganic fluorides causes fluorosis, which includes signs of joint pain and stiffness, tooth discolouration, nausea and vomiting, loss of petite, diarrhoea or constipation, weight loss, anaemia, weakness and general unwellness. There may also be frequent urination and thirst. Vidrogen fluoride easily penetrates the skin and causes destruction and corrosion of the bone and underlying tissue. Ingestion causes severe pains and burns the mouth and throat and blood calcium levels are dangerously reduced.
in our element was higher than the control of the c

	Hydrogen fluoride easily penetrates the skin and causes destruction and corrosion of the bone and underlying tissue. Ingestion causes severe pains and burns in the mouth and throat and blood calcium levels are dangerously reduced.			
RB-MMA-1	TOXICITY IRRITATION  Not Available Not Available			
hydrofluoric acid	Inhalation (rat) LC50: 1276 ppm/4hr <sup>[2]</sup> Inhalation (rat) LC50: 319 ppm/1hr <sup>[2]</sup>		IRRITATION  Eye (human): 50 mg - SE\	/ERE
nitric acid	TOXICITY Inhalation (rat) LC50: 625 ppm/1h*t <sup>[2]</sup>			IRRITATION Not Available
water	тохісіту	IRRI	TATION	

gue number: RB-MMA-1

Version No: 2.2

	Not Available	Not Available			
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances				
HYDROFLUORIC ACID	(liver and kidney damage) [Manufacturer] for hydrogen fluoride (as vapour)				
NITRIC ACID	For acid mists, aerosols, vapours  Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5.  The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.  Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]				
HYDROFLUORIC ACID & WATER	No significant acute toxicological data identified in literature search.				
HYDROFLUORIC ACID & NITRIC ACID	The material may produce severe irritation to the eye causing pronounced inflammation.				
HYDROFLUORIC ACID & NITRIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ends.				
HYDROFLUORIC ACID & NITRIC ACID	The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function.				
Acute Toxicity	<b>✓</b> Ca	✓ Carcinogenicity			
Skin Irritation/Corrosion	<b>✓</b> Ro	✓ Reproductivity			
Serious Eye Damage/Irritation	○ STOT - Sin	STOT - Single Exposure			
Respiratory or Skin sensitisation	○ STOT - Repeat	STOT - Repeated Exposure			
Mutagenicity	Aspir	ation Hazard	0		

Legend:

X – Data available but does not fill the criteria for classification

✓ – Data available to make classification

O - Data Not Available to make classification

#### **SECTION 12 ECOLOGICAL INFORMATION**

## Toxicity

RB-MMA-1	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE	
KD-IMIMA-1	Not Applicable	Not Applicable	Not App	olicable	Not Applicable	Not Applicable	
	ENDPOINT	TEST DURATION (HR)		SPECIES	VALUE	SOURCE	
	LC50	96		Fish	51mg/L	2	
hydrofluoric acid	EC50	48		Crustacea	=270mg/L	1	
	EC50	96		Crustacea	26-48mg/L	2	
	NOEC	504		Fish 4mg/L		2	
nitric acid	ENDPOINT	TEST DURATION (HR)		SPECIES	VALUE	SOURCE	
	NOEC	16		Crustacea 107mg/L 4			
	ENDPOINT	TEST DURATION (HR)	SPECIE	S	VALUE	SOURCE	
water	Not Applicable	Not Applicable	Not App	olicable	Not Applicable	Not Applicable	
Legend:	Extracted from 1. IUCL	.ID Toxicity Data 2. Europe ECHA Registe	ered Substances -	Ecotoxicologica	al Information - Aquatic To	oxicity 3. EPIWIN Suite	

#### Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

For Fluorides: Small amounts of fluoride have beneficial effects however, excessive intake over long periods may cause dental and/or skeletal fluorosis. Fluorides are absorbed by humans following inhalation of workplace and ambient air that has been contaminated, ingestion of drinking water and foods and dermal contact. Populations living in areas with high fluoride levels in groundwater may be exposed to higher levels of fluorides in their drinking water or in beverages prepared with the water. Among these populations, outdoor labourers, people living in hot climates, and people with excessive thirst will generally have the greatest daily intake of fluorides because they consume greater amounts of water.

Atmospheric Fate: Both hydrogen fluoride and particulate fluorides will be transported in the atmosphere and deposited on land or water by wet and dry deposition. Non-volatile inorganic fluoride particulates are removed from the atmosphere via condensation or nucleation processes. Fluorides adsorbed on particulate matter in the atmosphere are generally stable and are not readily hydrolyzed, although they may be degraded by radiation if they persist in the atmosphere. Fluorine and the silicon fluorides (fluosilicates, silicofluorides) are hydrolyzed in the atmosphere to form hydrogen fluoride. Hydrogen fluoride may combine with water vapour to produce an aerosol or fog of aqueous hydrofluoric acid. Inorganic fluoride compounds, with the exception of sulfur hexafluoride, are not expected to remain in the troposphere for long periods or to migrate to the stratosphere. Estimates of the residence time of sulfur hexafluoride in the atmosphere range from 500 to several thousand years. Fluoride in aerosols can be transported over large distances by wind or as a result of atmospheric turbulence. Fluorosilicic acid and hydrofluoric acid in high aquatic concentrations such as may be found in industrial waste ponds may volatilize, releasing silicon tetrafluoride and hydrogen fluoride into the atmosphere. Soluble inorganic fluorides may also form aerosols at the air/water interface or vaporize into the atmosphere whereas undissolved species generally undergo sedimentation.

Version No: 2.2

RB-MMA-1

Issue Date: **05/05/2017** 

Print Date: 05/05/2017

Terrestrial Fate: Soils - Atmospheric fluorides may be transported to soils and surface waters through both wet and dry deposition processes where they may form complexes and bind strongly to soil and sediment. Solubilisation of inorganic fluorides from minerals may also be enhanced by the presence of bentonite clays and humic acid. Factors that influence the mobility of inorganic fluorides in soil are pH and the formation of aluminium and calcium complexes. In more acidic soils, concentrations of inorganic fluoride were considerably higher in the deeper horizons. The low affinity of fluorides for organic material results in leaching from the more acidic surface horizon and increased retention by clay minerals and silts in the more alkaline, deeper horizons. The maximum adsorption of fluoride to soil was reported to occur at pH 5.5. In acidic soils with pH below 6, most of the fluoride is in complexes with either aluminium or iron. Fluoride in alkaline soils at pH 6.5 and above is almost completely fixed in soils as calcium fluoride, if sufficient calcium carbonate is available. Fluoride is extremely immobile in soil.

Aquatic Fate: Fresh Water: - In water, the transport and transformation of inorganic fluorides are influenced by pH, water hardness and the presence of ion-exchange materials such as clays. In natural water, fluoride forms strong complexes with aluminium in water, and fluorine chemistry in water is largely regulated by aluminium concentration and pH. Below pH 5, fluoride is almost entirely complexed with aluminium and consequently, the concentration of free F- is low. Once dissolved, inorganic fluorides remain in solution under conditions of low pH and hardness and in the presence of ion-exchange material. Sea Water - Fluoride forms stable complexes with calcium and magnesium, which are present in sea water. Calcium carbonate precipitation dominates the removal of dissolved fluoride from sea water. The residence time for fluoride in ocean sediment is calculated to be 2-3 million years.

Ecotoxicity: Fluorides have been shown to accumulate in animals that consume fluoride-containing foliage. However, accumulation is primarily in skeletal tissue and therefore, it is unlikely that fluoride will biomagnify up the food chain.

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

#### Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

#### Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)

#### **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

- ► Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

#### Otherwise

- ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

# Product / Packaging disposal

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility
  can be identified.
- Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

#### **SECTION 14 TRANSPORT INFORMATION**

## Labels Required



Marine Pollutant

NC

#### Land transport (DOT)

UN number	3264
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Transport hazard class(es)	Class 8 Subrisk Not Applicable
Packing group	
Environmental hazard	Not Applicable
Special precautions for user	Hazard Label 8 Special provisions 386, B2, IB2, T11, TP2, TP27

Version No: 2.2

UN number	3264		
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.		
	ICAO/IATA Class 8		
Transport hazard class(es)	ICAO / IATA Subrisk Not Applicable		
	ERG Code 8L		
Packing group	II		
Environmental hazard	Not Applicable		
	Special provisions	A3A803	
	Cargo Only Packing Instructions	855	
	Cargo Only Maximum Qty / Pack	30 L	
Special precautions for user	Passenger and Cargo Packing Instructions		
	Passenger and Cargo Maximum Qty / Pack		
	Passenger and Cargo Limited Quantity Packing Instructions		
	Passenger and Cargo Limited Maximum Qty / Pack	0.5 L	

### Sea transport (IMDG-Code / GGVSee)

UN number	3264		
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. *		
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable		
Packing group	П		
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number F-A, S-B Special provisions 274 Limited Quantities 1 L		

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Product name	Pollution Category	Ship Type
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Nitric acid (70% and over) Nitric acid (less than 70%)	Y; Y	2 2

## **SECTION 15 REGULATORY INFORMATION**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### HYDROFLUORIC ACID(7664-39-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS International Agency for Research on Cancer (IARC) - Agents Classified by the IARC US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Monographs US - Alaska Limits for Air Contaminants US - Washington Permissible exposure limits of air contaminants US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants (CRELs) US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, US - California Permissible Exposure Limits for Chemical Contaminants Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift US ACGIH Threshold Limit Values (TLV) US - Hawaii Air Contaminant Limits US ACGIH Threshold Limit Values (TLV) - Carcinogens US - Idaho - Acceptable Maximum Peak Concentrations US - Idaho - Limits for Air Contaminants US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs) US - Massachusetts - Right To Know Listed Chemicals US Clean Air Act - Hazardous Air Pollutants US - Michigan Exposure Limits for Air Contaminants US CWA (Clean Water Act) - List of Hazardous Substances US - Minnesota Permissible Exposure Limits (PELs) US EPCRA Section 313 Chemical List US - Oregon Permissible Exposure Limits (Z-1) US NIOSH Recommended Exposure Limits (RELs) US - Oregon Permissible Exposure Limits (Z-2) US OSHA Permissible Exposure Levels (PELs) - Table Z1 US - Pennsylvania - Hazardous Substance List US OSHA Permissible Exposure Levels (PELs) - Table Z2 US - Rhode Island Hazardous Substance List US SARA Section 302 Extremely Hazardous Substances US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### NITRIC ACID(7697-37-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

Chemwatch: 9-394570 Page 11 of 12
Catalogue number: RB-MMA-1

RB-MMA-1

Version No: 2.2

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
Passenger and Cargo Aircraft	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Alaska Limits for Air Contaminants	Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Massachusetts - Right To Know Listed Chemicals	US CWA (Clean Water Act) - List of Hazardous Substances
US - Michigan Exposure Limits for Air Contaminants	US EPCRA Section 313 Chemical List
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	US SARA Section 302 Extremely Hazardous Substances
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

## Federal Regulations

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SECTION 311/312 HAZARD CATEGORIES

US - Pennsylvania - Hazardous Substance List

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

### US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Hydrofluoric acid	100	45.4
Nitric acid	1000	454

## State Regulations

#### US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (water; hydrofluoric acid; nitric acid)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water; hydrofluoric acid; nitric acid)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Υ
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## **SECTION 16 OTHER INFORMATION**

## Other information

#### Ingredients with multiple cas numbers

Name	CAS No
hydrofluoric acid	7664-39-3, 790596-14-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

Issue Date: 05/05/2017

Print Date: 05/05/2017

Chemwatch: 9-394570 Catalogue number: RB-MMA-1

Page **12** of **12** RB-MMA-1 Issue Date: 05/05/2017 Print Date: 05/05/2017

Version No: 2.2

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。
IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.