

## Safety Data Sheet

### Section 1. Product and Company Identification

Product Identification: 1000 µg/mL Arsenic<sup>+3</sup> in 2% HCl  
SDS Number: 10003-6  
Recommended Use: For Laboratory Use.  
Company Identification: High-Purity Standards  
P.O. Box 41727  
Charleston, SC 29423  
Telephone: (843) 767-7900  
FAX: (843) 767-7906

In case of emergency call INFOTRAC: 800-535-5053

### Section 2. Hazard Identification

**Classification:**

**Classification:**

Skin Corrosion/Irritation, Category 1

Serious Eye Damage/ Eye Irritation, Category 1

Carcinogenicity, Category 1A

**Labeling:**



**Symbol:**

**Signal Word:** Danger.

**Hazard Statement:** Causes severe skin burns and eye damage. May cause cancer.

**Precautionary Statement:** Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

### Section 3. Composition

Component	CAS/EINECS Registry #	Percent Concentration
Arsenic (III) Oxide (As <sub>2</sub> O <sub>3</sub> )	1327-53-3/215-481-4	0.1 (as As <sup>+3</sup> )
Hydrochloric Acid	7647-01-0/231-595-7	2
Water, deionized	7732-18-5/ 231-791-2	Balance

### Section 4. First Aid Measures

**IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Call a physician if irritation develops. Harmful if absorbed through the skin.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Call a physician. May cause nausea, vomiting, and diarrhea.

**IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing. May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membrane and upper respiratory tract.

<b>Safety Data Sheet No. 10003-6</b>	<b>Date: March 6, 2014</b>	
<b>1000 µg/mL Arsenic<sup>+3</sup> in 2% HCl</b>	<b>Revision: 001</b>	<b>Page 2 of 4</b>

**Target Organs:** Eyes, skin.

#### Section 5. Fire Fighting Measures

Fire & Explosion hazards: Hydrochloric acid is a negligible fire hazard when exposed to heat and/or flames. Hydrochloric acid may react with the evolution of heat on contact with water; the acid may release toxic, corrosive, flammable, or explosive gases.

Extinguishing Media: Use regular dry chemical, carbon dioxide, water, or regular foam.

Specific Methods: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

#### Section 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Do not allow to enter drainage systems or water ways. Dike area and dilute spill with water and neutralize with soda ash, limestone, etc. Place the neutralized material into containers suitable for eventual disposal, reclamation, or destruction. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation. Always dispose of in accordance with local regulations.

#### Section 7. Handling and Storage

Store in a cool, dry, ventilated storage area with acid resistant floors and good drainage. Keep out of direct sunlight and away from heat, water, and incompatible materials. When diluting, the acid should always be added slowly to water and in small amounts. Refer to Section 8 for personal handling instructions.

#### Section 8. Exposure Controls and Personal Protection

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep any buildup of airborne contaminants below their respective threshold limit value. Ensure the availability of eyewash stations and safety showers.

Personal Protection: Wear proper gloves, safety glasses with side shields, lab coat/apron.

##### Exposure Limits:

Component	ACGIH TLV	OSHA PEL
Arsenic Oxide	0.01 mg/m <sup>3</sup>	10 µg/ m <sup>3</sup>
Hydrochloric Acid	C 2ppm	C 5ppm C 7 mg/m <sup>3</sup>

#### Section 9. Physical and Chemical Properties

Physical State: Liquid

Color: Clear, colorless

Odor: Odorless to a faint pungent odor

Odor threshold: None

pH: <2

Melting point: N/A

Freezing Point: N/A

Boiling Point: Approximately 100°C

Flash point: N/A

Evaporation rate: N/A

<b>Safety Data Sheet No. 10003-6</b>	<b>Date: March 6, 2014</b>	
<b>1000 µg/mL Arsenic<sup>+3</sup> in 2% HCl</b>	<b>Revision: 001</b>	<b>Page 3 of 4</b>

Flammability: N/A  
 Explosion limits: N/A  
 Vapor Pressure (mm): N/A  
 Vapor Density (air+1): N/A  
 Relative density: (H<sub>2</sub>O = 1): Approximately 1.0  
 Solubility in H<sub>2</sub>O: Complete  
 Auto ignition temperature: N/A  
 Decomposition temperature: N/A  
 Molecular Weight: 74.92 (As)

#### Section 10. Stability and Reactivity

Stability Indicator: YES  
 Conditions to Avoid: Metals, hydroxides, carbonates, cyanides  
 Incompatibles: Strong oxidizing agents  
 Hazardous Decomposition Products: When heated to decomposition, emits toxic hydrogen chloride fumes and will react with water or steam to produce heat and toxic and corrosive fumes.  
 Thermal oxidative decomposition produces toxic chlorine fumes and explosive hydrogen gas.  
 Hazardous Polymerization: Will not occur.

#### Section 11. Toxicological Information

May affect skin, mucous membranes and eyes. Swallowing may lead to a negative effect on mouth and throat and to the risk of perforation or the corrosion of esophagus and stomach.  
 Arsenic is considered a carcinogen.

##### RTECS#

HCl: MW4025000      As<sub>2</sub>O<sub>3</sub>: CG3325000  
 Oral, rabbit: (Hydrochloric Acid) LD<sub>50</sub> = 900 mg/kg  
 LD50, Oral, Rat: (Arsenic Oxide) 14.6mg/kg.

#### Section 12. Ecological Information

Ecotoxicological information: Do not allow material to reach ground water, water bodies, or sewage system.

#### Section 13. Disposal Considerations

General: Follow Federal, state and local regulations for waste.

#### Section 14. Transport Information

D.O.T. Classification: Hazardous by IATA and 49CFR regulations (based on concentration of acid).  
 D.O.T. Shipping Name: Corrosive liquid, Acidic, Inorganic, n.o.s. (Hydrochloric Acid Solution)  
 D.O.T. Hazard Class: 8  
 U.N./N.A. Number: 3264  
 Packing Group: II  
 D.O.T. Label: Corrosive (8)

<b>Safety Data Sheet No. 10003-6</b>	<b>Date: March 6, 2014</b>	
<b>1000 µg/mL Arsenic<sup>+3</sup> in 2% HCl</b>	<b>Revision: 001</b>	<b>Page 4 of 4</b>

#### Section 15. Regulations (Not meant to be all inclusive-selected regulation listed)

TSCA Status: Components of this solution are listed on the TSCA Inventory.

RCRA Status: No

SARA: Section 302 (Extremely Hazardous Substances) No

Section 313 No

Risk Phrases: R20/21/22 Harmful by inhalation, skin contact, or if swallowed.

Safety Phrases: S36/37/39 Wear suitable protective clothing, gloves and eye/face protection

WHMIS Information (Canada): E: Corrosive

D-1A Very toxic material causing immediate and serious toxic effects.

D-2A: Very toxic material causing other toxic effects

#### Section 16. Other Information

HPS products are intended for laboratory use only. All products should be handled and used by trained professional personnel only. The responsibility for the safe handling and use of these products rests solely with the buyer and/or user. The SDS was prepared carefully and represents the best data currently available to us; however, HPS does not certify the data on the SDS.

Certified values for this material are given only on the Certificate of Analysis.

Theodore C. Rains, Ph.D.