

# 10M11-2 Cesium (10,000µg/mL in 1% HCl)

### **High-Purity Standards**

Catalogue number: 10M11-2

Version No: 2.2

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

#### Chemwatch Hazard Alert Code: 3

Issue Date: **09/02/2016**Print Date: **09/02/2016**S.GHS.USA.EN

#### **SECTION 1 IDENTIFICATION**

#### **Product Identifier**

Product name	10M11-2 Cesium (10,000µg/mL in 1% HCl)
Synonyms	10,000μg/mL Cesium in 1% HCl
Proper shipping name	Hydrochloric acid (contains hydrochloric acid)
Other means of identification	10M11-2

#### Recommended use of the chemical and restrictions on use

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

#### **Emergency phone number**

• • • • • • • • • • • • • • • • • • • •	
Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

#### **SECTION 2 HAZARD(S) IDENTIFICATION**

# Classification of the substance or mixture

assification Germ cell mutagenicity Category 2, Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1

# Label elements

**GHS** label elements





SIGNAL WORD DANGER

# Hazard statement(s)

H341	Suspected of causing genetic defects.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Version No: 2.2 10M11-2 Cesium (10,000µg/mL in 1% HCI)

Not Applicable

#### Precautionary statement(s) Prevention

P201 Obtain special instructions before use.

#### Precautionary statement(s) Response

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

### Precautionary statement(s) Storage

P405

Store locked up.

#### Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
534-17-8	1 (as Ce)	caesium carbonate
7647-01-0	1	hydrochloric acid
7732-18-5	balance	water

# **SECTION 4 FIRST-AID MEASURES**

### Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Immediately hold eyelids apart and flush the eye continuously with running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.  Transport to hospital or doctor without delay.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  Immediately flush body and clothes with large amounts of water, using safety shower if available.  Quickly remove all contaminated clothing, including footwear.  Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.  Transport to hospital, or doctor.
Inhalation	<ul> <li>If furnes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> <li>Inhalation of vapours or aerosols (mists, furnes) may cause lung oedema.</li> <li>Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</li> <li>As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.</li> <li>Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</li> <li>This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)</li> </ul>
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

# Most important symptoms and effects, both acute and delayed

See Section 11

# Indication of any immediate medical attention and special treatment needed

for corrosives:

## BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema .

Issue Date: 09/02/2016

Print Date: 09/02/2016

Catalogue number: 10M11-2 Page 3 of 9

Version No: 2.2

### 10M11-2 Cesium (10,000µg/mL in 1% HCI)

Issue Date: 09/02/2016 Print Date: 09/02/2016

- Monitor and treat, where necessary, for shock.
- Anticipate seizures
- Where eyes have been exposed, flush immediately with water and continue to irrigate with normal saline during transport to hospital.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not droot
- Skin burns should be covered with dry, sterile bandages, following decontamination.
- ▶ DO NOT attempt neutralisation as exothermic reaction may occur.

# ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Figure 1. Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ► Consider endoscopy to evaluate oral injury.
- Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

#### **SECTION 5 FIRE-FIGHTING MEASURES**

#### Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

# Special protective equipment and precautions for fire-fighters

Fire Fighting	
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>May emit corrosive fumes.</li> </ul>

# **SECTION 6 ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</li> <li>Clean up all spills immediately.</li> </ul>
Major Spills	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 HANDLING AND STORAGE**

Treductions for sure nationing		
Safe handling	Avoid all personal contact, including inhalation.     DO NOT allow clothing wet with material to stay in contact with skin	
Other information	► Store in original containers.	

Conditions for safe storage, including any incompatibilities				
Suitable container	Lined metal can, lined metal pail/ can.  For low viscosity materials  Drums and jerricans must be of the non-removable head type.			
Storage incompatibility	Hydrogen chloride:  ► reacts strongly with strong oxidisers (releasing chlorine gas), acetic anhydride, caesium cyanotridecahydrodecaborate(2-), ethylidene difluoride, hexalithium disilicide, metal acetylide, sodium, silicon dioxide, tetraselenium tetranitride, and many organic materials  ► is incompatible with alkaline materials, acetic anhydride, acetylides, aliphatic amines, alkanolamines, alkylene oxides, aluminium, aluminium-titanium alloys, aromatic amines, amines, amines, amines, amines, carbonates, cyanides, chlorosulfonic acid, ethylenediamine, ethyleneimine, epichlorohydrin, formaldehyde, isocyanates, metals, metal oxides, metal hydroxides, metal acetylides,			

Version No: 2.2

# 10M11-2 Cesium (10,000μg/mL in 1% HCI)

Issue Date: **09/02/2016**Print Date: **09/02/2016** 

- metal carbides, oleum, organic anhydrides, potassium permanganate, perchloric acid, phosphides, 3-propiolactone, silicides, sulfides, sulfites, sulfuric acid, uranium phosphide, vinyl acetate, vinylidene fluoride
- ▶ attacks most metals forming flammable hydrogen gas, and some plastics, rubbers and coatings
- reacts with zinc, brass, galvanised iron, aluminium, copper and copper alloys
- ▶ Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.
- Avoid strong bases.

# **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

### **Control parameters**

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available
US ACGIH Threshold Limit Values (TLV)	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	2 ppm	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	hydrochloric acid	Anhydrous hydrogen chloride; Aqueous hydrogen chloride (i.e., Hydrochloric acid, Muriatic acid) [Note: Often used in an aqueous solution.]	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available

### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
caesium carbonate	Cesium carbonate	7 mg/m3	77 mg/m3	460 mg/m3
hydrochloric acid	Hydrogen chloride; (Hydrochloric acid)	Not Available	Not Available	Not Available
hydrochloric acid	Deuterochloric acid; (Deuterium chloride)	1.8 ppm	22 ppm	100 ppm

Ingredient	Original IDLH	Revised IDLH
caesium carbonate	Not Available	Not Available
hydrochloric acid	100 ppm	50 ppm
water	Not Available	Not Available

# **Exposure controls**

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	<ul> <li>Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Elbow length PVC gloves</li> <li>When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.</li> <li>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.</li> </ul>
Body protection	See Other protection below
Other protection	▶ Overalls.
Thermal hazards	Not Available

### Respiratory protection

Type B-P Filter of sufficient capacity.

76b-p()

# **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

# Information on basic physical and chemical properties

Appearance	colorless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available

10M11-2 Cesium (10,000µg/mL in 1% HCI)

Issue Date: **09/02/2016**Print Date: **09/02/2016** 

pH (as supplied)	<2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	► Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 TOXICOLOGICAL INFORMATION**

TOXICITY

Oral (rat) LD50: >90000 mg/kg<sup>[2]</sup>

Information	on	toxicologica	Leffects
minomination	<b>U</b> 11	LUXICUIUGICA	i ellecto

Inhaled	The material can cause respiratory irritation in some persons.  The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation".  Hydrogen chloride (HCI) vapour or fumes present a hazard from a single acute exposure.			
Ingestion	The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion.  The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion".			
Skin Contact	The material can produce severe chemical burns following direct contact with the skin.  Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.			
Eye	The material can produce severe chemical burns to the eye following direct contact.  If applied to the eyes, this material causes severe eye damage.			
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw.  Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.  Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure.  Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.  Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  Chronic minor exposure to hydrogen chloride (HCl) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and gums; and ulceration of the nasal mucous membranes.			
10M11-2 Cesium	TOXICITY	IRRITATI	ON	
(10,000μg/mL in 1% HCl)	Not Available Not Available			
caesium carbonate	TOXICITY  Oral (rat) LD50: 2333 mg/kg <sup>[2]</sup>			IRRITATION Nil reported
hydrochloric acid	TOXICITY  Inhalation (rat) LC50: 3124 ppm/1hr <sup>[2]</sup>		IRRITATION Eye (rabbit): 5m	g/30s - mild
,	Oral (rat) LD50: 900 mg/kg <sup>[2]</sup>		, ,	-

IRRITATION

Not Available

Catalogue number: 10M11-2 Page 6 of 9

for acid mists, aerosols, vapours

Version No: 2.2

# 10M11-2 Cesium (10,000µg/mL in 1% HCI)

Data from assays for genotoxic activity in vitro suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5.

Issue Date: 09/02/2016 Print Date: 09/02/2016

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

HYDROCHLORIC ACID

The material may be irritating to the eye, with prolonged contact causing inflammation. The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

10M11-2 Cesium (10,000 $\mu$ g/mL in 1% HCl) & **CAESIUM CARBONATE &** HYDROCHLORIC ACID

Asthma-like symptoms may continue for months or even years after exposure to the material ceases.

HYDROCHLORIC ACID & WATER

No significant acute toxicological data identified in literature search.

	<u> </u>		
Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	✓	Reproductivity	0
Serious Eye Damage/Irritation	<b>*</b>	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	✓	Aspiration Hazard	0

Legend:

X − Data available but does not fill the criteria for classification
 ✓ − Data required to make classification available

O – Data Not Available to make classification

#### **SECTION 12 ECOLOGICAL INFORMATION**

#### **Toxicity**

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
caesium carbonate	LC50	96	Fish	658.217mg/L	3
caesium carbonate	EC50	96	Algae or other aquatic plants	4630.937mg/L	3
caesium carbonate	EC50	384	Crustacea	149.200mg/L	3
hydrochloric acid	LC50	96	Fish	70.057mg/L	3
hydrochloric acid	EC50	96	Algae or other aquatic plants	344.947mg/L	3
hydrochloric acid	EC50	9.33	Fish	0.014000mg/L	4
hydrochloric acid	NOEC	0.08	Fish	10mg/L	4
water	LC50	96	Fish	897.520mg/L	3
water	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
water	EC50	384	Crustacea	199.179mg/L	3
Legend:	Aquatic Toxicity Data (E	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data			

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
caesium carbonate	LOW	LOW
hydrochloric acid	LOW	LOW
water	LOW	LOW

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
caesium carbonate	LOW (LogKOW = -0.4605)
hydrochloric acid	LOW (LogKOW = 0.5392)
water	LOW (LogKOW = -1.38)

# Mobility in soil

Ingredient	Mobility
caesium carbonate	HIGH (KOC = 1)
hydrochloric acid	LOW (KOC = 14.3)
water	LOW (KOC = 14.3)

10M11-2 Cesium (10,000µg/mL in 1% HCI)

Issue Date: 09/02/2016 Print Date: 09/02/2016

### **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory.

   DO NOT allow wash water from cleaning or process equipment to enter drains.
- ► Recycle wherever possible.

# **SECTION 14 TRANSPORT INFORMATION**

# **Labels Required**



Marine Pollutant

### Land transport (DOT)

UN number	1789
UN proper shipping name	Hydrochloric acid (contains hydrochloric acid)
Transport hazard class(es)	Class 8 Subrisk Not Applicable
Packing group	П
Environmental hazard	Not Applicable
Special precautions for user	Hazard Label 8 Special provisions A3, A6, B3, B15, IB2, N41, T8, TP2

### Air transport (ICAO-IATA / DGR)

# Sea transport (IMDG-Code / GGVSee)

UN number	1789
UN proper shipping name	HYDROCHLORIC ACID (contains hydrochloric acid)
Transport hazard class(es)	IMDG Class     8       IMDG Subrisk     Not Applicable
Packing group	
Environmental hazard	Not Applicable
Special precautions for user	EMS Number F-A, S-B Special provisions Not Applicable

Version No: 2.2 10M11-2 Cesium (10,000µg/mL in 1% HCI)

Limited Quantities 1 L

# Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### **SECTION 15 REGULATORY INFORMATION**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

### CAESIUM CARBONATE(534-17-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### HYDROCHLORIC ACID(7647-01-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs		
US - Alaska Limits for Air Contaminants		
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)		
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)		
US - California Permissible Exposure Limits for Chemical Contaminants		
US - Hawaii Air Contaminant Limits		
US - Idaho - Limits for Air Contaminants		
US - Michigan Exposure Limits for Air Contaminants		
US - Minnesota Permissible Exposure Limits (PELs)		
US - Oregon Permissible Exposure Limits (Z-1)		
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants		
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants		
WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS		

- US Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
- US Washington Permissible exposure limits of air contaminants
- US Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values

Issue Date: 09/02/2016

Print Date: 09/02/2016

- US Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
- US ACGIH Threshold Limit Values (TLV)
- US ACGIH Threshold Limit Values (TLV) Carcinogens
- US EPCRA Section 313 Chemical List
- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Permissible Exposure Levels (PELs) Table Z1
- US SARA Section 302 Extremely Hazardous Substances
- US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory

# US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

# Federal Regulations Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	Yes
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

# US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Hydrochloric acid	5000	2270

### State Regulations

### US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (hydrochloric acid; water; caesium carbonate)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water)
Korea - KECI	Υ
New Zealand - NZIoC	Y
Philippines - PICCS	Υ
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

# **SECTION 16 OTHER INFORMATION**

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using

Catalogue number: 10M11-2 Page 9 of 9 Issue Date: 09/02/2016 Print Date: 09/02/2016

Version No: 2.2 10M11-2 Cesium (10,000µg/mL in 1% HCI)

available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

#### **Definitions and abbreviations**

PC – TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.