

10M27-2 Lanthanum (10,000µg/mL in 2% HCl)

High-Purity Standards

Catalogue number: 10M27-2

Version No: 2.2

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: **09/02/2016** Print Date: **09/02/2016** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	10M27-2 Lanthanum (10,000µg/mL in 2% HCI)
Synonyms	10,000μg/mL Lanthanum in 2% HCl
Proper shipping name	Hydrochloric acid (contains hydrochloric acid)
Other means of identification	10M27-2

Recommended use of the chemical and restrictions on use

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

Assification Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1

Label elements

GHS label elements



SIGNAL WORD DANGER

Hazard statement(s)

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Hazard(s) not otherwise specified

Not Applicable

Version No: 2.2

Precautionary statement(s) Prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

Precautionary statement(s) Response

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Precautionary statement(s) Storage

Store locked up. P405

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1312-81-8	1 (as La)	lanthanum oxide
7647-01-0	2	hydrochloric acid
7732-18-5	balance	water

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Description of mist aid me	
Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- ▶ Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- > Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues. INGESTION:
- ▶ Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.

Catalogue number: 10M27-2 Page 3 of 9 Issue Date: 09/02/2016 Version No: 2.2 Print Date: 09/02/2016

10M27-2 Lanthanum (10,000µg/mL in 2% HCl)

- Charcoal has no place in acid management.
- ▶ Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any es. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury
- ▶ Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting	
Fire/Explosion Hazard	

▶ Non combustible.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor	Spills

- Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.
- Clean up all spills immediately.

Major Spills

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- Avoid all personal contact, including inhalation.
- ▶ DO NOT allow clothing wet with material to stay in contact with skin

Other information

Store in original containers

Conditions for safe storage, including any incompatibilities

Suitable container

- ► DO NOT use aluminium or galvanised containers
- Check regularly for spills and leaks
- Lined metal can, lined metal pail/ can.

For low viscosity materials

- ▶ Drums and jerricans must be of the non-removable head type.
- - Inorganic acids are generally soluble in water with the release of hydrogen ions.

Hydrogen chloride: reacts strongly with strong oxidisers (releasing chlorine gas), acetic anhydride, caesium cyanotridecahydrodecaborate(2-), ethylidene difluoride, hexalithium disilicide, metal acetylide, sodium, silicon dioxide, tetraselenium tetranitride, and many organic materials

Storage incompatibility

is incompatible with alkaline materials, acetic anhydride, acetylides, aliphatic amines, alkylene oxides, aluminium, aluminium-titanium alloys, aromatic amines, amines, amides, 2-aminoethanol, ammonia, ammonium hydroxide, borides, calcium phosphide, carbides, carbonates, cyanides chlorosulfonic acid, ethylenediamine, ethyleneimine, epichlorohydrin, formaldehyde, isocyanates, metal oxides, metal hydroxides, metal acetylides,

metal carbides, oleum, organic anhydrides, potassium permanganate, perchloric acid, phosphides, 3-propiolactone, silicides, sulfides, sulfitres, sulfuric acid,

- uranium phosphide, vinyl acetate, vinylidene fluoride attacks most metals forming flammable hydrogen gas, and some plastics, rubbers and coatings
- reacts with zinc, brass, galvanised iron, aluminium, copper and copper alloys
- ▶ Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Version No: 2.2

10M27-2 Lanthanum (10,000 μ g/mL in 2% HCI)

Issue Date: **09/02/2016**Print Date: **09/02/2016**

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available
US ACGIH Threshold Limit Values (TLV)	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	2 ppm	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	hydrochloric acid	Anhydrous hydrogen chloride; Aqueous hydrogen chloride (i.e., Hydrochloric acid, Muriatic acid) [Note: Often used in an aqueous solution.]	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
lanthanum oxide	Lanthanum oxide	4 mg/m3	44 mg/m3	270 mg/m3
hydrochloric acid	Hydrogen chloride; (Hydrochloric acid)	Not Available	Not Available	Not Available
hydrochloric acid	Deuterochloric acid; (Deuterium chloride)	1.8 ppm	22 ppm	100 ppm

Ingredient	Original IDLH	Revised IDLH
lanthanum oxide	Not Available	Not Available
hydrochloric acid	100 ppm	50 ppm
water	Not Available	Not Available

Exposure controls

• • • • • • • • • • • • • • • • • • • •	
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	 Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.
Skin protection	See Hand protection below
Hands/feet protection	 Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	See Other protection below
Other protection	► Overalls.
Thermal hazards	Not Available

Respiratory protection

Type B-P Filter of sufficient capacity.

76b-p()

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	colorless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available

10M27-2 Lanthanum (10,000 μ g/mL in 2% HCl)

Issue Date: 09/02/2016 Print Date: 09/02/2016

Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	► Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information	on	toxico	logical	ettects

Inhaled	The material can cause respiratory irritation in some persons. Corrosive acids can cause irritation of the respiratory tract, with coughing The material has NOT been classified by EC Directives or other classified Exposure to vapours of some rare earth salts can cause sensitivity to hear Hydrogen chloride (HCI) vapour or fumes present a hazard from a single	cation systems as at, itching, and inc	"harmful by inhalation". reased sensitivity of sme	
Ingestion	Ingestion of acidic corrosives may produce burns around and in the mout The material has NOT been classified by EC Directives or other classified	,		
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.			
Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivi	ity to light and bur	ns.	
Chronic	Repeated or prolonged exposure to acids may result in the erosion of tec Long-term exposure to respiratory irritants may result in disease of the a Substance accumulation, in the human body, may occur and may cause s There has been some concern that this material can cause cancer or mul Chronic minor exposure to hydrogen chloride (HCI) vapour or fume may ulceration of the nasal mucous membranes.	irways involving d some concern follo tations but there is	difficult breathing and rela cowing repeated or long-to s not enough data to mal	ated systemic problems. erm occupational exposure. ke an assessment.
10M27-2 Lanthanum	TOXICITY	IRRITAT	ION	
(10,000μg/mL in 2% HCI)	Not Available	Not Avail	lable	
	TOXICITY			IRRITATION
lanthanum oxide	Dermal (rabbit) LD50: >1087 mg/kg ^[1]			Not Available
	Oral (rat) LD50: >8500 mg ^[2]			
	TOXICITY		IRRITATION	
hudeshieds said	Inhalation (rat) LC50: 3124 ppm/1hr ^[2]		Eye (rabbit): 5mg/30s	s - mild
hydrochloric acid	Oral (rat) LD50: 900 mg/kg ^[2]		Lyc (rabbit). Smg/303	3 TIME
	TOXICITY		IF	RRITATION
	TOXICITY			
water	Oral (rat) LD50: >90000 mg/kg ^[2]		N	lot Available

LANTHANUM OXIDE	Lanthanide poisoning causes immediate defaecation, writhing, inco-ordination, laboured breathing, and inactivity.
HYDROCHLORIC ACID	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans.
10M27-2 Lanthanum (10,000µg/mL in 2% HCI) & LANTHANUM OXIDE & HYDROCHLORIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ceases.
10M27-2 Lanthanum (10,000μg/mL in 2% HCl) & HYDROCHLORIC ACID	for acid mists, aerosols, vapours Data from assays for genotoxic activity in vitro suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5.

Catalogue number: 10M27-2 Page 6 of 9

Version No: 2.2

10M27-2 Lanthanum (10,000µg/mL in 2% HCl)

Issue Date: 09/02/2016 Print Date: 09/02/2016

LANTHANUM OXIDE & HYDROCHLORIC ACID	The material may be irritating to the eye, with prolonged contact causing inflammation.		
LANTHANUM OXIDE & HYDROCHLORIC ACID & WATER	No significant acute toxicological data identified in literature search.		
Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	✓	Reproductivity	0
Serious Eye Damage/Irritation	~	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

X − Data available but does not fill the criteria for classification
✓ − Data required to make classification available

O - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
lanthanum oxide	EC50	72	Algae or other aquatic plants	13mg/L	2
lanthanum oxide	EC50	72	Algae or other aquatic plants	15.2mg/L	2
lanthanum oxide	NOEC	196	Algae or other aquatic plants	>=0.00001mg/L	2
hydrochloric acid	LC50	96	Fish	70.057mg/L	3
hydrochloric acid	EC50	96	Algae or other aquatic plants	344.947mg/L	3
hydrochloric acid	EC50	9.33	Fish	0.014000mg/L	4
hydrochloric acid	NOEC	0.08	Fish	10mg/L	4
water	LC50	96	Fish	897.520mg/L	3
water	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
water	EC50	384	Crustacea	199.179mg/L	3
Legend:	Aquatic Toxicity D	, ,	HA Registered Substances - Ecotoxicologica database - Aquatic Toxicity Data 5. ECETOC ation Data 8. Vendor Data	, ,	

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse.

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
hydrochloric acid	LOW	LOW
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
hydrochloric acid	LOW (LogKOW = 0.5392)
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
hydrochloric acid	LOW (KOC = 14.3)
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal Legislation addressing waste disposal requirements may differ by country, state and/ or territory.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ► Recycle wherever possible.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Catalogue number: **10M27-2**Version No: **2.2**

10M27-2 Lanthanum (10,000µg/mL in 2% HCl)

Issue Date: **09/02/2016** Print Date: **09/02/2016**



Land transport (DOT)

UN number	1789		
UN proper shipping name	Hydrochloric acid (contains hydrochloric acid)		
Transport hazard class(es)	Class 8 Subrisk Not Applicable		
Packing group			
Environmental hazard	Not Applicable		
Special precautions for user	Hazard Label 8 Special provisions A3, A6, B3, B15, IB2, N41, T8, TP2		

Air transport (ICAO-IATA / DGR)

UN number	1789		
UN proper shipping name	Hydrochloric acid (contains hydrochloric acid)		
	ICAO/IATA Class	8	
Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable	
	ERG Code	8L	
Packing group			
Environmental hazard	Not Applicable		
Special precautions for user	Special provisions		A3A803
	Cargo Only Packing Instructions		855
	Cargo Only Maximum Qty / Pack		30 L
	Passenger and Cargo Packing Instructions		851
	Passenger and Cargo Maximum Qty / Pack		1 L
	Passenger and Cargo Limited Quantity Packing Instructions		Y840
	Passenger and Cargo Limited Maximum Qty / Pack		0.5 L

Sea transport (IMDG-Code / GGVSee)

UN number	1789		
UN proper shipping name	HYDROCHLORIC ACID (contains hydrochloric acid)		
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable		
Packing group			
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number F-A, S-B Special provisions Not Applicable Limited Quantities 1 L		

Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Product name	Pollution Category	Ship Type
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Hydrochloric acid	Z	3

SECTION 15 REGULATORY INFORMATION

Version No: 2.2

10M27-2 Lanthanum (10,000µg/mL in 2% HCl)

Issue Date: **09/02/2016**Print Date: **09/02/2016**

LANTHANUM OXIDE(1312-81-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

HYDROCHLORIC ACID(7647-01-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

TI DROOME AGE (1947 OF O) TO THE TO ELEVATION TELEVA
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
US - Alaska Limits for Air Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)
US - California Permissible Exposure Limits for Chemical Contaminants
US - Hawaii Air Contaminant Limits
US - Idaho - Limits for Air Contaminants
US - Michigan Exposure Limits for Air Contaminants
US - Minnesota Permissible Exposure Limits (PELs)
US - Oregon Permissible Exposure Limits (Z-1)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

- US Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
- US Washington Permissible exposure limits of air contaminants
- US Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
- $\label{thm:continuous} \textbf{US-Wyoming Toxic} \ \textbf{and Hazardous Substances Table Z1 Limits for Air Contaminants}$
- US ACGIH Threshold Limit Values (TLV)
 US ACGIH Threshold Limit Values (TLV) Carcinogens
- US EPCRA Section 313 Chemical List
- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Permissible Exposure Levels (PELs) Table Z1
- US SARA Section 302 Extremely Hazardous Substances
- US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Hydrochloric acid	5000	2270

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status	
Australia - AICS	Y	
Canada - DSL	Y	
Canada - NDSL	N (hydrochloric acid; water; lanthanum oxide)	
China - IECSC	Y	
Europe - EINEC / ELINCS / NLP	Y	
Japan - ENCS	N (water)	
Korea - KECI	Υ	
New Zealand - NZIoC	Y	
Philippines - PICCS	Υ	
USA - TSCA	Y	
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

 ${\sf PC-TWA: Permissible \ Concentration-Time \ Weighted \ Average}$

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$

IDLH: Immediately Dangerous to Life or Health Concentrations

Catalogue number: 10M27-2 Page 9 of 9 Issue Date: 09/02/2016 Version No: 2.2 Print Date: 09/02/2016

10M27-2 Lanthanum (10,000 μ g/mL in 2% HCI)

OSF: Odour Safety Factor

NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.