

10M29-2 Lithium (10,000µg/mL in 1% HCl)

High-Purity Standards

Catalogue number: 10M29-2

Version No: 2.2

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: **09/02/2016**Print Date: **09/02/2016**S GHS USA EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	10M29-2 Lithium (10,000μg/mL in 1% HCl)
Synonyms	10,000μg/mL Lithium in 1% HCl
Proper shipping name	Hydrochloric acid (contains hydrochloric acid)
Other means of identification	10M29-2

Recommended use of the chemical and restrictions on use

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

assification Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1

Label elements

GHS label elements



SIGNAL WORD DANGER

Hazard statement(s)

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Hazard(s) not otherwise specified

Not Applicable

Catalogue number: 10M29-2 Page 2 of 9 Issue Date: 09/02/2016 Print Date: 09/02/2016

10M29-2 Lithium (10,000µg/mL in 1% HCI)

Version No: 2.2

Precautionary statement(s) Prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

Precautionary statement(s) Response

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
554-13-2	1 (as Li)	lithium carbonate
7647-01-0	1	hydrochloric acid
7732-18-5	balance	water

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

for corrosives:

BASIC TREATMENT

▶ Establish a patent airway with suction where necessary.

- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ► Monitor and treat, where necessary, for pulmonary oedema .
- ▶ Monitor and treat, where necessary, for shock

Catalogue number: 10M29-2 Page 3 of 9

Version No: 2.2

10M29-2 Lithium (10,000µg/mL in 1% HCI)

Issue Date: **09/02/2016**Print Date: **09/02/2016**

- Anticipate seizures.
- ▶ Where eyes have been exposed, flush immediately with water and continue to irrigate with normal saline during transport to hospital.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool
- ▶ Skin burns should be covered with dry, sterile bandages, following decontamination.
- DO NOT attempt neutralisation as exothermic reaction may occur.

.....

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- · Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- · Consider endoscopy to evaluate oral injury.
- Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting

Fire/Explosion Hazard

→ Non combustible.

May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.

Clean up all spills immediately.

Major Spills

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

Avoid all personal contact, including inhalation.

DO NOT allow clothing wet with material to stay in contact with skin

Other information

Note: Avoid all personal contact, including inhalation.

DO NOT allow clothing wet with material to stay in contact with skin

Store in original containers.

Conditions for safe storage, including any incompatibilities

Storage incompatibility

is incompatible with alkaline materials, acetic anhydride, acetylides, aliphatic amines, alkanolamines, alkylene oxides, aluminium, aluminium-titanium alloys, aromatic amines, amines, amines, amines, 2-aminoethanol, ammonia, ammonium hydroxide, borides, calcium phosphide, carbides, carbonates, cyanides, chlorosulfonic acid, ethylenediamine, ethyleneimine, epichlorohydrin, formaldehyde, isocyanates, metals, metal oxides, metal hydroxides, metal acetylides, metal carbides, oleum, organic anhydrides, potassium permanganate, perchloric acid, phosphides, 3-propiolactone, silicides, sulfides, sulfites, sulfuric acid,

Version No: 2.2

10M29-2 Lithium (10,000µg/mL in 1% HCI)

Issue Date: 09/02/2016 Print Date: 09/02/2016

- ▶ uranium phosphide, vinyl acetate, vinylidene fluoride
- attacks most metals forming flammable hydrogen gas, and some plastics, rubbers and coatings
 reacts with zinc, brass, galvanised iron, aluminium, copper and copper alloys
- ▶ Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.
- Avoid strong bases.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available
US ACGIH Threshold Limit Values (TLV)	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	2 ppm	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	hydrochloric acid	Anhydrous hydrogen chloride; Aqueous hydrogen chloride (i.e., Hydrochloric acid, Muriatic acid) [Note: Often used in an aqueous solution.]	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
lithium carbonate	Lithium carbonate	0.16 mg/m3	1.8 mg/m3	100 mg/m3
hydrochloric acid	Hydrogen chloride; (Hydrochloric acid)	Not Available	Not Available	Not Available
hydrochloric acid	Deuterochloric acid; (Deuterium chloride)	1.8 ppm	22 ppm	100 ppm

Ingredient	Original IDLH	Revised IDLH
lithium carbonate	Not Available	Not Available
hydrochloric acid	100 ppm	50 ppm
water	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	 Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.
Skin protection	See Hand protection below
Hands/feet protection	 Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	See Other protection below
Other protection	► Overalls.
Thermal hazards	Not Available

Respiratory protection

Type B-P Filter of sufficient capacity.

76b-p()

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	colorless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature	Not Available

10M29-2 Lithium (10,000µg/mL in 1% HCI)

Issue Date: **09/02/2016**Print Date: **09/02/2016**

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	► Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Inhaled	The material can cause respiratory irritation in some persons. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". Hydrogen chloride (HCl) vapour or fumes present a hazard from a single acute exposure.		
Ingestion	The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion".		
Skin Contact	The material can produce severe chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.		
Eye	The material can produce severe chemical burns to the eye following direct contact. If applied to the eyes, this material causes severe eye damage.		
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Chronic minor exposure to hydrogen chloride (HCI) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and gums; and ulceration of the nasal mucous membranes.		

10M29-2 Lithium	TOXICITY	IRRITATION
(10,000µg/mL in 1% HCl)	Not Available	Not Available

	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit) : Moderate *
lithium carbonate	Inhalation (rat) LC50: >0.8 mg/L/4h *[2]	Skin (rabbit) : Mild *
	Oral (rat) LD50: 525 mg/kg ^[2]	

	TOXICITY	IRRITATION
hydrochloric acid	Inhalation (rat) LC50: 3124 ppm/1hr ^[2]	Eye (rabbit): 5mg/30s - mild
	Oral (rat) LD50: 900 mg/kg ^[2]	

TOXICITY	IRRITATION
Oral (rat) LD50: >90000 mg/kg ^[2]	Not Available

Legend:
1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Version No: 2.2

10M29-2 Lithium (10,000µg/mL in 1% HCI)

Issue Date: **09/02/2016**Print Date: **09/02/2016**

O – Data Not Available to make classification

LITHIUM CARBONATE	Goitrogenic:. Lacrimation, altered sleep times, hallucinations, distorted perception, toxic psychosis, excitement, ataxia, respiratory depression, allergic dermatitis (after sytemic administration), foetoxicity and foetolethality and specific development abnormalities recorded. Non-sensitising guinea pig * * FMC SDS		
HYDROCHLORIC ACID	for acid mists, aerosols, vapours Data from assays for genotoxic activity in vitro suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. The material may be irritating to the eye, with prolonged contact causing inflammation. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans.		
10M29-2 Lithium (10,000µg/mL in 1% HCl) & LITHIUM CARBONATE & HYDROCHLORIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ceases.		
HYDROCHLORIC ACID & WATER	No significant acute toxicological data identified in literature search.		
Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	~	Reproductivity	0
Serious Eye Damage/Irritation	✓ STOT -	Single Exposure	0
Respiratory or Skin sensitisation	○ STOT - Re	peated Exposure	0
Mutagenicity		spiration Hazard	0
			Data available but does not fill the criteria for classification Data required to make classification available

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
lithium carbonate	LC50	96	Fish	5.69mg/L	2
lithium carbonate	EC50	48	Crustacea	6.24mg/L	2
lithium carbonate	EC50	72	Algae or other aquatic plants	>400mg/L	2
lithium carbonate	EC50	504	Crustacea	>1.7mg/L	2
lithium carbonate	NOEC	504	Crustacea	1.7mg/L	2
hydrochloric acid	LC50	96	Fish	70.057mg/L	3
hydrochloric acid	EC50	96	Algae or other aquatic plants	344.947mg/L	3
hydrochloric acid	EC50	9.33	Fish	0.014000mg/L	4
hydrochloric acid	NOEC	0.08	Fish	10mg/L	4
water	LC50	96	Fish	897.520mg/L	3
water	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
water	EC50	384	Crustacea	199.179mg/L	3
Legend:	Aquatic Toxicity Da		HA Registered Substances - Ecotoxicological I database - Aquatic Toxicity Data 5. ECETOC A tition Data 8. Vendor Data		

Prevent, by any means available, spillage from entering drains or water courses. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
lithium carbonate	LOW	LOW
hydrochloric acid	LOW	LOW
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
lithium carbonate	LOW (LogKOW = -0.4605)
hydrochloric acid	LOW (LogKOW = 0.5392)
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
lithium carbonate	HIGH (KOC = 1)
hydrochloric acid	LOW (KOC = 14.3)
water	LOW (KOC = 14.3)

Version No: 2.2 10M29-2 Lithium (10,000µg/mL in 1% HCI) Issue Date: 09/02/2016 Print Date: 09/02/2016

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal Legislation addressing waste disposal requirements may differ by country, state and/ or territory.

• DO NOT allow wash water from cleaning or process equipment to enter drains.

- ► Recycle wherever possible.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant

Land transport (DOT)

UN number	1789	
UN proper shipping name	Hydrochloric acid (contains hydrochloric acid)	
Transport hazard class(es)	Class 8 Subrisk Not Applicable	
Packing group		
Environmental hazard	Not Applicable	
Special precautions for user	Hazard Label 8 Special provisions A3, A6, B3, B15, IB2, N41, T8, TP2	

Air transport (ICAO-IATA / DGR)

UN number	1789		
UN proper shipping name	Hydrochloric acid (contains hydrochloric acid)		
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	8 Not Applicable 8L	
Packing group	II		
Environmental hazard	Not Applicable		
	Special provisions		A3A803
	Cargo Only Packing I	nstructions	855
	Cargo Only Maximum	Qty / Pack	30 L
Special precautions for user	Passenger and Cargo	Packing Instructions	851
	Passenger and Cargo	Maximum Qty / Pack	1 L
	Passenger and Cargo	Limited Quantity Packing Instructions	Y840
	Passenger and Cargo	Limited Maximum Qty / Pack	0.5 L

Sea transport (IMDG-Code / GGVSee)

UN number	1789		
UN proper shipping name	HYDROCHLORIC ACID (contains hydrochloric acid)		
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable		
Packing group			
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number F-A, S-B Special provisions Not Applicable		

Version No: 2.2

10M29-2 Lithium (10,000µg/mL in 1% HCI)

Issue Date: **09/02/2016**Print Date: **09/02/2016**

Limited Quantities 1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

LITHIUM CARBONATE(554-13-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - California Proposition 65 - Reproductive Toxicity US EPCRA Section 313 Chemical List

US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

HYDROCHLORIC ACID(7647-01-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

-	
	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
	US - Alaska Limits for Air Contaminants
	US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)
	US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)
	US - California Permissible Exposure Limits for Chemical Contaminants
	US - Hawaii Air Contaminant Limits
	US - Idaho - Limits for Air Contaminants
	US - Michigan Exposure Limits for Air Contaminants
	US - Minnesota Permissible Exposure Limits (PELs)
	US - Oregon Permissible Exposure Limits (Z-1)
	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

 $\ensuremath{\mathsf{US}}$ - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants

US - Washington Permissible exposure limits of air contaminants

US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Levels (PELs) - Table Z1 $\,$

US SARA Section 302 Extremely Hazardous Substances

US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Hydrochloric acid	5000	2270

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PREPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Lithium carbonate Listed

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Υ
Canada - NDSL	N (lithium carbonate; hydrochloric acid; water)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water)
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

Catalogue number: 10M29-2 Page 9 of 9 Issue Date: 09/02/2016 Version No: 2.2 Print Date: 09/02/2016

10M29-2 Lithium (10,000µg/mL in 1% HCI)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.