

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

High-Purity Standards

Catalogue number: 10M3-1

Version No: 2.3

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 4

Issue Date: **05/19/2017**Print Date: **05/19/2017**S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	10M3-1 Arsenic (10,000μg/mL in 20% HNO3)
Synonyms	Not Available
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (contains nitric acid)
Other means of identification	10M3-1

Recommended use of the chemical and restrictions on use

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

Emergency phone number

• • •	
Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

Classification

Serious Eye Damage Category 1, Skin Corrosion/Irritation Category 1A, Carcinogenicity Category 2, Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3, Metal Corrosion Category 1

Label elements

Hazard pictogram(s)





SIGNAL WORD

DANGER

Hazard statement(s)

H314	Causes severe skin burns and eye damage.	
H351	Suspected of causing cancer.	
H412	Harmful to aquatic life with long lasting effects.	
H290	May be corrosive to metals.	

Chemwatch: 9-241106 Catalogue number: 10M3-1 Page 2 of 12

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

Version No: 2.3

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) Prevention

P201

Obtain special instructions before use.

Precautionary statement(s) Response

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Precautionary statement(s) Storage

P405

Store locked up.

Precautionary statement(s) Disposal

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7697-37-2	20	nitric acid
7440-38-2	1	arsenic
7732-18-5	balance	water

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

If this product comes in contact with the eyes:

Eye Contact

- ▶ Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ► Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact

- If skin or hair contact occurs:
- ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.
- ▶ Quickly remove all contaminated clothing, including footwear
- Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
- Transport to hospital, or doctor.
- If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested.

 - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary
- Transport to hospital, or doctor, without delay. Inhalation
 - Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.
 - Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).
 - As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.
 - Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.

This must definitely be left to a doctor or person authorised by him/her.

(ICSC13719)

Ingestion

- ▶ For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed
- swallowed do **NOT** induce vomiting
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids

- ▶ Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise
- Figure Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues. INGESTION:

Issue Date: 05/19/2017 Print Date: 05/19/2017 Catalogue number: 10M3-1

Page 3 of 12

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

Issue Date: 05/19/2017 Print Date: 05/19/2017

Version No: 2.3

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- ▶ Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping
- Deep second-degree burns may benefit from topical silver sulfadiazine

FYF:

- Figure Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist)

[Ellenhorn and Barceloux: Medical Toxicology]

For intoxication due to nitrogen oxides:

- If patient encountered shortly after exposure, instruct the patient to breathe deeply.
- ▶ Enforce complete rest for 24-48 hours even when the patient is not symptomatic
- ▶ During the presymptomatic period inhalation of sodium bicarbonate-sodium chloride aerosol has been suggested as a prophylactic measure. Vitamin E (an antioxidant), in the form of mixed tocopherols, can be given by mouth in doses of several hundred milligrams. N-acetylcysteine (Mycomyst) by aerolization or direct installation may be worthwhile.
- When patient commences coughing or feels slightly fatigued commence oxygen therapy. Nasal prongs or the use of oxygen with continuous distending airway pressure may be appropriate. (Hyperbaric oxygen increased the risk of pulmonary oedema when given together with NO2 in dogs.)
- Removal of frothy exudate from the respiratory tract may be a major therapeutic problem. Suction, postural draining and other methods may be useful.
- Bronchospasm is corrected by inhalation of aerosols of albuterol, isoetharine, metaproterenol or terbutaline.
- Atropine, adrenaline, expectorants, emetics, sedatives (other than small doses of morphine) and, usually, cardiac glycosides are ineffective. In a few instances rapid digitalization with a drug like ouabain may be advisable.
- Fig. The role of venesection and blood replacement by isotonic saline is the subject of debate although venesection should certainly be avoided once circulatory collapse has become established.
- Artificial ventilation is seldom effective
- In the presence of severe, confirmed methaemoglobinaemia, a cautious trial of methylene blue may be justified even though the safety and efficacy of the procedure has not been established in nitrogen oxides poisoning.
- ► Steroid therapy, to minimize inflammatory reaction, remains controversial.
- Patients should be observed closely, for at least 6 weeks, to observe, for example, pulmonary oedema.

Gosselin, Smith and Hodge: Clinical Toxicology of Commercial Products: 5th Edition

Patients suspected of excessive exposure should be kept under observation.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- Water spray or fog.
- Foam
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

Special protective equipment and precautions for fire-fighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 		
Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous furnes. May emit acrid smoke. Decomposition may produce toxic furnes of: nitrogen oxides (NOx) arsenic compounds 		

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

▶ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.

Minor Spills

Check regularly for spills and leaks.

Chemwatch: **9-241106** Page **4** of **12**

Catalogue number: 10M3-1 10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

Version No: 2.3

Issue Date: **05/19/2017**Print Date: **05/19/2017**

 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Consider evacuation (or protect in place). Stop leak if safe to do so. **Major Spills** Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Safe handling

Other information

Suitable container

Precautions for safe handling

Avoid all personal contact, including inhalation.
 Wear protective clothing when risk of exposure occurs.
 Use in a well-ventilated area.
 WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.

If contamination of drains or waterways occurs, advise emergency services.

- Avoid smoking, naked lights or ignition sources.
- ► Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.
 - ▶ Use good occupational work practice
 - Observe manufacturer's storage and handling recommendations contained within this SDS.
 - ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- Store in original containers.
 Keep containers securely securely secure.
 - Keep containers securely sealed.
 - Store in a cool, dry, well-ventilated area.
 Store away from incompatible metarials
 - ▶ Store away from incompatible materials and foodstuff containers.
 - ▶ Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storage and handling recommendations contained within this SDS

Conditions for safe storage, including any incompatibilities

► DO NOT use aluminium or galvanised containers

- ► Check regularly for spills and leaks
- Lined metal can, lined metal pail/ can.
- ▶ Plastic pail.
- ► Polyliner drum.
- ► Packing as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

For low viscosity materials

- ▶ Drums and jerricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging;
- ► Cans with friction closures and
- low pressure tubes and cartridges

may be used.

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

Nitric acid:

- ▶ is a strong acid and oxidiser
- reacts with water or steam to form toxic and corrosive nitrous fumes
- reacts violently with water when added as the concentrated acid with generation of heat (always add acid to water to dilute)
- reacts violently with reducing agents, bases, combustible materials, finely dispersed or powdered metals and metal alloys, acetic anhydride, acetone, acetylene, acrolein, acrylonitrile, alcohols, aliphatic amines, allyl chloride, ammonia, aniline, anionic exchange resins, 1,4-benzoquinone diimine, 1,2-bis(trimethylsilyl)hydrazine, bromine pentafluoride, cresol, crotonaldehyde, cumene, cyanides, diethyl ether, 1,2-dimethyl-2-trimethylsilyhydrazine, diphenyltin, divinyl ether, N-ethylaniline, ethyl phosphine, 2-ethynylfuran, fluorine, halides of phosphorus or sulfur, hydrazine, hydrogen peroxide, germanium, hydrogen iodide, lithium triethylsilyl amide, metal acetylides, 2-methylthiophene, pentanethiol, phosphorus and phosphorus vapours, polyurethane foam, potassium permanganate, resorcinol, rubber (containing lead), sulfides, sulfur, sulfur dioxide, stibine, thiophene, triethylgallium, polydibromosilane, vinyl ether, zinc ethoxide, zinc phosphide, organic solvents and many other substances and ,materials
- is incompatible with many substances including acrylates, aldehydes, alkanolamines, alkylene oxides, aromatic amines, amides, cresols, cyclic ketones, epichlorohydrin, glycols, hydrocarbons, isocyanates, ketones, oleum, organic anhydrides, paraldehyde, phenols, silanes, strong oxidisers, substituted allyls, sulfuric acid, terpenes, vinyl acetate, vinylidene chloride
- Forms heat, impact, friction or shock explosive substances with acetic acid, acetoxyethylene glycol, ammonium nitrate, anilinium nitrate, 1,2-dichloroethane, dichloroethylene, dichloromethane, diethylaminoethanol, 3,6-dihydro-1,2,2H-oxazine, dimethyl ether, dinitrobenzenes, disodium phenyl orthophosphate, 2-hexanal, metal salicylates, 3-methylcyclohexanone, nitroaromatics, nitrobenzenes, nitromethane, beta-oropyl acrolein, salicylic acid

Storage incompatibility

Page 5 of 12

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

Issue Date: **05/19/2017**Print Date: **05/19/2017**

Version No: 2.3

Catalogue number: 10M3-1

- increases the explosive sensitivity of nitromethane
- may decompose when heated with the formation of nitrogen dioxide (which also produces discolouration colourless 100% acid cannot be stored in the presence of light with formation of nitrogen dioxide (which cause discolouration)
- attacks most metals and some plastics, rubber and coatings
- ▶ Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
- ▶ Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts neutralisation can generate dangerously large amounts of heat in small spaces.
- ▶ The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
- ► The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.
- Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.
- Inorganic acids can initiate the polymerisation of certain classes of organic compounds.
- Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.
- Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitrides, sulfides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H2S and SO3), dithionites (SO2), and even carbonates.
- Acids often catalyse (increase the rate of) chemical reactions.
- Inorganic peroxy compounds are potent oxidisers that pose fire or explosive hazards when in contact with ordinary combustible materials.
- ► Inorganic peroxides react with organic compounds to generate organic peroxide and hydroperoxide products that react violently with reducing agents.
- Inorganic oxidising agents can react with reducing agents to generate heat and products that may be gaseous (causing pressurization of closed containers). The products may themselves be capable of further reactions (such as combustion in the air).
- Organic compounds in general have some reducing power and can in principle react with compounds in this class. Actual reactivity varies greatly with the identity of the organic compound.
- Inorganic oxidising agents can react violently with active metals, cyanides, esters, and thiocyanates.
- Peroxides, in contact with inorganic cobalt and copper compounds, iron and iron compounds, acetone, metal oxide salts and acids and bases can react with rapid, uncontrolled decomposition, leading to fires and explosions.
- Inorganic reducing agents react with oxidizing agents to generate heat and products that may be flammable, combustible, or otherwise reactive. Their reactions with oxidizing agents may be violent.
- ► Incidents involving interaction of active oxidants and reducing agents, either by design or accident, are usually very energetic and examples of so-called redox reactions.
- Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous
- Avoid storage with reducing agents.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	nitric acid	nitric acid Nitric acid		10 mg/m3 / 4 ppm	Not Available	TLV® Basis: URT & eye irr; dental erosion
US NIOSH Recommended Exposure Limits (RELs)	nitric acid	Aqua fortis, Engravers acid, Hydrogen nitrate, Red fuming nitric acid (RFNA), White fuming nitric acid (WFNA)	5 mg/m3 / 2 ppm	4 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	nitric acid	Nitric acid	2 ppm	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	arsenic	Arsenic metal: Arsenia	Not Available	Not Available	0.002 mg/m3	Ca See Appendix A

| EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3	
nitric acid	Nitric acid Not Available		Not Available	Not Available	
Ingredient	Original IDLH		Revised IDLH		
nitric acid	100 ppm		25 ppm		
arsenic	100 mg/m3		5 mg/m3		
water	Not Available		Not Available		

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Appropriate engineering controls

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)

Page 6 of 12

Print Date: 05/19/2017

Version No: 2.3

Catalogue number: 10M3-1

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

0.5-1 m/s (100-200 f/min.)

Issue Date: 05/19/2017

aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into 1-2.5 m/s (200-500 zone of rapid air motion) f/min.) grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid 2.5-10 m/s (500-2000 air motion). f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range	
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	
3: Intermittent, low production.	3: High production, heavy use	
4: Large hood or large air mass in motion	4: Small hood-local control only	

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Personal protection











- Safety glasses with unperforated side shields may be used where continuous eve protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure
- Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.
- Full face shield (20 cm. 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Alternatively a gas mask may replace splash goggles and face shields. Eye and face protection
 - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

Hands/feet protection

▶ Elbow length PVC gloves ▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

NOTE:

- ► The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Body protection

See Other protection below

Other protection

Overalls PVC Apron.

Not Available

- PVC protective suit may be required if exposure severe.
- Evewash unit.
- Ensure there is ready access to a safety shower

Thermal hazards

Respiratory protection Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	colorless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available

Page **7** of **12**

Version No: 2.3

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

	1		
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Contact with alkaline material liberates heat Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

(10,000µg/mL in 20% HNO3)

Information on toxicological effects

Inhaled	nausea and weakness.	esponse to such irritation can cause further lung damage. hoking and mucous membrane damage. There may be dizziness, headache, bepending on the concentration and duration of exposure, cough, gagging, chest
Ingestion	produce serious damage to the health of the individual. Ingestion of acidic corrosives may produce burns around and in the mouth, speaking may also be evident. Symptoms of acute poisoning by arsenic ingestion, which develop within 4 h Blood may appear in vomitus and stools. If amount ingested is sufficiently h Severe gastritis or gastroenteritis may occur as a result of lesions produced may be delayed for several hours. Eventually a violent haemorrhagic gastro Occasionally alimentary symptoms are mild or absent in which case sympton spasm or convulsion, delirium and, sometimes, mania. In advanced poisoni of the brain (encephalopathies) and peripheral neuritis (more commonly) has sensation and pain (hypoesthesia), eventually paralysis and muscular atrop be prominent. The toxic moiety is presumed to be trivalent arsenic in the for active enzyme inhibitors. Arsenic and its compounds may damage the stem may result in pancytopenia (a reduction in the number of red and white bloo individual blood cells. Granulocytopenia (a reduction in granular leukocytes) 1-2 weeks, whilst loss of erythrocytes (red blood cells) need months to beco stem cells. Exposure to nitric acid causes burning pain, severe corrosion and scaring of	al experiments indicate that ingestion of less than 40 gram may be fatal or may the throat and oesophagus. Immediate pain and difficulties in swallowing and mours include epigastric pain, vomiting and watery diarrhoea, nausea and vomiting. Igh, shock, rapid pulse and coma may develop, followed by death within 24 hours. If by vascular damage from absorbed arsenic (and not local corrosion); symptoms enteritis leads to profound loss of fluid and electrolyte resulting in shock and death. If any are usually referable to the central nervous system, headache, vertigo, muscle ngs by arsenic and its inorganic salts, nervous symptoms are prominent; disorders are been described. A prickling sensation (paresthesia), decreased sensitivity to hy appear, usually in the legs. "Glove and stocking' distribution of sensory loss may rm of inorganic arsenious acid (arsenite) or an organic arsenoxide. Arsenites are cell which acts as the precursor to components of the blood. Loss of the stem cell d cells and platelets) with a latency period corresponding to the lifetime of the proceeding within days and thrombocytopenia (a disorder involving platelets), within me clinically manifest. Aplastic anaemia develops due to complete destruction of the fifthe digestive tract with adhesions, narrowing and obstruction and even anaemia. The delayed 12 hours to 14 days or several months from these complications.
Skin Contact	Skin contact is not thought to produce harmful health effects (as classified u identified following exposure of animals by at least one other route and the r abrasions. Skin contact with nitric acid may cause corrosion, skin thickening, yellow dis Open cuts, abraded or irritated skin should not be exposed to this material	be deep with distinct edges and may heal slowly with the formation of scar tissue. Inder EC Directives using animal models). Systemic harm, however, has been material may still produce health damage following entry through wounds, lesions o accolouration of the skin, blisters and scars depending on the concentration exposed In may produce systemic injury with harmful effects. Examine the skin prior to the us
Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity completely. Eye contact with both diluted and concentrated nitric acid may result in burn. Pain may be absent after contact with concentrated nitric acid.	to light and burns. Mild burns of the epithelia generally recover rapidly and s causing pain, adhesions, comeal damage, blindness or permanent eye damage.
Chronic	and inflammation of lung tissue often occurs. Long-term exposure to respiratory irritants may result in airways disease, in Substance accumulation, in the human body, may occur and may cause son There is limited evidence that, skin contact with this product is more likely to population. There is some evidence from animal testing that exposure to this material m	ne concern following repeated or long-term occupational exposure. o cause a sensitisation reaction in some persons compared to the general
10M3-1 Arsenic	тохісіту	IRRITATION

Issue Date: 05/19/2017

Print Date: 05/19/2017

Issue Date: 05/19/2017 Print Date: 05/19/2017

Catalogue number: 10M3-1 10M3-1 Arsenic (10,000µg/mL in 20% HNO3) Version No: 2.3

	Not Available	Not Available					
nitric acid	TOXICITY Inhalation (rat) LC50: 625 ppm/1h*t ^[2]			IRRITATION Not Available			
arsenic	TOXICITY Oral (rat) LD50: 763 mg/kg ^[2]			TATION Available			
water	TOXICITY Not Available	IRRITATION Not Available					
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute tox extracted from RTECS - Register of Toxic Effect of chemical Substances	city 2.* Value obtained from	manufactui	er's SDS. Unless otherwise specified data			
NITRIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ends. For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. The material may produce severe irritation to the eye causing pronounced inflammation. The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]						
ARSENIC	Arsenic compounds are classified by the European Union as toxic by inhat warning: This substance has been classified by the IARC as Group 1	-		life and long lasting in the environment.			
	Tumorigenic - Carcinogenic by RTECS criteria.						
WATER	Tumorigenic - Carcinogenic by RTECS criteria. No significant acute toxicological data identified in literature search.						
WATER Acute Toxicity	,	Carcinogenicity •					
	No significant acute toxicological data identified in literature search.		•				
Acute Toxicity	No significant acute toxicological data identified in literature search.	Carcinogenicity	•				
Acute Toxicity Skin Irritation/Corrosion Serious Eye	No significant acute toxicological data identified in literature search.	Carcinogenicity Reproductivity	•				

Legend:

X − Data available but does not fill the criteria for classification
✓ − Data available to make classification

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

ENDPOINT		TEST DURATION (HR)	SPEC	ES	VALUE	=		SOUF	RCE
Not Applicable		Not Applicable			Not Ap	plicable	9	Not Applicable	
ENDPOINT		TEST DURATION (HR)		SPECIES		VALU	JE	so	URCE
NOEC		16		Crustacea		107m	ng/L	4	
ENDPOINT	TES	ST DURATION (HR)	SPECIES				VALUE		SOURCE
LC50	96		Fish				9.9mg/L		4
EC50	336		Algae or other aquatic plants			0.63mg/L		4	
NOEC	336		Algae or other aquatic plants <0			<0.75mg/L		4	
_									
ENDPOINT		TEST DURATION (HR)	SPEC	ES	VALUE	=		SOUF	RCE
Not Applicable	Not Applicable Not Applicable		Not Applicable		Not Ap	Not Applicable		Not Applicable	
	Not Applicable ENDPOINT NOEC ENDPOINT LC50 EC50 NOEC	Not Applicable	Not Applicable Not Applicable ENDPOINT TEST DURATION (HR) NOEC 16 ENDPOINT TEST DURATION (HR) LC50 96 EC50 336 NOEC 336 ENDPOINT TEST DURATION (HR)	Not Applicable Not Applicable Not Applicable ENDPOINT TEST DURATION (HR) NOEC 16 ENDPOINT TEST DURATION (HR) SPECIES LC50 96 Fish EC50 336 Algae or othe NOEC 336 Algae or othe ENDPOINT TEST DURATION (HR) SPECIES	Not Applicable SPECIES Crustacea ENDPOINT TEST DURATION (HR) SPECIES NOEC 336 Algae or other aquatic plants NOEC 336 SPECIES ENDPOINT TEST DURATION (HR) SPECIES	Not Applicable Not Applicable	Not Applicable Not Applicable	Not Applicable Not Applicable Not Applicable ENDPOINT TEST DURATION (HR) SPECIES VALUE NOEC 16 Crustacea 107mg/L ENDPOINT TEST DURATION (HR) SPECIES VALUE LC50 96 Fish 9.9mg/L EC50 336 Algae or other aquatic plants 0.63mg/L NOEC 336 Algae or other aquatic plants <0.75mg/L	Not Applicable Not App

Page 9 of 12

Version No: 2.3

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

Issue Date: 05/19/2017 Print Date: 05/19/2017

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

Speciation of arsenic is an important consideration in the fate, movement, and action of this substance. Chemical and biochemical transformations of arsenic include oxidation, reduction and methylation which affects its volatilisation, adsorption, dissolution and biological disposition. The transport of arsenic in the environment is largely controlled by absorption/desorption processes in soils and sediments. Sediment movement is responsible for transport of arsenic soil residues to their ultimate sinks in deep ocean sediments. The clay fraction, plus ferrous and aluminium oxides which coat clay particles, adsorb arsenicals which then undergo transformation as discussed earlier. Conversions of arsenic to volatile alkylarsines leads to air transport losses from soil. Inorganic arsenic occurs in water in different oxidation states depending on the pH and Eh of the water. Arsenate is apparently reduced by bacteria to arsenite in marine environments because the ratio of total arsenate to total arsenic is much lower than that predicted thermodynamically. Methylation of arsenic occurs in both freshwater and marine systems where arsenate occurs as arsenate, arsenite, methanearsonic acid and dimethylarsinic acid. Arsenate predominates because this is the most stable form.

Bioaccumulation occurs in some aquatic species such as seaweeds, freshwater algae and crustaceans. Some arsenic in water flea (Daphnia Magna) and algae occurs as arseno-analogues of phospholipids leading to the mistaken impression that accumulation and utilisation of arsenic takes place at the expense of phosphate. Crabs, lobsters and other marine organisms accumulate organo-arsenicals in the food chain. Although human activity may alter the local picture of environmental arsenic there is little evidence that this affects the global scale arsenic cycle.

Airborne concentrations of arsenic in urban areas may range from a few nanograms to a few tenths of a microgram per cubic meter; airborne arsenic is generally inorganic. In oxygenated soils inorganic arsenic is present in pentavalent form; under reducing conditions it occurs as the trivalent form.

Drinking Water Standards:

arsenic: 50 ug/1 (UK max.) 0.01mg/L (WHO provisional guideline)

chloride:400 mg/l (UK max.) 250 mg/l (WHO guideline)

Soil Guideline:

Dutch Criteria: 29 mg/kg (target)

55 ma/ka (intervention)

Air Quality Standard:

No safe levels recommended due to carcinogenic properties (WHO guideline)

Prevent, by any means available, spillage from entering drains or water courses

DO NOT discharge into sewer or w

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

- ► Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

- ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Product / Packaging disposa

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible
- Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant

Land transport (DOT)

UN number	3264
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (contains nitric acid)

Chemwatch: 9-241106

Page **10** of **12**

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

Issue Date: **05/19/2017** Print Date: **05/19/2017**

Version No: 2.3

Catalogue number: 10M3-1

Transport hazard class(es)	Class 8 Subrisk Not Applicable
Packing group	
Environmental hazard	Not Applicable
Special precautions for user	Hazard Label 8 Special provisions 386, B2, IB2, T11, TP2, TP27

Air transport (ICAO-IATA / DGR)

UN number	3264					
UN proper shipping name	CORROSIVE LIQUID,	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains nitric acid)				
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	8 Not Applicable 8L				
Packing group	II					
Environmental hazard	Not Applicable					
	Special provisions		A3A803			
	Cargo Only Packing Instructions		855			
	Cargo Only Maximum		30 L			
Special precautions for user		Packing Instructions	851			
Special precaudons for user						
	Passenger and Cargo	·	1L			
	Passenger and Cargo	Limited Quantity Packing Instructions	Y840			
	Passenger and Cargo Limited Maximum Qty / Pack		0.5 L			

Sea transport (IMDG-Code / GGVSee)

UN number	3264				
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. * (contains nitric acid)				
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable				
Packing group	П				
Environmental hazard	Not Applicable				
Special precautions for user	EMS Number F-A, S-B Special provisions 274 Limited Quantities 1 L				

Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Product name	Pollution Category	Ship Type
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Nitric acid (70% and over) Nitric acid (less than 70%)	Y; Y	2 2

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

Catalogue number: 10M3-1

Version No: 2.3

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

Issue Date: 05/19/2017 Print Date: 05/19/2017

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants Passenger and Cargo Aircraft US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air US - Alaska Limits for Air Contaminants Contaminants US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) US - Washington Permissible exposure limits of air contaminants US - California Permissible Exposure Limits for Chemical Contaminants US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values US - Hawaii Air Contaminant Limits US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants US - Idaho - Limits for Air Contaminants US ACGIH Threshold Limit Values (TLV) US - Massachusetts - Right To Know Listed Chemicals US CWA (Clean Water Act) - List of Hazardous Substances US - Michigan Exposure Limits for Air Contaminants US EPCRA Section 313 Chemical List US - Minnesota Permissible Exposure Limits (PELs) US NIOSH Recommended Exposure Limits (RELs) US - Oregon Permissible Exposure Limits (Z-1) US OSHA Permissible Exposure Levels (PELs) - Table Z1 US - Pennsylvania - Hazardous Substance List US SARA Section 302 Extremely Hazardous Substances

ARSENIC(7440-38-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
US - Alaska Limits for Air Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)
US - California Permissible Exposure Limits for Chemical Contaminants
US - Hawaii Air Contaminant Limits
US - Idaho - Limits for Air Contaminants
US - Massachusetts - Right To Know Listed Chemicals
US - Minnesota Permissible Exposure Limits (PELs)

- US New Jersey Right to Know Special Health Hazard Substance List (SHHSL): Carcinogens
- US Pennsylvania Hazardous Substance List
- US Tennessee Occupational Exposure Limits Limits For Air Contaminants US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air

US - Washington Permissible exposure limits of air contaminants

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

- US Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
- US ACGIH Threshold Limit Values (TLV)
- US ACGIH Threshold Limit Values (TLV) Carcinogens
- US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
- US Clean Air Act Hazardous Air Pollutants US CWA (Clean Water Act) - Priority Pollutants
- US CWA (Clean Water Act) Toxic Pollutants US EPCRA Section 313 Chemical List
- US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens
- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Permissible Exposure Levels (PELs) Table Z1
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Pennsylvania - Hazardous Substance List

US - Rhode Island Hazardous Substance List

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	Yes
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Nitric acid	1000	454
Arsenic	1	0.454

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Υ
Canada - NDSL	N (water; arsenic; nitric acid)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water; arsenic; nitric acid)
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

Chemwatch: 9-241106 Page 12 of 12

Catalogue number: 10M3-1

Version No: 2.3

10M3-1 Arsenic (10,000µg/mL in 20% HNO3)

Issue Date: **05/19/2017**Print Date: **05/19/2017**

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.