

High-Purity Standards

Catalogue number: 10M42-2

Version No: 2.2 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

SECTION 1 IDENTIFICATION

Product Identifier

Product name	142-2 Praseodymium (10,000µg/mL in 4% HCI)	
Synonyms	ug/mL Praseodymium in 4% HCI	
Proper shipping name	Hydrochloric acid (contains hydrochloric acid)	
Other means of identification	10M42-2	

Recommended use of the chemical and restrictions on use

Relevant identified uses Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	h-Purity Standards	
Address	ox 41727 SC 29423 United States	
Telephone	843-767-7900	
Fax	843-767-7906	
Website	highpuritystandards.com	
Email	Not Available	

Emergency phone number

Association / Organisation	INFOTRAC	
Emergency telephone numbers	1-800-535-5053	
Other emergency telephone numbers	1-352-323-3500	

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture			
Classification	Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1		
Label elements			
GHS label elements	A CONTRACTOR OF THE OWNER OWNER OF THE OWNER		
SIGNAL WORD	DANGER		
Hazard statement(s)			
H290	May be corrosive to metals.		
H314	Causes severe skin burns and eye damage.		
H318	Causes serious eye damage.		

Hazard(s) not otherwise specified

Not Applicable

Chemwatch Hazard Alert Code: 3

Issue Date: 09/07/2016

Print Date: 09/07/2016

S.GHS.USA.EN

Precautionary statement(s) Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
Precautionary statement(s) Response			
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.			
Precautionary statement(s) Storage			
P405	Store locked up.			
Precautionary statement(s) Disposal				
P501	Dispose of contents/container in accordance with local regulations.			
	·			

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
12036-32-7	1 (as Pr)	praseodymium(III) oxide
7647-01-0	4	hydrochloric acid
7732-18-5	balance	water

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- + Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.
- INGESTION: • Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.

- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.

Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

There is no restriction on the type of extinguisher which may be used

Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting Fire/Explosion Hazard

Non combustible.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Clean up all spills immediately.
Major Spills	#

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling Safe handling • Avoid all personal contact, including inhalation. • DO NOT allow clothing wet with material to stay in contact with skin Other information • Store in original containers.

Conditions for safe storage, including any incompatibilities

Suitable container	 DO NOT use aluminium or galvanised containers Check regularly for spills and leaks Lined metal can, lined metal pail/ can. For low viscosity materials Drums and jerricans must be of the non-removable head type.
Storage incompatibility	 Inorganic acids are generally soluble in water with the release of hydrogen ions. Hydrogen chloride: reacts strongly with strong oxidisers (releasing chlorine gas), acetic anhydride, caesium cyanotridecahydrodecaborate(2-), ethylidene difluoride, hexalithium disilicide, metal acetylide, sodium, silicon dioxide, tetraselenium tetranitride, and many organic materials is incompatible with alkaline materials, acetic anhydride, acetylides, aliphatic amines, alkanolamines, alkylene oxides, aluminium, aluminium-titanium alloys, aromatic amines, amines, amines, amides, 2-aminoethanol, ammonia, ammonium hydroxide, borides, calcium phosphide, carbides, carbonates, cyanides, chlorosulfonic acid, ethylenediamine, ethyleneimine, epichlorohydrin, formaldehyde, isocyanates, metals, metals, metal acetylides, sulfides, potassium permanganate, perchloric acid, phosphides, 3-propiolactone, silicides, sulfides, sulfites, sulfuric acid, uranium phosphide, vinyl acetate, vinylidene fluoride attacks most metals forming flammable hydrogen gas, and some plastics, rubbers and coatings reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available
US ACGIH Threshold Limit Values (TLV)	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	2 ppm	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	hydrochloric acid	Anhydrous hydrogen chloride; Aqueous hydrogen chloride (i.e., Hydrochloric acid, Muriatic acid) [Note: Often used in an aqueous solution.]	Not Available	Not Available	7 mg/m3 / 5 ppm	Not Available

EMERGENCY LIMITS

Material name	TEEL-1		TEEL-2	TEEL-3		
Praseodymium oxide	6 mg/m3		66 mg/m3	400 mg/m3		
Hydrogen chloride; (Hydrochloric acid)	Not Available		Not Available	Not Available		
Deuterochloric acid; (Deuterium chloride)	1	.8 ppm	22 ppm	100 ppm		
Original IDLH		Revised IDLH				
Not Available		Not Available				
100 ppm		50 ppm				
Not Available	Not Available					
	Praseodymium oxide Hydrogen chloride; (Hydrochloric acid) Deuterochloric acid; (Deuterium chloride) Original IDLH Not Available 100 ppm	Praseodymium oxide 6 Hydrogen chloride; (Hydrochloric acid) N Deuterochloric acid; (Deuterium chloride) 1 Original IDLH 1 Not Available 100 ppm	Praseodymium oxide 6 mg/m3 Hydrogen chloride; (Hydrochloric acid) Not Available Deuterochloric acid; (Deuterium chloride) 1.8 ppm Original IDLH Revised IDLH Not Available Not Available 100 ppm 50 ppm	Praseodymium oxide 6 mg/m3 66 mg/m3 Hydrogen chloride; (Hydrochloric acid) Not Available Not Available Deuterochloric acid; (Deuterium chloride) 1.8 ppm 22 ppm Original IDLH Not Available Not Available 100 ppm 50 ppm		

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.		
Personal protection			
Eye and face protection	Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.		
Skin protection	See Hand protection below		
Hands/feet protection	 Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. 		
Body protection	See Other protection below		
Other protection	► Overalls.		
Thermal hazards	Not Available		

Respiratory protection

Type B-P Filter of sufficient capacity.

76b-p()

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	colorless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available

Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". Exposure to vapours of some rare earth salts can cause sensitivity to heat, itching, and increased sensitivity of smell and taste. Hydrogen chloride (HCI) vapour or fumes present a hazard from a single acute exposure.			
Ingestion	Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion".			
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.			
Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns.			
Chronic	Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Chronic minor exposure to hydrogen chloride (HCI) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and gums; and ulceration of the nasal mucous membranes.			
	ΤΟΧΙΟΙΤΥ			
10M42-2 Praseodymium (10,000µg/mL in 4% HCI)	Not Available	IRRITAT Not Ava		
praseodymium(III) oxide	TOXICITY Not Available	IRRITAT Not Ava		
hydrochloric acid	TOXICITY IRRITATION Inhalation (rat) LC50: 3124 ppm/1hr ^[2] Eye (rabbit): 5mg/30 Oral (rat) LD50: 900 mg/kg ^[2]		30s - mild	
water	TOXICITY IRRITATION Oral (rat) LD50: >90000 mg/kg ^[2] Not Available			
Legend:	1. Value obtained from Europe ECHA Registered Substances extracted from RTECS - Register of Toxic Effect of chemical S		tained from manufac	turer's SDS. Unless otherwise specified data
PRASEODYMIUM(III) OXIDE	Lanthanide poisoning causes immediate defaecation, writhing for typical lanthanides: The symptoms of toxicity of the rare earth elements include wri			
HYDROCHLORIC ACID	The symptoms of toxicity of the rare earth elements include writhing, ataxia, labored respiration, walking on the toes with arched back and sedation. The material may be irritating to the eye, with prolonged contact causing inflammation. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans.			
10M42-2 Praseodymium (10,000µg/mL in 4% HCI) & PRASEODYMIUM(III) OXIDE & HYDROCHLORIC ACID	Asthma-like symptoms may continue for months or even years	after exposure to the materi	al ceases.	

10M42-2 Praseodymium (10,000µg/mL in 4% HCI) & HYDROCHLORIC ACID	for acid mists, aerosols, vapours Data from assays for genotoxic activity in vitro suggest that eukaryotic cells are susceptible to gen	etic damage when the pH falls to about 6.5.
PRASEODYMIUM(III) OXIDE & HYDROCHLORIC ACID & WATER	No significant acute toxicological data identified in literature search.	
Acute Toxicity	Carcinogenicity	\otimes
Skin Irritation/Corrosion	✓ Reproductivity	0
Serious Eye Damage/Irritation	✓ STOT - Single Exposure	0
Respiratory or Skin sensitisation	STOT - Repeated Exposure	0
Mutagenicity	S Aspiration Hazard	0
		 Data available but does not fill the criteria for classification Data required to make classification available

🚫 – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
hydrochloric acid	LC50	96	Fish	70.057mg/L	3
hydrochloric acid	EC50	96	Algae or other aquatic plants	344.947mg/L	3
hydrochloric acid	EC50	9.33	Fish	0.014000mg/L	4
hydrochloric acid	NOEC	0.08	Fish	10mg/L	4
water	LC50	96	Fish	897.520mg/L	3
water	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
water	EC50	384	Crustacea	199.179mg/L	3
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
hydrochloric acid	LOW	LOW
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
hydrochloric acid	LOW (LogKOW = 0.5392)
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
hydrochloric acid	LOW (KOC = 14.3)
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	 Legislation addressing waste disposal requirements may differ by country, state and/ or territory. DO NOT allow wash water from cleaning or process equipment to enter drains. Recycle wherever possible.

SECTION 14 TRANSPORT INFORMATION

Labels Required

CORROSIVE

NO

Marine Pollutant

Land transport (DOT)

UN number	1789		
UN proper shipping name	Hydrochloric acid (contains hydrochloric acid)		
Transport hazard class(es)	Class8SubriskNot Applicable		
Packing group	II Contraction of the second sec		
Environmental hazard	Not Applicable		
Special precautions for user	Hazard Label8Special provisionsA3, A6, B3, B15, IB2, N41, T8, TP2		

Air transport (ICAO-IATA / DGR)

UN number	1789			
UN proper shipping name	Hydrochloric acid (contains hydrochloric acid)			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	8 Not Applicable 8L		
Packing group	II			
Environmental hazard	Not Applicable			
Special precautions for user	Passenger and Cargo Passenger and Cargo		A3A803 855 30 L 851 1 L Y840 0.5 L	

Sea transport (IMDG-Code / GGVSee)

UN number	1789		
UN proper shipping name	HYDROCHLORIC ACID (contains hydrochloric acid)		
Transport hazard class(es)	IMDG Class8IMDG SubriskNot Applicable		
Packing group	I		
Environmental hazard	Not Applicable		
Special precautions for user	EMS NumberF-A, S-BSpecial provisionsNot ApplicableLimited Quantities1 L		

Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Product name	Pollution Category	Ship Type
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Hydrochloric acid	Z	3

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

US - Washington Permissible exposure limits of air contaminants

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US SARA Section 302 Extremely Hazardous Substances

US NIOSH Recommended Exposure Limits (RELs)

US ACGIH Threshold Limit Values (TLV)

US EPCRA Section 313 Chemical List

US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

PRASEODYMIUM(III) OXIDE(12036-32-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

HYDROCHLORIC ACID(7647-01-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
Monographs	Contaminants

US - Alaska Limits for Air Contaminants

US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)

- US California OEHHA/ARB Chronic Reference Exposure Levels and Target Organs (CRELs)
- US California Permissible Exposure Limits for Chemical Contaminants
- US Hawaii Air Contaminant Limits
- US Idaho Limits for Air Contaminants
- US Michigan Exposure Limits for Air Contaminants
- US Minnesota Permissible Exposure Limits (PELs)
- US Oregon Permissible Exposure Limits (Z-1)
- US Tennessee Occupational Exposure Limits Limits For Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (Ib)	Reportable Quantity in kg
Hydrochloric acid	5000	2270

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status
Australia - AICS	N (praseodymium(III) oxide)
Canada - DSL	Υ
Canada - NDSL	N (hydrochloric acid; water)
China - IECSC	N (praseodymium(III) oxide)
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water)
Korea - KECI	Y
New Zealand - NZIoC	N (praseodymium(III) oxide)
Philippines - PICCS	N (praseodymium(III) oxide)
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
praseodymium(III) oxide	12036-32-7, 847941-37-1, 11113-81-8

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

BEI: Biological Exposure Index This document is copyright.

10M42-2 Praseodymium (10,000µg/mL in 4% HCI)

PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors

end of SDS