

**High-Purity Standards** 

Catalogue number: ICP-AM-11

Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: **06/03/2017** Print Date: **06/03/2017** S.GHS.USA.EN

### **SECTION 1 IDENTIFICATION**

#### **Product Identifier**

Product name	ICP Analytical Mixture 11
Synonyms	ICP-AM-11
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (contains nitric acid and hydrofluoric acid)
Other means of identification	ICP-AM-11

#### Recommended use of the chemical and restrictions on use

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

#### **Emergency phone number**

0 , .	
Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

#### **SECTION 2 HAZARD(S) IDENTIFICATION**

### Classification of the substance or mixture

Classification

Serious Eye Damage Category 1, Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 3, Acute Toxicity (Inhalation) Category 2, Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A

#### Label elements

Hazard pictogram(s)





SIGNAL WORD

DANGER

## Hazard statement(s)

H302	Harmful if swallowed.	
H311	in contact with skin.	
H330	Fatal if inhaled.	
H290	May be corrosive to metals.	
H314	Causes severe skin burns and eye damage.	

Page 2 of 15

**ICP Analytical Mixture 11** 

Catalogue number: ICP-AM-11 Version No: 1.1

Print Date: 06/03/2017

Issue Date: 06/03/2017

#### Hazard(s) not otherwise specified

Not Applicable

#### Precautionary statement(s) Prevention

P260

Do not breathe dust/fume/gas/mist/vapours/spray.

#### Precautionary statement(s) Response

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

#### Precautionary statement(s) Storage

P403+P233

Store in a well-ventilated place. Keep container tightly closed.

#### Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
7440-36-0	0.1	antimony
7440-42-8	0.1	<u>boron</u>
7439-98-7	0.02	molybdenum
16919-19-0	0.2	ammonium fluorosilicate
7440-31-5	0.1	<u>tin</u>
7440-32-6	0.02	titanium
7664-39-3	1	hydrofluoric acid
7697-37-2	4	nitric acid
7732-18-5	balance	water

#### **SECTION 4 FIRST-AID MEASURES**

#### Description of first aid measures

## Eye Contact

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

#### For thermal burns:

- Decontaminate area around burn.
- ▶ Consider the use of cold packs and topical antibiotics.

For first-degree burns (affecting top layer of skin)

- ▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides.
- Use compresses if running water is not available.
- Cover with sterile non-adhesive bandage or clean cloth
- ▶ Do NOT apply butter or ointments; this may cause infection.
- ▶ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur.

For second-degree burns (affecting top two layers of skin)

- ▶ Cool the burn by immerse in cold running water for 10-15 minutes.
- ▶ Use compresses if running water is not available. Do NOT apply ice as this may lower body temperature and cause further damage.
- ▶ Do NOT break blisters or apply butter or ointments; this may cause infection.
- ▶ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape. To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):

### Skin Contact

Lay the person flat.

- ▶ Elevate feet about 12 inches. Elevate burn area above heart level, if possible.
- Cover the person with coat or blanket.
- Seek medical assistance.

For third-degree burns

Seek immediate medical or emergency assistance.

#### In the mean time:

- ▶ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound.
- Separate burned toes and fingers with dry, sterile dressings.
- $\,\blacktriangleright\,$  Do not soak burn in water or apply ointments or butter; this may cause infection.
- ► To prevent shock see above.
- For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway
- Have a person with a facial burn sit up.

Chemwatch: 9-405941 Page 3 of 15
Catalogue number: ICP-AM-11

#### **ICP Analytical Mixture 11**

Issue Date: **06/03/2017**Print Date: **06/03/2017** 

▶ Check pulse and breathing to monitor for shock until emergency help arrives. If there is evidence of severe skin irritation or skin burns: ▶ Avoid further contact. Immediately remove contaminated clothing, including footwear. Flush skin under running water for 15 minutes. Avoiding contamination of the hands, massage calcium gluconate gel into affected areas, pay particular attention to creases in skin. ▶ Contact the Poisons Information Centre. Continue gel application for at least 15 minutes after burning sensation ceases. ▶ If pain recurs, repeat application of calcium gluconate gel or apply every 20 minutes. If no gel is available, continue washing for at least 15 minutes, using soap if available. If patient is conscious, give six calcium gluconate or calcium carbonate tablets in water by mouth. ▶ Transport to hospital, or doctor, urgently If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if ► Transport to hospital, or doctor, without delay. For massive exposures Inhalation ▶ If dusts, vapours, aerosols, fumes or combustion products are inhaled, remove from contaminated area. Lay patient down. ▶ Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ If victim is conscious, give six calcium gluconate or calcium carbonate tablets in water by mouth. ► Transport to hospital, or doctor, urgently. ▶ For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. red do NOT induce vomiting. Fig. 16 If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Ingestion Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.

## Most important symptoms and effects, both acute and delayed

See Section 11

Version No: 1.1

Indication of any immediate medical attention and special treatment needed

Chemwatch: 9-405941 Page 4 of 15

Catalogue number: ICP-AM-11

Version No: 1.1

### **ICP Analytical Mixture 11**

Issue Date: 06/03/2017 Print Date: 06/03/2017

Following acute or short term repeated exposure to hydrofluoric acid:

- ▶ Subcutaneous injections of Calcium Gluconate may be necessary around the burnt area. Continued application of Calcium Gluconate Gel or subcutaneous Calcium Gluconate should then continue for 3-4 days at a frequency of 4-6 times per day. If a "burning" sensation recurs, apply more frequently.
- > Systemic effects of extensive hydrofluoric acid burns include renal damage, hypocalcaemia and consequent cardiac arrhythmias. Monitor haematological, respiratory, renal, cardiac and electrolyte status at least daily. Tests should include FBE, blood gases, chest X-ray, creatinine and electrolytes, urine output, Ca ions, Mg ions and phosphate ions. Continuous ECG monitoring may be required.
- Where serum calcium is low, or clinical, or ECG signs of hypocalcaemia develop, infusions of calcium gluconate, or if less serious, oral Sandocal, should be given. Hydrocortisone 500 mg in a four to six hourly infusion may help
- Antibiotics should not be given as a routine, but only when indicated.
- Feye contact pain may be excruciating and 2-3 drops of 0.05% pentocaine hydrochloride may be instilled, followed by further irrigation

#### BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant Index Sampling Time Comments B. NS. SQ 1. Methaemoglobin in blood 1.5% of haemoglobin During or end of shift

- B: Background levels occur in specimens collected from subjects **NOT** exposed.
- NS: Non-specific determinant: Also seen after exposure to other materials
- SQ: Semi-quantitative determinant Interpretation may be ambiguous; should be used as a screening test or confirmatory test

For acute or short term repeated exposures to fluorides:

- Fluoride absorption from gastro-intestinal tract may be retarded by calcium salts, milk or antacids.
- Fluoride particulates or fume may be absorbed through the respiratory tract with 20-30% deposited at alveolar level.
- ▶ Peak serum levels are reached 30 mins. post-exposure; 50% appears in the urine within 24 hours.
- For acute poisoning (endotracheal intubation if inadequate tidal volume), monitor breathing and evaluate/monitor blood pressure and pulse frequently since shock may supervene with little warning. Monitor ECG immediately; watch for arrhythmias and evidence of Q-T prolongation or T-wave changes. Maintain monitor. Treat shock vigorously with isotonic saline (in 5% glucose) to restore blood volume and enhance renal excretion.
- ▶ Where evidence of hypocalcaemic or normocalcaemic tetany exists, calcium gluconate (10 ml of a 10% solution) is injected to avoid tachycardia.

#### **BIOLOGICAL EXPOSURE INDEX - BEI**

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Sampling Time Comments Determinant Index 3 mg/gm creatinine Fluorides in urine Prior to shift B. NS 10mg/gm creatinine End of shift

B: Background levels occur in specimens collected from subjects NOT exposed

NS: Non-specific determinant; also observed after exposure to other exposures.

#### **SECTION 5 FIRE-FIGHTING MEASURES**

#### **Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used
- Use extinguishing media suitable for surrounding area.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

None known

#### Special protective equipment and precautions for fire-fighters

	Alert i lie brigade and tell them location and hattie of hazard.
	Wear breathing apparatus plus protective gloves in the event of a fire.
	Prevent, by any means available, spillage from entering drains or water courses.
Fine Finisher	<ul> <li>Use fire fighting procedures suitable for surrounding area.</li> </ul>
Fire Fighting	▶ DO NOT approach containers suspected to be hot

- If safe to do so, remove containers from path of fire.

A Nort Eiro Prigado and tall them location and nature of hazard

- ▶ Equipment should be thoroughly decontaminated after use
- Fire/Explosion Hazard
- ▶ Non combustible
- Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.

Cool fire exposed containers with water spray from a protected location.

- May emit corrosive, poisonous fumes. May emit acrid smoke.

May emit poisonous fumes

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Chemwatch: 9-405941 Catalogue number: ICP-AM-11

Version No: 1.1

## **ICP Analytical Mixture 11**

Page 5 of 15

Issue Date: 06/03/2017 Print Date: 06/03/2017

Minor Spills

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eves
- Control personal contact with the substance, by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

**Major Spills** 

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 HANDLING AND STORAGE**

#### Precautions for safe handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
  - When handling, DO NOT eat, drink or smoke
  - Keep containers securely sealed when not in use.
  - Avoid physical damage to containers.
  - Always wash hands with soap and water after handling.
  - ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.
  - Use good occupational work practice.
  - Observe manufacturer's storage and handling recommendations contained within this SDS.
  - ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

## Other information

Safe handling

- ▶ Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

#### Conditions for safe storage, including any incompatibilities

- ▶ Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- ▶ Packing as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

For low viscosity materials

- ▶ Drums and jerricans must be of the non-removable head type.
- $\,\blacktriangleright\,$  Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging;
- ▶ Cans with friction closures and
- ▶ low pressure tubes and cartridges may be used.

## Suitable container

Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages \*

In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage \*.

\* unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.

- ▶ Material is corrosive to most metals, glass and other siliceous materials.
- ▶ WARNING: Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.
- ► The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive.
- ▶ Avoid reaction with borohydrides or cyanoborohydrides

Salts of inorganic fluoride:

- react with water forming acidic solutions.
- reviolent reactive with boron, bromine pentafluoride, bromine trifluoride, calcium disilicide, calcium hydride, oxygen difluoride, platinum, potassium.
- in aqueous solutions are incompatible with sulfuric acid, alkalis, ammonia, aliphatic amines, alkanolamines, alkylene oxides, amides, epichlorohydrin, isocyanates, nitromethane, organic anhydrides, vinyl acetate.
- ▶ corrode metals in presence of moisture Storage incompatibility
  - ▶ may be incompatible with glass and porcelain
  - Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.

#### Hydrogen fluoride:

- reacts violently with strong oxidisers, acetic anhydride, alkalis, 2-aminoethanol, arsenic trioxide (with generation of heat), bismuthic acid, calcium oxide, chlorosulfonic acid, cyanogen fluoride, ethylenediamine, ethyleneimine, fluorine (fluorine gas reacts vigorously with a 50% hydrofluoric acid solution and may burst into flame), nitrogen trifluoride, N-phenylazopiperidine, oleum, oxygen difluoride, phosphorus pentoxide, potassium permanganate, potassium tetrafluorosilicate(2-), beta-propiolactone, propylene oxide, sodium, sodium tetrafluorosilicate, sulfuric acid, vinyl acetate
- reacts (possibly violently) with aliphatic amines, alcohols, alkanolamines, alkylene oxides, aromatic amines, amides, ammonia, ammonium hydroxide, epichlorohydrin, isocyanates, metal acetylides, metal silicides, methanesulfonic acid, nitrogen compounds, organic anhydrides, oxides, silicon compounds, vinylidene fluoride
- attacks glass and siliceous materials, concrete, ceramics, metals (flammable hydrogen gas may be produced), metal alloys, some plastics, rubber coatings,

Catalogue number: **ICP-AM-11** Version No: **1.1** 

Issue Date: **06/03/2017**Print Date: **06/03/2017** 

- ▶ leather, and most other materials with the exception of lead, platinum, polyethylene, wax.
- Avoid strong bases.

## **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

## **Control parameters**

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	antimony	Antimony metal, Antimony powder, Stibium	0.5 mg/m3	Not Available	Not Available	[*Note: The REL also applies to other antimony compounds (as Sb).]
US NIOSH Recommended Exposure Limits (RELs)	molybdenum	Molybdenum metal	0.5 mg/m3	Not Available	Not Available	See Appendix D
US ACGIH Threshold Limit Values (TLV)	molybdenum	Molybdenum, as Mo	Not Available	Not Available	Not Available	TLV® Basis: LRT irr
US NIOSH Recommended Exposure Limits (RELs)	tin	Metallic tin, Tin flake, Tin metal, Tin powder	2 mg/m3	Not Available	Not Available	[*Note: The REL also applies to other inorganic tin compounds (as Sn) except tin oxides.]
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrofluoric acid	Hydrogen fluoride	2.5 mg/m3 / 3 ppm	Not Available	5 mg/m3 / 6 ppm	See Table Z-2;(as F)
US OSHA Permissible Exposure Levels (PELs) - Table Z2	hydrofluoric acid	Hydrogen fluoride	3 ppm	Not Available	2 ppm	(Z37.28–1969)
US NIOSH Recommended Exposure Limits (RELs)	hydrofluoric acid	Anhydrous hydrogen fluoride; Aqueous hydrogen fluoride (i.e., Hydrofluoric acid); HF-A	0.5 ppm	Not Available	Not Available	[15-minute]
US ACGIH Threshold Limit Values (TLV)	hydrofluoric acid	Hydrogen fluoride, as F	Not Available	Not Available	Not Available	TLV® Basis: URT, LRT, skin, & eye irr; fluorosis; BEI
US OSHA Permissible Exposure Levels (PELs) - Table Z1	nitric acid	Nitric acid	5 mg/m3 / 2 ppm	10 mg/m3 / 4 ppm	Not Available	TLV® Basis: URT & eye irr; dental erosion
US NIOSH Recommended Exposure Limits (RELs)	nitric acid	Aqua fortis, Engravers acid, Hydrogen nitrate, Red fuming nitric acid (RFNA), White fuming nitric acid (WFNA)	5 mg/m3 / 2 ppm	4 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	nitric acid	Nitric acid	2 ppm	Not Available	Not Available	Not Available

## EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
antimony	Antimony	1.5 mg/m3	13 mg/m3	80 mg/m3
boron	Boron	1.9 mg/m3	21 mg/m3	130 mg/m3
molybdenum	Molybdenum	30 mg/m3	330 mg/m3	2,000 mg/m3
ammonium fluorosilicate	Ammonium hexafluorosilicate; (Ammonium silicofluoride)	12 mg/m3	130 mg/m3	780 mg/m3
tin	Tin	6 mg/m3	67 mg/m3	400 mg/m3
titanium	Titanium	30 mg/m3	330 mg/m3	2,000 mg/m3
hydrofluoric acid	Hydrogen fluoride; (Hydrofluoric acid)	Not Available	Not Available	Not Available
nitric acid	Nitric acid	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH	
antimony	80 mg/m3	50 mg/m3	
boron	Not Available	Not Available	
molybdenum	N.E. / N.E.	5,000 mg/m3	
ammonium fluorosilicate	Not Available	Not Available	
tin	Unknown mg/m3 / 400 mg/m3 / Unknown ppm	25 mg/m3 / 100 mg/m3	
titanium	Not Available	Not Available	
hydrofluoric acid	30 ppm	30 [Unch] ppm	
nitric acid	100 ppm	25 ppm	
water	Not Available	Not Available	

#### **Exposure controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

# Appropriate engineering controls

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Version No: 1.1

### **ICP Analytical Mixture 11**

Issue Date: 06/03/2017 Print Date: 06/03/2017

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range	
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	
3: Intermittent, low production.	3: High production, heavy use	
4: Large hood or large air mass in motion	4: Small hood-local control only	

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

#### Personal protection











## Eye and face protection

Chemical goggles Full face shield may be required for supplementary but never for primary protection of eyes.

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH

Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] Skin protection

#### Hands/feet protection

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber
- ▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

## **Body protection**

See Other protection below

## Other protection

- Overalls.
- Evewash unit.
  - Barrier cream. Skin cleansing cream.
- Thermal hazards

Not Available

#### Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

Appearance	colorless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available

Chemwatch: 9-405941

Catalogue number: ICP-AM-11

Version No: 1.1

**ICP Analytical Mixture 11** 

Page 8 of 15 Issue Date: 06/03/2017 Print Date: 06/03/2017

Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

#### **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

Information on to	xicological	effects
-------------------	-------------	---------

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. Bronchial and alveolar exudate are apparent in animals exposed to molybdenum by inhalation. Molybdenum fume may produce bronchial irritation and moderate fatty changes in liver and kidney. Acute effects of fluoride inhalation include irritation of nose and throat, coughing and chest discomfort. A single acute over-exposure may even cause nose bleed. Inhaled Acute inhalation of hydrogen fluoride (hydrofluoric acid) vapours causes severe irritation of the eye, nose and throat, delayed fever, bluing of the extremities and water in the lungs, and may cause death. The above irritation occurs even with fairly low concentrations of hydrogen fluoride. Hydrogen fluoride has a strong irritating odour, that can be detected at concentrations of about 0.04 parts per million. Higher levels cause corrosion of the throat, nose and lungs, leading to severe inflammation and water buildup in the lungs (which may occur with 1 hour of exposure). A vapour concentration of 10 parts per million is regarded as intolerable, but a vapour concentration of 30 parts per million is considered as immediately dangerous to life and health. It is estimated that the lowest lethal concentration for a 5-minute human exposure to hydrogen fluoride is in the range of 50 to 250 parts per million. Exposure by either skin contact or inhalation may lead to low levels of calcium and magnesium in the blood, which may result in heart rhythm disturbances. Animal testing suggests that repeated exposure produces liver and kidney damage. ixic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. Ingestion Molybdenum, an essential trace element, can in large doses hamper growth and cause loss of appetite, listlessness and diarrhoea. Anaemia also occurs, and other symptoms include greying of hair, shrinking of the testicles, reduced fertility and milk production, shortness of breath, incoordination and irritation of the mucous membranes. Fluoride causes severe loss of calcium in the blood, with symptoms appearing several hours later including painful and rigid muscle contractions of the limbs. Cardiovascular collapse can occur and may cause death with increased heart rate and other heart rhythm irregularities. Skin contact with the material may produce toxic effects; systemic effects may result following absorption. The material can produce chemical burns following direct contact with the skin. Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.

#### Skin Contact

Contact of the skin with liquid hydrofluoric acid (hydrogen fluoride) may cause severe burns, erythema, and swelling, vesiculation, and serious crusting. With more serious burns, ulceration, blue-gray discoloration, and necrosis may occur. Solutions of hydrofluoric acid, as dilute as 2%, may cause severe skin burns. Fluorides are easily absorbed through the skin and cause death of soft tissue and erode bone. Healing is delayed and death of tissue may continue to spread beneath skin.

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

### Eye

The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage

Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely.

Animal testing showed that a 20% solution of hydrofluoric acid (hydrogen fluoride) in water caused immediate damage in the form of total clouding of the lens and ischaemia of the conjunctiva. Swelling of the stroma of the cornea occurred within 1 hour, followed by tissue death (necrosis) of structures of the front of the

Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

High levels of molybdenum can cause joint problems in the hands and feet with pain and lameness. Molybdenum compounds can also cause liver changes with elevated levels of enzymes and cause over-activity of the thyroid gland.

Chronic

Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs.

Extended exposure to inorganic fluorides causes fluorosis, which includes signs of joint pain and stiffness, tooth discolouration, nausea and vomiting, loss of appetite, diarrhoea or constipation, weight loss, anaemia, weakness and general unwellness. There may also be frequent urination and thirst.

Issue Date: **06/03/2017**Print Date: **06/03/2017** 

Version No: 1.1

Hydrogen fluoride easily penetrates the skin and causes destruction and corrosion of the bone and underlying tissue. Ingestion causes severe pains and burns in the mouth and throat and blood calcium levels are dangerously reduced. TOXICITY IRRITATION ICP Analytical Mixture 11 Not Available Not Available TOXICITY IRRITATION Dermal (rabbit) LD50: >8300 mg/kg<sup>[1]</sup> antimony Not Available Oral (rat) LD50: 100  $mg/kg^{[2]}$ TOXICITY IRRITATION boron Oral (rat) LD50: 650  $mg/kg^{[2]}$ Not Available TOXICITY IRRITATION dermal (rat) LD50: >2000 mg/kg<sup>[1]</sup> Not Available molvbdenum Oral (rat) LD50: >2000 mg/kg<sup>[1]</sup> TOXICITY IRRITATION ammonium fluorosilicate Oral (mouse) LD50: 70 mg/kg<sup>[2]</sup> Not Available TOXICITY IRRITATION dermal (rat) LD50: >2000 mg/kg<sup>[1]</sup> Not Available tin Oral (rat) LD50: >2000 mg/kg<sup>[1]</sup> TOXICITY IRRITATION titanium Oral (rat) LD50: >2000 mg/kg<sup>[1]</sup> Not Available TOXICITY IRRITATION Inhalation (rat) LC50: 1276 ppm/4hr<sup>[2]</sup> Eye (human): 50 mg - SEVERE hydrofluoric acid Inhalation (rat) LC50: 319 ppm/1hr<sup>[2]</sup> TOXICITY IRRITATION nitric acid Inhalation (rat) LC50: 625 ppm/1h\*t[2] Not Available IRRITATION TOXICITY Not Available Not Available 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data Legend: extracted from RTECS - Register of Toxic Effect of chemical Substances BORON Elemental boron produces lower foetal body weight in rats. HYDROFLUORIC ACID (liver and kidney damage) [Manufacturer] for hydrogen fluoride (as vapour) Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. NITRIC ACID The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Oral (?) LD50: 50-500 mg/kg \* [Various Manufacturers] **BORON &** HYDROFLUORIC ACID & Asthma-like symptoms may continue for months or even years after exposure to the material ends. NITRIC ACID MOLYBDENUM & TIN & TITANIUM & No significant acute toxicological data identified in literature search. **HYDROFLUORIC ACID &** WATER **HYDROFLUORIC ACID &** The material may produce severe irritation to the eye causing pronounced inflammation. NITRIC ACID **HYDROFLUORIC ACID &** The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. NITRIC ACID

Issue Date: **06/03/2017** Print Date: **06/03/2017** 

Acute Toxicity 0 Carcinogenicity Skin Irritation/Corrosion Reproductivity 0 Serious Eye Damage/Irritation STOT - Single Exposure 0 Respiratory or Skin 0 STOT - Repeated Exposure 0 sensitisation Aspiration Hazard Mutagenicity 0 0

Legend:

- 🗶 Data available but does not fill the criteria for classification
- Data available to make classification
- Data Not Available to make classification

## **SECTION 12 ECOLOGICAL INFORMATION**

### Toxicity

CD Applytical Mixture 11	ENDPOINT TEST DURATION (HR)			SPECIES VALUI		UE SOI		URCE	
CP Analytical Mixture 11	Not Applicable		Not Applicable		Not Applicable	Not Applic	able	Not	Applicable
	ENDPOINT	TEG	PT DUD ATION (UD)	enec	IEC .		VALUE		SOURCE
	LC50	TEST DURATION (HR)		Fish	SPECIES			0.93mg/L	
	EC50	96			2002		1mg/L		2
antimony	EC50	72		Crustacea  Algae or other aquatic plants			>2.4mg/L		2
	EC50	96			Crustacea				2
	NOEC	720		Fish			0.5mg/L >0.0075mg/L		2
	NOLO	720		1 1311			20.0073111	9'-	
	ENDPOINT	TE	ST DURATION (HR)	SPE	CIES		VALUE	<u> </u>	SOURCE
	LC50	96		Fish			74mg/L	_	2
	EC50	48		Crus	stacea		230mg	/L	5
boron	EC50	72		Alga	e or other aquatic plant	S	54mg/L	_	2
	BCF	336	3	Alga	e or other aquatic plant	S	8.5mg/		4
	EC50	336	3	Alga	e or other aquatic plant	S	8.5mg/	L	4
	NOEC	576	3	Fish	ı		0.001m	ng/L	5
	_								
	ENDPOINT	TE	TEST DURATION (HR)		SPECIES		VALUE		SOURCE
	LC50	96	96		Fish			609.1mg/L	
	EC50	72		Alga	Algae or other aquatic plants		289.2mg/L		2
molybdenum	BCF	336	3	Alga	Algae or other aquatic plants		64mg/L	64mg/L	
	EC50	336	3	Alga	Algae or other aquatic plants		64mg/L	_	4
	NOEC	672	2	Crus	stacea		0.67mg	3/L	2
nmonium fluorosilicate	ENDPOINT		TEST DURATION (HR)		SPECIES	VALUE		so	URCE
imonium nuorosiiicate	Not Applicable		Not Applicable		Not Applicable	Not Applic	able	Not	Applicable
	ENDPOINT	TES	ST DURATION (HR)	SPEC	IES		VALUE		SOURCE
	LC50	96		Fish	Fish			>0.0124mg/L	
tin	EC50	48	48		Crustacea			0.00018mg/L	
	EC50 72 Algae or other aquatic plants			>0.0192mg/L 2					
	EC50	72	72		Algae or other aquatic plants		>0.0192mg/L		2
	NOEC	168	168		Crustacea			<0.005mg/L 2	
	ENDPOINT	те	ET DURATION (UR)	ene	CIEC		\/A1 111	_	SOURCE
titanium	EC50	4.5	ST DURATION (HR)		Algae or other aquatic plants		VALUE		SOURCE 2
utamum	NOEC	4.5			Algae or other aquatic plants  Crustacea		1mg/L		
	INOLO	140		Cita	Juona		IIIIg/L		
	ENDPOINT		TEST DURATION (HR)		SPECIES	VAL	UE		SOURCE
	LC50		96		Fish				
hydrofluoric acid	EC50		48		Crustacea		0mg/L		1
							26-48mg/L 2		

Chemwatch: 9-405941

Issue Date: 06/03/2017

Page 11 of 15 Catalogue number: ICP-AM-11 Print Date: 06/03/2017 **ICP Analytical Mixture 11** Version No: 1.1

	NOEC	504		Fish	4mg/L	2
	ENDPOINT	TEST DURATION (HR)		SPECIES	VALUE	SOURCE
nitric acid	NOEC	16		Crustacea	107mg/L	4
water	ENDPOINT	( )	SPECIES		UE	SOURCE
	Not Applicable	Not Applicable	Not Appl	icable Not	Applicable	Not Applicable
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

For Fluorides: Small amounts of fluoride have beneficial effects however; excessive intake over long periods may cause dental and/or skeletal fluorosis. Fluorides are absorbed by humans following inhalation of workplace and ambient air that has been contaminated, ingestion of drinking water and foods and dermal contact. Populations living in areas with high fluoride levels in groundwater may be exposed to higher levels of fluorides in their drinking water or in beverages prepared with the water. Among these populations, outdoor labourers, people living in hot climates, and people with excessive thirst will generally have the greatest daily intake of fluorides because they consume greater amounts of water

Atmospheric Fate: Both hydrogen fluoride and particulate fluorides will be transported in the atmosphere and deposited on land or water by wet and dry deposition. Non-volatile inorganic fluoride particulates are removed from the atmosphere via condensation or nucleation processes. Fluorides adsorbed on particulate matter in the atmosphere are generally stable and are not readily hydrolyzed, although they may be degraded by radiation if they persist in the atmosphere. Fluorine and the silicon fluorides, silicofluorides) are hydrolyzed in the atmosphere to form hydrogen fluoride. Hydrogen fluoride may combine with water vapour to produce an aerosol or fog of aqueous hydrofluoric acid. Inorganic fluoride compounds, with the exception of sulfur hexafluoride, are not expected to remain in the troposphere for long periods or to migrate to the stratosphere. Estimates of the residence time of sulfur hexafluoride in the atmosphere range from 500 to several thousand years. Fluoride in aerosols can be transported over large distances by wind or as a result of atmospheric turbulence. Fluorosilicic acid and hydrofluoric acid in high aquatic concentrations such as may be found in industrial waste ponds may volatilize, releasing silicon tetrafluoride and hydrogen fluoride into the atmosphere. Soluble inorganic fluorides may also form aerosols at the air/water interface or vaporize into the atmosphere whereas undissolved species generally undergo sedimentation.

Terrestrial Fate: Soils - Atmospheric fluorides may be transported to soils and surface waters through both wet and dry deposition processes where they may form complexes and bind strongly to soil and sediment. Solubilisation of inorganic fluorides from minerals may also be enhanced by the presence of bentonite clays and humic acid. Factors that influence the mobility of inorganic fluorides in soil are pH and the formation of aluminium and calcium complexes. In more acidic soils, concentrations of inorganic fluoride were considerably higher in the deeper horizons. The low affinity of fluorides for organic material results in leaching from the more acidic surface horizon and increased retention by clay minerals and silts in the more alkaline, deeper horizons. The maximum adsorption of fluoride to soil was reported to occur at pH 5.5. In acidic soils with pH below 6, most of the fluoride is in complexes with either aluminium or iron. Fluoride in alkaline soils at pH 6.5 and above is almost completely fixed in soils as calcium fluoride, if sufficient calcium carbonate is available. Fluoride is extremely immobile in soil.

Aquatic Fate: Fresh Water: - In water, the transport and transformation of inorganic fluorides are influenced by pH, water hardness and the presence of ion-exchange materials such as clays. In natural water, fluoride forms strong complexes with aluminium in water, and fluorine chemistry in water is largely regulated by aluminium concentration and pH. Below pH 5, fluoride is almost entirely complexed with aluminium and consequently, the concentration of free F- is low. Once dissolved, inorganic fluorides remain in solution under conditions of low pH and hardness and in the presence of ion-exchange material. Sea Water - Fluoride forms stable complexes with calcium and magnesium, which are present in sea water. Calcium carbonate precipitation dominates the removal of dissolved fluoride from sea water. The residence time for fluoride in ocean sediment is calculated to be 2-3 million years.

Ecotoxicity: Fluorides have been shown to accumulate in animals that consume fluoride-containing foliage. However, accumulation is primarily in skeletal tissue and therefore, it is unlikely that fluoride will biomagnify up the food chain.

#### For Molybdenum:

Environmental Fate: Molybdenum is an essential micronutrient in plants and animals. It is commonly used in the manufacture of steel alloys. Based on the high concentration of molybdenum in all analyzed waste types, the exposure of the environment to molybdenum is regarded as significant. The limited amount of data regarding its toxicity makes it impossible to evaluate the potential for adverse environmental and health effects from molybdenum exposure. Molybdenum is generally found in two oxidation states in nature, Mo(IV) and Mo(VI). In oxidizing environments, Mo(VI) dominates and it is commonly present as molybdate. Natural molybdenum contains seven isotopes. Molybdenum oxidizes at elevated temperatures.

Atmospheric Fate: Molybdenum can be deposited via dry/wet deposition; however, atmospheric exposure has been identified as a minor source to terrestrial and aquatic habitats. Terrestrial Fate: Molybdenum is a naturally occurring substance in soil. Soil molybdenum is a potentially toxic element, but no cases have been reported of molybdenum toxicity to animals from consumption of forage grown on sludge-amended soils. Microbes are expected to transform the substance.

Aquatic Fate: Molybdenum disulfide is sparingly soluble in water but oxidizes to more soluble molybdates, which are stable in water. At pH 3-5, molybdate frequently shifts to hydrogen molybdate. Low pH molybdenum is usually adsorbed to sediment composed of clay, or other minerals that are prone to weathering. Molybdenum in the water is expected to be taken up by aquatic organisms. Concentrations of the substance in sediments are by site-specific factors like flow rate, and other factors, (e.g. organic content, pH)

Ecotoxicology: Molybdenum cause adverse effects in ruminant animals. Livestock have been injured by forage grown on soils containing the element. The substance 🕈 s toxicological properties in mammals are governed, to a large extent, by its interaction with copper and sulfur; residues of molybdenum alone are not sufficient to diagnose poisoning by the substance. Domestic ruminants, especially cattle, are especially sensitive to molybdenum poisoning, when copper and inorganic sulfate are deficient. The resistance of small laboratory animals, and wildlife, is at least 10X that of cattle. Mule deer are not adversely affected by the substance. The substance may have a negative impact on reproduction in domestic birds and there is inadequate data on its effects on waterfowl and most mammals

#### Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

DO NOT discharge into s

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
water	LOW	LOW	

## Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

#### Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)

## **SECTION 13 DISPOSAL CONSIDERATIONS**

### Page 12 of 15

#### **ICP Analytical Mixture 11**

Issue Date: **06/03/2017** Print Date: **06/03/2017** 

Version No: 1.1

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

#### Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

# Product / Packaging disposal

- Where possible retain label warnings and 5DS and observe all notices pertaining to the product.
   Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

### **SECTION 14 TRANSPORT INFORMATION**

#### **Labels Required**



Marine Pollutant

NO

### Land transport (DOT)

UN number	3264				
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (contains nitric acid and hydrofluoric acid)				
Transport hazard class(es)	Class 8 Subrisk Not Applicable				
Packing group	II				
Environmental hazard	Not Applicable				
Special precautions for user	Hazard Label 8 Special provisions 386, B2, IB2, T11, TP2, TP27				

#### Air transport (ICAO-IATA / DGR)

### Sea transport (IMDG-Code / GGVSee)

UN number	3264				
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains nitric acid and hydrofluoric acid)				
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable				
Packing group	П				
Environmental hazard	Not Applicable				

Page 13 of 15

Version No: 1.1

**ICP Analytical Mixture 11** 

Issue Date: 06/03/2017 Print Date: 06/03/2017

Special precautions for user

Catalogue number: ICP-AM-11

EMS Number	F-A, S-B
Special provisions	274
Limited Quantities	1 L

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Product name	Pollution Category	Ship Type
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Nitric acid (70% and over) Nitric acid (less than 70%)	Y; Y	2 2

#### **SECTION 15 REGULATORY INFORMATION**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

ANTIMONY(7440-36-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV)
US - Michigan Exposure Limits for Air Contaminants	US Clean Air Act - Hazardous Air Pollutants
US - Minnesota Permissible Exposure Limits (PELs)	US CWA (Clean Water Act) - Priority Pollutants
US - Oregon Permissible Exposure Limits (Z-1)	US CWA (Clean Water Act) - Toxic Pollutants
US - Pennsylvania - Hazardous Substance List	US EPCRA Section 313 Chemical List
US - Rhode Island Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### BORON(7440-42-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	;
Monographs	

- US California OEHHA/ARB Chronic Reference Exposure Levels and Target Organs (CRELs)
- US California Permissible Exposure Limits for Chemical Contaminants
- US Hawaii Air Contaminant Limits
- US Michigan Exposure Limits for Air Contaminants
- US Oregon Permissible Exposure Limits (Z-1)

- US Tennessee Occupational Exposure Limits Limits For Air Contaminants
- US Washington Permissible exposure limits of air contaminants
- US Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
- US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
- US EPA Carcinogens Listing
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory

#### MOLYBDENUM(7439-98-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Idaho - Limits for Air Contaminants	Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US - Washington Permissible exposure limits of air contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV)
US - Pennsylvania - Hazardous Substance List	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Rhode Island Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table Z1
	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### AMMONIUM FLUOROSILICATE(16919-19-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
Monographs	Contaminants
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US - Washington Permissible exposure limits of air contaminants
(CRELs)	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration,
US - Idaho - Limits for Air Contaminants	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
US - Massachusetts - Right To Know Listed Chemicals	US CWA (Clean Water Act) - List of Hazardous Substances
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-2)	US OSHA Permissible Exposure Levels (PELs) - Table Z2
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US - Oregon Permissible Exposure Limits (Z-2)	US OSHA Permissible Exposure Levels (PELs) - Table Z2
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
TIN(7440-31-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Idaho - Limits for Air Contaminants	Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US - Washington Permissible exposure limits of air contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### TITANIUM(7440-32-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemwatch: 9-405941 Page 14 of 15

Catalogue number: ICP-AM-11

Version No: 1.1

### **ICP Analytical Mixture 11**

Issue Date: 06/03/2017 Print Date: 06/03/2017

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)

- US California Permissible Exposure Limits for Chemical Contaminants
- US Hawaii Air Contaminant Limits
- US Michigan Exposure Limits for Air Contaminants

US - Rhode Island Hazardous Substance List

- US Oregon Permissible Exposure Limits (Z-1)
- US Tennessee Occupational Exposure Limits Limits For Air Contaminants
- US Washington Permissible exposure limits of air contaminants
- US Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory

## HYDROFLUORIC ACID(7664-39-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
(CRELs)	US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration,
US - California Permissible Exposure Limits for Chemical Contaminants	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV)
US - Idaho - Acceptable Maximum Peak Concentrations	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Idaho - Limits for Air Contaminants	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Massachusetts - Right To Know Listed Chemicals	US Clean Air Act - Hazardous Air Pollutants
US - Michigan Exposure Limits for Air Contaminants	US CWA (Clean Water Act) - List of Hazardous Substances
US - Minnesota Permissible Exposure Limits (PELs)	US EPCRA Section 313 Chemical List
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-2)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z2

#### NITRIC ACID(7697-37-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
Passenger and Cargo Aircraft	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Alaska Limits for Air Contaminants	Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Massachusetts - Right To Know Listed Chemicals	US CWA (Clean Water Act) - List of Hazardous Substances
US - Michigan Exposure Limits for Air Contaminants	US EPCRA Section 313 Chemical List
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1

US SARA Section 302 Extremely Hazardous Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

able Z1 US SARA Section 302 Extremely Hazardous Substances US - Pennsylvania - Hazardous Substance List US - Rhode Island Hazardous Substance List US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

## WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

## **Federal Regulations**

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

## SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

#### US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Antimony	5000	2270
Ammonium silicofluoride	1000	454
Hydrofluoric acid	100	45.4
Nitric acid	1000	454

#### **State Regulations**

#### US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status
Australia - AICS	Y

Chemwatch: **9-405941** Page **15** of **15** 

Catalogue number: ICP-AM-11

Version No: 1.1

#### **ICP Analytical Mixture 11**

Issue Date: **06/03/2017**Print Date: **06/03/2017** 

Canada - DSL	Y
Canada - NDSL	N (titanium; boron; water; antimony; ammonium fluorosilicate; molybdenum; tin; hydrofluoric acid; nitric acid)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (titanium; boron; water; antimony; ammonium fluorosilicate; molybdenum; tin; hydrofluoric acid; nitric acid)
Korea - KECI	Y
New Zealand - NZIoC	Υ
Philippines - PICCS	Y
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

#### **SECTION 16 OTHER INFORMATION**

#### Other information

#### Ingredients with multiple cas numbers

Name	CAS No
ammonium fluorosilicate	16919-19-0, 1309-32-6
hydrofluoric acid	7664-39-3, 790596-14-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.