

6020-ICSA

High-Purity Standards

Catalogue number: ICP-MS-ICS-3 Solution A

Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: **05/23/2017** Print Date: **05/23/2017** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	6020-ICSA
Synonyms	ICP-MS-ICS-3 Solution A
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Other means of identification	ICP-MS-ICS-3 Solution A

Recommended use of the chemical and restrictions on use

Relevant identified uses INTEGRITY CHECK: Product contains BOTH an acid and a base as ingredients.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards	
Address	PO Box 41727 SC 29423 United States	
Telephone	843-767-7900	
Fax	843-767-7906	
Website	ghpuritystandards.com	
Email	Not Available	

Emergency phone number

0 , .	
Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

Classification

Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 4, Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1A

Label elements

Hazard pictogram(s)





SIGNAL WORD D

DANGER

Hazard statement(s)

H302	Harmful if swallowed.	
H312 Harmful in contact with skin.		
H290	May be corrosive to metals.	
H314	Causes severe skin burns and eye damage.	

Version No: 1.1

6020-ICSA

Issue Date: **05/23/2017**Print Date: **05/23/2017**

Not Applicable

Precautionary statement(s) Prevention

P260

Do not breathe dust/fume/gas/mist/vapours/spray.

Precautionary statement(s) Response

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Precautionary statement(s) Storage

P405

Store locked up.

Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7429-90-5	0.1	aluminium
7440-70-2	0.3	calcium
7439-89-6	0.25	<u>iron</u>
7439-95-4	0.1	<u>magnesium</u>
7439-98-7	0.002	molybdenum
7722-76-1	0.1	ammonium phosphate, monobasic
7440-09-7	0.1	potassium
7440-23-5	0.25	sodium
75-75-2	0.1	methanesulfonic acid
7440-32-6	0.002	titanium
631-61-8	0.2 (as C)	ammonium acetate
12125-02-9	1.8	ammonium chloride
7697-37-2	2	nitric acid
7664-39-3	0-0.49	hydrofluoric acid
7732-18-5	Balance	water

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact

If this product comes in contact with the eyes

- ▶ Immediately hold eyelids apart and flush the eye continuously with running water.
- ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ► Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

For thermal burns:

- Decontaminate area around burn.
- ▶ Consider the use of cold packs and topical antibiotics.

For first-degree burns (affecting top layer of skin)

- ▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides.
- Use compresses if running water is not available.
- ► Cover with sterile non-adhesive bandage or clean cloth.
- Do NOT apply butter or ointments; this may cause infection.
- ▶ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur.

For second-degree burns (affecting top two layers of skin)

- Cool the burn by immerse in cold running water for 10-15 minutes.
- Skin Contact

 Use compresses if running water is not available.
 - ► Do NOT apply ice as this may lower body temperature and cause further damage.
 - ▶ Do NOT break blisters or apply butter or ointments; this may cause infection.
 - ▶ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape.

To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):

- ► Lay the person flat.
- ► Elevate feet about 12 inches.
- ▶ Elevate burn area above heart level, if possible.
- Cover the person with coat or blanket.
- Seek medical assistance.

For third-degree burns

Seek immediate medical or emergency assistance.

Version No: 1.1

6020-ICSA

Issue Date: 05/23/2017

Print Date: 05/23/2017

In the mean time:

- Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound.
- Separate burned toes and fingers with dry, sterile dressings.
- Do not soak burn in water or apply ointments or butter; this may cause infection.
- To prevent shock see above.
- For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway.
- ▶ Have a person with a facial burn sit up.
- Check pulse and breathing to monitor for shock until emergency help arrives.

If there is evidence of severe skin irritation or skin burns:

- ► Avoid further contact. Immediately remove contaminated clothing, including footwear.
- ▶ Flush skin under running water for 15 minutes.
- Avoiding contamination of the hands, massage calcium gluconate gel into affected areas, pay particular attention to creases in skin.
- Contact the Poisons Information Centre
- Continue gel application for at least 15 minutes after burning sensation ceases.
- If pain recurs, repeat application of calcium gluconate gel or apply every 20 minutes.
- If no gel is available, continue washing for at least 15 minutes, using soap if available. If patient is conscious, give six calcium gluconate or calcium carbonate tablets in water by mouth.
- Transport to hospital, or doctor, urgently.
- If fumes or combustion products are inhaled remove from contaminated area.
- ▶ Lay patient down. Keep warm and rested.
- ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary
- Transport to hospital, or doctor, without delay.
- ► Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.
- Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).
- As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.

▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her.

(ICSC13719)

For massive exposures:

- ▶ If dusts, vapours, aerosols, fumes or combustion products are inhaled, remove from contaminated area.
- Lav patient down.
- Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if
- If victim is conscious, give six calcium gluconate or calcium carbonate tablets in water by mouth.
- Transport to hospital, or doctor, urgently.

Ingestion

Inhalation

- ▶ For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- ved do **NOT** induce vomiti
 - Fig. 16 If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

 - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 - ▶ Transport to hospital or doctor without delay.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Following acute or short term repeated exposure to hydrofluoric acid:

- > Subcutaneous injections of Calcium Gluconate may be necessary around the burnt area. Continued application of Calcium Gluconate Gel or subcutaneous Calcium Gluconate should then continue for 3-4 days at a frequency of 4-6 times per day. If a "burning" sensation recurs, apply more frequently.
- Systemic effects of extensive hydrofluoric acid burns include renal damage, hypocalcaemia and consequent cardiac arrhythmias. Monitor haematological, respiratory, renal, cardiac and electrolyte status at least daily. Tests should include FBE, blood gases, chest X-ray, creatinine and electrolytes, urine output, Ca ions, Mg ions and phosphate ions. Continuous ECG monitoring may be required.
- Where serum calcium is low, or clinical, or ECG signs of hypocalcaemia develop, infusions of calcium gluconate, or if less serious, oral Sandocal, should be given. Hydrocortisone 500 mg in a four to six hourly infusion may help
- Antibiotics should not be given as a routine, but only when indicated.
- Eye contact pain may be excruciating and 2-3 drops of 0.05% pentocaine hydrochloride may be instilled, followed by further irrigation

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Comments Sampling Time 1.5% of haemoglobin B. NS. SQ 1. Methaemoglobin in blood During or end of shift

B: Background levels occur in specimens collected from subjects NOT exposed.

NS: Non-specific determinant; Also seen after exposure to other materials

SQ: Semi-quantitative determinant - Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

For acute or short term repeated exposures to fluorides:

- Fluoride absorption from gastro-intestinal tract may be retarded by calcium salts, milk or antacids.
- Fluoride particulates or fume may be absorbed through the respiratory tract with 20-30% deposited at alveolar level.
- Peak serum levels are reached 30 mins. post-exposure; 50% appears in the urine within 24 hours.
- For acute poisoning (endotracheal intubation if inadequate tidal volume), monitor breathing and evaluate/monitor blood pressure and pulse frequently since shock may supervene with little warning. Monitor ECG immediately; watch for arrhythmias and evidence of Q-T prolongation or T-wave changes. Maintain monitor. Treat shock vigorously with isotonic saline (in 5% glucose) to

Chemwatch: 9-401297

Page 4 of 17

Catalogue number: ICP-MS-ICS-3 Solution A

Version No: 1.1

6020-ICSA

Issue Date: **05/23/2017**Print Date: **05/23/2017**

- restore blood volume and enhance renal excretion.
- ▶ Where evidence of hypocalcaemic or normocalcaemic tetany exists, calcium gluconate (10 ml of a 10% solution) is injected to avoid tachycardia.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

 Determinant
 Index
 Sampling Time
 Comments

 Fluorides in urine
 3 mg/gm creatinine
 Prior to shift
 B, NS

 10mg/gm creatinine
 End of shift
 B, NS

B: Background levels occur in specimens collected from subjects NOT exposed

NS: Non-specific determinant; also observed after exposure to other exposures.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous fumes. May emit acrid smoke. When aluminium oxide dust is dispersed in air, firefighters should wear protection against inhalation of dust particles, which can also contain hazardous substances from the fire absorbed on the alumina particles. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Safe handling

Precautions for safe handling

► Avoid all personal contact, including inhalation.

▶ Wear protective clothing when risk of exposure occurs.

Use in a well-ventilated area.

▶ WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.

- Avoid smoking, naked lights or ignition sources.
- Avoid smoking, naked lights of ignition so
 Avoid contact with incompatible materials.
- ► When handling, **DO NOT** eat, drink or smoke.

Chemwatch: 9-401297 Catalogue number: ICP-MS-ICS-3 Solution A

Page 5 of 17 6020-ICSA Issue Date: 05/23/2017 Print Date: 05/23/2017

Version No: 1.1

Keep containers securely sealed when not in use.

- Avoid physical damage to containers
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Store in original containers.

- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS

Conditions for safe storage, including any incompatibilities

► DO NOT use aluminium or galvanised containers

- ▶ Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polvliner drum.
- ▶ Packing as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

For low viscosity materials

- Drums and ierricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

Suitable container

Storage incompatibility

Other information

- For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

Removable head packaging;

- Cans with friction closures and
- low pressure tubes and cartridges
- may be used.

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic

▶ Material is corrosive to most metals, glass and other siliceous materials.

For aluminas (aluminium oxide):

Incompatible with hot chlorinated rubber.

In the presence of chlorine trifluoride may react violently and ignite.

-May initiate explosive polymerisation of olefin oxides including ethylene oxide.

-Produces exothermic reaction above 200 C with halocarbons and an exothermic reaction at ambient temperatures with halocarbons in the presence of other metals.

-Produces exothermic reaction with oxygen difluoride.

-May form explosive mixture with oxygen difluoride.

-Forms explosive mixtures with sodium nitrate

-Reacts vigorously with vinyl acetate

Aluminium oxide is an amphoteric substance, meaning it can react with both acids and bases, such as hydrofluoric acid and sodium hydroxide, acting as an acid with a base and a base with an acid, neutralising the other and producing a salt.

- ▶ Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
- Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts neutralisation can generate dangerously large amounts of heat in small spaces
- ▶ The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
- ▶ The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.
- ▶ Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.
- ▶ Inorganic acids can initiate the polymerisation of certain classes of organic compounds.
- ▶ Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.
- Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitrides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H2S and SO3), dithionites (SO2), and even
- ► Acids often catalyse (increase the rate of) chemical reactions.
- ▶ WARNING: Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.
- ► The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive
- Avoid reaction with borohydrides or cyanoborohydrides

Salts of inorganic fluoride:

- react with water forming acidic solutions.
- reviolent reactive with boron, bromine pentafluoride, bromine trifluoride, calcium disilicide, calcium hydride, oxygen difluoride, platinum, potassium.
- Fin aqueous solutions are incompatible with sulfuric acid, alkalis, ammonia, aliphatic amines, alkanolamines, alkylene oxides, amides, epichlorohydrin, isocyanates, nitromethane, organic anhydrides, vinyl acetate
- ▶ corrode metals in presence of moisture
- ▶ may be incompatible with glass and porcelain
- ▶ Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.

Acetic acid:

- vapours forms explosive mixtures with air (above 39 C.)
- reacts violently with bases such as carbonates and hydroxides (giving off large quantities of heat), oxidisers, organic amines, acetaldehyde, potassium tert-butoxide
- reacts (sometimes violently), with strong acids, aliphatic amines, alkanolamines, alkylene oxides, epichlorohydrin, acetic anhydride, 2-aminoethanol, ammonia, ammonium nitrate, bromine pentafluoride, chlorosulfonic acid, chromic acid, chromium trioxide, ethylenediamine, ethyleneimine, hydrogen peroxide, isocyanates, oleum, perchloric acid, permanganates, phosphorus isocyanate, phosphorus trichloride, sodium peroxide, xylene
- ▶ attacks cast iron, stainless steel and other metals, forming flammable hydrogen gas
- attacks many forms of rubber, plastics and coatings

Hydrogen fluoride:

reacts violently with strong oxidisers, acetic anhydride, alkalis, 2-aminoethanol, arsenic trioxide (with generation of heat), bismuthic acid, calcium oxide, chlorosulfonic acid, cyanogen fluoride, ethylenediamine, ethyleneimine, fluorine (fluorine gas reacts vigorously with a 50% hydrofluoric acid solution and may burst into flame), nitrogen trifluoride, N-phenylazopiperidine, oleum, oxygen difluoride, phosphorus pentoxide, potassium permanganate, potassium

Version No: 1.1

Issue Date: 05/23/2017 Print Date: 05/23/2017

- $\bullet \ \ \text{tetrafluorosilicate} (2\text{-}), \ \text{beta-propiolactone, propylene oxide, sodium, sodium tetrafluorosilicate, sulfuric acid, vinyl acetate }$
- reacts (possibly violently) with aliphatic amines, alcohols, alkanolamines, alkylene oxides, aromatic amines, amides, ammonia, ammonium hydroxide, epichlorohydrin, isocyanates, metal acetylides, metal silicides, methanesulfonic acid, nitrogen compounds, organic anhydrides, oxides, silicon compounds, vinylidene fluoride
- ratfacks glass and siliceous materials, concrete, ceramics, metals (flammable hydrogen gas may be produced), metal alloys, some plastics, rubber coatings, leather, and most other materials with the exception of lead, platinum, polyethylene, wax.

 Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	aluminium	Aluminum, metal	15 mg/m3	Not Available	Not Available	Total dust; (as Al)
US OSHA Permissible Exposure Levels (PELs) - Table Z1	aluminium	Aluminum, metal- Respirable fraction	5 mg/m3	Not Available	Not Available	(as AI)
US NIOSH Recommended Exposure Limits (RELs)	aluminium	Aluminium, Aluminum metal, Aluminum powder, Elemental aluminum	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	molybdenum	Molybdenum metal	0.5 mg/m3	Not Available	Not Available	See Appendix D
US ACGIH Threshold Limit Values (TLV)	molybdenum	Molybdenum, as Mo	Not Available	Not Available	Not Available	TLV® Basis: LRT irr
US NIOSH Recommended Exposure Limits (RELs)	ammonium chloride	Ammonium chloride, Ammonium muriate fume, Sal ammoniac fume	10 mg/m3	20 mg/m3	Not Available	TLV® Basis: Eye & URT irr
US ACGIH Threshold Limit Values (TLV)	ammonium chloride	Ammonium chloride, fume	10 mg/m3	20 mg/m3	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	nitric acid	Nitric acid	5 mg/m3 / 2 ppm	10 mg/m3 / 4 ppm	Not Available	TLV® Basis: URT & eye irr; dental erosion
US NIOSH Recommended Exposure Limits (RELs)	nitric acid	Aqua fortis, Engravers acid, Hydrogen nitrate, Red furning nitric acid (RFNA), White furning nitric acid (WFNA)	5 mg/m3 / 2 ppm	4 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	nitric acid	Nitric acid	2 ppm	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrofluoric acid	Hydrogen fluoride	2.5 mg/m3 / 3 ppm	Not Available	5 mg/m3 / 6 ppm	See Table Z-2;(as F)
US OSHA Permissible Exposure Levels (PELs) - Table Z2	hydrofluoric acid	Hydrogen fluoride	3 ppm	Not Available	2 ppm	(Z37.28–1969)
US NIOSH Recommended Exposure Limits (RELs)	hydrofluoric acid	Anhydrous hydrogen fluoride; Aqueous hydrogen fluoride (i.e., Hydrofluoric acid); HF-A	0.5 ppm	Not Available	Not Available	[15-minute]
US ACGIH Threshold Limit Values (TLV)	hydrofluoric acid	Hydrogen fluoride, as F	Not Available	Not Available	Not Available	TLV® Basis: URT, LRT, skin, & eye irr; fluorosis; BEI

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
iron	Iron	3.2 mg/m3	35 mg/m3	150 mg/m3
magnesium	Magnesium	18 mg/m3	200 mg/m3	1,200 mg/m3
molybdenum	Molybdenum	30 mg/m3	330 mg/m3	2,000 mg/m3
ammonium phosphate, monobasic	Ammonium dihydrogen phosphate; (Monoammonium phosphate)	17 mg/m3	190 mg/m3	1,100 mg/m3
potassium	Potassium	2.3 mg/m3	25 mg/m3	150 mg/m3
sodium	Sodium	13 mg/m3	140 mg/m3	870 mg/m3
methanesulfonic acid	Methanesulfonic acid	0.99 mg/m3	11 mg/m3	65 mg/m3
titanium	Titanium	30 mg/m3	330 mg/m3	2,000 mg/m3
ammonium acetate	Ammonium acetate	3.8 mg/m3	42 mg/m3	250 mg/m3
ammonium chloride	Ammonium chloride	20 mg/m3	110 mg/m3	330 mg/m3
nitric acid	Nitric acid	Not Available	Not Available	Not Available
hydrofluoric acid	Hydrogen fluoride; (Hydrofluoric acid)	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
aluminium	Not Available	Not Available
calcium	Not Available	Not Available
iron	Not Available	Not Available

Chemwatch: 9-401297

Catalogue number: ICP-MS-ICS-3 Solution A

Version No: 1.1

Page **7** of **17**

Issue Date: **05/23/2017**Print Date: **05/23/2017**

magnesium	Not Available	Not Available
molybdenum	N.E. / N.E.	5,000 mg/m3
ammonium phosphate, monobasic	Not Available	Not Available
potassium	Not Available	Not Available
sodium	Not Available	Not Available
methanesulfonic acid	Not Available	Not Available
titanium	Not Available	Not Available
ammonium acetate	Not Available	Not Available
ammonium chloride	Not Available	Not Available
nitric acid	100 ppm	25 ppm
hydrofluoric acid	30 ppm	30 [Unch] ppm
water	Not Available	Not Available

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Appropriate engineering controls

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range	
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	
3: Intermittent, low production.	3: High production, heavy use	
4: Large hood or large air mass in motion	4: Small hood-local control only	

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Personal protection











r craonar protection

- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure
- ► Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Eve and face protection

 Alternatively a gas mask may replace splash goggles and face shields.
 - ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

Hands/feet protection

- ▶ Elbow length PVC gloves
- ▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

Body protection

See Other protection below

Issue Date: **05/23/2017** Print Date: **05/23/2017**

Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower.
Thermal hazards	Not Available

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Yellow		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	► Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.

Bronchial and alveolar exudate are apparent in animals exposed to molybdenum by inhalation. Molybdenum fume may produce bronchial irritation and moderate fatty changes in liver and kidney.

Acute effects of fluoride inhalation include irritation of nose and throat, coughing and chest discomfort. A single acute over-exposure may even cause nose bleed.

Acute inhalation of hydrogen fluoride (hydrofluoric acid) vapours causes severe irritation of the eye, nose and throat, delayed fever, bluing of the extremities and water in the lungs, and may cause death. The above irritation occurs even with fairly low concentrations of hydrogen fluoride. Hydrogen fluoride has a strong irritating odour, that can be detected at concentrations of about 0.04 parts per million. Higher levels cause corrosion of the throat, nose and lungs, leading to severe inflammation and water buildup in the lungs (which may occur with 1 hour of exposure). A vapour concentration of 10 parts per million is regarded as intolerable, but a vapour concentration of 30 parts per million is considered as immediately dangerous to life and health.

It is estimated that the lowest lethal concentration for a 5-minute human exposure to hydrogen fluoride is in the range of 50 to 250 parts per million. Exposure by either skin contact or inhalation may lead to low levels of calcium and magnesium in the blood, which may result in heart rhythm disturbances. Animal testing suggests that repeated exposure produces liver and kidney damage.

Accidental indestion of the material may be harmful: animal experim

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident.

Ingestion

Issue Date: **05/23/2017**Print Date: **05/23/2017**

	Molybdenum, an essential trace element, can in large doses hamper growth and cause loss of appetite, listlessness and diarrhoea. Anaemia also occurs, and other symptoms include greying of hair, shrinking of the testicles, reduced fertility and milk production, shortness of breath, incoordination and irritation of the mucous membranes. Fluoride causes severe loss of calcium in the blood, with symptoms appearing several hours later including painful and rigid muscle contractions of the limbs. Cardiovascular collapse can occur and may cause death with increased heart rate and other heart rhythm irregularities.						
Skin Contact	Skin contact with the material may be harmful; systemic effects may result following absorption. Though considered non-harmful, slight irritation may result from contact because of the abrasive nature of the aluminium oxide particles. Thus it may cause itching and skin reaction and inflammation. Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Contact of the skin with liquid hydrofluoric acid (hydrogen fluoride) may cause severe burns, erythema, and swelling, vesiculation, and serious crusting. With more serious burns, ulceration, blue-gray discoloration, and necrosis may occur. Solutions of hydrofluoric acid, as dilute as 2%, may cause severe skin burns. Fluorides are easily absorbed through the skin and cause death of soft tissue and erode bone. Healing is delayed and death of tissue may continue to spread beneath skin. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.						
Еуе	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to li completely. Animal testing showed that a 20% solution of hydrofluoric acid (hydrogen fluoric and ischaemia of the conjunctiva. Swelling of the stroma of the cornea occurred eye.	de) in water caused immediate da	mage in the form of total clouding of the lens				
Chronic	Long-term exposure to respiratory irritants may result in airways disease, involved Substance accumulation, in the human body, may occur and may cause some of Animal testing shows long term exposure to aluminium oxides may cause lung the greater the tendencies of causing harm. High levels of molybdenum can cause joint problems in the hands and feet with elevated levels of enzymes and cause over-activity of the thyroid gland. Repeated or prolonged exposure to acids may result in the erosion of teeth, swand inflammation of lung tissue often occurs. Extended exposure to inorganic fluorides causes fluorosis, which includes sign appetite, diarrhoea or constipation, weight loss, anaemia, weakness and gener Hydrogen fluoride easily penetrates the skin and causes destruction and corros in the mouth and throat and blood calcium levels are dangerously reduced.	oncern following repeated or long- disease and cancer, depending of pain and lameness. Molybdenum relling and/or ulceration of mouth s of joint pain and stiffness, tooth al unwellness. There may also be	term occupational exposure. In the size of the particle. The smaller the size, compounds can also cause liver changes with ining. Irritation of airways to lung, with cough, discolouration, nausea and vomiting, loss of frequent urination and thirst.				
6020-ICSA	TOXICITY Not Available	IRRITATION Not Available					
aluminium	TOXICITY Oral (rat) LD50: >2000 mg/kg ^[1]		RRITATION lot Available				
calcium	TOXICITY Dermal (rabbit) LD50: >2500 mg/kg ^[1] Oral (rat) LD50: >2000 mg/kg ^[1]		IRRITATION Not Available				
iron	TOXICITY Oral (rat) LD50: 98600 mg/kg] ^[2]		RRITATION lot Available				
magnesium	TOXICITY Oral (rat) LD50: >2000 mg/kg ^[1]		RRITATION lot Available				
molybdenum	TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Oral (rat) LD50: >2000 mg/kg ^[1]		IRRITATION Not Available				
ammonium phosphate, monobasic	TOXICITY dermal (rat) LD50: >5000 mg/kg ^[1] Oral (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Not Available					
potassium	TOXICITY Not Available						
sodium	TOXICITY Not Available	IRRITATION Not Available					

Issue Date: **05/23/2017**Print Date: **05/23/2017**

	TOXICITY	IRRITATION				
methanesulfonic acid	Dermal (rabbit) LD50: 2000 mg/kgd ^[2]			Not Available		
	Oral (rat) LD50: 200 mg/kg ^[2]					
titanium	TOXICITY	IRRITATION				
	Oral (rat) LD50: >2000 mg/kg ^[1]			Not Available		
	TOXICITY			IRRITATION		
	dermal (rat) LD50: >2000 mg/kg ^[1]			Not Available		
ammonium acetate				Not Available		
	Oral (rat) LD50: >=2000 mg/kg ^[1]					
	тохісіту	IRRI	TATION			
ammonium chloride	dermal (rat) LD50: >2000 mg/kg ^[1]		rabbit): 100 mg SEVER			
animonium chioride			· · ·			
	Oral (rat) LD50: 1650 mg/kgE ^[2]	Еуе (rabbit): 500 mg/24h SEV	/CRE		
	TOXICITY			IRRITATION		
nitric acid	Inhalation (rat) LC50: 625 ppm/1h*t ^[2]			Not Available		
	innaiation (rat) LC50. 625 ppni/ m t			Not Available		
	тохісіту		IRRITATION			
hydrofluoric acid	Inhalation (rat) LC50: 1276 ppm/4hr ^[2]		Eye (human): 50 mg - 5	SEVERE		
,	Inhalation (rat) LC50: 319 ppm/1hr ^[2]		, , ,			
water	TOXICITY	IRRI	TATION			
water	Not Available	Not A	vailable			
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicit extracted from RTECS - Register of Toxic Effect of chemical Substances	y 2.* Value	e obtained from manufac	turer's SDS. Unless otherwise specified data		
CALCIUM	The solid may react violently on contact with wet skin tissue, i.e. eyes, mouth or tissue death, severe eye damage (comeal burns or opacification), and pro calcium) will cause shortness of breath, nausea, headache, nose and respira	bable blin	dness. Inhalation of dust	or fumes (especially from a fire involving		
AMMONIUM ACETATE	Altered sleep time, muscle contraction, coma, dyspnae, hypoglycemia record	led.				
NITRIC ACID	For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers]	For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5.				
HYDROFLUORIC ACID	(liver and kidney damage) [Manufacturer] for hydrogen fluoride (as vapour)					
ALUMINIUM & CALCIUM & MOLYBDENUM & AMMONIUM PHOSPHATE, MONOBASIC & POTASSIUM & SODIUM & TITANIUM & HYDROFLUORIC ACID & WATER	No significant acute toxicological data identified in literature search.					
CALCIUM & AMMONIUM PHOSPHATE, MONOBASIC & POTASSIUM & SODIUM & METHANESULFONIC ACID & AMMONIUM ACETATE & NITRIC ACID & HYDROFLUORIC ACID	Asthma-like symptoms may continue for months or even years after exposure	to the mat	terial ends.			
METHANESULFONIC ACID & AMMONIUM CHLORIDE & NITRIC ACID & HYDROFLUORIC ACID	The material may produce severe irritation to the eye causing pronounced inf	flammation	1.			
METHANESULFONIC ACID & NITRIC ACID & HYDROFLUORIC ACID	The material may produce respiratory tract irritation, and result in damage to	The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function.				
METHANESULFONIC ACID & NITRIC ACID	The material may cause severe skin irritation after prolonged or repeated expusioles, scaling and thickening of the skin.	oosure and	may produce on contac	t skin redness, swelling, the production of		
Acute Toxicity	~	Carcino	genicity			
•						

Page **11** of **17**

Catalogue number: ICP-MS-ICS-3 Solution A

Version No: 1.1

6020-ICSA

Issue Date: 05/23/2017 Print Date: 05/23/2017

Skin Irritation/Corrosion	✓	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

X − Data available but does not fill the criteria for classification
 ✓ − Data available to make classification

O - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

2000 100	ENDPOINT	POINT TEST DURATION (HR)			SPECIES	VA	LUE		SOUR	CE	
6020-ICSA	Not Applicable		Not Applicable Not		Not Applicable	No	t Applicab	icable Not Ap		pplicable	
	ENDPOINT	TES	T DURATION (HR)	SPECIES			VAL	.UE		SOURCE	
	LC50	96		Fish				'8-0.108mg/L		2	
	EC50	48		Crustacea	a			64mg/L		2	
aluminium	EC50	96		Algae or o	other aquatic pla	ints)54mg/L		2	
	BCF	360			other aquatic pla		9mg			4	
	EC50	120		Fish			0.00	00051mg/L		5	
	NOEC	72		Algae or o	other aquatic pla	ints	>=0	.004mg/L		2	
	ENDPOINT		TEST DURATION (UR)		SPEC	NEC	VALU	ıE	601	JRCE	
calcium	EC50		TEST DURATION (HR)						5	JRCE	
Calcium					Crust		6934r	_	2		
	NOEC		48		Crust	acea	33.3n	1g/L			
				00000	•		1,4			0011000	
	ENDPOINT		T DURATION (HR)	SPECIES	S			LUE		SOURCE	
	LC50	96		Fish				05mg/L		2	
iron	EC50	96			other aquatic pl	ants		3.7mg/L		4	
	BCF	504			Crustacea			0.0000002mg/L		4	
	EC50			Crustace				4.49mg/L		2	
	NOEC	504		Fish	Fish			0.52mg/L 2		2	
	ENDPOINT	TES	ST DURATION (HR)	SPEC	EIES			VALUE		SOURCE	
	LC50	96				541mg/L		2			
magnesium	EC50	72		Algae	Algae or other aquatic plants			>20mg/L		2	
-	EC50	72	72		or other aquation	•		>20mg/L		2	
	NOEC	72		Algae	Algae or other aquatic plants			>25.5mg/L		2	
	ENDPOINT	TE	ST DURATION (HR)	SPEC	MEG			VALUE		SOURCE	
	LC50	96	31 DORATION (FIX)	Fish	AE3			609.1mg/L		2	
	EC50	72			or other aquation	nlante		289.2mg/L		2	
molybdenum	BCF	336			or other aquation	•		64mg/L	•	4	
	EC50	336		-	or other aquation	•		64mg/L		4	
	NOEC	672		Crusta		, piarits		0.67mg/L		2	
	NOLO	072		Ordate	4004			0.07mg/L			
	ENDPOINT	TES	ST DURATION (HR)	SPEC	IES			VALUE		SOURCE	
	LC50	96		Fish	Fish			>85.9mg/L		2	
ammonium phosphate, monobasic	EC50	72		Algae	Algae or other aquatic plants			>97.1mg/L		2	
o.iobadio	EC50	72		Algae	Algae or other aquatic plants			>97.1mg/L		2	
	NOEC	72		Algae	or other aquation	plants		3.57mg/L		2	
	ENDPOINT		TEST DURATION (HR)		SPF	CIES	VAI	.UE	SOL	JRCE	
potassium	EC50		24		SPECIES			VALUE SC 400mg/L 5			

Version No: 1.1

6020-ICSA

Issue Date: 05/23/2017 Print Date: 05/23/2017

	ENDPOINT		TEST DURATION (HR)			SPECIES	VALU			URCE
sodium	EC50		48			Crustacea	1640	mg/L	4	
	EC50 504			Crustacea	1020	ng/L	4			
	ENDPOINT	TEC	T DURATION (HR)	epe	CIES		VAL	_UE		SOURCE
	LC50	96	T DONATION (TIK)	Fish	CILO			.11549mg/L		3
methanesulfonic acid	EC50	48			tacea			mg/L		1
methanesunome acid	EC50	96			e or other aq	uatic plants		0.75364mg/L		3
	EC50	24		-	tacea	adio pidi ilo		7mg/L		1
	1000	ļ <u>-</u> :		0.00				9_		1 .
	ENDPOINT	TE	ST DURATION (HR)		SPECIES			VALUE		SOURCE
titanium	EC50	4.5				r aquatic plants		>100mg/L	_	2
	NOEC	48			Crustacea			1mg/L		2
								, J		
	ENDPOINT		TEST DURATION (HR)			SPECIES	VALU	E	so	URCE
ammonium acetate	EC50	48				Crustacea	>919r	ng/L	2	
	EC50		24			Crustacea >919m				
	ENDPOINT	TES	ST DURATION (HR)	S	PECIES			VALUE		SOURCE
	LC50	96		Fi	Fish			0.08mg/L		4
	EC50	48		С	rustacea			0.261mg/L		4
ammonium chloride	EC50	72	72		gae or other	aquatic plants		166.5mg/L		4
	EC0	168	168		Crustacea			=0.025mg/L	-	1
	NOEC	720		F	sh			0.006mg/L 4		4
						_				
nitric acid	ENDPOINT		TEST DURATION (HR)			SPECIES	VAL	.UE	SOL	URCE
	NOEC		16			Crustacea	107	mg/L	4	
	ENDPOINT		TEST DURATION (HR)			SPECIES	VALUI	=	so	URCE
	LC50		96			Fish	51mg/l		2	
hydrofluoric acid	EC50		48		Crustacea		=270mg/L		1	
•	EC50		96	Crustacea		26-48mg/L		2		
	NOEC		504					4mg/L		
			'							
	ENDPOINT		TEST DURATION (HR)		SPECIE	ES	VALUE		SOURCE	
water	Not Applicable		Not Applicable		Not App	olicable	Not Applicat	le	Not Ap	plicable

(Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For Molybdenum:

Environmental Fate: Molybdenum is an essential micronutrient in plants and animals. It is commonly used in the manufacture of steel alloys. Based on the high concentration of molybdenum in all analyzed waste types, the exposure of the environment to molybdenum is regarded as significant. The limited amount of data regarding its toxicity makes it impossible to evaluate the potential for adverse environmental and health effects from molybdenum exposure. Molybdenum is generally found in two oxidation states in nature, Mo(IV) and Mo(VI). In oxidizing environments, Mo(VI) dominates and it is commonly present as molybdate. Natural molybdenum contains seven isotopes. Molybdenum oxidizes at elevated temperatures.

Atmospheric Fate: Molybdenum can be deposited via dry/wet deposition; however, atmospheric exposure has been identified as a minor source to terrestrial and aquatic habitats Terrestrial Fate: Molybdenum is a naturally occurring substance in soil. Soil molybdenum is a potentially toxic element, but no cases have been reported of molybdenum toxicity to animals from consumption of forage grown on sludge-amended soils. Microbes are expected to transform the substance.

Aquatic Fate: Molybdenum disulfide is sparingly soluble in water but oxidizes to more soluble molybdates, which are stable in water. At pH 3-5, molybdate frequently shifts to hydrogen molybdate. Low pH molybdenum is usually adsorbed to sediment composed of clay, or other minerals that are prone to weathering. Molybdenum in the water is expected to be taken up by aquatic organisms. Concentrations of the substance in sediments are by site-specific factors like flow rate, and other factors, (e.g. organic content, pH)

Ecotoxicology: Molybdenum cause adverse effects in ruminant animals. Livestock have been injured by forage grown on soils containing the element. The substance 🕈 s toxicological properties in mammals are governed, to a large extent, by its interaction with copper and sulfur; residues of molybdenum alone are not sufficient to diagnose poisoning by the substance. Domestic ruminants, especially cattle, are especially sensitive to molybdenum poisoning, when copper and inorganic sulfate are deficient. The resistance of small laboratory animals, and wildlife, is at least 10X that of cattle. Mule deer are not adversely affected by the substance. The substance may have a negative impact on reproduction in domestic birds and there is inadequate data on its effects on waterfowl and most mammals

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

For Fluorides: Small amounts of fluoride have beneficial effects however, excessive intake over long periods may cause dental and/or skeletal fluorosis. Fluorides are absorbed by humans following inhalation of workplace and ambient air that has been contaminated, ingestion of drinking water and foods and dermal contact. Populations living in areas with high fluoride levels in groundwater may be exposed to higher levels of fluorides in their drinking water or in beverages prepared with the water. Among these populations, outdoor labourers, people living in hot climates, and people with excessive thirst will generally have the greatest daily intake of fluorides because they consume greater amounts of water.

Page 13 of 17

6020-ICSA

Version No: 1.1

Print Date: **05/23/2017**

Issue Date: 05/23/2017

Atmospheric Fate: Both hydrogen fluoride and particulate fluorides will be transported in the atmosphere and deposited on land or water by wet and dry deposition. Non-volatile inorganic fluoride particulates are removed from the atmosphere via condensation or nucleation processes. Fluorides adsorbed on particulate matter in the atmosphere are generally stable and are not readily hydrolyzed, although they may be degraded by radiation if they persist in the atmosphere. Fluorine and the silicon fluorides (fluosilicates, silicofluorides) are hydrolyzed in the atmosphere to form hydrogen fluoride. Hydrogen fluoride may combine with water vapour to produce an aerosol or fog of aqueous hydrofluoric acid. Inorganic fluoride compounds, with the exception of sulfur hexafluoride, are not expected to remain in the troposphere for long periods or to migrate to the stratosphere. Estimates of the residence time of sulfur hexafluoride in the atmosphere range from 500 to several thousand years. Fluoride in aerosols can be transported over large distances by wind or as a result of atmospheric turbulence. Fluorosilicic acid and hydrofluoric acid in high aquatic concentrations such as may be found in industrial waste ponds may volatilize, releasing silicon tetrafluoride and hydrogen fluoride into the atmosphere. Soluble inorganic fluorides may also form aerosols at the air/water interface or vaporize into the atmosphere whereas undissolved species generally undergo sedimentation.

Terrestrial Fate: Soils - Atmospheric fluorides may be transported to soils and surface waters through both wet and dry deposition processes where they may form complexes and bind strongly to soil and sediment. Solubilisation of inorganic fluorides from minerals may also be enhanced by the presence of bentonite clays and humic acid. Factors that influence the mobility of inorganic fluorides in soil are pH and the formation of aluminium and calcium complexes. In more acidic soils, concentrations of inorganic fluoride were considerably higher in the deeper horizons. The low affinity of fluorides for organic material results in leaching from the more acidic surface horizon and increased retention by clay minerals and silts in the more alkaline, deeper horizons. The maximum adsorption of fluoride to soil was reported to occur at pH 5.5. In acidic soils with pH below 6, most of the fluoride is in complexes with either aluminium or iron. Fluoride in alkaline soils at pH 6.5 and above is almost completely fixed in soils as calcium fluoride, if sufficient calcium carbonate is available. Fluoride is extremely immobile in soil.

Aquatic Fate: Fresh Water: - In water, the transport and transformation of inorganic fluorides are influenced by pH, water hardness and the presence of ion-exchange materials such as clays. In natural water, fluoride forms strong complexes with aluminium in water, and fluorine chemistry in water is largely regulated by aluminium concentration and pH. Below pH 5, fluoride is almost entirely complexed with aluminium and consequently, the concentration of free F- is low. Once dissolved, inorganic fluorides remain in solution under conditions of low pH and hardness and in the presence of ion-exchange material. Sea Water - Fluoride forms stable complexes with calcium and magnesium, which are present in sea water. Calcium carbonate precipitation dominates the removal of dissolved fluoride from sea water. The residence time for fluoride in ocean sediment is calculated to be 2-3 million years.

Ecotoxicity: Fluorides have been shown to accumulate in animals that consume fluoride-containing foliage. However, accumulation is primarily in skeletal tissue and therefore, it is unlikely that fluoride will biomagnify up the food chain.

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ammonium phosphate, monobasic	нівн	HIGH
methanesulfonic acid	HIGH	HIGH
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
ammonium phosphate, monobasic	LOW (LogKOW = -0.7699)
methanesulfonic acid	LOW (LogKOW = -2.3817)
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
ammonium phosphate, monobasic	HIGH (KOC = 1)
methanesulfonic acid	HIGH (KOC = 1)
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging

- ► Containers may still present a chemical hazard/ danger when empty.
- ► Return to supplier for reuse/ recycling if possible.

Otherwise

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and SDS and observe all notices pertaining to the product.
- Recycle wherever possible
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility
 can be identified.
- Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill
 specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible
 material).
- Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

disposal

Labels Required



Marine Pollutant

NC

Page **14** of **17**

6020-ICSA

Issue Date: **05/23/2017** Print Date: **05/23/2017**

Version No: 1.1

Land transport (DOT)

UN number	3264
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Transport hazard class(es)	Class 8 Subrisk Not Applicable
Packing group	
Environmental hazard	Not Applicable
Special precautions for user	Hazard Label 8 Special provisions 386, B2, IB2, T11, TP2, TP27

Air transport (ICAO-IATA / DGR)

Sea transport (IMDG-Code / GGVSee)

UN number	3264
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. *
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable
Packing group	II
Environmental hazard	Not Applicable
Special precautions for user	EMS Number F-A, S-B Special provisions 274 Limited Quantities 1 L

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

SECTION 15 REGULATORY INFORMATION

 ${\bf Safety, \, health \, and \, environmental \, regulations \, \textit{/} \, legislation \, specific \, for \, the \, substance \, or \, mixture}$

ALUMINIUM(7429-90-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Page 15 of 17

Catalogue number: ICP-MS-ICS-3 Solution A

Version No: 1.1

6020-ICSA

Issue Date: 05/23/2017 Print Date: 05/23/2017

US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Massachusetts - Right To Know Listed Chemicals	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Michigan Exposure Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Oregon Permissible Exposure Limits (Z-1)	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Pennsylvania - Hazardous Substance List	US EPCRA Section 313 Chemical List
US - Rhode Island Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table Z1

CALCIUM(7440-70-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

US - Massachusetts - Right To Know Listed Chemicals	
---	--

US - Pennsylvania - Hazardous Substance List

US - Rhode Island Hazardous Substance List

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

IRON(7439-89-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)

US - California Permissible Exposure Limits for Chemical Contaminants

US - Hawaii Air Contaminant Limits

US - Michigan Exposure Limits for Air Contaminants

US - Oregon Permissible Exposure Limits (Z-1)

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Washington Permissible exposure limits of air contaminants

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

MAGNESIUM(7439-95-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)

US - California Permissible Exposure Limits for Chemical Contaminants

US - Hawaii Air Contaminant Limits US - Massachusetts - Right To Know Listed Chemicals

US - Michigan Exposure Limits for Air Contaminants

US - Oregon Permissible Exposure Limits (Z-1)

US - Pennsylvania - Hazardous Substance List

US - Rhode Island Hazardous Substance List

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Washington Permissible exposure limits of air contaminants

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

MOLYBDENUM(7439-98-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants US - Hawaii Air Contaminant Limits US - Idaho - Limits for Air Contaminants

US - Massachusetts - Right To Know Listed Chemicals US - Minnesota Permissible Exposure Limits (PELs)

US - Pennsylvania - Hazardous Substance List US - Rhode Island Hazardous Substance List

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants

US - Washington Permissible exposure limits of air contaminants

US ACGIH Threshold Limit Values (TLV) US ACGIH Threshold Limit Values (TLV) - Carcinogens

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

AMMONIUM PHOSPHATE, MONOBASIC(7722-76-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

POTASSIUM(7440-09-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

US - Massachusetts - Right To Know Listed Chemicals

US - Pennsylvania - Hazardous Substance List

US - Rhode Island Hazardous Substance List

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

SODIUM(7440-23-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

US - Massachusetts - Right To Know Listed Chemicals

US - Pennsylvania - Hazardous Substance List

US - Rhode Island Hazardous Substance List

US CWA (Clean Water Act) - List of Hazardous Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

METHANESULFONIC ACID(75-75-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

TITANIUM(7440-32-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)

US - California Permissible Exposure Limits for Chemical Contaminants

US - Hawaii Air Contaminant Limits

US - Michigan Exposure Limits for Air Contaminants

US - Oregon Permissible Exposure Limits (Z-1)

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Washington Permissible exposure limits of air contaminants

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Version No: 1.1

6020-ICSA

Issue Date: 05/23/2017 Print Date: 05/23/2017

US - Massachusetts - Right To Know Listed Chemicals	US EPA Carcinogens Listing
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
LIS CWA (Clean Water Act) - Liet of Hazardous Substances	

AMMONIUM CHLORIDE(12125-02-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Massachusetts - Right To Know Listed Chemicals	Contaminants
US - Michigan Exposure Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV)
US - Oregon Permissible Exposure Limits (Z-1)	US CWA (Clean Water Act) - List of Hazardous Substances
US - Pennsylvania - Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

NITRIC ACID(7697-37-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
Passenger and Cargo Aircraft	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Alaska Limits for Air Contaminants	Contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Massachusetts - Right To Know Listed Chemicals	US CWA (Clean Water Act) - List of Hazardous Substances
US - Michigan Exposure Limits for Air Contaminants	US EPCRA Section 313 Chemical List
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	US SARA Section 302 Extremely Hazardous Substances
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

HYDROFLUORIC ACID(7664-39-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

 $\ensuremath{\mathsf{US}}$ - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
Monographs	Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
(CRELs)	US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration,
US - California Permissible Exposure Limits for Chemical Contaminants	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV)
US - Idaho - Acceptable Maximum Peak Concentrations	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Idaho - Limits for Air Contaminants	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Massachusetts - Right To Know Listed Chemicals	US Clean Air Act - Hazardous Air Pollutants
US - Michigan Exposure Limits for Air Contaminants	US CWA (Clean Water Act) - List of Hazardous Substances
US - Minnesota Permissible Exposure Limits (PELs)	US EPCRA Section 313 Chemical List
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-2)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z2
US - Rhode Island Hazardous Substance List	US SARA Section 302 Extremely Hazardous Substances
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table 7-1-A Final Rule Limits for Air Contaminants	

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
--	---

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Sodium	10	4.54
Ammonium acetate	5000	2270
Ammonium chloride	5000	2270
Nitric acid	1000	454
Hydrofluoric acid	100	45.4

6020-ICSA

Issue Date: 05/23/2017 Print Date: 05/23/2017

Version No: 1.1

US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status	
Australia - AICS	Y	
Canada - DSL	Y	
Canada - NDSL	N (sodium; calcium; ammonium chloride; potassium; titanium; magnesium; ammonium phosphate, monobasic; water; methanesulfonic acid; aluminium; molybdenum; iron; ammonium acetate; hydrofluoric acid; nitric acid)	
China - IECSC	Y	
Europe - EINEC / ELINCS / NLP	Y	
Japan - ENCS	N (sodium; calcium; potassium; titanium; magnesium; ammonium phosphate, monobasic; water; methanesulfonic acid; aluminium; molybdenum; iron; ammonium acetate; hydrofluoric acid; nitric acid)	
Korea - KECI	Y	
New Zealand - NZIoC	Υ	
Philippines - PICCS	Y	
USA - TSCA	Y	
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
aluminium	7429-90-5, 91728-14-2
calcium	7440-70-2, 8047-59-4
ammonium chloride	12125-02-9, 152128-19-3
hydrofluoric acid	7664-39-3, 790596-14-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.