

High-Purity Standards

Catalogue number: CAF-LC_3

Version No: 1.1 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Caffeine LC Performance Solution 3
Synonyms	CAF-LC_3
Other means of identification	CAF-LC_3

Recommended use of the chemical and restrictions on use

Relevant identified uses Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	High-Purity Standards
Address	PO Box 41727 SC 29423 United States
Telephone	843-767-7900
Fax	843-767-7906
Website	highpuritystandards.com
Email	Not Available

Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	1-800-535-5053
Other emergency telephone numbers	1-352-323-3500

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

Classification	Not Applicable		
Label elements			
Hazard pictogram(s)	Not Applicable		
SIGNAL WORD	NOT APPLICABLE		

Hazard statement(s)

Not Applicable

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Chemwatch Hazard Alert Code: 0

Issue Date: 06/06/2017 Print Date: 06/06/2017

S.GHS.USA.EN

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7732-18-5	balance	water
58-08-2	0.0125	caffeine

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting Use water delivered as a fine spray to control fire and cool adjacent area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 	
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
--------------	--

Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment. Prevent spillage from entering drains, sewers or water courses. Recover product wherever possible. Put residues in labelled containers for disposal. If contamination of drains or waterways occurs, advise emergency services. 	
--------------	--	--

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Other information

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. 	
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed. None known	

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Caffeine LC Performance Solution 3	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
water	Not Available		Not Available	
caffeine	Not Available		Not Available	

Exposure controls

Appropriate engineering	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or controls to prevent employee overexposure. Employers may need to use multiple types of controls to prevent employee overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.				
controls	Type of Contaminant:	Air Speed:			
	solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)			
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)				
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)				
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)			

Issue Date: 06/06/2017 Print Date: 06/06/2017

Caffeine LC Performance Solution 3

	Within each range the appropriate value depends on:						
	Lower end of the range	Upper end of the range					
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents					
	2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity					
	3: Intermittent, low production.	3: High production, heavy use					
	4: Large hood or large air mass in motion	4: Small hood - local control only					
	Simple theory shows that air velocity falls rapidly with distance away from the ope of distance from the extraction point (in simple cases). Therefore the air speed a distance from the contaminating source. The air velocity at the extraction fan, for solvents generated in a tank 2 meters distant from the extraction point. Other me apparatus, make it essential that theoretical air velocities are multiplied by factors	at the extraction point should be adjusted, accordingly, after reference to example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of echanical considerations, producing performance deficits within the extraction					
Personal protection	tection						
Eye and face protection	lenses or restrictions on use, should be created for each workplace or task. chemicals in use and an account of injury experience. Medical and first-aid readily available. In the event of chemical exposure, begin eye irrigation imm	and concentrate irritants. A written policy document, describing the wearing of This should include a review of lens absorption and adsorption for the class of personnel should be trained in their removal and suitable equipment should be rediately and remove contact lens as soon as practicable. Lens should be removed aan environment only after workers have washed hands thoroughly. [CDC NIOSH					
Skin protection	See Hand protection below						
	Wear general protective gloves, eg. light weight rubber gloves. The selection of suitable gloves does not only depend on the material, but also o the chemical is a preparation of several substances, the resistance of the glove r to the application. The exact break through time for substances has to be obtained from the manufa choice. Personal hygiene is a key element of effective hand care. Gloves must only be w thoroughly. Application of a non-perfumed moisturizer is recommended.	material can not be calculated in advance and has therefore to be checked prior acturer of the protective gloves and has to be observed when making a final					

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

frequency and duration of contact,

· chemical resistance of glove material,

- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

•	When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240	
mir	es according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.	

• When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

•	Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
•	Contaminated gloves should be replaced.

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: • Overalls. • Barrier cream. • Eyewash unit.
Thermal hazards	Not Available
	Other protection

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Hands/feet protection

Information on basic physical and chemical properties

Appearance	Not Available				
Physical state	Liquid	Relative density (Water = 1)	Not Available		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7	
Chemical stability	luct is considered stable and hazardous polymerisation will not occur.	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.				
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.				
Skin Contact	The material is not thought to produce adverse health effects Nevertheless, good hygiene practice requires that exposure b				
Eye	Although the liquid is not thought to be an irritant (as classified by tearing or conjunctival redness (as with windburn).	ed by EC Directives), direct contact v	with the eye may produce transient discomfort characterised		
Chronic	Long-term exposure to the product is not thought to produce nevertheless exposure by all routes should be minimised as a		n (as classified by EC Directives using animal models);		
	-				
Caffeine LC Performance	ΤΟΧΙΟΙΤΥ	IRRITATION			
Solution 3	Not Available	Not Available			
	ΤΟΧΙΟΙΤΥ	IRRITATION			
water	Not Available				
	TOXICITY		IRRITATION		
caffeine	Oral (rat) LD50: 192 mg/kg ^[2] Not Available				
	l				
Legend:	1. Value obtained from Europe ECHA Registered Substance extracted from RTECS - Register of Toxic Effect of chemical		from manufacturer's SDS. Unless otherwise specified data		
	1				
WATER	No significant acute toxicological data identified in literature search.				
CAFFEINE	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Oral (woman) TDLo: 96 mg/kg/1d-l Tumorigenic - Carcinogenic by RTECS criteria.				
Acute Toxicity	0	Carcinogenicity	0		
Skin Irritation/Corrosion	\otimes	Reproductivity	0		
Serious Eye Damage/Irritation	0	STOT - Single Exposure	\odot		

Version No: 1.1

Caffeine LC Performance Solution 3

Respiratory or Skin sensitisation	\odot	STOT - Repeated Exposure	\otimes
Mutagenicity	0	Aspiration Hazard	0
		Legend: 🗙	- Data available but does not fill the criteria for classification

Logenu. /

Data available but does not init the citienta for class
 Data available but does not init the citienta for class

🚫 – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Caffeine LC Performance	ENDPOINT	TEST DURATION (HR)		SPECIES	VALUE		SOURCE
Solution 3	Not Applicable	Not Applicable		Not Applicable	Not Applica	able	Not Applicable
	ENDPOINT	TEST DURATION (HR)		SPECIES	VALUE		SOURCE
water	Not Applicable	Not Applicable		Not Applicable	Not Applica	able	Not Applicable
	ENDPOINT	TEST DURATION (HR)	SPEC	IFS		VALUE	SOURCE
	LC50	96	Fish			805.076mg/L	3
caffeine	EC50	96	Algae	or other aquatic plants		46.859mg/L	3
	EC50	120	Fish			70mg/L	4
Legend:	(QSAR) - Aquatic	UCLID Toxicity Data 2. Europe ECHA Toxicity Data (Estimated) 4. US EPA, entration Data 7. METI (Japan) - Bioco	Ecotox database	- Aquatic Toxicity Data			

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW
caffeine	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)
caffeine	LOW (LogKOW = -0.07)

Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)
caffeine	LOW (KOC = 10)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.
	,
	A Hierarchy of Controls seems to be common - the user should investigate:
	▶ Reduction
	▶ Reuse
	► Recycling
	Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be
	possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type.
Product / Packaging	Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.
disposal	DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	Recycle wherever possible.
	Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility
	can be identified.
	 Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after
	admixture with suitable combustible material).
	 Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Issue Date: 06/06/2017 Print Date: 06/06/2017

Caffeine LC Performance Solution 3

Labels Required

Marine Pollutant NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Source	Product name	Pollution Category	Ship Type
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	Poly(2+)cyclic aromatics	x	1

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
CAFFEINE(58-08-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US EPCRA Section 313 Chemical List
Monographs	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US Clean Air Act - Hazardous Air Pollutants	
Federal Regulations	
Superfund Amendments and Reauthorization Act of 1986 (SARA)	
SECTION 311/312 HAZARD CATEGORIES	
Immediate (acute) health hazard	No

Immediate (acute) health hazard	No
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4) None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (water; caffeine)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water; caffeine)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
caffeine	58-08-2, 5743-12-4, 75639-14-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

Chemwatch: 9-407217 Catalogue number: CAF-LC_3 Version No: 1.1

Issue Date: 06/06/2017 Print Date: 06/06/2017

end of SDS

Caffeine LC Performance Solution 3

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.