



Industrial Hygiene and Air Monitoring Standards

ISO 9001: 2015 Registered • ISO/IEC 17025:2005 Accredited • ISO 17034:2016 Accredited

Introducing Our New Expanded Product Line

High-Purity Standards (HPS) continues to expand our offerings in Industrial Hygiene and Air Monitoring Standards. The new products listed below address the need for quality control or method development for industrial hygiene analyses. These standards can be used with industrial hygiene methods including: NIOSH Methods 7300, 7500 and 1000 Series, and OSHA Method 91. All products are ISO 17034 certified reference materials.



Absorbent Tubes & Diffusive Samplers

Organic solvent analytes are gravimetrically applied to tubes or passive sampler badges containing charcoal sorbents. Following manufacture, products are desorbed and tested using NIOSH/OSHA methods established for applicable components. Second source certified reference materials are used to validate concentration.

To order a standard, please provide the following information:

- Analytes of interest
- Analyte mass per tube or badge
- If ordering a diffusive sampler, indicate brand of package: 3M, Assay Technology or SKC
- Quantity of spiked tubes/badges and blanks

Provide your information to us via phone at **843.767.7900** or toll free at **866.767.4771** or via email to info@highpuritystandards.com or visit our website at www.highpuritystandards.com and click on the **CUSTOM BLENDS** tab at the top of the page. A quote form is provided on the back of this brochure.

Silica for XRD/IR Analysis

TMFM-Crystalline Silica

We offer standards of alpha-Quartz or Cristobalite on PVC filters. These forms of silica come in concentration ranges of 10 µg/filter to 500 µg/filter for the alpha-Quartz and 5 µg/filter to 250 µg/filter for the Cristobalite.

Available as custom products which may include background materials.

Please contact **Customer Service** for details on concentrations and pricing.

Toxic Air Metals on Quartz Filter

Metals currently listed as Hazardous Air Pollutants (HAP) include: antimony, arsenic, beryllium, cadmium, chromium, cobalt, lead, manganese, mercury, nickel, and selenium. HPS has designed products that comply with the intent of EPA methods for Air Monitoring. The more popular filter media for these products includes quartz or PTFE-coated filters. Dissolved metals are applied to the selected filter media and tested against appropriate certified reference materials. These products can be accompanied with an ISO 17034:2016 Certificate of Analysis.

To request varying elements/concentrations and your choice of type of filter (Quartz, MCE, PVC, PTFE-coated, or Acrylic), please contact us to discuss your special mix needs.

Hexavalent Chromium on MCE or PVC Filters

This is a custom product due to the short stability period. Validation via IC or IC-ICP-MS are available. Please send custom specifications to info@highpuritystandards.com.

Clean Filters

To address the need for clean blank PVC filters, HPS offers two methods of cleaning PVC filters to remove specific contaminants.

1. A patented process to remove chromium or vanadium¹
2. An in-house method to remove silicon

A Certificate of Analysis with the concentration per filter of the removed analyte is included with the product.

Clean Filters	
Description	Catalog No.
Cleaned, 37 mm PVC filters in quantities of 25. Bulk pricing available.	PVC37MMPC

¹ Licensed from the United States of America under U.S. Patent No. 8,415,452, Rubenstein, M. "Hexavalent chromium and total chromium removal from polyvinylchloride (PVC) polymers".

Industrial Hygiene and Ambient Air Analysis

The following trace metals on mixed cellulose ester are designed to meet QC requirements for NIOSH Method 7300. Additional blanks are available.

Description					Catalog No.		
Trace metals on mixed cellulose ester; 10 spiked filters and 5 blanks					QC-TMFM-A through QC-TMFM-G		
Element	QC-TMFM-A	QC-TMFM-B	QC-TMFM-C	QC-TMFM-D	QC-TMFM-E	QC-TMFM-F	QC-TMFM-G
	µg/filter	µg/filter	µg/filter	µg/filter	µg/filter	µg/filter	µg/filter
Aluminum	—	—	—	50	100	—	—
Arsenic	10	50	100	10	20	10	50
Barium	2.5	10	25	2.5	5	2.5	10
Beryllium	1	10	25	0.1	0.2	1	10
Cadmium	1	10	25	1	2	1	10
Chromium	2.5	10	25	2.5	5	2.5	10
Cobalt	2.5	10	25	2.5	5	2.5	10
Copper	2.5	25	50	2.5	5	2.5	25
Iron	2.5	25	50	2.5	5	2.5	25
Lead	2.5	25	50	2.5	5	2.5	25
Manganese	1	10	25	1	2	1	10
Nickel	2.5	10	25	2.5	5	2.5	10
Silver	1	5	10	1	2	1	5
Thallium	2.5	10	25	2.5	5	2.5	10
Uranium	—	—	—	—	—	2.5	5
Vanadium	2.5	10	25	2.5	5	2.5	10
Zinc	2.5	50	100	2.5	5	2.5	50

Beryllium Oxide

Beryllium Oxide is a toxic particulate material present in workplace samples that is known to be resistant to dissolution. These standards are available for method development or quality control checks. The source of the beryllium oxide applied to the filter is NIST SRM 1877 high-fired BeO powder. Blanks are supplied separately, see catalog number TMFM-CBEO-BLANK.

Beryllium Oxide Particulates on Filter		
Description	µg/filter	Catalog No.
0.05 µg/filter of BeO as Be (2 filters)	0.05	TMFM-CBEO-0.05
0.1 µg/filter of BeO as Be (2 filters)	0.1	TMFM-CBEO-0.1
0.2 µg/filter of BeO as Be (2 filters)	0.2	TMFM-CBEO-0.2
0.5 µg/filter of BeO as Be (2 filters)	0.5	TMFM-CBEO-0.5
1 µg/filter of BeO as Be (2 filters)	1	TMFM-CBEO-1.0
2 µg/filter of BeO as Be (2 filters)	2	TMFM-CBEO-2.0
5 µg/filter of BeO as Be (2 filters)	5	TMFM-CBEO-5.0
10 µg/filter of BeO as Be (2 filters)	10	TMFM-CBEO-10.0
25 µg/filter of BeO as Be (2 filters)	25	TMFM-CBEO-25.0
Blanks (2 blanks)	—	TMFM-CBEO-BLANK

Custom Standards

HPS offers custom standards for Industrial Hygiene or Air Monitoring. Metals are available on a wide range of filter media including MCE, PVC, Acrylic, Quartz, and PTFE-coated filters. Organic Solvents are available on a variety of sorbent tubes or diffusive samplers. Please send custom specifications to info@highpuritystandards.com. A quote form is provided on the back of this brochure.



Custom Standard Quote Form

Contact Person: _____

Company Name: _____ Customer Number: _____

Email: _____

Telephone Number: _____ Fax Number: _____

Address Line 1: _____ Address Line 2: _____

City: _____ State: _____

Zip/Postal Code: _____ Country: _____

Mix Name: _____

Standards

Custom Industrial Hygiene Standards come in sets that include blanks. This portion of the form will provide specifications as to the number of spiked standards and the number and type of blanks.

Filter Media (for filters): _____

Diameter (for filters): _____ Pore Size (optional for filters): _____

Diffusive Badge Type (for diffusive samplers): _____

Sorbent Tube Type (for organic solvents on sorbent tubes): _____

Number of Standards per set:

Spiked: _____ Blank: _____

Type of Blank: _____

Total Number of Sets: _____

Elements/Components

You may add as many components to your custom blend as you wish. Metals are assumed to be dissolved, unless otherwise stated (ex. BeO solid, crystalline silica solid, etc). If requesting a crystalline silica standard, indicate the form (ex. alpha quartz, cristobalite, amorphous, etc). Include the mass units of each component concentration (ex. μg). Please provide a separate document for multiple components and attach with this quote form.

Element/Component: _____ CAS Number (for organic component) _____

Concentration (mass per media): _____ Concentration Unit: _____

Sample Preparation/Analytical Method: _____

Special Instructions

The custom standards will be prepared within the confines of a quality system that is ISO 9001:2015 registered and ISO/IEC 17025:2005 and ISO 17034:2016 accredited. Please indicate if the ISO 17034:2016 symbol is required for the Certificate of Analysis. Also describe any requirements for specific matrix or non-certified background material that will need to be applied. Please provide all special instructions on a separate piece of paper and attach with this quote form.

